NOT MEASUREMENT SENSITIVE

MIL-PRF-52342D(AT)
6 March 1996
SUPERSEDING
MIL-S-52342C(ME)
9 May 1990

PERFORMANCE SPECIFICATION

SLING ASSEMBLY: FLAKING BOX, LIFTING

This specification is approved for use by U.S. Army Tank-automotive and Armaments Command, Department of Army, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers a four-leg lifting sling equipped with a spreader bar.

2. APPLICABLE DOCUMENTS

2.1 General. The documents listed in this section are specified in sections 3 and 4 of this specification. This section does not include documents cited in other section of this specification or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all specified requirements documents cited in sections 3 and 4 of this specification, whether or not they are listed.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: U.S. Army Tank-automotive and Armaments Command, ATTN: AMSTA-TR-E/BLUE, Warren, MI 48397-5000, by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document, or by letter.

AMSC N/A FSC 3835

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:15Z
Check the source to verify that this is the current version before use.

2.2 Government documents, drawings, and publications. The following Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

DRAWING

ARMY

TA13212E7102- Sling Assembly, Four-Leg with Spreader Bar.

(Copies of these drawings are available from the U.S. Army Tank-automotive and Armaments Command, AMSTA-TR-E/BLUE, Warren, MI 48397-5000.)

2.3 Non-Government publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted are those listed in the issue of the DoDISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DoDISS are the issues of the documents cited in the solicitation (see 6.2).

AMERICAN NATIONAL STANDARD INSTITUTE (ANSI)

ANSI/ASQC Z1.4 - Sampling Procedures and Tables for Inspection by Attributes (DoD Adopted).

(Application for copies should be addressed to American National Standard Institute, 11 West 42nd Street, New York, NY 10036.)

SOCIETY OF AUTOMOTIVE ENGINEERS, INC. (SAE)

SAE AMS 2640J - Magnetic Particle Inspection (DoD Adopted).

(Application for copies should be addressed to Society of Automotive Engineers, Inc., 400 Commonwealth Drive, Warrendale, PA 15096.)

2.4 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:15Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 First article. When specified (see 6.2), a sample shall be subjected to first article inspection in accordance with 4.3.

3.2 Materials. Materials shall be as specified herein and as shown on Drawing TA13212E7102 and associated parts list. Materials not specified shall be selected by the contractor and shall be subject to all provisions of this specification (see 4.5.1).

3.2.1 Material deterioration prevention and control. The sling shall be fabricated from compatible materials, inherently corrosion resistant or treated to provide protection against the various forms of corrosion and deterioration that may be encountered in any of the applicable operating and storage environments to which the sling maybe exposed (see 45.1).

3.2.1.1 Dissimilar metals. Dissimilar metals shall not be used in intimate contact with each other unless protected against galvanic corrosion (see 4.5.1).

3.2.1.2 Welded materials. Welded parts shall meet the specification of the non-destructive magnetic particle test of 4.5.2.1.

* 3.2.2 Recycled, recovered or environmentally preferable materials. Recycled, recovered, or environmentally preferable materials should be used to the maximum extent -possible provided that the material meets or exceeds the operational and maintenance requirements and promotes economically advantageous life cycle costs. The components, pieces, and parts incorporated in the sling maybe newly fabricated from recovered materials to the maximum extent practicable provided the slings produced meet all other requirements of this specification. Used, rebuilt or remanufactured components, pieces, and parts shall not be incorporated in the sling (see 4.5.1 and 6.3).

3.3 Design and construction. Unless otherwise specified herein, the sling assemblies shall conform to the interface and envelope dimensions of Drawing TA13212E7102 and associated parts list (see 4.5.1).

3.4 Performance. The sling shall lift and hold a load of 6000 pounds ((2722 kilograms (kg)) (1500 pounds (680 kg)) on each of 4 hooks) (see 4.5.2).

3.5 Treatment and painting. Unless otherwise specified (see 6.2) the sling assembly, except the wire rope assemblies, shall be treated and painted with a minimum of a one coat top finish in accordance with the manufacturers standard practice for slings (see 4.5.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:15Z
Check the source to verify that this is the current version before use.

3.6 Identification and marking. Identification and marking of the sling assemblies shall be permanent and legible and shall include as a minimum the manufacturer's name, cage code and component serial number (see 4.5.1).

3.7 Workmanship. The sling shall be free of ail burrs, sharp edges, rust, or scale (see 4.5.1).

4. VERIFICATION

4.1 Component and material inspection. The contractor is responsible for ensuring that components and materials used are manufactured, examined, and tested as specified in referenced specifications and standards, as applicable.

4.2 Classification of inspection. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Conformance inspection (see 4.4).

4.3 First aticle inspection.

4.3.1 Examination. The first article sling shall be examined as specified in 4.5.1. Presence of one or more defects shall be cause for rejection.

4.3.2 Tests. The first article sling shall be tested as specified in 4.5.2 and 4.5.2.1. Failure of any test shall be cause for rejection.

4.4 Conformance inspection.

4.4.1 Sampling. Sampling for examination and tests shall conform to ANSI/ASQC Z1.4. A lot shall consist of all slings offered for acceptance at one time. The sample unit shall be one fully assembled sling.

4.4.2 Examination. Samples selected as specified in 4.4.1 shall be examined for defects specified in 4.5.1. Presence of one or more defects shall be cause for rejection.

4.4.3 Tests. Samples selected as specified in 4.4.1 shall be tested as specified in 4.5.2 and 4.5.2.1. Failure of any test shall be cause for rejection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:15Z
Check the source to verify that this is the current version before use.

4.5 Inspection procedure.

4.5.1 Examination. The sling shall be examined as specified herein for the following defects:

TABLE I. Examination.

Category	Defect	Method of examination
Major:		
101	Material not as specified (see 3.2).	SIE 1/
102	Materials not resistant to corrosion and deterioration, or treated to be resistant to corrosion and deterioration for the applicable storage and operating environments (see 3.2.1).	Visual and SIE
103	Dissimilar metals are not effectively insulated from each other (see 3.2.1.1)	Visual
104	Used, rebuilt or remanufactured components, pieces, or parts incorporated in the sling (see 3.2.2).	Visual
105	Dimensions not as specified (see 3.3).	Visual and SIE
106	Treatment and painting not as specified (see 3.5).	Visual
107	Identification marking not as specified (see 3.6).	Visual
108	Workmanship not as specified (see 3.7).	Visual

1/ SIE = Standard Inspection Equipment

4.5.2 Test. A 1500-pound (689 kg) load shall be attached to each of the four hooks. The total load (6000 pounds (2722 kg)) shall be lifted at least 1 foot above the floor and suspended in this position for not less than 1 minute. Any evidence of slippage of the wire rope in the mechanical splices, or bending or breaking of welds or other components shall constitute failure of this test (see 3.4).

4.5.2.1 Weldment test. The welded assembly shall conform to the non-destructive magnetic particle inspection test of SAE 2640J (see 3.2.1.2).

5. PACKAGING

5.1 Packaging. For acquisition purposes, the packaging requirements shall be as specified in the contract or order (see 6.2). When actual packaging of material is to be performed by DoD personnel, these personnel need to contact the responsible packaging activity to ascertain requisite packaging requirements. Packaging requirements are maintained by the Inventory Control Point's packaging activity within the Military Department or Defense Agency, or within

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:15Z
Check the source to verify that this is the current version before use.

the Military Department's System Command. Packaging data retrieval is available from the managing Military Department's or Defense Agency's automated packaging files, CD-ROM products, or by contacting the responsible packaging activity.

6. NOTES

(This section contains information of a general or explanatory nature that maybe helpful, but is not mandatory.)

6.1 Intended use. The sling is intended to lift the flaking boxes containing the 4-inch collapsible hoseline. The hoseline and flaking box conform to MIL-H-52262.

6.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number, and date of this specification.
b. Issue of DoDISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.2 and 2.3).
c. If a first article inspection is required (see 3.1).
d. If treatment and painting is other than as specified (see 3.5).
e. Level of preservation and packing required (see 5.1).

6.3 Recovered materials. Recovered materials are those materials which have been collected from solid waste and reprocessed to become a source of raw materials, as distinguished from virgin raw materials.

6.4 subject term (keyword) listing.

Bar, Spreader
Hooks
Mechanical splices
Rope, wire

6.5 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodian:
Army - AT

Preparing Activity:
Army - AT

(Project 3835-0108)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:15Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER MIL-PRF-52342D(AT)	2. DOCUMENT DATE (YYMMDD) 960306

3. DOCUMENT TITLE
Sling Assembly: Flaking Box, Lifting

4. NATURE OF CHANGE *(Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)*

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME	b. TELEPHONE (Include Area Code) (1) Commercial: (810) 574-8745 (2) AUTOVON: 786-8745
c. ADDRESS (Include Zip Code) U.S. Army Tank-automotive and Armaments Command, ATTN: AMSTA-TR-E/BLUE, Warren, MI 48397-5000	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:15Z
Check the source to verify that this is the current version before use.