MIL-P-60523A (AR)
AMENDMENT 1
28 October 1980

MILITARY SPECIFICATION

PROJECTILE, 165MM, HEP
M123A1, METAL PARTS

This amendment forms a part of Military Specification MIL-P-60523A, dated 18 May 1979,

PAGE 3

Paragraph 3.5.1, Delete and substitute the following:

"3.5.1 Raw material. The billets, bars, tubes or plate material from which projectile components are formed shall be free from cracks, splits, cold shuts, inclusions, pipe, porosity, folds, bursts, seams, laminations and other metal defects."

PAGE 4

Paragraph 3.6.b, Delete "band (s)" and substitute "band"

Paragraph 3.6.c, Delete "band (s)" and substitute "band"

Paragraph 3.8.2, Add to end: "see (6.8)."

PAGE 8

Paragraph 4.4.2.1.3, Delete and substitute the following:

"4.4.2.1.3 Inspections of raw material prior to forming. Each slug, tube or disc obtained from bar, tube or plate stock shall be visually examined for surface indications of the types of metal defects described in 3.5.1 which are visible to the unaided eye on all exterior surfaces. Visual standards may be selected to aid in the determination of a slug's tube's or disc's acceptability."

PAGE 9

4.4.2.2, Under Critical
Delete: "2 magnetic particle inspection -3.1-Test/4.5.6"

FSC: 1315

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:41Z
Check the source to verify that this is the current version before use.

PAGE 10

4.4.2.3, Under Critical, Delete "1. Magnetic particle inspection stamp missing 3.1 Visual"

PAGE 11

4.4.2.4, Under Critical
Add: (Exam or Test) (Req para) (Para Ref) (Insp Meth)
"4. Magnetic Particle Inspection - 3.1 - Test - 4.5.6"

(Exam or Test) (Reg Para)
Add: "5 Magnetic Particle Inspection acceptance stamp missing - 3.1 (Para Ref)
Visual"

PAGE 18

Paragraph 4.4.2.7, Title, Delete "Carton, Packing, Prior to Sealing" and substitute "Carton, Packed, Prior to Sealing (Base Plug)"

PAGE 19

Paragraph 4.4.2.8, Title, Delete "Cartons, Packed, After Sealing" and substitute "Cartons, Packed, After Sealing (Base Plug)"

PAGE 20

Paragraph 4.4.2.9, Title, Delete "Pallet" and substitute "Pallet (Projectile Body)"

PAGE 21

Paragraph 4.4.3.1, Delete third sentence and substitute the following:

"If two or more projectile bodies of a sample fail to meet the hardness requirement specified on dwg. 9327406, the batch

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:41Z
Check the source to verify that this is the current version before use.

represented by that sample shall be rejected and a new stress-relieved lot established as prescribed herein. The first batch of the new stress-relieved lot may be a failing batch which, after re-processing and subsequent testing, meets the applicable requirements."

Paragraph 4.4.3.1.2, Delete and substitute the following:

"4.4.3.1.2 Tensile strength and elongation of bourrelet. Two projectile bodies of the twenty-five bodies selected from the first batch of a stress-relieved lot for the hardness test of 4.4.3.1.1 shall be subjected to this test. Following the satisfactory compliance of this initial sample with the requirements of dwg. 8845046, a sample of two projectile bodies from every five batches, or fraction thereof, of a stress-relieved lot shall be selected for this test. Failure of any projectile body tensile specimen to meet the applicable requirements shall reject the lot of stress-relieved bodies which it represents and shall require the establishment of a new stress-relieved lot as prescribed in 4.4.3.1.1."

"4.4.3.1.3 Tensile strength of base plug. Two base plugs from the first batch of a stress-relief or heat-treatment lot shall be tested to determine the compliance of the samples with the mechanical properties specified on dwg. 8845045. Following the successful establishment of a stress-relief or heat-treatment base plug lot, two base plugs from every five batches, or fraction thereof, shall be subjected to this test. Failure of any base plug tensile specimen to comply with the requirements of dwg. 8845045 shall reject the lot of base plugs represented by the failing specimen and shall require the establishment of a new stress-relief or heat-treatment lot. If stress relief or heat-treatment is not performed in order to obtain the required mechanical properties, then two base plugs per five thousand base plugs, or fraction thereof, shall be subjected to this tensile test."

Paragraph 4.4.3.2, Delete the second sentence and substitute the following:

"Failure to comply with the applicable specification and drawing requirements shall be cause for the rejection of the material represented by the failing samples."

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:41Z
Check the source to verify that this is the current version before use.

PAGE 22

Paragraph 4.5.1.1, Delete and substitute the following:

"4.5.1.1 Hardness of the nose/ogive. After final stress relief, but prior to final machining, a Rockwell Superficial Hardness Test shall be performed on the samples provided by 4.4.3.1.1. The requirement and procedures for performing this test are prescribed by ASTM E18. Four equally spaced readings shall be taken at a point which is four inches from the tip of the projectile body nose and averaged in order to determine the acceptability of each sample. One reading shall be taken on the inside surface of the projectile body tensile samples, obtained as prescribed in 4.5.1.2, at locataions directly opposite points that are one, four and seven inches from the projectile body nose. Two equally spaced and averaged readings on each sample shall be taken at the tip of the projectile body nose when the nose is welded or brazed as allowed by dwg. 8845046."

PAGE 23

Paragraph 4.5.1.4, Add the following title: "Reporting and format of data."

Paragraph 4.5.2, Add the following sentence:

"The contractor shall prepare a written standard operation procedure, to include the inspection of projectile bodies and calibration procedures, which shall be submitted for the review and approval of the Contracting Officer prior to the submission of the first article sample (see 6.2)"

Paragraph 4.5.2.1, Delete the last sentence in its entirety.

PAGE 24

Paragraph 4.5.3, Add the following sentence:

"The contractor shall prepare a written standard operation procedure, to include the inspection of projectile bodies and calibration procedures, which shall be submitted for the review and approval of the Contracting Officer prior to the submission of the first article sample (see 6.2)."

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:41Z
Check the source to verify that this is the current version before use.

Paragraph 4.5.3.1, Delete this paragraph in its entirety.

PAGE 25

Paragraph 4.5.5.4, Add the following sentence:

"The proving ground shall prepare a written assembly procedure for the assembly of projectile metal parts ballistic samples and submit the procedure for review to the Contracting Officer prior to the assembly of the first article ballistic test samples (see 6.4)."

PAGE 27

Paragraph 5.2.2.2, Delete and substitute the following:

"5.2.2.2 Size. Dimensions of the fiberboard boxes shall be 5 1/2" W X 5 1/2" L X 12 3/16" D. The dimension of the discs shall be 5 inches in diameter."

PAGE 29

Add the following paragraph"

"6.8 Burr. A burr that is loose, injurious to personnel, interferes with assembly of other components or interferes with inspection gaging is not permissible."

Custodian:
ARMY-AR

Preparing Activity:
ARMY-AR

Project No. 1315-A349

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:41Z
Check the source to verify that this is the current version before use.