MILITARY SPECIFICATION

BARRIER MATERIAL, WATERPROOF, FLEXIBLE; LUMBER PROTECTIVE

This specification is mandatory for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers waterproof barrier material used for protection of lumber during storage out of doors and transportation under all climatic conditions (see 6.1).

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of the specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

MMM-A-260	-	Adhesive, Water-Resistant, (For Sealing Waterproofed Paper)
PPP-B-1055	-	Barrier Material, Waterproofed, Flexible

STANDARDS

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	-	Marking for Shipment and Storage

(Copies of specifications, standards and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

FSC 8135

Source: https://assist.dla.mil -- Downloaded: 202610-21T22:05Z
Check the source to verify that this is the current version before use.

2.2 Other publications.- The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

TECHNICAL ASSOCIATION OF THE PULP AND PAPER

INDUSTRY (TAPPI) PUBLICATION:

T402 - Conditioning of Paper and Paperboard for Testing.

T404 - Tensile Breaking Strength of Paper and Paperboard.

T475 - Bleeding Resistance of Asphalted Paper at Elevated Temperature.

T489 - Stiffness of Paperboard.

(Application for copies should be addressed to the Technical Association of the Pulp and Paper Industry, 360 Lexington Avenue, New York, New York 10017.)

NATIONAL MOTOR FREIGHT TRAFFIC ASSOCIATION, INC.

National Motor Freight Classification

(Application for copies should be addressed to the American Trucking Associations, ATTN: Tariff Order Section, 1616 P Street, N. W., Washington, D. C. 20036.)

UNIFORM CLASSIFICATION COMMITTEE

Uniform Freight Classification

(Application for copies should be addressed to the Uniform Classification Committee, Room 202 Union Station 516 W. Jackson Blvd., Chicago, Ill. 60606.)

(Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:05Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Material.- The flexible, waterproof barrier material shall consist of white, opaque polyethylene, two layers of kraft paper laminated with asphalt and reinforcing, and so processed as to be in compliance with all the requirements of this specification.

3.2 Form.- The barrier material shall be furnished in roll form. The length of the roll shall be 100 or 300 yards, as specified in the contract or purchase order (see 6.2), and the width of the roll shall be 48 inches, 59 inches, 72 inches, 84 inches, 96 inches, 110 inches, 116 inches, or 119 inches, as specified (see 6.2 and 6.3). When this material is being used as a packing component for a lumber procurement, the material employed by the lumber supplier shall be of the proper width (see above options) to cover the tops and edges of the unit loads being supplied.

3.2.1 Rolls.- The rolls shall be uniformly and smoothly wound on non-returnable cores having a minimum inside diameter of 3 inches, with a plus 1/8 inch tolerance, and shall be suitably restrained to prevent unwinding. The length of the core shall be equal to the specified width of the roll, with a plus 1/4 inch tolerance. The cores shall be protected by fitted plugs at each end, and shall be of sufficient rigidity to prevent distortion of the roll under normal conditions of transportation and use.

3.2.2 Tolerances.- The average length of the rolls shall be not less than the length specified. The width of the rolls shall be within ± 1/2 inch of the specified width (see 3.2).

3.2.3 Splices.- No more than 10 percent of the rolls within an inspection lot shall contain splices. No roll shall contain more than one splice (2 pieces) and no piece shall be less than 10 yards in length. Splices, indicated on both sides of the roll with bright colored markers, shall be evenly and neatly made the entire width of the roll and shall not separate during unwinding of the roll.

3.3 Construction.- The waterproof barrier material covered by this specification shall consist of an outer layer of white, opaque polyethylene, two layers of kraft paper laminated with asphalt and reinforcing cords or strands, and the tacking and padding strips as detailed below. The reinforcing shall be a three-way, fiberglass reinforced pattern, embedded in the laminating resin, with a distance between adjacent cords not exceeding 1 inch.

3.3.1 Tacking strip.- A metal or fiber tacking or stapling strip, 3/16 inch minimum width, shall be incorporated in the lengthwise direction. The strip shall be continous and shall be located 2 inches ± 1/2 inch from each longitudinal edge of the sheet. The location of the strip shall be easily discernible from the outer surface of the material.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:05Z
Check the source to verify that this is the current version before use.

3.3.2 Padding strips.- The longitudinal direction of the material shall be reinforced with a padding strip fabricated of creped or extensible kraft paper having a minimum basis weight, after creping, of 40 pounds (24 x 36 - 500). The padding strip shall be a minimum of 6 inches in width and shall be firmly and securely laminated to the wrap with a minimum of 50 pounds asphalt (24 x 36 - 500) or, as an alternative method, shall be securely laminated within the sheet. The padding strips shall be parallel to the longitudinal edges of the sheet, ± 1 inch, and shall be equidistant from such edges ± 1 inch. The locations of the padding strips are determined by the height and width of the lumber load to be covered. The distance of the strips from adjacent edges will be governed by the height of the load while the separation of the strips from each other will be governed by the width of the load.

When this material is being used as a packing component for a lumber procurement, the material employed by the lumber supplier shall have the padding strips spaced so that they lie along the longitudinal top edges of the load and thereby pad the barrier material from these edges.

When this material is being procured as an end item, the center line spacing of the padding strips (equivalent to the width of the lumber loads to be covered) shall be as specified ± 1 inch (see 6.2).

3.4 Physical properties.- The barrier material shall conform to the requirements below when tested as specified in 4.2.2.2.

TABLE I.- Construction and basis weight of paper

Basis weight (24 by 36 inches - 500 sheets)			
Paper, pounds, minimum		Asphalt, pounds, minimum	Polyethylene, pounds, minimum
1st ply	2nd ply		
30	30	50	10

TABLE II.- Physical properties

Average tensile strength, minimum 2/		Water resistance, minimum	Average stiffness maximum 1/
lbs/inch, width		Hours	
MD	CD	24	80 gms. (Taber) Stiffest
50	20		4700 mgms. (Gurley) direction

1/ Supplier's option (See 4.3.4).

2/ MD = Machine direction
CD = Cross direction

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:05Z
Check the source to verify that this is the current version before use.

The material shall be capable of being sealed by adhesives, pressure sealing, or taping to effect water resistance of joints and closures equal to the material itself. The sealed material, when tested as specified in 4.2.2.2, shall have the water resistance indicated in table II.

3.5 Bleeding.- Unless otherwise specified (see 6.2) neither side of the waterproof barrier material shall show more than slight bleeding, that is, staining in the form of a few isolated specks when tested as specified in 4.2.2.2.

3.6 Workmanship.- The barrier material shall be uniformly constructed and free from holes, tears, cuts, or defects listed in 4.2.2.1.1 which impair its usefulness. The barrier material shall not stick together to such an extent as to cause tearing or injury to any surface, when unrolled.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.- Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Inspection.- Sampling for inspection shall be performed in accordance with MIL-STD-105, except where otherwise indicated hereinafter.

4.2.1 Components and material inspection.- In accordance with 4.1 above, components and material shall be inspected and tested in accordance with all the requirements of referenced specifications and standards unless otherwise excluded, amended, modified or qualified in this specification or applicable purchase documents.

4.2.2 Inspection of the end item.-

4.2.2.1 Examination of the end item.- The end item shall be examined in accordance with the defects set forth in the applicable subparagraphs, at the inspection levels and acceptable quality levels (AQL's) set forth in 4.2.2.1.6. A random sample shall be drawn from each lot of material offered for examination of visual, dimensional, roll construction, roll length and width, and preparation for delivery defects. The lot, for purposes of determining the sample size in accordance with MIL-STD-105, shall be expressed in units of linear yards for examination in 4.2.2.1.1, and in units of rolls for examinations under 4.2.2.1.2 through 4.2.2.1.5 inclusive.

Source: https://assist.dla.mil -- Downloaded: 20260-21T22:05Z
Check the source to verify that this is the current version before use.

4.2.2.1.1 Examination for visual defects.- The sample unit for this examination shall be one yard, full width of the roll. No more than 10 sample units shall be selected from any one roll, and no sample unit shall be taken from the first or last convolution of the roll. Both sides of the material shall be examined. Defects of each type shall be scored only once within a sample unit.

Examine	Defect
Workmanship	Not uniformly constructed. Presence of any foreign matter, dirt, sand, grit or oil spots.
	Delamination or embrittlement.
	Any hole (including pinhole) tear, cut, sharp crease, crack, blister or puncture.
	Number or combination of layers not in compliance with requirement.

4.2.2.1.2 Examination for defects in dimensions, except length.- The sample unit for this examination shall be one roll.

Examine	Defect
Roll Width	Varies by more than ± 1/2 inch of specified width (when being procured as an end item).
	Not proper width to completely cover top and edges of unit loads (when used as a packing component).
Core Length	Length less than specified width of roll material or greater by more than 1/4 inch.
Diameter	Inside diameter less than 3 inches and more than 3-1/8 inches.

4.2.2.1.3 Examination for length per roll.- The sample unit for this examination shall be one roll. The lot shall be unacceptable if the average length per roll for all rolls examined is less than specified.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:05Z
Check the source to verify that this is the current version before use.

4.2.2.1.4 Examination for defects in roll construction.- The sample unit for this examination shall be one roll.

Examine	Defect
Assembly of roll	Material not wound uniformly and smoothly on roll causing uneven edges or telescoping of roll.
	Not suitably restrained to prevent unwinding.
	Material not wound on a substantial rigid core; core broken, collapsed, crushed or mutilated.
	Plugs omitted from one or both ends of core; do not fit properly; too loose to the extent that plug(s) fall in or out of opening.
Unwinding of roll (examine both sides)	When unwound, material sticks together, causing tearing or injury to either surface.
	Roll wound unevenly, causing wrinkles, sharp creases, or folds within roll.
Splices	Roll contains more than one splice (2 pieces); piece less than 10 yards in length.
	Splices not neatly and evenly made; not full width of roll; comes apart during unwinding. Splice not flagged at both ends with bright colored marker.
Tacking strip	Missing; location not readily discernible from outer surface. Width less than 3/16 inch; not continuous lengthwise; not 2" ± 1/2 inch from each longitudinal edge of sheet.
Padding strip	Missing; less than 6 inches wide; not firmly and securely laminated to or within lengthwise direction.
	Not properly placed to pad the longitudinal top edges of the lumber load (when being procured as a packing component).
	Centerline distance between padding strips varies from specified distance by more than ± 1 inch (when being procured as an end item).

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:05Z
Check the source to verify that this is the current version before use.

Examine	Defect
Padding strip (Cont'd)	Not parallel to adjacent edge (distance varies by more than 1 inch).
	Spacings of strips from their adjacent edges unequal (differ by more than 1 inch).

4.2.2.1.5 Examination of preparation for delivery.- An examination shall be made to determine that marking, material, and workmanship comply with the requirements of section 5. The sample unit for this examination shall be one roll, fully packed, selected just prior to the sealing operation. Sealed rolls shall be examined for closure defects.

Examine	Defect
Marking	Incorrect; incomplete; illegible; omitted, of improper size, location, sequence, or method of application.
Material	Any nonconforming component; component missing or damaged.
Workmanship	Inadequate application of components, such as; inadequate sealing of seams of wrapper and leaders.

4.2.2.1.6 Inspection levels and acceptable quality levels (AQLs) for examination.- The inspection levels, for determining the sample size, and AQLs, expressed in defects per one hundred units, shall be as follows:

Examination paragraph 1/	Inspection level	AQLs
4.2.2.1.1	I	2.5
4.2.2.1.2	S-2	2.5
4.2.2.1.3	S-2	---
4.2.2.1.4	S-4	4.0
4.2.2.1.5	S-1	2.5

1/ The same rolls may be used for examinations under 4.2.2.1.2, 4.2.2.1.3 and 4.2.2.1.4 and may be within the rolls randomly selected for examination under 4.2.2.1.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:05Z
Check the source to verify that this is the current version before use.

4.2.2.2 Testing of the end item.- The end item shall be tested for the applicable characteristics in table III. Unless otherwise specified herein, specimens for test shall be conditioned and tested in accordance with TAPPI Method T 402. The sample unit shall be 12 square feet of material taken from one roll. The sample size shall be based upon inspection level S-3, with an AQL of 2.5 defects per hundred units. The lot shall be expressed in units of rolls. There shall be no failure to meet the sample unit or lot average requirements in any test for lot acceptability.

4.3 Test procedures.-

4.3.1 Basis weight of paper, polyethylene, and asphalt.-

4.3.1.1 Procedure.- Cut three specimens exactly 2 x 5 inches from each sample unit. These specimens shall be taken from the same sample sheets as the specimens used for tensile elongation test. Weigh the specimens on an analytical balance and record as the total weight. Fold the specimens in accordion pleats parallel to the 2 inch dimension, then place in a suitable extraction apparatus such as a Soxhlet or Underwriters. Extract the asphalt with benzene until the extract is practically colorless. Allow the paper to dry, then recondition and reweigh, care being exercised to retain all the reinforcing strands. From the difference between this weight and the original weight, calculate the basis weight of the asphalt. Weigh and record the weight for each ply separately. Place the ply with the polyethylene in a clean extraction apparatus and extract the polyethylene with tetrachloroethylene. Allow the paper to dry, recondition and reweigh. From the difference between this weight and the first weight, calculate the basis weight of the polyethylene. Calculate the basis weight of the paper.

4.3.2 Reinforcement.- Cut a specimen 3 x 7 inches from each sample unit. Immerse one end (approximately 3 inches square) in a suitable solvent, such as trichloroethylene or carbon tetrachloride, until the plies can be separated and the reinforcing strands are visible (approximately 15 minutes). Avoid excessive agitation in order to preserve the relative number and spacing of the strands. Measure the distance between the strands to determine compliance with 3.3.

4.3.3 Tensile breaking strength.- Tensile breaking strength shall be determined in accordance with TAPPI Method T404.

4.3.4 Stiffness.- Stiffness shall be determined in accordance with TAPPI Method T489, (Tabor Instrument), or as specified in 4.3.4.1 (Gurley Stiffness), at the option of the supplier.

4.3.4.1 Gurley stiffness method.- From each sample unit to be tested, cut five specimens each for cross direction and machine direction tests. If initial tests indicate which direction is the stiffest direction without any

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:05Z
Check the source to verify that this is the current version before use.

question, only the specimens in this direction need to be cut and tested, since the requirement applies to the stiffest direction only. With each instrument, a factor table is supplied, which cites several optional widths and lengths of specimens, pendulum weights and weight positions which can be used to accommodate various stiffness properties. Typical materials of the stiffness range required have provided suitable mid-scale readings with specimens 2-1/2 inches long and 1 inch wide, 25 gram pendulum weight located 4 inches from the center hole for machine direction determinations and 2 inches from the center hole for cross direction determinations. Use these options in preliminary pre-tests in accordance with the procedures indicated below. If the stiffness of the materials being tested is such that the pre-test determinations do not fall at approximately mid-range on the instrument scales, make appropriate changes of options as indicated in the factor table, to obtain mid-range readings. Do not change specimen length if possible to obtain mid-range readings by change of other options. Then make the actual test determinations and apply the factor as indicated in the table to convert the readings for the particular option being used to values for the standard conditions upon which the requirements are based.

Level the instrument. The pointer must hang at zero when loaded. Insert the specimen centrally in the clamp so that it is seated all the way into the slot with the bottom edge of the specimen parallel with the top of the vane.

Apply a load to the free end of the specimen in one direction by pressing one of the buttons on motorized models or by slowly and evenly turning the capstan handle on hand-operated models. This will cause the specimen to push the vane-pendulum pointer system out of the vertical position up to the point where the pointer tilt and scale reading reach a maximum and the specimen bends enough to slip over the top of the vane. This maximum reading is recorded for that bending direction. Repeat the load application in the other direction and average the two maximum readings to obtain the stiffness value for the specimen. Apply the factor as indicated above to convert this value to the standard condition value.

For the stiffest direction of the barrier material, average the values of the five specimens of each sample unit to obtain the test result for that unit, and average the test results of the sample units to obtain the sample average results.

4.3.5 Bleeding resistance.- Bleeding resistance shall be determined in accordance with TAPPI, Method T475, except that the oven shall be maintained at a temperature of $160^{\circ} \pm 2^{\circ}F$.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:05Z
Check the source to verify that this is the current version before use.

4.3.6 Water resistance.- Cut two 3 x 3 inch specimens from each sample unit to be tested. Crease one of the two specimens. The apparatus for creasing shall consist of a smooth, flat, base plate having a top plate hinged to it at one edge, capable of matching and surfacing the base plate, and weighing 10 pounds. Fold the test specimen without creasing it so that the corners of the sheet diagonally opposite, coincide. Place the folded specimen on the base plate of the apparatus with the fold towards the hinge. Position the top plate so that its center is directly above the fold, lower it on the specimen, and allow it to remain on the specimen for 30 seconds. At the end of this period, remove the specimen and repeat the procedure to make a crease on the other side of the specimen, and at right angles to the first crease. Place the specimens on a smooth, clean, dry surface and with a medicine dropper put a drop of water in the center of each specimen. Cover with a 2 inch diameter watch glass and seal the edges with paraffin wax. Allow the specimen to stand for 24 hours. Any evidence of water penetration shall constitute failure of this test.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:05Z
Check the source to verify that this is the current version before use.

TABLE III.- Instructions for testing of the end item

Characteristic	Specification reference Requirement	Specification reference Test method	Requirements applicable to Individ unit	Requirements applicable to Lot aver	Number determinations per sample unit	Results reported as Pass or fail	Results reported as Numerically to nearest
Basis weight (24 by 36 - 500)							
Paper	Table I	4.3.1		X	Average of 10		0.5 pound
Asphalt	Table I	4.3.1		X	Average of 10		0.5 pound
Polyethylene	Table I	4.3.1		X	Average of 10		0.5 pound
Reinforcement: One direction	3.3	4.3.2	X		1	X	0.25 in.
Tensile strength (dry)							
Machine direction (MD)	Table II	T 404 1/		X	Average of 5		0.1 lbs./ in. wide
Cross direction (CD)	Table II	T 404 1/		X	Average of 5		0.1 lbs./ in. wide
Stiffness							
Taber	Table II	4.3.4		X	Average of 10		Gram
Gurley	Table II	4.3.4.1		X	Average of 5		Mgms.
Bleeding resistance	3.5	4.3.5	X		1	X 2/	Degree
Water resistance	Table II	4.3.6	X		1	X	

1/ Indicates TAPPI test method T404.

2/ In case of failure, the degree of staining observed for each unit shall be reported in accordance with the categories stated in TAPPI method T475.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:05Z
Check the source to verify that this is the current version before use.

5. PREPARATION FOR DELIVERY

5.1 Packing.- Packing shall be level A, B, or C, as specified (see 6.2).

5.1.1 Level A.- Each roll of barrier material shall be wrapped overall with one thickness of barrier material covered by this specification. The wrapper shall be closed at the ends by means of inside and outside headers. The wrapper seams and the headers shall be sealed with a water-resistant adhesive conforming to MMM-A-260, using sufficient adhesive to effect a water-tight seal. Alternatively, the wrapper shall be a barrier material conforming to PPP-B-1055, except when class C-1 is used, two thicknesses shall be required.

5.1.2 Level B.- Each roll of barrier material shall be wrapped overall with kraft paper having a minimum basis weight of 60 pounds per ream (24 by 36 - 500). The wrapper shall be closed at the ends by means of inside and outside headers. The wrapper seams and the headers shall be securely sealed with an adhesive commercially used for this purpose.

5.1.3 Level C.- Rolls of barrier material shall be packed in a manner to insure carrier acceptance and safe delivery at destination at the lowest transportation rate for such supplies. Shipments shall be in accordance with Uniform Freight Classification Rules or National Motor Freight Classification Rules, as applicable.

5.2 Marking.- In addition to any special marking required by the contract or order, shipments shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use.- The intended use of the waterproof barrier material covered by this specification is for wrapping the top, ends and sides of strapped units of lumber, leaving the bottom open for the purpose of ventilation.

6.2 Ordering data.- Purchasers should exercise any desired options offered herein and procurement documents should specify the following:

a. Title, number and date of this specification.
b. Length and width of rolls required (see 3.2).
c. Whether bleeding resistance is required (see 3.5).
d. Selection of the applicable level of packing (see 5.1).

6.3 The height and width of the lumber load to be covered must be known. The width of the roll must cover the top and both sides of the load. The purchaser shall specify the width which will give the proper coverage (see 6.2).

Source: https://assist.dla.mil -- Downloaded: 202640-21T22:05Z
Check the source to verify that this is the current version before use.

6.4 The padding strips must be spaced so that the approximate centers of the padding strips run along the top side edges of the stock and closely approximate the width of the load. The purchaser shall therefore specify the spacing of the padding strips in inches (equivalent to the width of the unit load) in ordering data (see 6.2).

Custodians:

Army - GL
Navy - SA
Air Force - 69

Review activities:

Army - ME
Navy - SH
Air Force - 84

Preparing activity:

Army - GL

Project No. 8135-0340

Source: https://assist.dla.mil -- Downloaded: 202640-21T22:05Z
Check the source to verify that this is the currentversion before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION
MIL-B-43711; Barrier Material, Waterproof, Flexible; Lumber Protective

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A
☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?
   A. GIVE PARAGRAPH NUMBER AND WORDING.

   B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?
   ☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)*

DATE

DD FORM 1 JAN 66 1426

REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

Source: https://assist.dla.mil -- Downloaded: 202640-21T22:05Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY
U. S. Army Natick Laboratories
Natick, Massachusetts 01760

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY

OFFICIAL BUSINESS

Commanding General
U. S. Army Natick Laboratories
ATTN: AMXRES-EQS
Natick, Massachusetts 01760

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:05Z
Check the source to verify that this is the current version before use.