MIL-C-43689C
31 March 1987
SUPERSEDING
MIL-C-43689B
30 September 1977

MILITARY SPECIFICATION

COVER, WATER CANTEEN, 2-QUART, COLLAPSIBLE (WITH PILE LINING)

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This document covers one type and size of cover, for a collapsible canteen, made of olive green nylon duck and acrylic fiber pile with a cotton webbing sling.

2. APPLICABLE DOCUMENTS

* 2.1 Government documents.

* 2.1.1 Documents. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

FEDERAL

A-A-203	- Paper, Kraft, Untreated
V-T-285	- Thread, Polyester

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to U.S.: Army Natick Research, Development, and Engineering Center, Natick, MA 01760-5014, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 8465

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:02Z
Check the source to verify that this is the current version before use.

DDD-L-20	- Label: for Clothing, Equipage, and Tentage, (General Use)
PPP-B-636	- Boxes, Shipping, Fiberboard

MILITARY

MIL-S-1698	- Slings, Bag and Case, Carrying
MIL-R-3390	- Rings, Dee
MIL-W-4088	- Webbing, Textile, Woven Nylon
MIL-T-5038	- Tape, Textile and Webbing, Textile, Reinforcing, Nylon
MIL-C-7219	- Cloth, Duck, Nylon
MIL-H-9890	- Hardware, Individual Load Carrying Equipment: and Hardware, Miscellaneous
MIL-W-17337	- Webbing, Textile, Woven Nylon
MIL-E-20652/1	- Eyelet, Metallic, Rolled Flange Type, and Eyelet Washer
MIL-F-21840	- Fastener Tapes, Hook and Pile, Synthetic
MIL-W-27265	- Webbing, Textile, Woven Nylon Impregnated
MIL-L-35078	- Loads, Unit: Preparation of Semiperishable Subsistence Items; Clothing, Personal Equipment and Equipage; General Specification For
MIL-C-43128	- Cloth, Plain Weave, Nylon: Water Repellent, OG-106
MIL-C-43251	- Cloth, Pile, Synthetic Fiber Pile
MIL-F-43514	- Fastener, Plastic, for Equipage Items

STANDARDS

FEDERAL

FED-STD-751	- Stitches, Seams, and Stitchings

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	- Marking for Shipment and Storage
MIL-STD-147	- Palletized Unit Loads
MIL-STD-731	- Quality of Wood Members for Containers and Pallets

* 2.1.2 Other Government documents. The following other Government documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

Source: https://assist.dla.mil -- Downloaded: 202610-21T22:02Z
Check the source to verify that this is the current version before use.

DRAWINGS

U.S. ARMY NATICK RESEARCH, DEVELOPMENT, AND ENGINEERING CENTER

2-2-279	- Cover, Water Canteen, 2-Quart, Collapsible (With Pile Lining); Assembly and Sections
2-2-280	- Cover, Water Canteen, 2-Quart, Collapsible (With Pile Lining); Details
2-2-281	- Cover, Water Canteen, 2-Quart, Collapsible (With Pile Lining); Details

(Copies of documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

* 2.2 Other publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted shall be those listed in the issue of the DODISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS shall be the issues of the nongovernment documents which are current on the date of the solicitation.

COLOR ASSOCIATION OF THE UNITED STATES

Standard Color Reference of America

(Application for copies should be addressed to the Color Association of the United States, Inc., 343 Lexington Avenue, New York, NY 10016.)

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

D 3951 - Standard Practice for Commercial Packaging

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

(Technical society and technical association documents are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:02Z
Check the source to verify that this is the current version before use.

* 2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document shall take precedence. Nothing in this document, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Guide samples. Guide samples of the end item are solely for guidance and information to the contractor (see 6.3). Variation from this document may appear in the sample, in which case this document shall govern.

3.2 First article. When specified in the contract or purchase order, a sample shall be subjected to first article inspection (see 4.3, 6.2, and 6.4).

3.3 Materials. (See 6.5)

3.3.1 Cloth, duck, nylon. The 7.25 ounce nylon duck shall conform to type III, class 3 of MIL-C-7219. The color shall be Olive Green 106.

3.3.2 Cloth, nylon. The 3.8 ounce nylon cloth shall be Olive Green 106, water repellent, conforming to MIL-C-43128.

3.3.3 Cloth, acrylic fiber pile. The cloth for lining the canteen cover shall conform to class 1 or 3 of MIL-C-43251 except that the requirements for color matching, dullness, and colorfastness shall not apply.

3.3.4 Fastener tape, hook and pile. The hook and pile nylon tape fastener shall be dyed Olive Green 106 and shall conform to type II, class 1, 5/8 inch width of MIL-F-21840.

3.3.5 Webbing, nylon.

3.3.5.1 3/4 inch and 2 1/4 inch widths. The 3/4 inch and 2 1/4 inch nylon webbing shall be dyed Olive Drab 7 and shall conform to types Ia and XXVIII, respectively, of MIL-W-4088.

3.3.5.1.1 Treatment. The types Ia and XXVIII nylon webbing shall be resin impregnated to conform to class R of MIL-W-27265.

3.3.5.2 1 inch width. The 1 inch nylon webbing used for the reinforcement shall conform to class 2 of MIL-W-17337. The color shall be Olive Drab 7.

3.3.6 Tape, nylon. The nylon binding tape shall be dyed Olive Drab 7 and shall conform to type III, 1 inch of MIL-T-5038.

Source: https://assist.dla.mil -- Downloaded: 202610-21T22:02Z
Check the source to verify that this is the current version before use.

3.3.7 Thread, polyester. The thread for all stitching shall conform to type I, class 1, sub-class B, size E of V-T-285.

3.3.7.1 Color. The thread shall be dyed Olive Drab S-1 (C.A. 66022) and shall show fastness to weathering equal to or better than the standard sample. If no standard sample is available, the thread shall show good fastness to weathering.

3.3.8 Fastener, plastic. The plastic fastener shall be black and shall conform to MIL-F-43514.

3.3.9 Eyelet, aluminum black. The black enameled aluminum eyelet shall conform to dash No.-ABE 131 of MIL-E-20652/1.

3.3.10 Ring, dee. The dee ring shall conform to class 1 or class 2, configuration A, 25/32 inch by 3/8 inch of MIL-R-3390.

3.3.11 Keeper with slide. The keeper with slide shall conform to type X of MIL-H-9890.

3.3.12 Sling. The sling shall conform to type I of MIL-S-1698.

3.4 Construction. The construction shall conform in all respects to Drawings 2-2-279 through 2-2-281 and as specified herein.

3.4.1 Stitches, seams, and stitching. All machine stitching except bartacking shall conform to FED-STD-751. All stitching except bartacking shall be stitch type 301, 8 to 10 stitches per inch.

3.4.1.1 Automatic stitching. Any of the stitching operations cited in this document may be performed with an automatic machine provided that the requirements for stitch pattern, stitches per inch, and size and types of thread are met and that at least three tying, overlapping, or back stitches are used to secure the ends of stitching.

3.4.1.2 Type 301 stitching. Ends of all stitching except box and w-w shall be backstitched or backtacked not less than 1 inch at the ends, except where ends are caught in other seams and stitching. On box and W-W stitching, all ends shall be backstitched or backtacked 1/2 inch. Thread tension shall be maintained so that there will be no loose or tight stitching and the lock will be embedded in the sewed material.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:02Z
Check the source to verify that this is the current version before use.

3.4.1.2.1 Repairs of type 301 stitching. Repairs of type 301 stitching shall be as follows:

a. When thread breaks, skipped stitches, run-offs, or bobbin run-outs occur during sewing, the stitching shall be repaired by restarting the stitching a minimum of 1 inch (1/2 inch for box and W-W stitching) back of the end of the stitching. 1/

b. Thread breaks, or two or more consecutive skipped or run-off stitches, noted during inspection of the item (in-process or end item) shall be repaired by overstitching. The stitching shall start a minimum of 1 inch in back of the defective area (1/2 inch for box and W-W stitching), continue over the defective area and continue a minimum of 1 inch (1/2 inch for box and W-W stitching) beyond the defective area onto the existing stitching. Loose or excessively tight stitching shall be repaired by removing the defective stitching, without damaging the materials and restitching in the required manner. 1/

1/ When making the above repairs, the ends of the stitching are not required to be backstitched.

* 3.4.1.3 Bartacking. Unless otherwise specified, bartacks shall be as listed in table I. The bartack shall be free from thread breaks and loose or tight stitching.

TABLE I. Bartack requirements

Length (inches)	Width (inches)	Tolerances (inches) Length	Width	Stitches per bartack
1/2	1/8	± 1/16	± 1/32	28
3/4	1/8	± 1/16	± 1/32	42

3.4.1.4 Thread ends. All thread ends shall be trimmed to 1/4 inch maximum length.

3.4.1.5 Lubrication of thread. There shall be no lubrication of the thread prior to or during sewing (see 4.4.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:02Z
Check the source to verify that this is the current version before use.

3.4.2 Eyelet, aluminum. A hole shall be prepunched through the nylon duck and acrylic fiber pile cloth before inserting the eyelet barrel. The prepunched hole for receiving the eyelet shall be smaller than the outside diameter of the barrel of the eyelet so that the eyelet barrel must be forced through the hole. The eyelet shall be installed using score setting dies conforming to J.C. Rhodes part No. 1-KW-1KL and 101Y-1Klom, or Stimpson Co., part No. A2744-7 score, or equal (see 6.6). The eyelets shall be securely set in a manner that will prevent detachment from or cutting of the surrounding material. The scored side of the eyelet shall be on the inside of the assembly.

3.4.3 Setting of plastic fastener. Holes for assembling the fastener components shall be prepunched or predrilled and shall be smaller than the diameter of the posts of the latch and latch receptacle components so that the posts must be forced through the holes. Surfaces around the holes shall be free of uncut thread ends when prepunched and shall be free of melted residue when predrilled. The posts shall be securely set to provide a tight clinch of the assembled components.

3.4.4 Repairs. Repairs such as mends, darns, patches, or splices are not permitted on the canteen cover.

3.5 Marking. The identification marking shall be applied in the location shown on Drawing 2-2-280 and shall conform to type IV, class 5 of DDD-L-20. The letters "US" shall be applied in the size characters and in the location shown on Drawing 2-2-281 and shall conform to type IV, class 9 of DDD-L-20. Fastness of the class 9 marking shall be as specified for class 5 marking.

3.5.1 Instruction label. An instruction label approximately 4 5/8 inches by 3 3/8 inches shall be sewn on the inside of the flap as indicated on Drawing 2-2-281. The label shall conform to type VI, class 7 of DDD-L-20 except that the color of the label shall be medium green and shall approximate the Cable No. 70034, 70130, or 70131 as listed in the Standard Color Reference of America. The characters used in printing the label shall be of maximum size commensurate with the area and contents specified. The legend shall be located on the label so that no part of the legend will be obscured by stitching or binding when sewn in the cover.

Source: https://assist.dla.mil -- Downloaded: 20261 0-21T22:02Z
Check the source to verify that this is the current version before use.

3.5.1.1 Legend. The contents of the instruction label shall be as follows:

FILLING INSTRUCTIONS

Remove bladder and unscrew cap. Fully extend bladder by blowing into it. Float empty bladder on side, holding neck of bladder with 1/3 to 1/2 of opening under water. Do not totally submerge opening. Slowly submerge bladder as it fills. If bladder collapses, remove from water allowing air to enter and proceed as above. To hasten filling, use a scooping motion with opening partially under water. Insert correct number of water purification tablets as directed on tablet bottle. Note: capacity of canteen is two quarts. To reduce sloshing noise of partially full canteen, squeeze to force water into neck and replace cap tightly. Wet the pile lining during hot weather to help keep water cool. Keep lining material dry during cold weather to provide limited protection from freezing.

Carry under the parka during cold weather to keep the water from freezing. Keep bladder and cover away from heat or flame.

3.6 Workmanship. The cover shall conform to the quality of product established by this document, and the occurrence of defects shall not exceed the applicable acceptable quality levels.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this document where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

* 4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this document shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirement in the document shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the

Source: https://assist.dla.mil -- Downloaded: 202610-21T22:02Z
Check the source to verify that this is the currentversion before use.

contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

* 4.1.2 Responsibility for dimensional requirements. Unless otherwise specified in the contract or purchase order, the contractor is responsible for assuring that all specified dimensions have been met. When dimensions cannot be examined on the end item, inspection shall be made at any point or at all points in the manufacturing process necessary to assure compliance with all dimensional requirements.

4.1.3 Certificates of compliance. When certificates of compliance are submitted, the Government reserves the right to inspect such items to determine the validity of the certification.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).

4.3 First article inspection. When a first article is required (see 6.2), it shall be examined for the defects specified in 4.4.3 and 4.4.4. The presence of any defect shall be cause for rejection of the first article.

4.4 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.4.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this document or applicable purchase document.

4.4.2 In-process inspection. Inspection of sub-assemblies shall be made to ascertain that construction details which cannot be examined in the finished product are in accordance with specified requirements. The Government reserves the right to exclude from consideration for acceptance, any material or service for which in-process inspection has indicated nonconformance.

* 4.4.3 End item visual examination. The end item shall be examined for the defects listed in table II. The lot size shall be expressed in units of covers with sling. The sample unit shall be one cover with sling. The inspection level shall be II and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 2.5 for major defects and 6.5 for total (major and minor combined) defects.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:02Z
Check the source to verify that this is the current version before use.

TABLE II. End item visual defects

Examine	Defect	Classification	
		Major	Minor
Cloth, nylon	Hole, cut, tear, smash, open place, or broken or missing yarn clearly visible at normal inspection distance, approximately 3 feet	X	
	Shade bar, fine or course filling bar, or abrasion mark		X
Cloth, acrylic fiber pile	Any cut, hole, or tear	X	
Webbing and tape	Frayed or scalloped edges; not firmly and tightly woven	X	
	Multiple floats		X
	Any cut, hole, tear, or smash	X	
Tape	Abrasion mark, slub, or broken end or pick	X	
Webbing	Abrasion mark, slub, or broken end or pick		X
Hardware	Broken or malformed, corroded areas, burrs, or sharp edges (unless otherwise classified herein)	X	
	Any required component improperly installed causing failure to serve intended purpose (unless otherwise classified herein)	X	
	Finish omitted or not as specified:		
	- on steel components	X	
	- on brass or aluminum components		X
	Size or type not as specified (unless otherwise classified herein)	X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:02Z
Check the source to verify that this is the current version before use.

TABLE II. End item visual defects - Continued

Examine	Defect	Classification	
		Major	Minor
Fastener, plastic	Not as specified	X	
	Broken, cracked, chipped, malformed, failing to serve intended purpose, burr, sharp edge, or flash	X	
	Not attached as specified	X	
	Color and finish not as specified		X
	Not functioning, failing to effect a secure closure or open freely	X	
Eyelet, aluminum	Installed with scored side on outside of cover	X	
	Not set with a scored setting	X	
	Insecurely clinched; clinched excessively tight cutting fabric	X	
Open seam	1/2 inch or less		X
	More than 1/2 inch	X	
NOTE:	A seam shall be classified as open when one or more stitches joining a seam are broken or when two or more continuous skipped or run-off stitches occur.		
Raw edge (on edge required to be finished)	More than 1/2 inch when securely caught in stitching		X
NOTE:	Raw edge not securely caught in stitching shall be classified as open seam.		
Run-offs (see open seam)			
Seam and stitch type	Wrong seam or stitch type	X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:02Z
Check the source to verify that this is the current version before use.

TABLE II. End item visual defects - Continued

Examine	Defect	Classification	
		Major	Minor
Stitch tension	Loose tension, resulting in a loose top or bobbin thread		X
	Tight tension, resulting in puckering of fabric on seams		X
Stitches per inch (except on bartack)	Three or more stitches less than minimum specified	X	
	One or two stitches less than minimum specified		X
	One or more stitches in excess of maximum specified		X
	NOTE: Variation in the number of stitches per inch caused by the operator's speeding up the machine and pulling the fabric in order to sew over heavy places or in turning corners shall be classified as follows: a. Within the minor defect classification - no defect b. Within the major defect classification - minor defect		
Bartacks	One or both bartacks omitted	X	
	Any bartack not as specified or not in specified location		X
	Number of stitches not as specified		X
Stitching margin or gage of stitching	Not as specified		X

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:02Z
Check the source to verify that this is the current version before use.

TABLE II. End item visual defects - Continued

Examine		Defect	Classification	
			Major	Minor
Stitching end on stitch type 301		Not backstitched or secured as specified (except where ends are held down by other stitching or turned under in a hem)	X	
Thread breaks		Not overstitched as specified		X
	NOTE:	Thread breaks not backstitched or not overstitched shall be classified as open seams.		
Boxstitching and "W" stitching		Dimensions of boxstitching less than specified by more than 1/8 inch		X
		Height of "W" stitching less than specified by more than 1/8 inch		X
Cleanness		Grease or oil stains clearly noticeable; thread ends not trimmed to 1/4 inch maximum length		X
Components and assembly		Any component omitted or not as specified, or required operation omitted (unless otherwise classified herein)	X	
		Any mend, darn, patch, or splice	X	
		One or more rows of required stitching omitted	X	
		Needle chews	X	
Dee ring chape		Ends not abutted by:		
		- more than 1/4 inch	X	
		- more than 1/8 inch but not more than 1/4 inch		X

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:02Z
Check the source to verify that this is the current version before use.

TABLE II. End item visual defects - Continued

Examine	Defect	Classification	
		Major	Minor
Pocket and pocket flap	Omitted, not as specified, or not in specified location	X	
	Pocket darts omitted or positioned more than 3/8 inch from edge		X
Body reinforcement	Omitted, not as specified, or not in specified location	X	
Binding	Edge of binding not turned under and stitched as specified		X
	Loosely applied		X
	End of binding not finished as specified		X
Pile lining	Pile lining not stitched as specified to body of cover prior to closing operation		X
Marking	Omitted, incorrect, illegible, misplaced, or size of characters not as specified		X

* 4.4.4 End item dimensional examination. The end item shall be examined for the defects listed in table III. The lot size shall be expressed in units of finished covers with sling. The sample unit shall be one finished cover with sling. The inspection level shall be S-3 and the AQL, expressed in terms of defects per hundred units, shall be 2.5 for major defects and 10.0 for total major and minor defects.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:02Z
Check the source to verify that this is the current version before use.

TABLE III. End item dimensional defects

Examine	Defect	Classification	
		Major	Minor
Dimensions (overall)			
Height	Less than 6 1/2 inches	X	
	Less than 6 5/8 inches, but not less than 6 1/2 inches		X
	More than 6 7/8 inches		X
Length	Less than 6 3/4 inches	X	
	Less than 6 7/8 inches, but not less than 6 3/4 inches		X
	More than 7 1/8 inches		X
Width	Less than 3 1/4 inches	X	
	Less than 3 3/8 inches, but not less than 3 1/4 inches		X
	More than 3 5/8 inches		X

4.4.5 Packaging examination. The fully packaged end items shall be examined for the defects listed below. The lot size shall be expressed in units of shipping containers. The sample unit shall be one shipping container fully packaged. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 2.5.

Examine	Defect
Marking (exterior and interior)	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application
Materials	Any component missing, damaged, or not as specified

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:02Z
Check the source to verify that this is the current version before use.

Examine	Defect
Workmanship	Inadequate application of components, such as incomplete sealing or closure of flap, improper taping, loose strapping, or inadequate stapling Bulged or distorted container
Content	Number per container is more or less than required Number of covers per bundle is more or less than specified 1/

1/ For this defect, one bundle shall be examined from each shipping container in the sample.

4.4.6 Palletization examination. The fully packaged and palletized end items shall be examined for the defects listed below. The lot size shall be expressed in units of palletized unit loads. The sample unit shall be one palletized unit load, fully packaged. The inspection level shall be S-1 and the AQL, expressed in terms of defects per hundred units, shall be 6.5.

Examine	Defect
Finished dimensions	Length, width, or height exceeds specified maximum requirement
Palletization	Pallet pattern not as specified Load not bonded as specified
Weight	Exceeds maximum load limits
Marking	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application

5. PACKAGING

5.1 Preservation. Preservation shall be level A or Commercial, as specified (see 6.2).

5.1.1 Level A. Each cover shall have the sling assembly neatly folded or rolled and placed inside. The cover flaps and keepers shall be closed. Two such covers shall be placed together with fronts facing, reversed top to bottom and smoothly flattened. Ten covers shall be evenly stacked and then securely cross-tied with cotton tape or twine to form a bundle measuring approximately 9 by 8 by 8 inches.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:02Z
Check the source to verify that this is the current version before use.

* 5.1.2 Commercial. Covers shall be preserved in accordance with ASTM D 3951.

5.2 Packing. Packing shall be level A, B, or Commercial, as specified (see 6.2).

* 5.2.1 Level A packing. One hundred and twenty covers, preserved as specified in 5.1, shall be packed in a fiberboard shipping container conforming to style RSC-L, grade V2s of PPP-B-636. The inside of each fiberboard container shall be fitted with a box liner conforming to type CF, class weather-resistant, variety DW, grade V15c of PPP-B-636. Covers, unit packed level A, shall be packed flat, three in length, two in width, and two in depth within a shipping container. Inside dimensions of each shipping container shall be approximately 24 1/2 inches in length, 18 1/2 inches in width, and 16 inches in depth. Approximate dimensions are furnished as a guide only. Each container shall have the contents completely covered on the top and bottom with a sheet of 30-pound minimum basis weight kraft paper conforming to A-A-203. Each fiberboard container shall be closed in accordance with method III, waterproofed in accordance with method V, and reinforced in accordance with the appendix of PPP-B-636, except that the inspection shall be in accordance with 4.4.5. Shipping containers shall be arranged in unit loads in accordance with MIL-L-35078 for the type and class of load specified (see 6.2). Strapping shall be limited to nonmetallic strapping, except for type II, class F loads.

* 5.2.2 Level B packing. One hundred and twenty covers, preserved as specified in 5.1, shall be packed in a fiberboard shipping container conforming to style RSC-L, type CF (variety SW) or SF, class domestic, grade 275 of PPP-B-636. The inside of each fiberboard container shall be fitted with a box liner conforming to class domestic, variety DW, grade 275 of PPP-B-636. Covers, unit packed level A, shall be packed flat, three in length, two in width, and two in depth within a shipping container. Inside dimensions of each shipping container shall be approximately 24 1/2 inches in length, 18 1/2 inches in width, and 16 inches in depth. Approximate dimensions are furnished as a guide only. Each container shall have the contents completely covered on the top and bottom with a sheet of 30-pound minimum basis weight kraft paper conforming to A-A-203. Each shipping container shall be closed in accordance with method II as specified in the appendix of PPP-B-636, except that the inspection shall be in accordance with 4.4.5.

5.2.2.1 Weather-resistant shipping containers. When specified (see 6.2), the shipping container shall be a grade V3c, V3s, or V4s fiberboard box fabricated in accordance with PPP-B-636 and closed in accordance with method III as specified in the appendix of PPP-B-636, except that the inspection level shall be in accordance with 4.4.5.

Source: https://assist.dla.mil -- Downloaded: 202610-21T22:02Z
Check the source to verify that this is the current version before use.

* 5.2.3 Commercial packing. Covers, preserved as specified in 5.1, shall be packed in accordance with ASTM D 3951.

5.3 Palletization. When specified (see 6.2), covers, packed as specified in 5.2.2 and 5.2.3, shall be palletized on a 4-way entry pallet in accordance with load type Ia of MIL-STD-147. Pallet types shall be type I (4-way entry), type IV or type V in accordance with MIL-STD-147. Pallets shall be fabricated from wood groups I, II, III, or IV of MIL-STD-731. Each prepared load shall be bonded with primary and secondary straps in accordance with bonding means K and L or film bonding means O or P. Pallet pattern shall be number 90 in accordance with the appendix of MIL-STD-147.

* 5.4 Marking. In addition to any special marking required by the contract or purchase order, shipping containers and palletized unit loads shall be marked in accordance with MIL-STD-129 or ASTM D 3951, as applicable.

6. NOTES

6.1 Intended use. The cover is designed to serve as a protective carrier for the 2-quart collapsible water canteen (MIL-C-43603).

6.2 Ordering data. Acquisition documents should specify the following:

a. Title, number, and date of this document.
b. When a first article is required (see 3.2, 4.3, and 6.3).
c. Selection of applicable levels of preservation and packing (see 5.1 and 5.2).
d. Type and class of unit load required (see 5.2.1).
e. When weather-resistant grade fiberboard shipping containers are required for level B packing (see 5.2.2.1).
f. When palletization is required (see 5.3).

6.3 Standard sample. For access to samples, address the contracting activity issuing the invitation for bids.

6.4 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of FAR 52.209. The first article should be a preproduction sample. The contracting officer should specify the appropriate type of first article and the number of units to be furnished. The contracting officer should include specific instructions in all acquisition instruments regarding arrangements for selection, inspection, and approval of the first article.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:02Z
Check the source to verify that this is the current version before use.

6.5 Recycled material. It is encouraged that recycled material be used when practical as long as it meets the requirements of this document (see 3.3).

6.6 Die, eyelet, clinching. Sources of supply of the clinching eyelet die are PCI Group, J.C. Rhodes Division, P.O. Box B-976, New Bedford, MA 02741 and Stimpson Co., Inc., Bayport, NY 11705.

* 6.7 Subject term (key word) listing.

Canteen
Carrier, water canteen
Cover, water canteen

6.8 Changes from previous issue. The margins of this document have been marked with an asterisk (*) to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content as written, irrespective of the marginal notations and relationship to the last previous issue.)

Custodians:

Army - GL
Navy - NU

Review activity:

Army - MD

User activities:

Navy - MC
Air Force - 82

Preparing activity:

Army - GL

Project No. 8465-0940

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:02Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

US Army Natick Research, Development, and
Engineering Center
Natick, MA 01760-5014

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300
STRNC-ES

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Natick Research, Development,
and Engineering Center
ATTN: STRNC-ES
Box 14A
Natick, MA 01760-5014

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:02Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-C-43689C	Cover, Water Canteen, 2-Quart, Collapsible (With Pile Lining)

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

NATICK OP, 1 Apr 84

Source: https://assist.dla.mil -- Downloaded: 202610-21T22:02Z
Check the source to verify that this is the current version before use.