MIL-F-43695B
15 September 1987
SUPERSEDING
MIL-F-43695A(GL)
1 August 1974

MILITARY SPECIFICATION

FRAME SECTIONS, TENT, FRAME TYPE, EXPANDABLE

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This document covers the frame sections of the expandable frame type tent.

1.2 Classification. Frame sections shall be classified as follows (see 6.2):

End section.
Expandable section.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

* 2.1.1 Documents. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

FEDERAL

V-T-285 - Thread, Polyester
QQ-A-200/3 - Aluminum Alloy, 2024, Rod, Bar, Shapes, Tube, and Wire, Extruded.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: U.S. Army Natick Research, Development and Engineering Center, Natick, MA 01760-5014 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 8340

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.
Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:03Z
Check the source to verify that this is the current version before use.

QQ-A-200/8 - Aluminum Alloy 6061, Bar, Rod, Shapes, Tube and Wire, Extruded.
QQ-A-200/9 - Aluminum Alloy 6063, Bar, Rod, Shapes, Tube and Wire, Extruded.
QQ-A-225/6 - Aluminum Alloy 2024, Bar, Rod and Wire; Rolled, Drawn or Cold Finished.
QQ-A-225/8 - Aluminum Alloy 6061, Bar, Rod, Wire and Special Shapes; Rolled, Drawn or Cold Finished.
QQ-A-250/11 - Aluminum Alloy 6061, Plate and Sheet.
QQ-A-601 - Aluminum Alloy Sand Castings.
QQ-S-763 - Steel Bars, Wire, Shapes and Forgings, Corrosion-Resisting.
TT-E-529 - Enamel, Alkyd, Semigloss.
TT-P-1757 - Primer Coating, Zinc Chromate, Low-Moisture-Sensitivity.
WW-T-700/6 - Tube, Aluminum Alloy, Drawn, Seamless, 6061.
PPP-B-601 - Boxes, Wood, Cleated-Plywood.
PPP-B-640 - Boxes, Fiberboard, Corrugated, Triple-Wall.

MILITARY

MIL-C-496 - Clips, End, Strap.
MIL-W-530 - Webbing, Textile, Cotton, General Purpose, Natural or in Colors.
MIL-B-543 - Buckles, Tongueless and Web Strap.
MIL-W-44049 - Webbing, Textile and Tape, Textile, Polypropylene, General Purpose, Natural or in Colors.
MIL-C-5541 - Chemical Conversion Coatings On Aluminum and Aluminum Alloys.

STANDARDS

FEDERAL

FED-STD-751 - Stitches, Seams, and Stitching.

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.
MIL-STD-1186 - Cushioning, Anchoring, Bracing, Blocking, and Waterproofing, with Appropriate Test Methods.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:03Z
Check the source to verify that this is the current version before use.

DRAWINGS

U.S. ARMY NATICK RESEARCH, DEVELOPMENT, AND ENGINEERING CENTER

5-4-975	-	Frame sections, Tent, Frame Type, Expandable; End Section and Expandable Section Assemblies.
5-4-976	-	Frame sections, Tent, Frame Type, Expandable; Frame Details "A".
5-4-977	-	Frame sections, Tent, Frame Type, Expandable; Frame Details "B".
5-4-2302	-	Frame sections, Tent, Frame Type, Expandable; Foot Plate Assembly.
5-4-3331	-	Binding Strap Assembly.

(Copies of documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

* 2.2 Other publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted shall be those listed in the issues of the DODISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS shall be the issues of the nongovernment documents which are current on the date of the solicitation.

* AMERICAN SOCIETY OF TESTING AND MATERIALS (ASTM)

A 108	-	Cold-Finished Carbon Steel Bars and Shafting
A 569	-	Steel, Carbon (0.15 Maximum percent), Hot-Rolled-Sheet and Strip, Commercial Quality
D 3951	-	Standard Practice for Commercial Packaging

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

(Technical society and technical association documents are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

* 2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document shall take precedence. Nothing in this document, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

* 3.1 First article. When specified in the contract or purchase order, a sample shall be subjected to first article inspection (see 4.3, 6.2 and 6.3).

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:03Z
Check the source to verify that this is the current version before use.

* 3.2 Materials and components. The materials and components shall be as specified herein and as shown on the applicable drawings. Materials and components not definitely specified shall be of the quality normally used by the manufacturer provided the completed item complies with all the provisions of this document (see 6.4).

3.2.1 Aluminum Alloys.

* 3.2.1.1 Casting. Aluminum alloy castings shall conform to alloy number D 712.0 or 713.0, F or T5 temper of QQ-A-601.

3.2.1.2 Plate and sheet, 6061. Aluminum alloy 6061 plate and sheet shall conform to temper T6 of QQ-A-250/11.

3.2.1.3 Bar, 6061. Aluminum alloy 6061 bar shall conform to temper T6 of QQ-A-225/8.

3.2.1.4 Bar and rod, 2024. Aluminum alloy 2024 bar and rod shall conform to temper T4 of QQ-A-225/6 or QQ-A-200/3.

3.2.1.5 Shapes, 6063. Aluminum alloy 6063 shapes shall be extruded conforming to temper T5 of QQ-A-200/9.

3.2.1.6 Tube, 6061. Aluminum alloy 6061 tube shall conform to temper T6 of QQ-A-200/8 or WW-T-700/6.

3.2.2 Steel.

* 3.2.2.1 Sheet, carbon. Carbon steel sheet shall conform to commercial quality, hot rolled of ASTM A 569.

* 3.2.2.2 Bar, carbon. Carbon steel bar shall conform to ASTM A 108 in the grade designations as specified on applicable drawings.

3.2.2.3 Bar, corrosion-resisting. Corrosion-resisting steel round bar shall conform to class 304, condition A, cold finished of QQ-S-763.

* 3.2.3 Buckle, double bar with lip. The double bar buckle with lip shall conform to 1-inch, No. 789 steel Waterbury buckle or equal (see 6.5 and Drawing 5-4-3331).

* 3.2.4 Webbing. Webbing shall conform to type IIb, class 4, Olive Drab 7, size 1 inch of MIL-W-530 or MIL-W-44049.

3.2.5 Primer. Primer shall conform to composition G or L, as applicable, color Y of TT-P-1757.

3.2.6 Enamel. Enamel shall conform to either class A or B, composition G or L, as applicable, Olive Drab color No. 24087 of TT-E-529.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:03Z
Check the source to verify that this is the current version before use.

* 3.2.7 Clip, end. The end clip shall conform to type I, class 1, size 1 inch of MIL-C-496.

* 3.2.8 Thread, polyester. Polyester thread shall conform to type I, class 1, subclass B, Olive Drab S-1 (CA 66022), and thread size F of V-T-285.

3.3 Alternate components. Components offered as equivalent to components specified in this document and on the referenced drawings as a specific manufacturer's part number or equal shall be functionally equal to the manufacturer's part number identified as of equal or better quality. The incorporation and inclusion of such a component in the design of the specified end product shall not require modification or change to any other specified component, and shall not reduce ease of maintenance to it or any other components, unless such modification or change is specifically approved by the contracting officer. Prior to manufacture of the first article, or if none is required, prior to commencing production, the contractor shall submit for the contracting officer's approval, a list identifying each proposed alternate component, together with proof that each listed component complies with requirements specified herein. The contracting officer, at his option, may require a physical sample of the proposed substitution. Approval of the submitted listing, together with necessary supporting data, authorizes the commencement of first article or production manufacture, as applicable, and does not relieve the contractor of the responsibility that these components perform in accordance with specified requirements when incorporated into the end product.

3.4 Design. The frame sections shall be designed to provide a 16 foot wide by 8 foot 6 inch high tent frame. The frame shall be expandable in length by increasing the number of expandable sections. The end section shall provide for the first 8 foot length of frame. Each expandable section shall provide for an additional 8 foot length of frame.

* 3.5 Construction. Construction of the frame sections shall conform to Drawings 5-4-975, 5-4-976, 5-4-977, 5-4-2302, and as specified herein. The frame sections shall be capable of being erected and the stud (item 7-6) shall be capable of being turned within the pad (item 7-5) by hand operation without having to use a tool for force. Where rivets are used as hinge pins (items 7-10 and 7-11), the set of the rivets shall be such as to allow for ease of rotation. The diagonal brace (item 7-4) and shackle brace (item 7-7) shall be capable of being rotated by hand operation. Heating of the hinge pin (item 8) is allowed to facilitate upsetting the ends of the hinge pin securely into the countersink of (item 3-6) and (item 3-7) so as to prevent hinge pin from becoming loose and disengaged.

3.5.1 Welding. All welding shall be sound, smooth and uniform.

3.5.2 Riveting. All rivets shall be securely set.

3.5.3 Castings. Castings shall be clean and free from pits, blowholes and scale.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:03Z
Check the source to verify that this is the current version before use.

* 3.5.4 Stitching. Stitch type shall be 301, 5 to 7 stitches per inch in accordance with FED-STD-751. Box stitching shall be free of any thread break.

3.6 Finish. Interior surfaces of rectangular tubes, where slotted or diagonally cut at end, and shank of through rivets need not be primed or enameled.

3.6.1 Cleaning and treatment. Prior to assembly, all completely fabricated metal components of the frame sections shall be thoroughly cleaned and exterior surfaces of aluminum alloy shall be prepared for painting in accordance with class 1A treatment of MIL-C-5541.

* 3.6.2 Priming. After cleaning and treatment, as applicable, and prior to assembly, exterior surfaces of metal components including chains, rings, screws, plus both sides of steel eave and ridge gusset-plates and header end plates, shall be completely coated with primer specified in 3.2.6 except the shank of the quick release pin shall be free of primer.

3.6.3 Enameling. After the primer has been allowed to dry, the exterior surfaces of the assembled frame section components shall be completely coated with enamel specified in 3.2.7 except the shank of the quick release pin shall be free of enamel. The finish coating shall not be wet or tacky and shall be continuous and uniform, i.e., free of sag, run, pinhole, blister, wrinkle, area of thin or no film, scratch or scuff, and foreign matter imbedded in finish. The contractor shall touch up areas of finish damaged during flexing of movable joints.

3.7 Marking for identification. The lower segment of each side arch assembly having the binding strap shall be permanently and distinctly stamped or marked for identification. The letters "U.S." shall be in characters a minimum of one inch in height. The name of the manufacturer or brand or mark of such known character as to make the source of manufacture determinable and the number and year of contract shall be in characters a minimum of one-half inch in height.

* 3.8 Workmanship. All components of the finished frame sections shall not be bent out of shape and shall be free from split, puncture, fracture, twist, malformation, sharp edge and burr. Roll of a rivet shall be free from more than one split. Welds shall also be free from burn through area, pits, slag inclusion, porosity, crack, flash and excess flux deposit. Rivets shall be free from looseness.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:03Z
Check the source to verify that this is the current version before use.

herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this document where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

* 4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this document shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the document shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

* 4.1.2 Responsibility for dimensional requirements. Unless otherwise specified in the contract or purchase order, the contractor is responsible for assuring that all specified dimensions have been met. When dimensions cannot be examined on the end item, inspection shall be made at any point, or at all points in the manufacturing process necessary to assure compliance with all dimensional requirements.

4.2 Classification of inspection. The inspection requirements specified herein are classified as follows:

(a) First article inspection (see 4.3).
(b) Quality conformance inspection (see 4.4).

4.3 First article inspection. When a first article is required (see 3.1), it shall be examined for the defects specified in table II, 4.4.4 and 4.4.5. The presence of any defect shall be cause for rejection of the first article.

4.4 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.4.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this document or applicable purchase document.

* 4.4.2 In-process inspection. Inspection shall be made of the operations and requirements listed in table I to establish conformance with the specified requirements. Whenever a nonconformance is noted, correction shall be made to the items affected and to the operation.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:03Z
Check the source to verify that this is the current version before use.

TABLE I. In-process inspection

Requirement or operation	Requirement paragraph
Welds are sound, smooth, uniform and free from burn through area, pits, slag inclusion, porosity, crack, fracture, flash and excess flux deposit.	3.5.1 and 3.8
Castings are clean and free from pits, blowholes and scale.	3.5.3
All completely fabricated metal components are clean and exterior surfaces of aluminum are treated prior to assembly.	3.6.1
Exterior surfaces of metal components including chains, rings, screws, plus both sides of steel eave and ridge gusset plates and header end plates (except shaft of quick release pin) are primed before assembly.	3.6.2
Enamel is not applied before the primer has dried.	3.6.3

* 4.4.3 End item visual examination. The end item shall be examined for the defects listed in table II. The lot size shall be expressed in units of frame sections of one type only. The sample unit shall be one completely fabricated frame section. The inspection level shall be I and the AQL, expressed in terms of defects per hundred units, shall be 15 for major defects, and 65 for total (major and minor combined) defects.

TABLE II. Classification of defects

Examine	Defect	Classification Major	Minor
Finish	Color of finish is not as specified.		X
	Not finished (except shaft of quick release pin).	X	
	Shaft of quick release pin has been coated with primer or enamel.		X
	Not continuous and not uniform (e.g., sag, pinhole, blister, wrinkle, foreign matter imbedded in finish, wet or tacky finish.		X
	Any run exceeding 3 inches in length.	X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:03Z
Check the source to verify that this is the current version before use.

TABLE II. Classification of defects (cont'd)

Examine	Defect	Classification Major	Minor
Finish (cont'd)	Area of no film:		
	- bare metal showing in area more than 3 square inches.	X	
	- bare metal showing in area 3 square inches or less.		X
	NOTE: Areas of no film on interior surfaces of rectangular tubes, where slotted or diagonally cut at end, and shank of through rivets are allowed. Areas of no film of 1/4 inch or less are allowed on inside of boss, purlin end fittings and in area of brace pad adjacent to brace stud. Area of no enamel 1/16 inch wide is allowed at junction of riveted assemblies to tube.		
	Area of thin film:		
	- primer shows through in area 9 square inches or more.	X	
	- primer shows through in area of less than 9 square inches.		X
	Scratch or scuff exposing bare metal:		
	- 12 inches or more in longest dimension.	X	
	- less than 12 inches in longest dimension.		X
	NOTE: Defects in finish attributable to flexing of movable joints during examination will not be scored as a defect. However, the supplier shall touch up areas of finish damaged during flexing of movable joints.		
Construction and Workmanship	Any part or component not fabricated of applicable referenced materials.	X	
	Any component or part missing.	X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:03Z
Check the source to verify that this is the current version before use.

LD type I, class 1. X 1/2-8 thread, polyester, polyester thread shall conform

TABLE II. Classification of defects (cont'd)

Examine	Defect	Classification Major	Minor
Construction and Workmanship (cont'd)	Any component not fabricated as specified, e.g.:		
	- stud not capable of being turned within the pad by hand operation without having to use a tool for force.		X
	- end of hinge pin (item 8) not securely set into countersink of eave gusset plate assembly	X	
	Any component split, punctured, fractured, twisted, malformed, bent out of shape (expect end plate of header assembly, rivet and dowel pin).	X	
	End plate of header assembly is bent out of shape to a degree that it will not function.	X	
	End plate of header assembly is bent out of shape but will function.		X
	Sharp edge or burr.		X
Welding	Missing.	X	
	Not sound, not smooth, not uniform or has burn through area, pits, slag inclusion, porosity, crack, fracture, flash or excess flux deposit.		X
Riveting	Loose rivet.		X
	Set of rivet is such that the diagonal brace (item 7-4) or shackle brace (item 7-7) is not capable of being rotated by hand operation.	X	
Casting	Not clean or has pits, blowholes and scale.		X
Workmanship (rivet and dowel pin)	Split, puncture, fracture or bent out of shape.		X
	Roll of a rivet contains more than one split.		X

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:03Z
Check the source to verify that this is the current version before use.

TABLE II. Classification of defects (cont'd)

Examine	Defect	Classification Major	Minor
Marking for identification	Missing, illegible, incorrect, or improper size or location.		X
Stitching	Not stitch type specified.		X
	Evidence of a thread break.		X

* 4.4.4 End item dimensional examination. Examination shall be made of the end item for compliance with the dimensions marked with an asterisk on the drawings. Any dimension not within the specified tolerance shall be classified as a defect. The lot size shall be expressed in units of frame sections of one type only. The sample unit shall be one frame section. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 15.

4.4.5 Examination of frame sections for defects during erection. The completely fabricated frame sections shall be examined, during erection and striking, for the defects listed in table III. The lot size shall be expressed in units of frame sections of one type only. The sample unit shall be one completely fabricated frame section. The inspection level shall be S-1 and the AQL, expressed in terms of defects per hundred units, shall be 6.5.

TABLE III. Examination for defects in erection

Examine	Defect
Assembly	Any assembly that cannot be connected or joined with companion assembly, i.e., assembling requires realignment of parts, drilling or enlargement of holes, use of drift pin or other mechanical means.
	Side arch becomes disassembled from roof arch due to disengagement of hinge pin.
	Assembly hole missing or misplaced.
	Special tool is required to effect assembly.
	Buckled, bent out of shape or otherwise damaged.
	Any component missing (check all clevis bolts, self locking nuts and quick release pins).
	Component is too loose or does not fit properly with mating components.
	Component is out of alignment.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:03Z
Check the source to verify that this is the current version before use.

TABLE III. Examination for defects in erection (cont'd)

Examine	Defect
Assembly (cont'd)	NOTE: The supplier shall touch up areas of finish damaged during erection and disassembly of the frame sections.

* 4.4.6 Packaging examination. The fully packaged end items shall be examined for the defects listed below. The lot size shall be expressed in units of shipping containers. The sample unit shall be one shipping container fully packaged. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 2.5.

Examine	Defect
Marking	Omitted; incorrect; illegible; of improper size, location, sequence or method of application.
Materials	Any component missing, damaged or not as specified.
Workmanship	Bulged or distorted container. Component of frame section missing. Wrapping is missing on foot plates or side arch at the joint of the roof arch. Combined side arch and roof arch assembly not folded or not secured with the binding strap. Ends of folded arch assembly not wrapped or not cushioned to prevent damage to finish. Shackle brace end of the diagonal brace or the strap braces of purlin not wrapped. Wrapped diagonal braces not folded toward each other or not secured to the purlin. Quick release pins of header not secured inside the header end. Skid missing when specified.

5. PACKAGING

* 5.1 Preservation. Preservation shall be level A or Commercial as specified (see 6.2).

5.1.1 Level A. Each arch assembly of the frame section shall have the foot plates wrapped, side arch wrapped at the joint of the roof arch and shall be completely folded and secured with the binding strap provided. The ends of the folded assembly shall be wrapped or cushioned to prevent damage to finish. The shackle brace end of the diagonal braces and thestrap braces of each purlin

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:03Z
Check the source to verify that this is the current version before use.

shall be wrapped. The wrapped diagonal braces shall be folded toward each other and secured to the respective frame section purlins with reusable cloth tape or retaining straps. The pins of the header shall be secured inside the header end.

* 5.1.2 Commercial. Components of each frame section shall be preserved in accordance with ASTM D 3951.

5.2 Packing. Packing shall be level A, B or Commercial as specified (see 6.2).

5.2.1 Level A Packing.

5.2.1.1 End section. One complete end section consisting of 2 arches, 2 headers and 5 purlins, preserved as specified in 5.1 shall be packed in a close-fitting box conforming to overseas type style A, type 3 load of PPP-B-601. Each box shall be provided with skids fabricated in accordance with the requirements of the box document. Cushioning material shall be used to prevent damage to the finish of the frame. The contents of each box shall be cushioned, anchored, braced and blocked in accordance with MIL-STD-1186. Each box shall be closed and reinforced with strapping in accordance with the appendix of the applicable box document.

5.2.1.2 Expandable section. One complete expandable section consisting of 1 arch, 1 header and 5 purlins preserved as specified in 5.1, shall be packed in the same manner as specified in 5.2.1.1.

5.2.1.3 Components when procured separately. Components of like description only, preserved as specified in 5.1, shall be packed in the same manner as specified in 5.2.1.1, except the quantities of each component shall be as specified. The quantities per shipping container shall be: 10 arch assemblies, 70 header assemblies, or 70 purlin assemblies.

* 5.2.2 Level B Packing. One complete end section or expandable section preserved as specified in 5.1.1, shall be packed in the same manner as specified in 5.2.1, except that the box shall conform to domestic type of PPP-B-601 or style C, No. 3 or 4 end, class 2 of PPP-B-640 provided with handling base. The handling base shall be made with a minimum of three nominal 1 x 6 inch longitudinal deck boards secured to three nominal 2 x 6 inch skids.

5.2.2.1 Components when procured separately. Components of like description only, preserved as specified in 5.1, shall be packed in the same manner as specified in 5.2.1.1, except the quantities of each component shall be as specified. The quantities per shipping container shall be: 10 arch assemblies, 70 header assemblies, or 70 purlin assemblies.

* 5.2.3 Commercial packing. Frame sections or components, preserved as specified in 5.1, shall be packed in accordance with ASTM D 3951.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:03Z
Check the source to verify that this is the current version before use.

* 5.3 Marking. In addition to any special marking required by the contract or purchase order, shipping containers shall be marked in accordance with MIL-STD-129 or ASTM D 3951, as applicable.

6. NOTES

6.1 Intended use. The frame sections covered by this document are intended to be used to support the expandable frame type tent of MIL-T-43492. One end section and one expandable section are required to support the first 16 foot length of tent. Two additional expandable sections will be required to support each additional 16 foot length of tent desired.

6.2 Ordering data. Acquisition documents should specify the following:

a. Title, number and date of this specification.
b. Section required, as applicable (see 1.2).
c. When a first article is required (see 3.1, 4.3, and 6.3).
d. Selection of applicable levels of preservation and packing (see 5.1 and 5.2).

* 6.3 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of FAR 52.209. The first article should be a preproduction sample. The contracting officer should specify the appropriate type of first article and the number of units to be furnished. The contracting officer should include specific instructions in all acquisition instruments regarding arrangements for selection, inspection, and approval of the first article.

* 6.4 Recycled material. It is encouraged that recycled material be used when practical as long as it meets the requirements of the document (see 3.2).

* 6.5 Commercial product. The Waterbury buckle No. 789 manufactured by the Waterbury Buckle Co., Waterbury, CT, has been found to meet the requirements specified in 3.2.3.

6.6 Subject term (key word) listing.

Frame sections
Shelters
Tents

6.7 Changes from the previous issue. The margins of this document have been marked with an asterisk (*) to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content as written irrespective of the marginal notations and relationship to the last previous issue.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:03Z
Check the source to verify that this is the current version before use.

Palletization Pallet pattern not as specified

Custodians:

Army - GL
Navy - NU
Air Force - 99

Review activities:

Air Force - 82
DLA - CT

User activities:

Navy - MC
Air Force - 45

Preparing activity:

Army - GL

Project No. 8340-0493

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:03Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

US ARMY NATICK RESEARCH
and DEVELOPMENT CENTER
ATTN: STRNC-ES
Natick, MA 01760-5014

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Natick Research
and Development Center
ATTN: STRNC-ES
Natick, MA 01760-5014

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:03Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions - Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-F-43695B	Frame Sections, Tent, Frame Type Expandable

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR ☐ USER ☐ MANUFACTURER ☐ OTHER *(Specify)*: _____
b. ADDRESS *(Street, City, State, ZIP Code)*	

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

NATICK OP 20 Nov 84

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:03Z
Check the source to verify that this is the current version before use.