INCH-POUND

MIL-DTL-43695C
23 June, 2000

SUPERSEDING
MIL-F-43695B
15 September, 1987

DETAILED SPECIFICATION

FRAME SECTIONS, TENT, FRAME TYPE, EXPANDABLE

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the frame sections of the expandable frame type tent.

*1.2 Classification. The frames are provided in the following sections (see 6.2)

End section
Expandable section

2. APPLICABLE DOCUMENTS

*2.1 General. The documents listed in this section are specified in sections 3 and 4 of this specification. This section does not include documents cited in other sections of this specification or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all specified requirements documents cited in sections 3 and 4 of this specification, whether or not they are listed.

Beneficial comments (recommendations, additions, deletions, clarifications) and any pertinent data which may be of use in improving this document should be addressed to: Defense Supply Center Philadelphia, Clothing and Textiles Directorate, Attn: DSCP-CNR, 700 Robbins Ave., Philadelphia, PA 19111-5096 by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 8340

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:02Z
Check the source to verify that this is the current version before use.

2.2 Government documents.

2.2.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

SPECIFICATIONS

FEDERAL

V-T-285	- Thread, Polyester
TT-E-529	- Enamel, Alkyd, Semigloss
TT-P-1757	- Primer Coating, Zinc Chromate, Low-Moisture Sensitivity
WW-T-700/6	- Tube, Aluminum Alloy, Drawn, Seamless, 6061

MILITARY

MIL-C-496	- Clips, End Strap
MIL-W-530	- Webbing, Textile, Cotton, General Purpose, Natural or In Colors
MIL-W-44049	- Webbing, Textile and Tape, Textile, Polypropylene, Natural or In Colors
MIL-C-5541	- Chemical Conversion Coatings on Aluminum and Aluminum Alloys

(Unless otherwise indicated. copies of federal and military specifications, standards, and handbooks are available from the Document Automation and Production Service (DAPS), Bldg. 4D (DPM-DODSSP), 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

*2.2.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

SOCIETY OF AUTOMOTIVE ENGINEERS

SAE-AMS-QQ-S-763 - Steel Bars, Wire, Shapes and Forgings, Corrosion Resistant

(Applications for copies of referenced documents should be addressed to the Society of Automotive Engineers, 400 Commonwealth Drive, Warrendale, PA 15096-0001

DRAWINGS

U.S. ARMY BIOLOGICAL & CHEMICAL COMMAND

5-4-975	- Frame Sections, Tent, Frame Type, Expandable; End Section and Expandable Section Assemblies
5-4-976	- Frame Sections, Tent, Frame Type, Expandable; Frame Details “A”
5-4-977	- Frame Sections, Tent, Frame Type, Expandable; Frame Details “B”
5-4-2302	- Frame Sections, Tent, Frame Type, Expandable; Foot Plate Assembly
5-4-3331	- Binding, Strap Assembly

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:02Z
Check the source to verify that this is the current version before use.

(Copies of drawings are available from the U. S. Army Biological Chemical Command, ATTN: AMSSB-REO-S(N), NATICK, MA 01760-5017.)

*2.3 Non-Government publications. The following document(s) form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.2).

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

ASTM-A-108	- Cold-Finished Carbon Steel Bars and Shafting
ASTM-A-569	- Steel, Carbon (0.15 Maximum percent), Hot-Rolled-Sheet and Strip, Commercial Quality
ASTM-B26/B26M	- Aluminum-Alloy Sand Casting
ASTM-B-209	- Aluminum and Aluminum-Alloy Sheet and Plate
ASTM-B-211	- Aluminum and Aluminum-Alloy Bar, Rod and Wire
ASTM-B-221	- Aluminum and Aluminum-Alloy Bar Extruded Bars, Rods, Shapes and Tubes
ASTM-B-308	- Aluminum-Alloy 6061 –T6 Standard Structural Shapes
ASTM-D-1005	- Measurement of Dry Film Thickness of Organic Coating Using Micrometers
ASTM-D-6193	- Standard Practice for Stitches and Seams

(Applications for copies of referenced documents should be addressed to the American Society for Testing and Materials, 100 Barr Harbor Drive, West Conshohocken, PA 19426-2959.)

*2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification takes precedence. Nothing in this specification, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

*3.1 First article. When specified (see 6.2), a sample shall be subjected to first article inspection (see 4.2 and 6.2).

3.2 Materials and components. Materials and components shall be as specified herein and on the applicable drawings. Materials and components not definitely specified shall be of the quality normally used by the manufacturer provided the completed item complies with all the provisions of this document.

3.2.1 Aluminum alloys.

*3.2.1.1 Casting. Aluminum alloy castings shall conform to alloy number D 712.0 or 713.0, F or T5 temper of ASTM B26/B26M.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:02Z
Check the source to verify that this is the current version before use.

*3.2.1.2 Plate and sheet, 6061. Aluminum alloy 6061 plate and sheet shall conform to temper T6 of ASTM-B-209.

*3.2.1.3 Bar, 6061. Aluminum alloy 6061 bar shall conform to temper T6 of ASTM-B-211.

*3.2.1.4 Bar and rod, 2024. Aluminum alloy 2024 bar and rod shall conform to temper T4 of ASTM-B-211 or ASTM-B-221.

*3.2.1.5 Shapes, 6063. Aluminum alloy 6063 shapes shall be extruded conforming to temper T5 of ASTM-B-221.

*3.2.1.6 Tube, 6061. Aluminum alloy 6061 tube shall conform to temper T6 of ASTM-B-308 or WW-T-700/6.

3.2.2 Steel.

3.2.2.1 Sheet, carbon. Carbon steel sheet shall conform to commercial quality, hot rolled of ASTM-A-569.

3.2.2.2 Bar, carbon. Carbon steel bar shall conform to ASTM A 108 in the grade designations as specified on the applicable drawings.

*3.2.2.3 Bar, corrosion-resisting. Corrosion-resisting steel round bar shall conform to class 304, condition A, cold finished of SAE-AMS-QQ-S-763.

3.2.3 Buckle, double bar with lip. The double bar buckle with lip shall conform to Waterbury Buckle Co. (or equal) 1-inch, No 789 steel (see 6.5 and drawing 5-4-3331).

3.2.4 Webbing. Webbing shall conform to type IIb, class 4, camouflage green 483 size 1 inch of MIL-W-530 or MIL-W-44049.

3.2.5 Primer. Primer shall conform to composition G or L, as applicable, color Y of TT-P-1757.

3.2.6 Enamel. Enamel shall conform to either class A or B, composition G or L, as applicable Olive Drab color No. 20487 of TT-E-529.

3.2.7 Clip ends. The end clip shall conform to type I, class1, size 1 inch of MIL-C-496.

3.2.8 Thread, polyester. Polyester thread shall conform to type I, class 1, subclass B, camouflage green 483, thread size F of V-T-285.

3.3 Alternate components. Components offered as equivalent to components specified in this document and on the referenced drawings as a specific manufacturer's part number or equal shall be functionally equal to the manufacturer's part number identified as of equal or better quality. The incorporation and inclusion of such a component in the design of the specified end product shall not require modification or change to any other specified component and shall not reduce ease of maintenance to it or any other components, unless such modification or change is specifically approved by the contracting officer. Prior to manufacture of the first article, or if none is required, prior o commencing production, the contractor shall submit for the contracting officer's approval, a list identifying each proposed alternate component, together with proof that

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:02Z
Check the source to verify that this is the current version before use.

each listed component complies with requirements specified herein. The contracting officer, at his option, may require a physical sample of the proposed substitution. Approval of the submitted listing, together with necessary supporting data, authorizes the commencement of first article or production manufacture, as applicable, and does not relieve the contractor of the responsibility that these components perform in accordance with specified requirements when incorporated into the end product.

3.4 Design. The frame sections shall be designed to provide a 16 foot wide by 8 foot 6 inch high tent frame. The frame shall be expandable in length by increasing the number of expandable sections. The end section shall provide for the first 8 foot length of frame. Each expandable section shall provide for an additional 8 foot length of frame.

3.5 Construction. Construction of the frame sections shall conform to Drawings 5-4-975, 5-4-976, 5-4-977, 5-4-2302 and as specified herein. The frame sections shall be capable of being erected and the stud (item 7-6) shall be capable of being turned within the pad (item 7-5) by hand operation without having to use a tool for force. Where rivets are used as hinge pins (items 7-10 and 7-11), the set of the rivets shall be such as to allow for ease of rotation. The diagonal brace (item 7-4) and shackle brace (item 7-7) shall be capable of being rotated by hand operation. Heating of the hinge pin (item 8) is allowed to facilitate upsetting the ends of the hinge pin securely into the countersink of (item 3-6) and (item 3-7) so as to prevent hinge pins from becoming loose and disengaged.

3.5.1 Welding. All welding shall be sound, smooth and uniform.

3.5.2 Riveting. All rivets shall be securely set.

*3.5.3 Castings. Castings shall be clean and free from pits, blowholes flashing and scale.

*3.5.4 Stitching. Stitch type shall be 301, 5-7 stitches per inch in accordance with ASTM-D-6193.

3.6 Finish. Interior surfaces of rectangular tubes, where slotted or diagonally cut at end, and shank of through rivets need not be primed or enameled.

3.6.1 Cleaning and treatment. Prior to assembly, all completely fabricated metal components of the frame sections shall be thoroughly cleaned and exterior surfaces of aluminum alloy shall be prepared for painting in accordance with class 1A treatment of MIL-C-5541.

3.6.2 Priming. After cleaning and treatment, as applicable, and prior to assembly, exterior surfaces of metal components including chains, rings, screws, plus both sides of steel eave and ridge-gusset plates and header end plates shall be completely coated with primer specified in 3.2.6 except the shank of the quick release pin shall be free of primer.

3.6.3 Enameling. After the primer has been allowed to dry, the exterior surfaces of the assembled frame section components shall be completely coated with enamel specified in 3.2.7 except the shank of the quick release pin shall be free of enamel. The finished coating shall not be wet or tacky and shall be continuous and uniform, i.e., free of sag, run, pinhole, blister, wrinkle, area of thin or no film, scratch or scuff, and foreign matter imbedded in finish. The contractor shall touch up areas of finish damaged during flexing of movable joints.

*3.6.4 Epoxy powder coating. As an alternate to pretreatment and lacquering or enameling specified in 3.6.1 and 3.6.2 the surface of the frame shall be prepared and coated as follows:

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:02Z
Check the source to verify that this is the current version before use.

a. The surfaces shall be thoroughly cleaned and textured by blasting and/or tumbling using 30-60 grit steel shot. Prepared surfaces shall be kept clean and shall be epoxy coated within 8 hours after cleaning and texturizing.

b. The frames shall be finished with an electrodeposited epoxy powder coating. The epoxy coating shall conform to epoxy coatings produced by H. B. Fuller Co., or the O'Brien corporation, or equal (see 6.6 and 6.8).

c. The electrodeposited epoxy powder coating shall be baked on in accordance with commercial practices. The thickness of the coating shall be .003 ± .001 inch.

d. The final coating shall be smooth and uniform in appearance and shall be free from corrosion, blistering, peels, cracks or sags.

3.7 Marking for identification. The lower segment of each side arch assembly having the binding strap shall be permanently and distinctly stamped or marked for identification. The letters "U.S." shall be in characters a minimum of one inch in height. The name of the manufacturer or brand or mark of such known character as to make the source of manufacture determinable and the number and year of contract shall be in characters a minimum of one-half inch in height.

3.8 Workmanship. All components of the finished frame sections shall not be bent out of shape and shall be free from split, puncture, fracture, twist, malformation, sharp edge and burr. Roll of a rivet shall be free from more than one split. Welds shall also be free from burn through areas, pits, slag inclusion, porosity, crack, flash and excess flux deposit. Rivets shall be free from looseness.

*3.9 Recycled, recovered, or environmentally preferable materials. Recycled, recovered, or environmentally preferable materials should be used to the maximum extent possible provided that the material meets or exceeds the operational and maintenance requirements, and promotes economically advantageous life cycle costs.

4. VERIFICATION

4.1 Responsibility for dimensional requirements. Unless otherwise specified in the contract or purchase order, the contractor is responsible for ensuring that all dimensions specified in the component specifications have been met. When dimensions cannot be examined on the end item, inspection shall be made at any point, or at all points in the manufacturing process necessary to ensure compliance with all dimensional requirements.

4.1 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.2).
b. Conformance inspection (see 4.3).

4.2 First article inspection. When a first article is required (see 6.2) it shall be examined for the defects listed in 4.4.3 and 4.4.4 and tested as specified in 4.4. The erection/striking test (see 4.5.2) shall be performed for ten complete erect/strike cycles for the first article inspection only. Any nonconformance shall be cause for rejection of the first article.

4.3 Conformance inspection. Sampling for inspection shall be as specified in the contract or purchase order.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:02Z
Check the source to verify that this is the current version before use.

4.4.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified or qualified in this specification or applicable purchase document.

4.4.2 In-process inspection. Inspection shall be made of the operations and requirements listed in Table I to establish conformance with the specified requirements. Whenever nonconformance is noted, correction shall be made to the items affected and the operations.

Table I. In-process inspection.

Requirement or operation	Requirement paragraph
Welds are sound, smooth, uniform and free from burn through area, pits, slag inclusion porosity, crack, fracture flash and excess flux deposit.	3.5.1 and 3.8
Castings are clean and free from pits, blowholes, flashing and scale	3.5.3
All completely fabricated metal components are clean and exterior surfaces of aluminum are treated prior to assembly.	3.6.1
Exterior surfaces of metal components including chains, rings, screws, plus both sides of steel eave and ridge gusset plates and header end plates (except shaft of quick release pin) are primed before assembly.	3.6.2
Enamel is not applied before the primer has dried.	3.6.3

*4.4.3 End item visual examination. The end item shall be examined for the defects listed in Table II. The lot size shall be expressed in units of frame sections of one type only. The sample unit shall be one completely fabricated frame section. The inspection level shall be I.

TABLE II. Classification of defects

Examine	Defect	Classification Major	Minor
Finish	Color of finish is not as specified		201
	Not finished (except shaft of quick release pin)	101	
	Shaft of quick release pin has been coated with primer or enamel		202
	Not continuous or uniform (e.g., sag, pinhole, Blister, wrinkle, foreign matter imbedded in finish, wet or tacky finish		203
	Any run exceeding 3 inches in length	102	

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:02Z
Check the source to verify that this is the current version before use.

TABLE II. Classification of defects

Examine	Defect	Classification Major	Minor
Finish (continued)	Area of no film:		
	- bare metal showing in area more than 3 square inches	103	
	- bare metal showing in area 3 square inches or less		204
	Note: Areas of no film on interior surfaces of rectangular tubes, where slotted or diagonally cut at end, and shank of through rivets are allowed. Areas of no film of ¼ inch or less are allowed on inside of boss, purlin end fittings and in area of brace pad adjacent to brace stud. Area of no enamel 1/16 inch wide is allowed at junction of riveted assemblies to tube.		
	Area of thin film: primer shows through in area		
	9 square inches or more	104	
	- primer shows through in area less than 9 square inches		205
	Scratch or scuff exposing bare metal:		
	- 12 inches or more in longest dimension	105	
	- less than 12 inches in longest dimension		206
	Note: Defects in finish attributable to flexing of movable joints during examination will not be scored as a defect. However, the supplier shall touch up areas of finish damaged during flexing of movable joints. Minor shade variations resulting from touch up operations shall not be considered a defect.		
	Coating thickness not as specified (see 1/)	106	
Construction & workmanship	Any part of component not fabricated of applicable reference materials	107	
	Any component or part missing	108	
	Any component not fabricated as specified, e.g.:		
	- stud not capable of being turned within the pad by hand operation without having to use a tool for force		207
	- end of hinge pin (item 8) not securely set into countersink of eave gusset plate assembly	109	

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:02Z
Check the source to verify that this is the current version before use.

TABLE II. Classification of defects

Examine	Defect	Classification Major	Minor
	Any component split, punctured, fractured, twisted, malformed, bent out of shape (except end plate of header assembly, rivet and dowl pin)	110	
	End plate of header assembly is bent out of shape to a degree that it will not function	111	
	End plate of header assembly is bent out of shape but will function		208
	Sharp edge or burr		209
Welding	Missing	112	
	Not sound, not smooth, not uniform or has burn through area, pits, slag inclusion, porosity, crack, fracture, flash or excess flux deposit		210
Riveting	Loose rivet		211
	Set of rivet is such that the diagonal brace (item 7-4) or shackle brace (item 7-7) is not capable of being rotated by hand operation	113	
Casting	Not clean or has pits, blowholes flashing and scale		212
Workman-ship (rivet & dowel pin)	Split, puncture, fracture or bent out of shape		213
	Roll of a rivet contains more than one split		214
Marking for identification	Missing, illegible, incorrect or improper size or location		215
Stitching	Not stitch type specified		216
	Evidence of a thread break		217

1/ When the powder epoxy coating finishing method is used, it shall be tested in accordance with ASTM-D-1005.

*4.4.4 End item dimensional examination. Examination shall be made of the end item for compliance with the dimensions marked with an asterisk on the drawings. Any dimension not within the specified tolerance shall be classified as a defect. The lot size shall be expressed in units of frame sections of one type only. The sample unit shall be one frame section. The inspection level shall be S-2.

*4.4.5 Examination of frame sections for defects during erection. The completely fabricated frame sections shall be examined, during erection and striking, for the defects listed in Table III. The lot size shall be expressed in units of frame sections of one type only. The sample unit shall be one completely fabricated frame section. The inspection level shall be S-1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:02Z
Check the source to verify that this is the current version before use.

TABLE III. Examination for defects in erection

Examine	Defect
Assembly	Any assembly that cannot be connected or joined with companion assembly, i.e., assembling requires realignment of parts, drilling or enlargement of holes, use of drift pin or other mechanical means. Side arch becomes disassembled from roof arch due to disengagement of hinge pin. Assembly hole missing or misplaced. Special tool is required to effect assembly. Buckled, bent out of shape or otherwise damaged. Any component missing (check all clevis bolts, self locking nuts and quick release pins). Component is too loose or does not fit properly with mating components. Component is out of alignment. Note: The supplier shall touch up areas of finish damaged during the erection and disassembly of the frame sections.

*4.4.6 Packaging examination. The fully packaged end items shall be examined for marking, materials, workmanship and content defects.

5. PACKAGING

*5.1 Packaging. For acquisition purposes, the packaging requirements shall be as specified in the contract or order (see 6.2). When actual packaging of materiel is to be performed by DoD personnel, these personnel need to contact the responsible packaging activity to ascertain requisite packaging requirements. Packaging requirements are maintained by the Inventory Control Point's packaging activity within the Military Department or Defense Agency, or within the Military Department's System Command. Packaging data retrieval is available from the managing Military Department's or Defense Agency's automated packaging files, CD-ROM products, or by contacting the responsible packaging activity.

6. NOTES

*(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The frame sections tent are intended to be used to support the expandable frame type tent of MIL-T-43492. One end section and one expandable section are required to support the first 16 foot length of tent. Two additional expandable sections will be required to support each additional 16 foot length of tent desired.

*6.2 Acquisition requirements. Acquisition documents must specify the following:

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:02Z
Check the source to verify that this is the current version before use.

a. Title, number, and date of this specification.
b. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1.1 and 2.2).
c. Section required, as applicable (see 1.2).
d. When first article is required (see 3.1, 4.2 and 6.4).
e. Levels of preservation and packing (see 5.1).

6.3 Sample. For access to standard sample, address the contracting activity issuing the invitation for bids.

6.4 First article. When a first article is required, it will be inspected and approved under the appropriate provisions of FAR 52.209. The first article should be a preproduction sample. The contracting officer should specify the appropriate type of first article and the number of units to be furnished. The contracting officer should include specific instructions in all acquisition instruments regarding arrangements for selection, inspection, and approval of the first article.

*6.5 Commercial product. Waterbury Buckle No. 789 manufactured by ITT Waterbury Buckle, 952-T South Main St., Waterbury, CT, 06706 has been found to meet the requirements specified in 3.2.3.

*6.6 Manufacturers of epoxy powder paint products. Epoxy paint conforming to the requirements of 3.6.4 may be obtained from the following manufacturers:

H.B. Fuller Co.
North American Adhesives, Sealants
& Coatings Group
3530 Lexington Ave. N.
St. Paul, Minnesota 55110

O'Brien Powder Products, Inc.
9800 Genard Rd.
Houston, TX 77021

*6.7 Subject term (key word) listing.
Shelters

*6.8 Equal item. Prior to the use of an "or equal" item, the supplier will submit the item, with supporting data to the contracting officer for subsequent approval or disapproval by the responsible military agency.

6.9 Changes from previous issue. The margins of this document have been marked with an asterisk(*) to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content, as written, irrespective of the marginal notations and relationship to the last previous issue.

Custodians:
Army - GL
Air Force - 99

Preparing activity
DLA-CT

Project No: 8340-0586

Review activities:
Air Force – 11.6, 82

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:02Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.

2. The submitter of this form must complete blocks 4, 5, 6, and 7 and send to preparing activity.

3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	**1. DOCUMENT NUMBER** MIL-DTL-43695C	**2. DOCUMENT DATE** ***(YYYYMMDD)*** 2000/06/23

3. DOCUMENT TITLE
FRAME SECTIONS, TENT, FRAME TYPE, EXPANDABLE

4. NATURE OF CHANGE *(Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)*

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME *(Last, First, Middle Initial)*	b. ORGANIZATION	
c. ADDRESS *(Include Zip Code)*	d. TELEPHONE *(Include Area Code)* (1) Commercial (2) DSN *(If applicable)*	7. DATE SUBMITTED *(YYYYMMDD)*

8. PREPARING ACTIVITY

a. NAME DEFENSE SUPPLY CENTER PHILADELPHIA DSCP-CNRP	b. TELEPHONE *(Include Area Code)* (1) Commercial (2) DSN (215) 737-3290 444-3290
c. ADDRESS *(Include Zip Code)* 700 Robbins Ave. (Bldg 6, C&T) PHILADELPHIA, PA 19111-5092	**IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT:** Defense Standardization Program Office (DLSC-LM) 8725 John J. Kingman Road, Suite 2533 Fort Belvoir, Virginia 22060-6221 Telephone (703) 767-6888 DSN 427-6888

DD Form 1426, FEB 1999 (EG) PREVIOUS EDITION IS OBSOLETE
WHS/DIOR, Feb 99

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:02Z
Check the source to verify that this is the current version before use.