MIL-I-43682D
AMENDMENT-2
1 February 1988
SUPERSEDING
AMENDMENT-1
10 October 1986

MILITARY SPECIFICATION

ICEMAKER-DISPENSER: WITH WATER DISPENSER ATTACHMENT

This amendment forms a part of Military Specification MIL-I-43682D, dated 27 December 1982, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 2

2.1 under "Standards/Military": Add the following:

* "MIL-STD-167/1 - Mechanical Vibration of Shipboard Equipment (Type I - Environmental and Type II - Internally Excited).

* MIL-STD-1472 - Human Engineering Design Criteria for Military Systems, Equipment and Facilities."

PAGE 6

3.4, lines 18 and 19, sentence beginning "Controls shall be designed": Delete entire sentence.

PAGE 7

Add the following paragraph:

"3.4.2 Controls. Controls shall be designed for operation on a nominal 208/230 volt, single phase, 60 Hz voltage system, or a 115 volt, single phase, 60 Hz voltage system (see 3.12). Controls rated at 115 volt, single phase, 50/60 Hz may be used with a 50 Hz voltage system provided that the voltage can be obtained from either a hotline and neutral, or through a transformer (see 3.12). Relays and transformers, or any other components necessary for a complete control system, shall be furnished and installed as an integral part of the icemaker-dispenser."

AMSC N/A FSC 4110

DISTRIBUTION STATEMENT A. Approved for pubic release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-21T22:01Z
Check the source to verify that this is the currentversion before use.

PAGE 8

3.5.1.1.2: Delete and substitute:

"3.5.1.1.2 Compressor motor. Unless otherwise specified (see 6.2), the compressor motors, up to and including 3/4 horsepower, shall operate on a nominal 115 volt, single phase, 60 Hz voltage system. Compressor motors over 3/4 horsepower shall operate on a nominal 208/230 volt, single phase, 60 Hz voltage system. Motors shall be protected against damage from overloads and voltage fluctuations when starting or running by means of a thermal overload protector. When 50 Hz frequency is specified, the motor shall be specifically designed for operation on that frequency."

PAGE 9

3.5.1.2.1, line two, after "1/8 inch": Insert "(minimum)".

PAGE 10

3.5.9: Delete the word "reservoir" throughout the paragraph and substitute "bin".

Line 3: Delete "95" and substitute "80".

PAGE 11

* 3.7, after last sentence: Add "When specified for shipboard use, requirements and test limits of class A4 for surface ships and class A5 for submarines of MIL-STD-461 apply. Shipboard equipment shall meet the emission and susceptibility requirements for CE01, CE03 and RE02."

PAGE 12

Add the following new paragraphs:

"3.12 Electrical requirements. Unless otherwise specified (see 3.4.2 and 6.2), electrical components shall be rated for operation on a nominal 208/230 volt, single phase, 60 Hz voltage system, or a 115 volt, single phase, 60 Hz voltage system, or a combination of both. Transformers, when supplied as part of the system, shall not be used to step-up or step-down the voltage for end item use. Transformers shall not be used where specifically prohibited (see 3.5.1), but are permitted as part of the control system (see 3.4.2). When 50 Hz operation is specified (see 6.2), all motors shall be rated at 50 Hz.



Source: https://assist.dla.mil -- Downloaded: 20261[illegible]-21T22:01Z
Check the source to verify that this is the current version before use.

PAGE 12 (cont'd)

* 3.13 Human factors criteria (for Navy use only). Human factors engineering criteria, principles, and practices, as defined in MIL-STD-1472, shall be incorporated into the design of the icemaker-dispenser. Maintenance and operational activities shall permit safe and efficient performance by the 5th percentile female to the 95th percentile male as defined in MIL-STD-1472. Controls and switches shall be selected and integrated into the design of the icemaker-dispenser so as to meet the applicable requirements of MIL-STD-1472. Sufficient clearance or free area required around an item shall permit an individual with applicable body dimensions and physical capabilities to safely operate, maintain, remove, or replace that item. When establishing accessibility requirements, both physical and visual access must be provided along with access for the use of any tools, test equipment or repair parts needed. When inspecting for defects and performing tests, the equipment shall adhere to the human factors engineering considerations listed herein.

* 3.14 Environmental suitability. When specified for shipboard use, the icemaker-dispenser shall be capable of withstanding ship's vibration and motion. Contols, switches, moving parts, and electrical circuits shall operate under shipboard conditions without malfunction, binding, excessive looseness, or damage when tested as specified in 4.3.7 and 4.3.8."

PAGE 16

* 4.3.6, at end of the paragraph: Add "When required for shipboard use, test methods CE01, CE03 and RE02 apply."

* 4.3.7, line 1, after "test": Add "(For shipboard use)."

Add the following new paragraph:

* "4.3.8 Shipboard environmental test. The icemaker-dispenser under normal operating conditions, shall be tested in accordance with MIL-STD-167/1, Type I equipment. The icemaker-dispenser shall be secured to the test machine in the same manner that it will be secured on shipboard (see 3.5.8.1). Failure of the icemaker-dispenser to perform its function during and after testing, or to meet the requirements of 3.13 shall constitute failure of this test."

* 6.2(f): Delete "(see 3.4 and 3.5)" and substitute "(see 3.4, 3.5 and 3.13)."

PAGE 17

6.2: Delete subparagraph (i) and substitute:

"(i) When electrical characteristics other than specified are required, the contracting officer shall provide voltage, phase, and cycle to facilitate operation and installation (see 3.5.1.1.2 and 3.12)."



Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:01Z
Check the source to verify that this is the current version before use.

PAGE 17 (cont'd)

Add the following new paragraph:

* "6.5.1 Technical manuals. The requirement for technical manuals should be considered when this document is cited in a contract. If technical manuals are required, a contract exhibit must be prepared to fully describe statement of work criteria and delivery instructions, and cite the applicable technical manual specification. The manuals must be acquired by separate Contract Line Item Number (CLIN) in the contract."

The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodians:

Army - GL
Navy - YD

Preparing activity:

Army - GL

Project No. 4110-0418

Review activities:

Army - MD, TS
Navy - MS, SA, SH
DLA - GS

User activity:

Navy - MC



Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:01Z
Check the source to verify that this is the current version before use.