INCH-POUND

MIL-L-43693A(GL)
28 June 1991
SUPERSEDING
MIL-43693(GL)
20 March 1970

MILITARY SPECIFICATION

LOWERING DEVICE, PERSONNEL AND CARGO

This specification is approved for use by the Natick Research, Development, and Engineering Center, Department of the Army,and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers one type of device for lowering personnel or cargo from elevations of 150 feet or less. Prevision is made for procurement of the complete assembly or certain components of the assembly.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specificaitons, standards, and handbook. The following specificatires, standards, and handbooks form a part of this document ot the extent specified herein. Unless otherwise specified, the issues of these are those listed in the issue of the Department of Defense Index of Specifications and standards(DODISS) and supplement thereto, cited in the solicitation (see 6.2).

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be used in improving this document should be addressed to: Us. Army Natick Research, Development, and Engineering Center, Natick, MA 01760-5017 by using the Standardization Document Improvement (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 1670

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-21T22:02Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

FEDERAL

PPP-B-26 — Bag, Plastic (General Purpose)
PPP-T-60 — Tape: Packaging, waterproof
PPP-B-601 — Boxes, Wood, Cleated-Plywood
PPP-B-636 — Boxes, Shipping, Fiberboard

MILITARY

MIL-R-24050 — Rope, Fibrous, Double-Braided (Nylon)

STANDARDS

MILITARY

MIL-STD-105 — Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129 — Marking for Shipment and Storage
MIL-STD-147 — Palletized unit Loads

(Unless otherwise indicated, copies of federal and military specifications, Stanards, and handbooks are available from Standardization Documents Order Desk, Building 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.1.2 Other Government documents, drawings, and publicaitons. The following other Governments, documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

DRAWINGS

U.S. ARMY NATICK RESEARCH, DEVELOPMENT, AND ENGINERING CENTER

11-1-599 — Ring, Harness
11-1-701 — Lowering Device, Personnel/Cargo, Assembly of
11-1-702 — Harness Assembly, Personnel Lowering Device
11-1-703 — Governor Assembly, Personnel/Cargo Lowering Device
11-1-704 — Case Assembly, Carrying; Personnel/Cargo Lowering Device
11-1-705 — Snap-Hook Assembly
11-1-706 — Gage, Governor Wear
11-1-707 — Governor
11-1-3368 — Snap Hook, Rope Assembly
11-1-3369 — Hook
11-1-3370 — Guard, Snap Hook

(Copies of drawings are available from the U.S. Army Natick Research, Development, and Engineering Center, ATTN: STRNC-UX, Natick, MA 01760-5017.)

Source: https://assist.dla.mil -- Downloaded: 202610-21T22:02Z
Check the source to verify that this is the current version before use.

2.2 Non-Government Publications. The following document forms a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.2).

AMERICAN SOCIETY FOR TESTING AND MATERIALS (AST)

D 3951 – Standard Practice for commercial Packaging

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103-1187.)

(Non-Government standards and other publications are normally available from organizaitons that prepare or distribute the documents. The documents also may be available in or through libraries a other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified (see 6.2), a sample shall be subjected to first article inspection (see 6.3) in accordance with 4.3.

3.2 Materials and construction. Materials and construction shall conform to the requirements of the applicable drawings to subsidiary specifications, standards, and drawings applicable thereto, and as specified herein. It is encouraged that recycled material be used when practical as long as it meets the requirements of this specification.

3.2.1 Rope. The rope shall be nylon, double braided, 3/8-inch nominal diameter, in accordance with MIL-R-24050, except that the nylon fiber shall be a long chain polymer made of hexamethylene diamine and adipic acid or its derivatives (Nylon 6.6), melting point 250 ± 6°C. The rope shall be free of braider yam splices and shall conform to construction requirements indicated in the table below.

TABLE I. Construction requirements

No. of carriers	Picks per inch	Ends per carrier	Total ends	Basic yarn denier	Ply twist turns per inch
Core 8	2.6 to 2.8	4	32	840	6 Same as cover 1/
Cover 16	5.65 to 6.0	2	32	840	4.0 to 5.0 1/

Source: https://assist.dla.mil -- Downloaded: 202610-21T22:02Z
Check the source to verify that this is the current version before use.

1/ "S" yarn twist in"Z" carrier direction.
"Z" yarn twist in "S" carrier direction.

3.2.2.1 Length. The length of the rope shall be 150 feet with a permissible tolerance of plus 7.5 feet. Prior to cutting the rope, the section to be cut through shall be wrapped tightly with two turns of 2-inch width tape, type IV, color OD 7, conform to PPP-T-60. The rope shall then be cut at the center of the tape seared smooth and even.

3.2.2 Hardware. The rope assembly, snaphook, Drawing 11-1-3368; harness ring, Drawing 11-1-599: and governor,Drawing 11-1-707, shall show no evidence of failure when tested as specified on the applicable drawings.

3.2.3 Operator's manual and log record card. One operator's manual and one log record card shall be furnished with each lowering device assembly (see 6.4). The log record card only shall be furnished with each governor assembly when procured seperately.

3.2.4 Stitches and stitching.

3.2.4.1 Carring case. Thread breaks, bobbin runouts, or two or more more consecutive skipped stitches shall be restitched not less than 1 inch over each end of teh defect. Runoffs shall be restitched to conform to the required stitch pattern. Ends of stitching (except for 3.2.4.3) shall be backstitched not less than l/2-inch, except where ends are turned under in a hem or held down by other stitching. Thread ends shall be trimmed throughout.

3.2.4.2 Harness and governor assembly. Stitching defects shall not be repaired.

3.2.4.3 Automatic stitching. Automatic Stitching machines may be used to perform any of the required stitch patterns provided the requirements for the stitch pattern, stitches per inch, size and type of thread are met; and at least three or more tying, overlapping, or back stitches are used to secure the ends of stitching.

3.3 Marking. Identification marking of each component shall be in accordance with the applicable drawing.

3.4 Special marking. When applicable (see 6.2), the procuring activity will provide attractors with serial numbers for application to each governor. The serial number marking shall be in accordance with Drawing 11-1-707.

3.5 Workmanship. The workmanship shall conform to the quality of product established by this specification and the occurrence of defects shall not exceed the applicable acceptable quality levels.

Source: https://assist.dla.mil -- Downloaded: 2026l0-21T22:02Z
Check the source to verify that this is the currentversion before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection reuqirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where suchj inspections are deemed necessary to ensure supplies and servicesonform to prescribed requirements.

4.1.1 Responsibility for compliance. All items shall meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall no relieve the contractor of the responsibilities of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspeciton, as part of manufacturing operation,is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material either indicated or, actual, nor does it commit the Government to accept defective material.

4.1.2 Responsibility for dimensional requirements. Unless otherwise specified in the contract or purchase order, the contractor is responsible for ensuring that all specified dimensions have been met. When dimensions cannot be examined on the item, inspection shall be made at any point, or stall points in the manufacturing process necessary to ensure compliance with all dimensional requirements.

4.2 Classification of inspections. The inspection requirements specified herein are Classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.3).

4.3 First article inspection. When a first article is required (see 3.1 and 6.2), it shall be examined for the defects specified in 4.4.3 and 4.4.4 and shall be tested for the characteristics specified in 4.4.5. Any nonconformance shall be cause for the rejection of the first article.

4.4 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.4.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or quilified in this specification or applicable purchase document.

Source: https://assist.dla.mil -- Downloaded: 202610-21T22:02Z
Check the source to verify that this is the currentversion before use.

4.4.2 In-process inspection. Inspection of subassemblies shall be made to ascertain that construction details shich cannot be examined in the firished product are in accordance with specified requirements. The Government reserves the right to exclude from consideration for acceptance, any material or service for which in-process inspection has indicated nonconformance.

4.4.3 End item visual examination.

4.4.3.1 Harness assembly. The end items shall be examined for the defects listed in table II. The lot size shall be expressed in terms of harness assemblies. The sample unit shall be one harness assembly. The inspection level shall be III and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 0.25 for major defects and 6.5 for total (major and minor combined) defects.

TABIE II. End item visual defects for harness assembly

Examine	Defect	Classification Major	Minor
Webbing, (nylon and cotton elastic)	Not specified type or class	101	
	Cut, tear, hole, abrasion, or Weak area	102	
	Ends not seared or wax dipped as specified		201
	color not as specified		202
Metal components	Fractured, malformed, bent, or otherwise damanged	103	
	Burrs or sharp edges	104	
	Finished not as specified or any corroded area	105	
Thread (nylon)	Not type, class, or size specified	106	
	Color not as specified		203
Stitches and stitching	stitching pattern not as specified	107	
	Any row of stitching missing	108	
	One stitch per inch fewer than minimum or more than maximum specified		204
	Two or more stitches per inch fewer than minimum or more than maximum specified	109	
	Thread breaks, bobbin runouts, skipped stitches, and runoffs	110	
	Ends of stitching not backstitched or secured as specified	111	

Source: https://assist.dla.mil -- Downloaded: 202610-21T22:02Z
Check the source to verify that this is the current version before use.

TABLE II. End item visual defects for harness assembly (cont'd)

Examine	Defect	Classification Major	Minor
Stitches and stitching (cont'd)	Tension loose, resulting in loose top or bobbin thread, or tight tension, causing puckering of material at stitch line		205
	Needle or bunched stitching	112	
Constuction and assembly	Any component missing, not assembled or joined as specified	113	
Marking	Omitted, incorrect, illegible: location, size or color not as specified		206
Workmanship	Grease, oil, ink smears, dirt or other foreign matter; thread ends not trimmed throughout		207

4.4.3.2 Carring case. The end items shall be examined for the defects listed in table III. The lot size shall be expressed in terms of carrying cases. The sample unit shall be one carrying case. The inspection level shall be III and the AQL,expressed in terms of defects per hundred units, shall be 2.5 for major defects and 10 for total (major and minor combined) defects.

TABLE III. End item visual defects for carrying case

Examine	Defect	Classification Major	Minor
Cloth (nylon)	Not specified type or class	101	
	Cut, tear, hole, abrasion, or weak area	102	
	Color not as specified		201
Thread (nylon)	Not type, class or size specified	103	
	Color not as specified		202
Webbing (nylon)	Cut, tear, hole, abrasion, or Weak area	104	
	Not specified type or class	105	
	Free end not seared		203
	Color not as specified		204
Tape	Cut, tear, or hole	106	

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:02Z
Check the source to verify that this is the current version before use.

TABLE III. End item visual defects for carring case (cont'd)

Examine	Defect	CLassification Major	Minor
Fastener (nylon hook and pile)	Hooks flattened, broken, or missing, impairing function of tape	107	
	Color not as specified		205
Metal component	Fractured, malformed, bent	108	
	Finish not as specified or corroded area		206
Stitches and stitching	stitching pattern not as specified	109	
	Any row of stitching missing	110	
	One stitch per inch fewer than minimum or more than maximum specified		207
	Two more stitches per inch fewer than minimum or more than maximum specified	111	
	Needle chews or bundled stitching	112	
	Tension loose, resulting in loose top or bobbin thread, or tight tension, causing puckering of material at stitch line		208
	Thread breaks, bobbin runouts, or two or more consecutive skipped Stitches not overstitched as specified; or runoffs not re-stitched according to stitch pattern; or ends of stitching not backstitched as specified		209
Constructiom and assembly	Any component missing, not assembled or joined as specified	113	
Marking	Omitted, incorrect, illegible; location, size, or color not as specified		210
Workmnship	Grease, oil, ink smears, dirt or other foreign matter: thread ends not trimmed throughout		211

4.4.3.3 Govenor assembly and governor wear gage. The end items shall be examined for the defects listed in table IV. The lot size shall be expressed in terms of governor assemblies and governor wear gages. The sample unit shall be one govenor assembly and governor wear gage. The inspection level shall be III

Source: https://assist.dla.mil -- Downloaded: 202610-21T22:02Z
Check the source to verify that this is the current version before use.

and the AQL, expressed in terms of defects per hurdred units, shall be 0.25 for major defects and 10 for total (major and minor combined) defects.

TABLE IV. End item visual defect for governor assembly and govenor wear gage

Examine	Defect	Classification Major	Minor
Webbing	Cut, tear, hole, abrasion, or weak area	101	
	Not specified type or class	102	
	Ends not seared		201
	Color not as specified		202
Thread	Type, class, or size not as specified	103	
Cord (lanyard)	Color not as specified		203
	Not type specified		204
	Core not removed, knots, insecure, free ends not seared		205
Metal components (snap hook, gage, or governot, as applicable)	Fractured, malformed, bent, or otherwise damaged	104	
	Snap hook attached with open side facing in wrong direction in relation to the governor rope clip		206
	Burrs, slivers, or sharp edges	105	
	Finish not as specified or corroded area	106	
	Dip brazing not as specified, i.e., incomplete penetration of filler metal into joints; porosity or flux inclusions	107	
	Any functional surface with surface roughness in excess of maximum specified on drawing	108	
	Rough surface on or around brazing fillets caused by dripping of dip brazing metal	109	
	Any filler metal on exterior or rung in excess of required fillet	110	
	Excessive flow of filler metal into frame of governor		207
Stitches and stitching	Stitching pattern not as specified	111	
	Any row ofstitching missing	112	

Source: https://assist.dla.mil -- Downloaded: 202610-21T22:02Z
Check the source to verify that this is the current version before use.

TABLE IV. End item visual defects for govenor assembly and governor wear gage (cont't)

Examine	Defect	Classification Major	Minor
Stitchs and stitching (cont'd)	One stitich per inch fewer than minimum or more than maximum specified		208
	Two or more stitches per inch fewer than minimum or more than maximum specified	113	
	Needle chews or bunched stitching	114	
	Thread breaks, bobbin runouts, skipped stitches, and runoffs	115	
	Ends of stitching backstitched or secured as specified		209
	Tension loose, resulting in loose top or bobbin thread, or tight tension causing puckering of mateial at stitch line	116	
Construction and assembly	Any component missing, not assembled or joined as specified	117	
Marking	Omitted, incorrect, illegible: location, size, or color not as specified		210
	Serial number not applied as specified		211
Workmanship	Grease, oil, ink smear's, dirt or other foreign matter; thread ends not trimmed throughout		212

4.4.3.4 Rope. The end items shall be examined for the defects listed in table V. The lot size shall be expressed in terms of ropes. The sample unit shall be on rope. The inspection level shall be III and the AQL, espressed in terms of defect per hundred units, shall be 0.25 for major defects and 4.0 for total (major and minor combined) defects.

TABLE V. End item visual defects for rope

Examine	Defect	Classification Major	Minor
Rope	Any cuts, abrasions, broken or protruding ends, kinks, or soft spots	101	

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:02Z
Check the source to verify that this is the current version before use.

TABLE V. End item visual defects for rope (cont'd)

Examine	Defect	Classification Major	Minor
Rope (cont'd)	Fiber other than specified	102	
	Any braider yam splices		201
	Loose fiber ends on surface		202
	Ends not taped and seared as Specified		203
Workmanship	Dirt, grease, oil, or other foreign matter		204

4.4.4 End item dimensional examination. The end items shall be examined for conformance to dimensions on the drawings specified in section 2. Only those dimension that can evaluated without damging or disassembling the end items shall be examined. Any dimensitons not within the specified tolerance shall be considered a defect. The lot size, sample unit, inspection level, and AQL, expressed in terms of defects per hundred units, shall be as specified in table VI.

TABLE VI. End item dimensional examination criteria

Component	Lot size expresded in units of	Sample unit	Inspection level	AQL
Harness assembly	Harness assemblies	1 Harness assembly	S-3	6.5
Carrying case	Carrying cases	1 Carrying case	S-3	6.5
Governor assembly and governor wear gage	Governot assemblies and governor wear gages	Governor assembly and governor Wear gage	S-3	6.5
Rope	Ropes	1 Rope	S-3	6.5

4.4.5 End item testing. One complete snap hook assembly or ring harness or governor shall be tested as specified in the applicable drawings (see 3.2.2) for conformance to the proof loadrequirements contained therein. The lot size shall consist of completely fabricaticated rope snap hook assemblies, ring harnesses, or governors offered for inspection at one time. The sample size Shall be the number of end items indicted by inspection level III. Any test failure shall be cause for rejection of the lot.

4.4.6 Packaging examination. The fully packaged end items shall be examined for the defects listed below. The lot size shall be expressed in units of

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:02Z
Check the source to verify that this is the current version before use.

Shipping containers. The sample unit shall be one shipping container fully packaged. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 2.5.

Examine	Defect
Marking (exterior and interior)	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application
Materials	Any component missing, damaged, or not as specified
Workmanship	Inadequate application of components, such as: incomplete sealing or closure of flap, improper taping, loose strapping, or inadequate stapling
Contents	Number per container is more or less than required

4.4.7 Palletization examination. The fully packaged and palletized end items shall be examined for the defects listed below. The lot size shall be expressed in units of palletized unit loads. The Sample unit shall be one palletized unit load, fully packaged. The inspection level shall be S-l and the AQL, expressed in terms of defects per hundred units, shall be 6.5.

Examine	Defect
Finished dimensions	Length, width, or height exceeds specified maximum requirement
Palletization	Pallet pattern not as specified Load not bonded as specified
Weight	Exceeds maximum load limits
Marking	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application

5. PACKAGING

5.1 Preservation. Preservation Shall be level A or Commercial, as specified (see 6.2) .

5.1.1 Level A preservation.

5.1.1.1 Lowering device, complete. The Carrying case assembly, harness assembly, and governor assembly of each lowering device shall be compactly folded or arranged as applicable. The governor shall be prevented from having metal–to-metal contact with the attached snap hook and linking pin components by means of cushioning material. Prior to folding the carrying case, the record card and operator's manual shall be placed in the log record and manual pocket inside the carrying case. The rope shall be lap or accordion folded in manner

Source: https://assist.dla.mil -- Downloaded: 202610-21T22:02Z
Check the source to verify that this is the current version before use.

to prevent twists and then tied at each end with twine. The complete lowering device shall be packaged in a fiberboard box conforming to FSC, class dometic type CF, minimum grade 200 of PPP-B-636. Inside dimensions of the box shall be approximately 12 inches in length, 11 inches in width, 4-1/2 inches in depth. Each box shall be closed in accordance with method I,as specified in the appendix of PPP-B-636.

5.1.1.2 Components. Each component when procured separately (see 6.2),shall be unit packed in a plastic bag, 0.003 inch thick, conforming to type I or type II, style 1, of PPP-B-26.

5.1.2 Commercial preservaion. Each complete lowering device or component shall be preserved in accordance with ASTM D 3951.

5.2 Packing. Packing shall be level A, B, or Commerial, as specified (see 6.2).

5.2.1 Level A packing. Each item in quantities cited in table VII, preserved as specified in 5.1, shall be packed in a Shipping container conforming to overseas type, skyle A or J, type 2 load of PPP-B-601. Approximate inside dimensions of each box shall be as specified in table VII. Each box shall be closed and reinforced in accordance with the appendix of PPP-B-601.

5.2.2 Level B packing. Each item in the quantities cited in table VII, preserved as specified in 5.1, shall be packed in a shipping container conforming to style RSC-L, type CF (variety SW) or SF, class domestic, grade 275 of PPP-B-636. Approximate inside dimensions of the box shall be as specified in table VII. Each box shall be closed in accordance with method II as specified in the appendix of PPP-B-636.

TABLE VII. Item dimensions and pallet patterns

Item	Number in each box	Box dimensions (inches)	Pallet pattern
Compete system	5	23-1/2 by 12-1/2 by 11-1/2	91
Harness	10	15 by 13 by 9	37
Carrying case	50	20 by 12 by 11	102
Governor	10	14 by 10 by5	28
Snap hook	50	10 by 8 by 4	112
Gage, governor wear	100	12 by 10 by 3-1/2	104
Rope	10	24 by 12 by 15	35

Source: https://assist.dla.mil -- Downloaded: 202610-21T22:02Z
Check the source to verify that this is the current version before use.

5.2.2.1 Weather-resistant shipping container. When specified (see 6.2), the shipping container shall be a grade V3c, V3s, or V4s fiberboard box fabricated in accordance with PPP-B636 and closed in accordance with the appendix of PPP-B-636.

5.2.3 Commercial packing Each item preserved as specified in 5.1, shall be packed in accordance with ASTM D 3951.

5.3 Palletization When specified (see 6.2), items packed as specfied in 5.2.2 and 5.2.3, shall be palletized on a 4-way entry pallet in accordance with load type Ia of MIL-STD-147. Pallet types shall be type I (4-way entry), type IV or type V in accordance with MIL-STD-147. Each prepared load shall be bonded with straps in accordance with bonding means C and D or film bonding means F or G. Pallet patterns shall be in accordance with table VII and the appendix of MIL-STD-147.

5.4 Marking. In addition to any special marking required by the contract or purchase order, unit packs, shipping containers, and palletized unit loads shall be marked in accordance with MIL-STD-129 or ASTM D 3951, as applicable.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The lowering device is used to lower either personnel or cargo from elevations of 150 feet or less at a controllable rate of descent. Typical use include lowering of personnel or cargo from hovering helicopters and lowering parachutists from trees.

6.1.1 Limitations of use. Information for load capacities and use of the lowering device may be obtained from TM 10-1670-251-12 .

6.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number, and date of this specification.
13. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1.1 and 2.2).
c. When a first article is required (see 3.1, 4.3, and 6.3).
d. Serial numbers for governors (see 3.4).
e. Levels of preservation and packing (see 5.1 and 5.2).
f. When components are procured seperately (see 5.1.1.2).
g. When weather-resistant grade fiberboard shipping containers are required for level B packing (see 5.2.2.1.1).
h. When palletization is required (see 5.3).
i. When government furnished Property is required (see 6.4) .

Source: https://assist.dla.mil -- Downloaded: 202610-21T22:02Z
Check the source to verify that this is the current version before use.

6.3 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of Federal Acquisition Regulation (FAR) 52.209. The first article should be a preproduction sample. The contracting officer should specify the appropriate type of first article and the number of units to be furnished. The contracting officer should also include specific instruction in acquisition documents regarding arrangements for selection, inspection, and approval of the first article.

6.4 Government ~~furnished property~~. Except as may be otherwise prescribed by the contracting activity contract furnished the required quantities of operator's manuals and log record cards (see 3.2.3).

6.5 Subject term (key word) listing.

Descent apparatus

6.6 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodian:

Army-GL

Review activity:

Army-AV

Preparing activity:

Army-GL

(Project 1670-A782)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:02Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER	2. DOCUMENT DATE (YYMMDD)
	MIL-L-43693A(GL)	1991 June 28

3. DOCUMENT TITLE
LOWERING DEVICE, PERSONNEL AND CARGO

4. NATURE OF CHANGE (*Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.*)

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME	b. TELEPHONE (Include Area Code) (1) Commercial	(2) AUTOVON/DSN
U.S. Army Natick RD&E Center	508-651-4531	256-4531
c. ADDRESS (Include Zip Code) Commander, U.S. Army Natick RD&E Center ATTN: STRNC-UXT Natick, MA 01760-5017	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340	

Source: https://assist.dla.mil -- Downloaded: 2026-02-21T22:42Z
Check the source to verify that this is the current version before use.