INCH-POUND

MIL-S-43674C(GL)
25 April 1989
SUPERSEDING
MIL-S-43674B
23 April 1985

MILITARY SPECIFICATION

SHOWER PAIL, COLLAPSIBLE, COTTON DUCK, 5-GALLON CAPACITY

This specification is approved for use by the U.S. Army Natick Research, Development, and Engineering Center, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers a collapsible shower pail.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

* 2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: U.S. Army Natick Research, Development, and Engineering Center, Natick, MA 01760-5014 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A

FSC 8465

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:00Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

FEDERAL

DDD-L-20	-	Label: For Clothing, Equipage, and Tentage, (General Use)
PPP-B-601	-	Boxes, Wood, Cleated-Plywood
PPP-B-636	-	Boxes, Shipping, Fiberboard

MILITARY

MIL-L- 35078	-	Loads, Unit: Preparation of Semiperishable Subsistence Items; Clothing, Personal Equipment and Equipage; General Specification for

STANDARDS

FEDERAL

FED-STD-751	-	Stitches, Seams and Stitchings

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	-	Marking for Shipment and Storage
MIL-STD-147	-	Palletized Unit Loads
MIL-STD-731	-	Quality of Wood Members for Containers and Pallets

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Naval Publications and Forms Center, (ATTN: NPODS), 5801 Tabor Avenue, Philadelphia, PA 19120-5099.)

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

DRAWINGS

US ARMY NATICK RESEARCH, DEVELOPMENT, AND ENGINEERING CENTER

5-4-984	-	Shower Pail, Collapsible, Cotton Duck, 5-Gallon Capacity; Assembly and Details
5-4-985	-	Shower Pail, Collapsible, Cotton Duck, 5-Gallon Capacity; Sections

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:00Z
Check the source to verify that this is the current version before use.

5-4-986 - Shower Pail, Collapsible, Cotton Duck, 5-Gallon Capacity; Showerhead Assembly and Details
5-4-1243 - Shower Pail, Collapsible, Cotton Duck, 5-Gallon Capacity; Alternate Showerhead Assembly and Details

(Copies of drawings are available from the U.S. Army Natick Research, Development, and Engineering Center, Natick, MA 01760-5014.)

* 2.2 Non-Government publications. The following document forms a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.2).

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

D 3951 - Standard Practice for Commercial Packaging

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103-1187.)

* (Non-Government standards and other publications are normally available from the organizations that prepare or distribute the documents. These documents also may be available in or through libraries or other informational services.)

* 2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified (see 6.2), a sample shall be subjected to first article inspection (see 6.3), in accordance with 4.3.

* 3.2 Materials and components. Materials and components shall conform to the requirements specified herein and on applicable drawings. It is encouraged that recycled material be used when practical as long as it meets the requirements of this document.

3.3 Construction. The shower pail shall conform in all respects to the drawings listed in section 2 and as specified herein.

3.3.1 Types of stitching. All stitching shall conform to FED-STD-751 as follows:

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:00Z
Check the source to verify that this is the current version before use.

For all stitching	Stitch type 301, 6 to 8 stitches per inch

* 3.3.1.1 Type 301 stitching. Ends of all stitching shall be backstitched or overstitched 1 inch minimum except when caught in other stitching or turned under in a hem. Thread tension shall be maintained so that there will be no loose bobbin, or top thread, or excessively tight stitching resulting in puckering of the materials sewn. The inter lock shall be embedded in the material sewn.

* 3.3.1.1.1 Repairs of type 301 stitching. Repairs of type 301 stitching shall be as follows:

a. When thread breaks or bobbin run-outs occur during sewing, the stitching shall be repaired by restarting the stitching a minimum of 1 inch behind the end of the stitching.

b. Thread breaks or two or more consecutive skipped or run-off stitches noted during inspection of the item (in-process or end item) shall be repaired by overstitching. The stitching shall start a minimum of 1 inch before the defective area (1/2 inch on box, box and cross and W-W stitching) and continue a minimum of 1 inch beyond the defective area onto the existing stitching. Loose or excessively tight stitching shall be repaired by removing the defective stitching, without damaging the materials, and restitching in the required manner. When damaged thread has been removed, needle holes do not constitute damage to the material.

(When making the repairs in a. and b. above, the ends of the stitching are not required to be backstitched.)

* 3.3.1.2 Automatic stitching. Automatic stitching machines may be used to perform any of the required stitch patterns provided the requirements of the stitch pattern, stitches per inch, size and type of thread are met, and at least three or more tying, overlapping or backstitches are used to secure the ends of the stitching.

* 3.3.1.3 Thread ends. All thread ends that are visible on the finished item shall be trimmed to a maximum length of 1/4 inch.

* 3.3.1.4 Lubrication of thread. The addition of any lubricant to the polyester sewing thread prior to or during the sewing operation is prohibited.

* 3.3.1.5 Stitching margins. Unless otherwise specified, all stitch margins shall be 1/8, +1/8 -0 inch.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:00Z
Check the source to verify that this is the current version before use.

3.3.2 Showerhead assembly. The showerhead assembly shall be attached to the bottom of the pail as shown on Drawing 5-4-984. The water shower valve shall turn "on" or "off" without binding.

* 3.3.2.1 Metal showerhead. The flange nut shall be tightly secured to prevent rotation of the flange when rotating the showerhead. The pail with showerhead assembly attached shall not leak more than 10 percent of its volume over a 1½ hour period when tested as specified in 4.4.5.1.

* 3.3.2.2 Plastic showerhead (alternate). The pail with showerhead attached shall not leak more than 10 percent of its volume over a 1½ hour period when tested as specified in 4.4.5.2. The showerhead shall be capable of withstanding cold and hot soaking and dropping without showing signs of fracture, breakage, deformation of the showerhead contours in excess of 1/2 inch, or loosening of cemented parts when tested as specified in 4.4.5.2. The showerhead shall be tightened without the alignment pin showing signs of breaking or deforming and without the pin cutting or deforming the wall of the alignment slot.

3.3.3 Attachment to bottom. The showerhead assembly shall be attached to the bottom of the pail as shown on Drawing 5-4-984. The flange nut shall be tightly secured to prevent rotation of flange when regulating showerhead.

3.3.4 Bottom reinforcement. The bottom reinforcement webbing shall be stretched taut when stitching to bottom.

3.3.5 Soldering. All soldering shall be as specified on Drawing 5-4-986. Soldering shall be adherent and the soldered joint shall be free from splatter or excess solder.

3.3.6 Welds. Welds shall be smooth and free from porosity, cracks, incomplete fusion, and deformation of material.

3.4 Marking. The identification marking shall be applied in the location shown on Drawing 5-4-984 and shall conform to type IV, class 5 of DDD-L-20. The letters "U.S." and the warning marking "NOT TO BE USED FOR THE STORAGE OF DRINKING WATER" shall be applied in the size characters and in the location indicated on the drawing and shall conform to type IV, class 9 of DDD-L-20. Fastness of the class 9 marking shall be as specified for class 5 marking.

* 3.5 Workmanship. Cloth components shall be clean and free of holes, cuts, tears, or cloth defects such as multiple floats or broken or missing yarns. Webbing shall contain no frayed or scalloped edges. Seam allowances shall be maintained with seams secured so that no runoffs or twisted, pleated, or open seams shall result. Care shall be exercised in sewing to see that no needle

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:00Z
Check the source to verify that this is the current version before use.

chews occur. Metal components shall be smooth; shall be free of burrs, porosity, cracks, sharp edges, and corroded area; and shall not be broken or malformed. Plastic components of the plastic showerhead, when applicable, shall be smooth and free from visible variable thickness and warpage. The shower pail shall conform to the quality of product established by this specification and the occurrence of defects shall not exceed the applicable acceptable quality levels.

4. QUALITY ASSURANCE PROVISIONS

* 4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

* 4.1.1 Responsibility for compliance. All items shall meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

* 4.1.2 Responsibility for dimensional requirements. Unless otherwise specified in the contract or purchase order, the contractor is responsible for ensuring that all specified dimensions have been met. When dimensions cannot be examined on the end item, inspection shall be made at any point, or at all points in the manufacturing process necessary to assure compliance with all dimensional requirements.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3)
b. Quality conformance inspection (see 4.4)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:00Z
Check the source to verify that this is the current version before use.

* 4.3 First article inspection. When a first article is required (see 3.1 and 6.2), it shall be examined for the defects specified in 4.4.3 and 4.4.4 and tested as specified in 4.4.5.

4.4 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.4.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase document.

* 4.4.2 In-process inspection. Inspection shall be made of the following operations or assemblies to establish conformance to specified requirements. Whenever nonconformance is noted, correction shall be made to the items affected and to the operation. Items which cannot be corrected shall be removed from production.

a. Soldering is in compliance with 3.3.5.

b. Welding of metal showerhead is in compliance with 3.3.6.

* 4.4.3 End item visual examination. The end item shall be examined for the defects listed in table I. The lot size shall be expressed in units of shower pails. The sample unit shall be one shower pail. The inspection level shall be II and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 4.0 for major defects, 10 for major and minor A combined defects, and 15 for total (major, minor A and B combined) defects.

TABLE I. End item visual defects

Examine	Defects	Classification		
		Major	Minor A	Minor B
Cloth	Hole, cut, or tear	101		
	Broken or missing yarns, multiple floats clearly visible at normal inspection distance (approximately 3 feet)		201	
Webbing	Edge frayed or scalloped		202	
	Webbing not taut stitched to bottom			301
Seams and stitching	Open seam on stitch type 301: -more than 1 inch	102		

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:00Z
Check the source to verify that this is the current version before use.

TABLE I. End item visual defects (cont'd)

Examine	Defects	Classification Major	Minor A	Minor B
Seams and stitching (cont'd)	-more than 1/4 inch but not more than 1 inch		203	
	-1/4 inch or less			302
NOTE:	A seam shall be classified as open when one or more stitches joining a seam are broken or when one or more skipped stitches or runnoffs occur. On double stitched seams, a seam shall be classified as open when either one or both sides of a seam are open.			
	Raw edges caught in stitching (where turnunder is required):			
	-more than 3/4 inch but not more than 1-1/2 inches			303
	-more than 1-1/2 inches		204	
	Thread breaks:			
	-overstitched less than 1 inch			304
NOTE:	Thread breaks not overstitched shall be classified as open seams.			
	Needle chews resulting in hole, cut, or tear	103		
	Skipped stitches overstitched less than 1 inch on stitch type 301 (where two or more stitches are skipped consecutively)			305
NOTE:	Skipped stitches not overstitched shall be classified as open seams.			
	One or more required rows of stitching omitted (except on boxstitching)	104		
Boxstitching	Incomplete:			
	-one row of stitching omitted			306
	-two or more rows of stitching omitted		205	

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:00Z
Check the source to verify that this is the current version before use.

TABLE I. End item visual defects (cont'd)

Examine	Defects	Classification Major	Minor A	Minor B
Boxstitching (cont'd)	Any boxstitching less than specified length by more than 1/8 inch			307
Seam and stitch type	Wrong seam or stitch type	105		
Stitch tension	Loose, resulting in loosely exposed top or bottom thread for more than 6 inches		206	
Stitches per inch	One stitch less than minimum specified			308
	Two or more stitches less than minimum specified		207	
	One or more stitches in excess of maximum specified			309
	NOTE: Variation in the number of stitches per inch, caused by the operator speeding the machine and pulling the fabric in order to sew over heavy places or in turning corners shall be classified as follows: a. Within the minor A defect classification - minor B defect b. Within the minor B defect classification - no defect			
Stitching gage	Not as specified		208	
Stitching margin	Larger than specified by more than 1/4 inch			
	-for more than 2 inches but not more than 4 inches in length			310
	-for more than 4 inches in length		209	
	-less than specified		210	
Stitching ends	Overstitched less than 1 inch (except where ends are held down by other stitching or turned under in a hem or where stitching is performed automatically)		211	

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:00Z
Check the source to verify that this is the current version before use.

TABLE I. End item visual defects (cont'd)

Examine	Defects	Classification Major	Minor A	Minor B
Stitching ends (cont'd)	Secured with less than three tying, overlapping, or backstitches when automatic stitching is performed		212	
Components and assembly	Any component broken or fractured, or required operation omitted (unless otherwise classified)	106		
Showerheads (with post and cotter pin)	Any component broken or fractured	107		
	Water valve does not turn "ON" or "OFF" without binding	108		
Metal showerhead	Not smooth or not free from burrs or sharp edges	109		
	Not free from cracks, porosity, or corroded area	110		
Plastic showerhead (alternate)	Not smooth and not free of variable thickness or surface warpage	111		
	Loosening of cemented parts	112		
	Cracked, broken, or deformed	113		
Handle	Not constructed as specified on applicable drawing; not set to body of pail as specified on drawing	114		
Markings	Omitted, incorrect, illegible, misplaced, or not type specified			311
Cleanness	Grease or oil stains; thread ends not trimmed to 1/4 inch or less			312

* 4.4.4 End item dimensional examination. The end items shall be examined for conformance to the dimensions specified on the drawings. Only those dimensions that can be evaluated without damaging or dissassembling the end items shall be examined. Any dimension not within the specified tolerance shall be classified as a defect. The lot size shall be expressed in units of shower pails. The sample unit shall be one shower pail. The inspection level shall be S-3 and the AQL, expressed in terms of defects per hundred units, shall be 10.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:00Z
Check the source to verify that this is the current version before use.

4.4.5 End item testing. End item testing shall be performed in accordance with 4.4.5.1 or 4.4.5.2 as applicable.

4.4.5.1 Testing of shower pails with metal showerheads. The shower pails shall meet the leakage requirement in 3.3.2.1 when tested as specified in 4.5.1. The lot size shall be expressed in units of shower pails. The sample unit shall be one shower pail. The inspection level shall be S-3 and the AQL, expressed in terms of defects per hundred units, shall be 0.65.

4.4.5.2 Testing of shower pails with plastic showerheads. The shower pails shall be tested for the characteristics as indicated in table II. The lot size shall be expressed in units of shower pails. The sample unit shall be two shower pails. The inspection level shall be S-1 and the AQL, expressed in terms of defects per hundred units, shall be 2.5.

TABLE II. End item tests (plastic showerhead)

Characteristic	Requirement paragraph	Test method	No. of determs	Results reported as
Leakage	3.3.2.2	4.5.1	1	Pass or fail
Cold soak	3.3.2.2	4.5.2	1	Pass or fail
Heat soak	3.3.2.2	4.5.3	1	Pass or fail

* 4.4.6 Packaging examination. The fully packaged end items shall be examined for the defects listed below. The lot size shall be expressed in units of shipping containers. The sample unit shall be one shipping container fully packaged. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 2.5.

Examine	Defect
Marking (exterior and interior)	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application.
Materials	Any component missing, damaged, or not as specified.
Workmanship	Inadequate application of components, such as: incomplete sealing or closure of flap, improper taping, loose strapping or inadequate stapling. Bulged or distorted container.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:00Z
Check the source to verify that this is the current version before use.

	Defect (cont'd)
Content	Number per container is more or less than required.

* 4.4.7 Palletization examination. The fully packaged and palletized end items shall be examined for the defects listed below. The lot size shall be expressed in units of palletized unit loads. The sample unit shall be one palletized unit load, fully packaged. The inspection level shall be S-1, and the AQL, expressed in terms of defects per hundred units, shall be 6.5.

Examine	Defect
Finished dimensions	Length, width, or height exceeds specified maximum requirements
Palletization	Pallet pattern not as specified Interlocking of loads not as specified Load not bonded as specified
Weight	Exceeds maximum load limits
Marking	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application

4.5 Methods of inspection.

* 4.5.1 Leak test. At 65°F ambient conditions, the shower pail shall be filled with water and suspended for four hours. The shower pails shall then be refilled, the showerhead turned to the "ON" position, and a check made for the starting of the water shower and leaks at the connection between the canvas pail and the showerhead. The showerhead shall then be turned to the "OFF" position, the pail refilled if needed, and checked again for leaks at the connection of the canvas pail and showerhead. For the plastic showerhead, the leak test shall be conducted after the cold soak test of 4.5.2. Any noncompliance with the applicable requirements of 3.3.2.1 and 3.3.2.2 shall constitute failure of this test.

* 4.5.2 Cold soak test. A shower pail with the plastic showerhead shall be cold soaked at -0°F temperature for 24 hours and in this cold soaked condition with the showerhead spray plate facing down and at a height of 42 inches, the pail shall be dropped in free fall on a concrete floor. The showerhead shall then be examined to determine compliance with the fracture, breakage, contour deformation, or loosening of cemented parts requirements of 3.3.2.2. Any noncompliance shall consititute a failure.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:00Z
Check the source to verify that this is the current version before use.

4.5.3 Heat soak test. A shower pail with the plastic showerhead shall be heat soaked at 125°F temperature for 24 hours and in this heat soaked condition shall be drop tested as specified in 4.5.2 to determine compliance with the fracture, breakage, contour deformation, or the loosening of cemented parts requirement of 3.3.2.2. Any nonconformance shall constitute a failure.

5. PACKAGING

* 5.1 Preservation. Preservation shall be level A or Commercial, as specified (see 6.2).

* 5.1.1 Level A. Each shower pail shall be collapsed and compactly arranged. The cotton pin of the metal showerhead or the hexagonal nut of the plastic showerhead shall be covered with wadding or tape to prevent puncturing of the fabric.

* 5.1.2 Commercial. Pails shall be preserved in accordance with ASTM D 3951.

* 5.2 Packing. Packing shall be level A, B or Commercial, as specified (see 6.2).

* 5.2.1 Level A packing. One shower pail, preserved as specified in 5.1, shall be packed in a shipping container. The shipping container shall be a fiberboard box conforming to style RSC-L, grade V2s of PPP-B-636. The inside of each box shall be fitted with a box liner conforming to type CF, class weather-resistant, variety DW, grade V15c of PPP-B-636. Inside dimensions of the box shall be approximately 12 inches in length, 12 inches in width and 3-1/2 inches in depth. Each box shall be closed, waterproofed, and reinforced with strapping or tape banding in accordance with the appendix of PPP-B-636. Boxes shall be arranged in unit loads in accordance with MIL-L-35078 for the type and class of load specified (see 6.2). Strapping shall be limited to nonmetallic strapping, except for type II, class F loads.

* 5.2.2 Level B packing. One shower pail, preserved as specified in 5.1, shall be packed in a shipping container. The shipping container shall be a fiberboard box conforming to style RSC-L, type CF (variety SW) or SF, class domestic, grade 275 of PPP-B-636. The inside of each box shall be fitted with a box liner conforming to type CF, class domestic, variety DW, grade 275 of PPP-B-636. Inside dimensions of the box shall be approximately 12 inches in length, 12 inches in width and 3-1/2 inches in depth. Each box shall be closed in accordance with method II as specified in the appendix of PPP-B-636.

* 5.2.2.1 Weather-resistant shipping container. When specified (see 6.2), the shipping container shall be a grade V3c, V3s, or V4s fiberboard box fabricated in accordance with PPP-B-636 and closed in accordance with the appendix of PPP-B-636.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:00Z
Check the source to verify that this is the current version before use.

* 5.2.3 Commercial packing. Shower pails, preserved as specified in 5.1, shall be packed in accordance with ASTM D 3951.

* 5.3 Palletization. When specified (see 6.2), shower pails packed as specified in 5.2.2 and 5.2.3, shall be palletized on a 4-way entry pallet in accordance with load type Ia of MIL-STD-147. Pallet types shall be type I (4-way entry), type IV or type V in accordance with MIL-STD-147. Pallets shall be fabricated from wood groups I, II, III, or IV of MIL-STD-731. Each prepared load shall be bonded with primary and secondary straps in accordance with bonding means K and L or film bonding means O or P. Pallet pattern shall be number 28 in accordance with the appendix of MIL-STD-147. Interlocking of loads shall be effected by reversing the pattern of each course.

5.4 Marking. In addition to any special marking required by the contract or purchase order, shipping containers and palletized unit loads shall be marked in accordance with MIL-STD-129 or ASTM D 3951, as applicable.

6. NOTES

* (This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The shower pail is intended for use in tropical combat zones.

* 6.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number, and date of this specification.
b. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1.1 and 2.2).
c. When a first article is required (see 3.1, 4.3, and 6.3).
d. Levels of preservation and packing (see 5.1 and 5.2).
e. Type and class of unit load required (see 5.2.1).
f. When weather-resistant grade fiberboard shipping containers are required for level B packing (see 5.2.2.1).
g. When palletization is required (see 5.3).

* 6.3 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of FAR 52.209. The first article should be a preproduction sample. The contracting officer should specify the appropriate type of first article and the number of units to be furnished. The contracting officer should include specific instructions in acquisition documents regarding arrangements for selection, inspection, and approval of the first article.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:00Z
Check the source to verify that this is the current version before use.

* 6.4 Subject term (key word) listing.

Containers
Hygiene, personal
Individual equipment

6.5 Changes from previous issue. The margins of this specification are marked with asterisks to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content, irrespective of the marginal notations and relationship to the last previous issue.

Custodian:

Army - GL

Preparing activity:

Army - GL

(Project 8465-0010)

Review activities:

Army - MD
DLA - CT

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:00Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:00Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-S-43674C(GL)	Shower Pail, Callapsible, Cotton Duck, 5-Gallon Capacity

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR ☐ USER ☐ MANUFACTURER ☐ OTHER *(Specify)*: _____
b. ADDRESS *(Street, City, State, ZIP Code)*	

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:00Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

U.S. ARMY NATICK RESEARCH, DEVELOPMENT
and ENGINEERING CENTER
ATTN: STRNC-ES
Natick, MA 01760-5014

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
U.S. Army Natick Research, Development
and Engineering Center
ATTN: STRNC-ES
Natick, MA 01760-5014

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:00Z
Check the source to verify that this is the current version before use.