A-A-1454
September 26, 1980

COMMERCIAL ITEM DESCRIPTION

TIMER, INTERVAL, ELECTRIC (ANALOG)

The General Services Administration has authorized the use of this commercial item description.

Salient characteristics:

Material. The materials used shall be of sufficient strength and durability to ensure that the timers are securely and sturdily constructed and will remain usable over the normal lifetime of a timer. Any metals used shall be corrosion resistant or treated to resist any type of corrosion, consistent with their normal functioning. The crystal material shall be clear, non-yellowing and not easily scratched.

Dimensions. The overall dimensions of the timer shall be no more than 6 inches high, 6 inches wide and 4 inches deep.

Mounting. The base shall be stable, with no rocking or wobbling, when placed on a flat, level surface. The base shall have at least two mounting holes. The timer shall have a suspension device securely attached to the case and capable of supporting the entire weight of the timer.

Marking. The timer shall have two scales: The outer scale shall be marked every 15 seconds and numbered for each minute. The inner scale shall be marked and numbered for each ten minute interval.

Hands. There shall be two hands, one of appropriate length for each scale. The hands shall be easily set for any desired interval to a maximum of at least 119 minutes. The hands shall indicate the time remaining in the interval.

Clock Mechanism. The clock mechanism shall be electrically driven, drawing power from standard 110 to 120 volt, 60 Hertz, alternating current outlets. It shall be accurate to $\pm$ 1.0 seconds per hour with no need for adjustment. The power cord, complete with plug, shall be at least 5 feet long.

Alarm. An alarm shall sound at the end of an interval for no more than 5 seconds. It shall be audible from a distance of 25 feet.

Safety. The completed timers shall conform to the applicable requirements of Underwriters Laboratories (UL) Standard No. 863. Acceptable certification of this conformance shall be the UL Label, UL Listing Mark or certified report from a recognized independent testing laboratory acceptable to the Government, indicating that the timers offered have been tested and conform to UL 863.

The issues of UL 863 in effect on the date of the solicitation shall be used to determine compliance with stated requirements.

Readability. The markings, numbers and hands shall contrast with the dial and readability from a distance of 5 feet in normal office light. They shall also be readable from a distance of 3 feet in total darkness or in the light from a safelight.

Starting Device. The starting device shall be conveniently located on the outside of the timer case. It shall activate the timer when placed in the "start" position and automatically return to its original position by the end of an interval.

Workmanship. The workmanship shall ensure that the timer is of "professional" quality. The timer shall be free from sharp or rough edges, or any other defects which may injure the user or impair serviceability.

Certification. The contractor shall certify that the product offered meets the salient characteristics of this description, and that the product conforms to the producer's own drawings, specifications, standards, and quality assurance practices and is the same product offered for sale in the commercial marketplace. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

Source: https://assist.dla.mil -- Downloaded: 202640-26T08:14Z
Check the source to verify that this is the current version before use.

Recovered materials. The manufacturer shall utilize recovered materials to the maximum extent practicable.

Packaging, packing, and marking. The packing and packing shall be in accordance with normal commercial practice and shall assure acceptance by common carrier and provide product protection against loss and damage during multiple shipments, handling, and storage. The shipping container shall be in compliance with the National Motor Freight Classification and Uniform Freight Classification. Marking shall be as specified in the contract or order.

GSA DC-01108505

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:14Z
Check the source to verify that this is the current version before use.