INCH-POUND

A-A-2513A
May 16, 2002
SUPERSEDING
A-A-2513
April 1, 1987

COMMERCIAL ITEM DESCRIPTION

BRUSHES, WIRE, ROTARY, END ATTACHMENT, SOLID WIRE FILLED

The General Services Administration has authorized the use of this Commercial Item Description by all federal agencies.


1. SCOPE. This Commercial Item Description covers brushes for use with pneumatic or electric tools in the removal of rust, scale, paint, or burrs from small or confined areas of all types of metal surfaces.

2. CLASSIFICATION. Unless otherwise specified brushes shall conform to the following types.

2.1 Type I. Brass.

2.2 Type II. Stainless Steel.

2.3 Type III. High carbon tempered steel.



End attachment brush.

3. SALIENT CHARACTERISTICS.

3.1 Design. Solid filled brush with crimped wire extending parallel to 1/4 arbor shaft, filled to the center of the brush.

3.1.1 Body. The body shall be of specified diameter and steel overall. Construction shall be in such a manner as to insure even distribution of the wire throughout the brush to provide a balanced unit for minimal vibration at maximum safe free speed. Provisions shall be made for securely holding the fill wires in place to prevent the wire from detaching due to flex during use or at maximum safe free speed.

3.1.2 Arbor. The brush shall possess a round arbor shaft 1/4 inch in diameter and of steel. To minimize vibration the arbor shall be referenced to the body in a manner that allows the brush to run true while in use.

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any other data that may improve this document should be sent to: General Services Administration, Federal Supply Service, Hardware SuperStore, 6FEE, 1500 Bannister Rd., Bldg.# 6, Kansas City, Missouri 64131.

FSC 5130

Source: https://assist.dla.mil -- Downloaded: 202640-26T08:23Z
Check the source to verify that this is the currentversion before use.

3.1.3 Wire. As specified, the crimped wire shall be of brass, stainless, or high carbon tempered steel. The crimped wire shall be comprised of at least four, single-amplitude, three; dimensional-crimps per inch of specified diameter and wire points (wire-density). Where welded construction is used, the wire shall not be burned, broken, or affected in any way by the welding process.

3.2 Identification marking. The tool shall be marked with the Maximum Safe Free Speed, (RPM or MSFS), and the words "Wear Eye Protection", the manufacturer's name or identifying symbol and the state or country of manufacture, unless otherwise specified. All identification markings shall be etched, engraved, molded, or indented directly on the item's surface in such a manner that it remains clearly legible throughout the life of the item.

3.3 Workmanship. Details of workmanship shall be in accordance with the best commercial practices. Paints, coatings, plating, and finishes shall be smooth, adherent, continuous and not stained or discolored. External surfaces shall be free of tool and gouge marks, nicks, or other surface imperfections. The item shall be free from manufacturing workmanship defects (e.g. sharp or rough external edges, corners, or surfaces) and material workmanship defects (e.g. pits, rips, fins, burrs, tears, nodules, cracks, or blisters), which may adversely impact the item's serviceability, durability, safety, or appearance.

4. REGULATORY REQUIREMENTS.

4.1 Recovered materials. The supplier/manufacturer is encouraged to use recovered materials to the maximum extent practicable, in accordance with paragraph 23.403 of the Federal Acquisition Regulation (FAR).

4.2 Metric products. Products manufactured to metric dimensions will be considered on an equal basis with those manufactured using inch-pound units, provided they fall within the tolerances specified (using conversion tables contained in the latest revision of Federal Standard 376) and all other requirements of this document are met. If a product is manufactured to metric dimensions and those dimensions exceed the tolerances specified in the inch- pound units, a request should be made to the contracting officer to determine if the product is acceptable.

5. PRODUCT CONFORMANCE.

5.1 Safety. The brushes shall comply with American National Standards Institute (ANSI) standard B165.1, Safety Requirements for the design, Care and Use of Power Driven Brushing Tools.

5.2 Product Conformance. The products provided shall meet the salient characteristics of this Commercial Item Description, conform to the supplier's own drawings, specifications, standards and quality assurance practices, and the same product and offered for sale in the commercial market. The government reserves the right to require proof of such conformance.

5.3 Responsibility for inspection. Unless otherwise specified, the supplier is responsible for the performance of all inspection requirements and may use any commercial facilities (including the supplier's own facilities) suitable for performance of the inspection requirements, unless disapproved by the Government. The Government reserves the right to perform any inspections deemed necessary to assure the item conforms to the specified requirements.

6. PACKAGING. Requirements of preservation, packing, packaging, and marking of packages shall be as specified in the contract or order.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:23Z
Check the source to verify that this is the current version before use.

7. NOTES.

(This section contains information of a general or explanatory nature that is not mandatory.)

7.1 Addresses for obtaining copies of referenced documents:

Federal Acquisition Regulation (FAR): Government Printing Office, Superintendent of Documents, Washington, DC 20401-9371

GSA Specification Section (3FP-E), Suite 8100, 470 L'Enfant Plaza, SW, Washington, DC, 20407.

American National Standards Institute (ANSI), Washington, DC Headquarters, 1819 L Street. NW, 6th Fl., Washington, DC, 20036

7.2 National Stock Numbers (NSNs). The following NSN list corresponds to the types specified in this CID This list may not be indicative of all possible NSNs associated with this CID.

Rotary wheel wire brush.						
National Stock Numbers	Type	Outside brush diameter (inch)	Wire diameter. (inch)	Arbor diameter (inch)	Wire trim length (inch) (min-max)	Max safe free speed. (RPM)
5130-01-027-0493	I	1.	.006	1/4	3/4-1 1/8	15,000
5130-00-900-3584	I	1.	.006	1/4	3/4-1.	8,000
5130-01-027-0494	I	1/2	.006	1/4	3/4-1 1/8	25,000
5130-00-199-6648	II	1.	.0094	1/4	3/4-1 1/8	8,000
5130-00-456-5482	II	1/2	.014	1/4	3/4-1 1/8	8,000
5130-00-435-2310	II	1/2	.006	1/4	1/4-1.	8,000
5130-00-960-9743	II	3/16	.006	1/4	1 1/2-1 5/8	8,000
5130-00-455-9053	II	5/16	.006	1/4	9/16-7/8	8,000
5130-00-263-0235	III	1.	.0204	1/4	3/4-1 1/8	8,000
5130-00-456-5483	III	1.	.014	1/4	3/4-1 1/8	8,000
5130-00-539-7762	III	1.	.006	1/4	3/4-1 1/8	15,000
5130-01-015-3971	III	1/2	.0204	1/4	3/4-1 1/8	15,000
5130-00-293-2410	III	3/4	.0204	1/4	3/4-1 1/8	8,000
5130-00-435-2309	III	3/4	.006	1/4	3/4-1 1/8	8,000

7.3 Ordering data. The contract order should specify the following (in inches):

(A) Title, number, and date of Commercial Item Description.
(B) Type.
(C) Brush outside diameter. (O.D.)
(D) Wire diameter.
(E) Wire trim-length.
(F) Max RPM. (Free-speed)
(G) Preservation, packing, packaging, and marking of brushes, required.

7.4 Key words. End attachment wire brushes.

MILITARY INTERESTS:

NONE: DoD has no registered interest in revisions and amendments to this Commercial Description until further notice.

Preparing Activity:

GSA - FSS

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:23Z
Check the source to verify that this is the current version before use.