A-A-2603
February 24, 1989
SUPERSEDING
FF-S-001169
July 5, 1971

COMMERCIAL ITEM DESCRIPTION

SHREDDING MACHINE, PAPER, OFFICE (STRAIGHT CUT, HIGH SPEED)

The General Services Administration has authorized the use of this commercial item description in preference to Interim Federal Specification FF-S-001169.

This description covers straight cut paper shredders operating at a speed of 100 feet/minute or more, which are intended for use with letter size paper and computer printout forms. They shall be of the following classes and types:

Class I - Throat width - 9 inches, min.

Type A - Shred width - 3/64 inch, max.; capacity - 5 sheets, min.

Type B - Shred width - 7/32 inch, max.; capacity - 15 sheets, min.

Class II - Throat width - 12 inches, min.; capacity - 10 sheets, min.; shred width - 9/32 inch, max.

Class III - Throat width - 16 inches, min.; capacity - 10 sheets, min; shred width - 9/32 inch, max.

Salient characteristics.

Speed. Shredders shall have a minimum speed of 100 feet/minute while engaged in shredding operations.

Models. Machine shall be furnished either as a tabletop model with mounting stand/cabinet or as a console type with casters.

Capacity. Capacity is defined as the number of sheets of 20-lb. bond paper, 8-1/2 by 11 inches in size, that can be fed simultaneously into the machine without jamming.

FSC 7490

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:24Z
Check the source to verify that this is the current version before use.

Controls. Shredders shall be provided with either automatic shut-off and reverse controls or manual shut-off and forward and reverse flow controls.

Power requirements. Shredders shall be capable of operating on 115 volt, 60 Hz AC electrical current.

Identification. Each shredder shall have the manufacturer's serial number permanently and legibly stamped or affixed on a major component in a readily accessible location. In addition, each shredder shall be permanently marked in a conspicuous location with the manufacturer's name or trademark.

Instruction manual. An instruction manual shall be furnished with each machine. The manual shall contain complete instructions necessary for operation, maintenance and minor repair of the machine.

Paper clips, etc. All shredders, except Class I, Type A, shall be capable of shredding material containing regular metal paper clips and staples without jamming.

Workmanship. The machine, including all parts and accessories, shall be fabricated and finished in accordance with good workmanship standards. The machine shall be free from any defect which affects the appearance, durability or serviceability or which might cause personal injury.

Conformance. Shall be in compliance with the requirements of Underwriters Laboratories (UL) Standard 478.

Safety. All units shall have either a self-closing feed door design or have a feed throat or hopper design that protects any operator(s) from flying debris that may be ejected from the pulverizer due to rotor/cutter damage, etc.

Quality Assurance Provisions.

Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein.

Lot acceptance inspection. The finished items shall be visually inspected and functionally tested in order to establish acceptability based on conformance to the following requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:24Z
Check the source to verify that this is the current version before use.

Sampling. Sampling for visual inspection and testing of shredding machines shall be performed in accordance with the provisions of MIL-STD-105. Inspection levels and acceptable quality levels shall be as follows:

Visual inspections: Level II, AQL = 2.5% for major and 4.0% for minor defects.

Performance testing: Level S-2, AQL = 1.5%.

Visual inspection. Samples of the finished items selected in accordance with the requirements herein shall be visually inspected to verify compliance with item description and salient characteristics of the CID. Compliance with the above shall be determined based upon the presence or absence of defects as classified below.

Defects

Major

- Machine class/type, not as specified.
- Throat width less than specified minimum.
- Machine controls not as specified.
- No evidence of conformance to UL Standard 478.
- Machine identification not as specified, missing, illegible, not permanently stamped/affixed.
- Parts/components, cables, wires, damaged, missing, loose or misplaced.
- Poorly finished surfaces, sharp edges, severe dents, nicks, scratches.
- Nicked, worn or loose cutters.
- Poor finish, incomplete paint coverage of metal parts.
- Machine stability, poor.
- Machine rigidity, poor.
- Instruction manual not available, inadequate, illegible.

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:24Z
Check the source to verify that this is the currentversion before use.

Minor

- Minor paint streaks.
- Minor nicks, scratches.
- Departure from basic color requirement (if applicable).
- Dusted/unclean surfaces.

Performance testing. Samples selected in accordance with the requirements herein shall be tested to verify conformance with requirements of the CID for machine capability to operate under the specified/rated power, capacity, shredding speed and pattern, single feed capacity, and durability. Nonconformance with any of the above shall be regarded as a test failure and grounds for rejection.

Shredding speed. A measured length of 8-1/2" wide, 20-lb. bond paper shall be fed into the the cutters of the machine. The time required to shred the paper shall be noted. The speed shall then be calculated on the basis of feet per minute.

Single feed capacity. The shredder shall be fed a series of test sets consisting of 8-1/2" wide, 20-lb. bond paper. The number of sheets in each succeeding test set shall be increased by one. The maximum number of sheets accepted in a single pass without jamming or stalling the machine shall be noted.

Durability test. The machine under test shall be manually fed an assortment of paper sizes at its maximum rated capacity for sixty minutes. The rate of feed shall be that which can normally be accomplished by an average adult. The machine shall then be evaluated to the stated requirements listed in the Workmanship paragraph. Periodically, samples of the shredded material shall be taken from the machine and measured for compliance with the applicable shred width requirement.

Cutters. After completion of tests, cutters shall be examined for nicks, wear or other evidence of damage that could affect the normal shredding operation.

Regulatory requirements. In accordance with section 23.403 of the Federal Acquisition Regulations, the Government's policy is to acquire items composed of the highest percentage of recovered materials practicable, consistent with maintaining a satisfactory level of competition without adversely affecting performance requirements or exposing supplier's employees to undue hazards from the recovered materials.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:24Z
Check the source to verify that this is the current version before use.

Preservation, packaging, packing, labeling and marking. The preservation, packaging, packing, labeling and marking shall be as specified in the contract or purchase order.

Notes.

(1) UL Standard 478 is available from the Underwriters Laboratories Inc., 333 Pfingsten Road, Northbrook, IL 60062.

(2) Purchaser shall specify:

Class I, Type A,	NSN 7490-01-288-0439
Class I, Type B,	NSN 7490-01-288-0440
Class II,	NSN 7490-01-288-0441
Class III,	NSN 7490-01-288-0442

PREPARING ACTIVITY:

GSA - FSS

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:24Z
Check the source to verify that this is the current version before use.