[METRIC]

A-A-2794
June 18, 1992

COMMERCIAL ITEM DESCRIPTION

CASE, FILING, TRANSFER

The General Services Administration has authorized the use of this commercial item description.

This description covers case, filing, transfer, used for maintenance, transfer or storage of index cards, without damaging them, and to readily permit their removal and replacement.

1. SALIENT CHARACTERISTICS

A. TYPE:

Type I - Holds 7.62 X 12.70 centimeter <cm> (3 X 5") cards.
Type II - Holds 10.16 X 15.24 centimeter <cm> (4 X 6") cards.
Type III - Holds 12.70 X 20.32 centimeter <cm> (5 X 8") cards.

B. INSIDE DIMENSIONS:

	Height	Width	Depth
Type I -	8.89 cm (3-1/2")	13.34 cm (5-1/4")	27.31 cm (10-3/4")
Type II -	11.43 cm (4-1/2")	15.88 cm (6-1/4")	27.31 cm (10-3/4")
Type III -	13.97 cm (5-1/2")	20.96 cm (8-1/4")	27.31 cm (10-3/4")

C. DIMENSIONAL TOLERANCES: A plus tolerance of 6.4 millimeters <mm> (1/4 inch), or a minus tolerance of 3.2 mm (1/8 inch) will be permitted in height, width and, depth.

D. Tray and cover shall be made of a base stock of binders' board, heavy chipboard, hard-pressed fiberboard, or a suitable combination thereof. The thickness of the tray or cover including the cover paper shall be not less than 3.5 mm (0.138 inch) thick.

DISTRIBUTION STATEMENT A : Approved for public release; distribution is unlimited.

FSC 7520

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:26Z
Check the source to verify that this is the current version before use.

E. A locking follower plate and a centered reinforcing follower strip shall be used. The centered strip shall be 6.35 cm (2-1/2 inches) minimum, in width. Index cards shall rest on the follower assembly.

F. Instead of a centered strip, a follower rod may be used together with two reinforcing strips, one on each side of the rod. Each side strip shall be 1.27 cm (1/2 inch) minimum, in width.

G. The locking follower plate, the center reinforcing strip and the follower rod shall be made of corrosion resistant metal or plastic. Side strips shall be made of wood, plastic, corrosion resistance metal, binders' board, chipboard or hard pressed fiberboard. Side strips shall be of sufficient thickness to permit index cards to rest on the strip, not on the follower rod.

H. A centered reinforcing follower strip that is less than 6.35 cm (2-1/2 inches) in width may be used if the two side strips mentioned above are added.

I. All adjoining corners and edges of both the tray and cover shall be reinforced with cloth, or filament tape. The tape shall cover the entire outside corners, and shall extend a minimum of 9.5 mm (3/8 inch) on each side.

J. The tray and cover shall fit together and all sides of the cover shall extend down over the tray 2.54 cm (1 inch) $\pm$ 3.2 mm (1/8 inch).

K. Both the exterior of the tray and cover shall be covered with matching agate marbleized paper. The paper shall extend a minimum of 1.27 cm (1/2 inch) over the edges into the sides and extend over the entire tray bottom.

L. The interior of the tray and cover shall be colored black.

M. The exterior of the tray and cover shall be black agate.

N. The tray shall include a follower assembly consisting of a locking follower plate on a rod or track. The locking follower plate shall be of sufficient size and construction to hold the specified size cards securely in place without damage. Corners and edges of the locking follower plate shall be smooth.

O. The tray shall have a label holder and pull made of a commercially acceptable corrosion resistant metal.

P. The label holder and pull shall be placed in the middle of the tray front and securely attached.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:26Z
Check the source to verify that this is the current version before use.

Q. Workmanship: All cases shall be free of any defects which may impair appearance or serviceability. Defects include, but are not limited to: incorrect dimensions, unapproved color, misapplied lining or covering, wrinkles, bubbles or ragged edges in lining or covering, or any corners not reinforced according to standard manufacturing practice.

2. RECOVERED MATERIALS

The Tray and cover shall have a minimum of 40% post consumer recovered material in accordance with 40 CFR, part 250. Parts made of metal or plastic shall contain recovered material to the maximum extent practical.

3. QUALITY ASSURANCE

A. Each lot of Cases, Filing, Transfer shall be inspected for conformance to the requirements herein. Inspection shall be in accordance with MIL-STD-105 using the sampling plans specified below.

B. Visual characteristics - Inspection Level S-4 with an Acceptable Quality Level (AQL) of 4.0 percent defective. The sample unit shall be one Case, Filing, Transfer.

C. Dimensional characteristics - Inspection Level S-2 with an Acceptable Quality Level (AQL) of 4.0 percent defective. The sample unit shall be one Case, Filing, Transfer.

D. Packaging, Packing, and Marking - Inspection Level S-2 with an AQL of 4.0 percent defective. The sample unit shall be one fully prepared shipping container.

4. APPLICATION FOR COPIES OF TECHNICAL DOCUMENTS REFERENCED HEREIN

The issue date in effect on date of invitation for bids or request for proposal shall apply.

A. MIL-STD-105 is available from Standardization Documents Order Desk; Building 4D; 700 Robbins Avenue; Philadelphia, PA 19111- 5094.

B. Code of Federal Regulations, Title 40, Part 250 is available through the Superintendent of documents, U.S. Government Printing Office, Washington DC 20402.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:26Z
Check the source to verify that this is the current version before use.