[INCH-POUND]
A-A-419A
July 08, 1998
SUPERSEDING
A-A-419
October 1, 1985

COMMERCIAL ITEM DESCRIPTION
RIBBON, TELETYPEWRITER

The General Services Administration has authorized the use of this commercial item description by all federal agencies.

1. **Scope:** This commercial item description covers nylon fabric ribbons to be used on teletypewriters.

2. **Salient Characteristics.**

2.1 **Weave.** The fabric used shall have a regular commercial weave suitable for the purpose intended.

2.2 **Edges.** Ribbon edges shall be straight and paralleled to the warp threads. To prevent fraying, edges of ribbons shall be fused.

2.3 **Thickness and Yarn Count.** Ribbon thickness and yarn count shall be as specified in table I. ASTM D 1777 shall be used to determine thickness. Edges shall not be used to determine fabric thickness.

2.4 **Color.** Ribbons shall be single color or two color as specified. Two-color ribbons shall have an equal width for each color, unless otherwise specified.

2.5 **Inking.** Ribbons shall be evenly inked. The division of two-color ribbons shall be clearly delineated, and neither color shall bleed into the other prior to or during ribbon use.

2.6 **Length.** Length shall be as specified as a minimum. Ribbons shall be furnished in continuous lengths without joining or splicing.

2.7 **Width.** Width shall be as specified. A tolerance of + 1/64 inch – 0.0 inch) shall be permitted, provided print quality and ribbon operation are not affected.

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any data which may improve this document should be sent to General Services Administration, Federal Supply Service, Engineering Branch, 26 Federal Plaza, New York, NY 10278.

FSC 7510

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:08Z
Check the source to verify that this is the current version before use.

Table I.
Ribbon Thickness Chart

Thickness (Inches)	Total Yarn Count Threads Per Sq. Inch	Warp Minimum Threads Per Inch	Fill Minimum Threads Per Inch
0.0038 - 0.0042 inch	277 - 296	165	112
0.0048 - 0.0052 inch	272 - 286	164	108

2.8 Spools, Cartridges, & Cores. Each ribbon shall be furnished on a metal or plastic spool, cartridge, fiber core, fiber center or in a coreless configuration for the specified machine. Metal, except aluminum, shall have an enamel, lacquer, or plated finish. Each ribbon shall be designed to operate satisfactorily with the ribbon feed and reversing mechanisms of the machine specified.

2.9 Workmanship. Ribbons shall be evenly woven and free from imperfections of manufacture that may affect their durability, appearance or serviceability. Examples of ribbon defects are uneven weave, frayed edges, slits, and knots. The ribbon spools, cartridges or cores shall be free from all defects that will affect performance and serviceability or present a hazard to the user.

2.10 Shelf Life. Ribbons shall have a shelf life of one year after delivery and shall be capable of withstanding normal usage and handling and pass the performance test as specified in paragraph 4.2.1.

3. Regulatory Requirements: The offerer/contractor is encouraged to use recovered materials to the maximum extent practical, in accordance with paragraph 23.403 of the Federal Acquisition Regulation (FAR).

3.1 Hazardous Material Requirements.

3.1.1 Toxicity. Use of any toxic substance must be in accordance with all applicable federal statutes. The use of any known carcinogens as ingredients is prohibited. The harmful substances shall be defined as the poison and injurious substances as designated in Fed Std. 313. The vendor shall prepare a certification that the ribbon conforms to the above requirements.

3.1.2 Material Safety Data Sheets. Safety data shall be furnished in accordance with Fed Std. 313. The pertinent government mailing addresses for submission of data are listed in appendix B of Fed. Std. 313.

3.1.3 Labeling. Containers shall be labeled to comply with the Federal Hazardous Substances Act Regulations, 16 Code of Federal Regulations, Part 1500.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:08Z
Check the source to verify that this is the current version before use.

4. Quality Assurance Provisions:

4.1 Product Conformance. The products provided shall meet the salient characteristics of this commercial item description. Quality of the product sold to the government shall be equal to or better than the quality of the product sold by the manufacturer in the commercial market. The government reserves the right to require proof of such conformance.

4.2 Performance Test.

4.2.1 Place a sample ribbon and place in the machine designated for its use in the contract and operate the machine in the normal manner until the ribbon has run its full course and is wound from one side to the other. During the course of the test operation, the ribbon shall be observed to ensure that it is not binding or twisting so as to interfere with proper printing. Upon completion of the test, the printed matter (the product of the ribbon printing test) shall be examined to ensure that the quality of print is uniformly dark and with no blank spots, light spots, or discontinuities. Failure to comply with any of these requirements shall be cause for rejection after testing in accordance with ASTM F 92.

4.2.2 As an alternative to the prescribed performance test, the contractor may supply a certification from the equipment manufacturer that the ribbon, identified by part number has been tested and will function properly on the equipment for which it was designed. Selected samples will then be tested on any compatible printer for the print quality defined above.

4.2.3 If the equipment manufacturer refuses to certify the ribbon or tape, then the ribbon manufacturer may then certify that the ribbon manufacturer (contractor) guarantees that the ribbon or tape will function properly on the equipment for which it has been designed.

4.2.4 Ribbon Condition (end of test). Ribbon shall withstand the test without signs of excessive frayed edges, excessive curling, or the development of holes. Excessive shall be interpreted to mean when frayed edges or curling (1) is the cause of broken characters or (2) interfere with proper ribbon feed.

Table II.
Impression/ Character Yield of Printer Ribbons

	Test Hours	Percent Reflectance (not more than)
Single - color, black	5	40
Two - color, black and red:		
Black Portion	4	45
Red Portion	3	65

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:08Z
Check the source to verify that this is the current version before use.

5. Packaging:

5.1 Packaging, packing, palletization and marking shall be as specified in the contract or order.

6. Notes:

6.1 **Source of Documents.** The following documents form a part of the commercial item description to the extent specified herein. Unless otherwise indicated, the issue in effect on the date of invitation for bids or request for proposal shall apply:

6.1.1 Federal Acquisition Regulation (FAR) may be obtained from the Superintendent of Documents, Government Printing Office, Washington DC 20402.

6.1.2 Copies of the appropriate ASTM's may be obtained from the American Society for Testing and Materials at 100 Barr Harbor Dr., West Conshohocken, PA 19428-2959.

6.1.3 Federal Standards and Specifications may be obtained from the General Services Administration Specifications Section (3FBO-W) in Suite 8100 at 470 L'Enfant Plaza, SW Washington DC 20407.

6.2 **Ordering information.** Purchasers shall select the required options permitted herein, and include the following information in procurement documents:

(1) Title, number, and date of this commercial item description.
(2) Purchaser shall specify the ribbon dimensions and shall indicate length, width, color and inking criteria (if other than specified in the CID), manufacturer's name and model number of the machine on which the ribbon will be used in the procurement document. Purchasers shall indicate the original manufacturers specifications (OEM) if required.
(3) Material safety data sheets required, in addition to those required by Fed-Std-313.

6.3 **National Stock Number Listing (NSN's).** The following is a list of nsn's assigned which correspond to this commercial item description. The list may not be indicative of all possible nsn's associated with the (CID).

7510-01-017-6155	7510-00-082-2649	7510-00-181-7507
7510-00-082-2648	7510-00-148-9771	7510-00-923-0252

MILITARY INTERESTS:
NONE:

Preparing Activity:
GSA-FSS

Source: https://assist.dla.mil -- Downloaded: 2026l0-26T08:08Z
Check the source to verify that this is the currentversion before use.