

MILITARY SPECIFICATION SHEET
BATTERY, STORAGE BB-431/U

The complete requirements for procuring storage batteries described herein shall consist of this document and the issue in effect of Specification MIL-B-55118(EL).



DETAIL A



INCHES	MM
.005	0.13
.015	0.38
.025	0.64
.397	10.08
.540	13.72
1.080	27.43
1.625	41.28
2.420	61.47
6.280	159.5
6.875	174.6
6.950	176.5

NOTE: See notes on next sheet.

FSC 6140

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:26Z
Check the source to verify that this is the current version before use.

NOTES (Applicable to foregoing drawing):

1. All dimensions shown on figure are in inches. Unless otherwise specified, tolerance is ± 0.015 in.

2. Metric equivalent shown on specification sheet are for general information only and are based upon 1 inch = 25.4 millimeters.

3. The standard bayonet type filler cap shall be Military Part No. MS75046-2.

4. An electrolyte level line should not be furnished on cell's container. The level of electrolyte shall be measurable by a glass tube. Level shall be adjusted with distilled water to 1/4 to 3/8 in. above the top of the plates after full charge.

5. The two threaded stud type terminals shall be UNF-2A, Grade 1018 cold rolled steel per Fed. Spec. QQ-S-634, AMS 5069, ASTM A-108 with M212 finish per Mil. Spec. MIL-F-14072.

6. The two 5/16-24 UNF-2A hex nuts on each terminal shall be nickel plated steel.

7. The cell post top on each terminal shall be alkali resistant metal, compatible with the hex nuts.

8. The Belleville spring on each terminal shall be 302 stainless steel similar to Part No. MS75044-2 except hole diameter (B) is 0.323 ± 0.003, "c" dimension is 0.013 and thickness is 0.025. Force to flatten shall be 150 pounds ± 15%.

9. The 6.525 height dimension measures from cell bottom to the top surface of bottom cell nut, as shown in Detail A.

10. The intercell link shown in Detail A is not furnished as part of the cell when cells are procured.

11. The head-space for the cell is defined as the space between plate tops and bottom of the cell's cover for electrolyte and gas. This space shall be at least twenty (20)% of the overall cell container volume.

12. For design feature purposes, this specification sheet takes precedence over procurement documents referenced herein.

13. Referenced documents shall be of the issue in effect on date of invitation for bid unless a specific exception is taken to same.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:26Z
Check the source to verify that this is the current version before use.

BATTERY, STORAGE
BB-431/U
(CELL)

REQUIREMENTS:

Class: Vented nickel cadmium cell

Dimensions and configuration: See figure and notes.

Weight (max.): 1.25 pounds.

Terminals: Two studs, each complete with a Belleville spring and two hex nuts per figure and notes.

Container: Polyamide, ABS or equal.

Head space: 20% minimum per Note 11.

Filler cap: Std. per Note 3.

Vent release pressure: 6.0 ± 4.0 psig.

Nominal voltage: 1.2 volts.

Final voltage: 1.0 volt.

Rated capacity, (5 hr. rate): 14.0 amp. hrs.

Normal charge: 0.55 C_5 to 1.58 volts, then 0.17 C_5 for 2.0 hrs.

Normal discharge rate: 0.20 C_5.

0.17 C_5 rate: 2.3 amps.

0.20 C_5 rate: 2.8 amps.

0.23 C_5 rate: 3.2 amps.

0.33 C_5 rate: 4.7 amps.

0.55 C_5 rate: 7.7 amps.

Source: https://assist.dla.mil -- Downloaded: 20261O-22T22:26Z
Check the source to verify that this is the current version before use.

BATTERY, STORAGE
(CELL)
BB-431/U

First Article Inspections	MIL-B-55118 Inspection Paragraph	Requirement
Visual and mechanical examination	4.7.1	Table IX
Initial full capacity Discharged (upright)	4.7.14.1	14.0 AH @ 0.20 C_5
Discharged (on side)	4.7.3.1	14.0 AH @ 0.20 C_5
Cycle life	4.7.15	1008 cycles to 9.8 AH
Potassium carbonate	4.7.7	Less than 60 grams per liter
Retention of charge I (14 days)	4.7.13.1	12.6 AH @ 0.20 C_5
Retention of charge II (4 days)	4.7.13.2	5.6 AH @ 0.20 C_5
Low temperature	4.7.14.5	8.4 AH @ 0.20 C_5
Temperature cycling	4.7.10	No physical defects per Table I
Full capacity (upright)	4.7.14.3	14.0 AH @ 0.20 C_5
Mechanical shock	4.7.11	No physical defects per Table I
Full capacity (upright)	4.7.14.3	14.0 AH @ 0.20 C_5
Vibration	4.7.12	No physical defects per Table I
Full capacity (upright)	4.7.14.3	14.0 AH @ 0.20 C_5
Internal pressure	4.7.2	No leakage
Electrical leakage	4.7.9	More than 50 megohms

Quality conformance inspection:

It encompasses same inspections as first article except cycle life shall be 504 cycles to 11.9 AH.

Sampling: See latest issue of MIL-B-55118(EL).

Custodian:
Army-EL

Preparing Activity
Army-EL

Project No. 6140-A300

Source: https://assist.dla.mil -- Downloaded: 202610-22T22:26Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION MIL-R-55118/2(EL) MILITARY SPECIFICATION SHEET BATTERY, STORAGE BB-431/U

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)*

DATE

DD FORM 1 JAN 66 1426

REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

ESC-FM 1068-68

Source: https://assist.dla.mil -- Downloaded: 202610-22T22:26Z
Check the source to verify that this is the current version before use.

FOLD

Department of the Army
Headquarters
U.S.Army Electronics Command
Fort Monmouth, New Jersey 07703

POSTAGE AND FEES PAID

OFFICIAL BUSINESS

Commanding General
U.S.Army Electronics Command
ATTN: AMSEL-PP-ED
Fort Monmouth, New Jersey 07703

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:26Z
Check the source to verify that this is the current version before use.