MIL-C-50744A(AR)
30 June 1981
SUPERSEDING
MIL-C-50744(AR)
8 AUGUST 1973

MILITARY SPECIFICATION

CIRCUIT CARD ASSEMBLY: 11737802 INTERFACE

This specification is approved for use by the US Army Armament Research and Development Command (ARRADCOM) and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification establishes the requirements and quality assurance provisions for the Circuit Card Assembly: 11737802 Interface, which is the A7 component of the Electronic Unit, 11743131.

2. APPLICABLE DOCUMENTS

2.1 Issues of documents. The following documents of the issue in effect on data of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-F-13926	Fire Control Materiel, General Specification Governing the Manufacture and Inspection of
MIL-I-45607	Inspection Equipment; Acquisition, Maintenance, and Disposition of
MIL-STD-45662	Calibration System Requirements

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Command, Attn. DRDAR-QA, Dover, New Jersey 07801 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 1240

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:36Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-810	Environmental Test Methods

DRAWINGS

ARRADCOM

11737802	Circuit Card Assembly: 11737802 Interface

Inspection Equipment

11750202	Automatic Card and Unit, Test Set
11750435	Adapter, Interface
11821457	Fixture Shock, Vertical and Horizontal Plane
11821458	Shock Adapter, Plate Vib Horz-Vert Plane/ Shock-Z
11821520	Automatic Test Assembly Central Processor Unit
11821647	Vibration/Shock Test Fixture - Electronic Unit, AC, FAT

Packaging Data Sheet

P11737802	Packaging of Circuit Card Assembly: 11737802 Interface

(Copies of specifications, standards, drawings, and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:36Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Fabrication. The interface circuit card assembly, herein referred to as the assembly, shall be manufactured in accordance with Drawing 11737802 and drawings pertaining thereto and, when assembled, shall meet the requirements of this specification. (See 4.5.1)

3.1.1 Function. The assembly shall provide the following functions:

	Function Designation
a.	$\overline{\text{A-trigger}}$
b.	$\overline{\text{Video}}$
c.	Test range
d.	$\overline{\text{Reset}}$
e.	$\overline{\text{Malfunction 4}}$ logic
f.	+200 volt malfunction
g.	$\overline{\text{Malfunction 2}}$ logic
h.	+15V interlock and range light signals
i.	$\overline{\text{Minimum range inhibit}}$
j.	$\overline{\text{Range}}$ signal
k.	$\overline{\text{Alarm}}$ signal

3.1.2 General specifications. The following provisions of MIL-F-13926 apply: (See 4.5.1)

a. Order of precedence
b. Dimensions and tolerances
c. Inorganic protective surface finishes
d. Part identification and marking
e. Workmanship

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:36Z
Check the source to verify that this is the current version before use.

3.1.3 Ambient Conditions. Standard ambient conditions shall be as follows:

a.	Temperature	73° ±18°F
b.	Relative humidity	50 percent ±30 percent
c.	Atmospheric pressure	28.5 + 2.0 −3.0 in. Hg.

3.2. First article. When specified (see 6.2), the contractor shall furnish sample units for first article inspection and approval (see 4.4 and 6.2).

3.3 Performance. Unless otherwise specified, the assembly shall meet the performance requirements specified herein under standard ambient conditions of 3.1.3.

3.3.1 $\overline{\text{A-trigger}}$. With the digital type-B signals of table I applied to P1-11 and P1-12 as shown on figure 1, the output signal at P1-10 shall be as shown on figure 1. (See 4.6.2.1)

3.3.2 $\overline{\text{Video}}$. With the digital type-B signals of table I applied to P1-7 and P1-8, as shown on figure 2, the output signal at P1-9 shall be as shown on figure 2, the output signals at P1-9 shall be as shown on figure 2. (See 4.6.2.2)

3.3.3 Test range. With the digital type-B signal of table I applied to P1-32, as shown on figure 3, the output signals at P1-35 and P1-33 shall be as shown on figure 3. (See 4.6.2.3)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:36Z
Check the source to verify that this is the current version before use.

TABLE I. Loads, power and signals.

Item	Condition	Characteristics	Connections
1.0	Loads		Connected between the following pins:
1.1	Resistor	1500 ±5 percent ohms	P1-4 and P1-15
1.2	Resistor	750 ±5 percent ohms	P1-10 and P1-15
1.3	Resistor	1500 ±5 percent ohms	P1-26 and P1-15
1.4	Resistor	2000 ±5 percent ohms	P1-27 and P1-16
1.5	Resistor	470 ±5 percent ohms	P1-29 and P1-15
1.6	Resistor	300 ±5 percent ohms	P1-24 and P1-14
1.7	Impedance	160 ±5 percent ohms in series with 62 ±10 percent picofarads	P1-33 and P1-35
1.8	NAND Gate	3 gates - DT micro L 9946	P1-9 and P1-16
1.9	NAND Gate	3 gates - DT micro L 9946	P1-30 and P1-16
1.10	NAND Gate	2 gates - DT micro L 9946	P1-19 and P1-16
1.11	NAND Gate	2 gates - DT micro L 9946	P1-17 and P1-16
2.0	Power sources		Applied between the following pins:
2.1	+15 Vdc	Tolerance: ±0.7 Vdc Ripple: 25 mV p-p max	P1-14(+) and P1-16(-)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:36Z
Check the source to verify that this is the current version before use.

TABLE I. Loads, power and signals. - Continued

Item	Condition	Characteristics	Connections
2.2	+5 Vdc	Tolerance: ±0.2 Vdc Ripple: 25 mV p-p max	P1-15(+) and P1-16(-)
2.3	-6 Vdc	Tolerance: ±0.2 Vdc Ripple: 25 mv p-p max	P1-21(-) and P1-16(+)
2.4	+220 Vdc	Tolerance: ±10.0 Vdc Ripple: 100 mV p-p max	P1-25(+) and P1-16(-)
3.0	Signal sources		Applied as specified herein.
3.1	Digital Type-A	Logical one: +4.0 ±1.0 Vdc 1/ Source impedance: 6K ±15 percent ohms Logical zero: +0.2 ±0.2 Vdc	
3.2	Digital type-B	Logical one: +4.0 ±1.0 Vdc 1/ Source impedance: 150 ±30 percent ohms Logical zero: +0.2 ±0.2 Vdc	

1/ Pulse width and repetition rate as specified herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:36Z
Check the source to verify that this is the current version before use.




FIGURE 1. A-Trigger signal waveforms.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:36Z
Check the source to verify that this is the current version before use.




FIGURE 2. Video signal waveforms.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:36Z
Check the source to verify that this is the current version before use.




FIGURE 3. Test range signals waveforms.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:36Z
Check the source to verify that this is the current version before use.

3.3.4 Reset. With the digital type-B signal specified in table I applied to P1-3 and P1-2 as shown in figure 4, the output signal at P1-29 shall be as shown in figure 4. (See 4.6.2.4)

3.3.5 Malfunction 4 logic. With the digital type-A signals specified in table I applied to pins as listed in table II, the Malfunction 4 signal at P1-19 shall be as listed in table II. (See 4.6.2.5)

3.3.6 +200 volt malfunction. With the logical zero digital type-A signal specified in table I momentarily applied to P1-13, the voltage at P1-19 shall be 4.2 ±1 Vdc. With the +220 Vdc power source of table I reduced to +145 ±5 Vdc, the voltage at P1-19 shall be +0.2 ±0.2 Vdc. (See 4.6.2.6)

3.3.7 Malfunction 2 logic. With the digital type-B signals of table I applied to pins as listed in table III, the output at P1-17 shall be as listed in table III. (See 4.6.2.7)

3.3.8 +15V interlock and range light signals. With the digital type-A signals specified in table I applied to P1-34, the voltages at P1-26 and P1-27 shall be as listed in table IV. (See 4.6.2.8)

3.3.9 Minimum range inhibit. With the digital type-A signal of table I applied to P1-6 as shown in figure 5, the output signal at P1-4 shall be as shown in figure 5. (See 4.6.2.9)

3.3.10 Range signal. With the logical one digital type-A signal of table I applied to P1-20, the output at P1-30 shall be +0.2 ±0.2 Vdc. With the logical zero digital type-A signal of table I applied to P1-20, the output at P1-30 shall be +4.2 ±1.0 Vdc. (See 4.6.2.10)

3.3.11 Alarm signal. With the logical one digital type-A signal of table I applied to P1-26, the output at P1-24 shall be +0.3 ±0.3 Vdc. With the logical zero digital type-A signal of table I applied to P1-26, the output at P1-24 shall be +15.0 ±1.0 Vdc. (See 4.6.2.11)

3.4 Environmental.

3.4.1 Shock. The assembly shall be capable of operating as specified herein after exposure under the conditions of 3.1.3 to three half sine wave shock pulses of 40 ±4 gravity unit (g) for a duration of 18 ±3 milliseconds (msec) applied in each direction along three mutually perpendicular axes. In addition, the assembly shall be capable of withstanding three half sine wave shock pulses of 100.0 ±10.0 g for a duration of 1.5 ±0.2 msec applied in each direction along three mutually perpendicular axes. (See 4.6.3.1)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:36Z
Check the source to verify that this is the current version before use.

3.4.2 Vibration. The assembly shall be capable of operating as specified herein after exposure under the conditions of 3.1.3 to the vibration profile of figure 6. Duration of exposure shall be not less than 80 minutes in each of three mutually perpendicular axes. (See 4.6.3.2)

3.4.3 Operating temperature. The assembly shall be capable of operating as specified herein over the operating temperature range of -40°F to +160°F. (See 4.6.3.1)

3.4.4 Storage temperature. The assembly shall be capable of operating as specified herein after exposure to storage temperatures ranging from -65°F to +160°F. (See 4.6.3.1)




FIGURE 4. Reset signal waveforms.

(See 4.6.3.2)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:36Z
Check the source to verify that this is the current version before use.

TABLE II. Malfunction 4 logic.

Item	Inputs 1/ to Pins					Output at Pin P1-19
	P1-34	P1-20	P1-28	P1-13	P1-23	
1	1	1	1	0 1/	NC	+4.2 ±1.0 Vdc
2	1	0 2/	1	1	NC	+0.2 ±0.2 Vdc
3	1	1	0 2/	1	NC	+1.2 ±1.0 Vdc
4	1	0 2/	1	1	NC	+4.2 ±1.0 Vdc
5	1	1	1	0 2/	NC	+4.2 ±1.0 Vdc
6	1	0 2/	1	1	NC	+0.2 ±0.2 Vdc
7	1	1	1	0 2/	NC	+4.2 ±1.0 Vdc
8	0	0 2/	1	1	NC	+4.2 ±1.0 Vdc
9	1	1	1	1	0	+0.2 ±0.2 Vdc

1/ Input signal legend: 1 = Logical one, Type-A
0 = Logical zero, Type-A
NC = No Connection

2/ Applied momentarily.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:36Z
Check the source to verify that this is the current version before use.

TABLE III. Malfunction 2 logic.

Item	Inputs to Pins 1/		Output at Pin P1-17
	P1-5	P1-31	
1	1	1	+4.2 ±1.0 Vdc
2	1	0	+0.2 ±0.2 Vdc
3	0	1	+0.2 ±0.2 Vdc
4	0	0	+0.2 ±0.2 Vdc

1/ Input signal legend: 1 = Logical one, Type-A
0 = Logical zero, Type-A

TABLE IV. +15V interlock and range light signals.

Item	Inputs to Pin P1-34 1/	Outputs at Pins	
		P1-26	P1-27
1	1	+4.2 ±1.0 Vdc	+15.0 ±1.5 Vdc
2	0	+0.2 ±0.2 Vdc	+0.2 ±0.2 Vdc

1/ Input signal legend: 1 = Logical one, Type-A
0 = Logical zero, Type-A

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:36Z
Check the source to verify that this is the current version before use.




FIGURE 5. Minimum Range Inhibit waveforms.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:36Z
Check the source to verify that this is the current version before use.




FIGURE 6. Vibration profile.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:36Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsbile for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilites suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

1. First article inspection (see 4.4).
2. Quality conformance inspection (see 4.5).

4.3 Inspection conditions. Unless otherwise specified, all inspections shall be performed in accordance with the quality assurance provisions of MIL-F-13926 and the conditions of 3.1.3.

4.4 First article. The requirements for first article approval and the designation of responsibility for first article inspection to either the Government or the contractor shall be specified in the contract.

4.4.1 Sample. The first article sample shall be three assemblies selected at random by the Government representative from the first fifteen production assemblies.

4.4.2 Inspection. The sample shall be subjected to all the inspections specified in tables V, VI and VII.

4.4.3 Failure. Failure of any assembly to meet any requirement shall be cause for refusal to grant first article approval. The Government reserves the right to terminate first article inspection upon any failure of any assembly to comply with any stated requirement.

4.4.4 Responsibility. The contractor, whether or not responsible, shall inspect the sample for conformance to all contractual requirements and shall submit a record of this inspection with the sample and certificates of conformance for materials. The Government reserves the right to witness inspections performed by the contractor.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:36Z
Check the source to verify that this is the current version before use.

4.5 Quality conformance inspection.

4.5.1 Procurement conditions. The following inspection plans shall apply where the assembly is procured for use as a:

	Use	Plan
a.	Logistics spare assembly apart from the next higher assembly	A and C
b.	Component assembly of the next higher assembly	B and C

4.5.2 Inspection plan A.

4.5.2.1 General sample and tests. One assembly, as a control sample, shall be selected at random by the Government representative from each 100 assemblies produced and shall be subjected to all the tests in table VI.

4.5.2.2 Environmental sample and tests. Three assemblies, as a control sample, shall be selected at random by the Government representative from each 50 assemblies produced or from each month's production, whichever occurs first. All the tests in table VII shall be applied separately to each assembly in the sample.

4.5.2.3 Acceptance. Where any one assembly of either sample fails to meet any specified requirement, the lot shall be rejected. Rejected lots shall be subject to the provisions of MIL-STD-105.

4.5.3 Inspection plan B.

4.5.3.1 Sample and tests. The sample shall be selected by the Government representative in accordance with the provisions of MIL-STD-105. All the tests in table VI and only the test of item 307 in table VII shall be applied.

4.5.3.2 Acceptance. Acceptance and rejection shall be in accordance with MIL-STD-105.

4.5.4 Inspection plan C.

4.5.4.1 Sample and tests. Each assembly in every lot shall be subjected to all the tests in table V and shall be examined visually for completeness, improper assembly and evidence of poor workmanship.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:36Z
Check the source to verify that this is the current version before use.

4.5.4.2 Acceptance. Where any one assembly fails to meet any specified requirement, the defective assembly shall be removed from the lot and resubmitted only after all defects have been corrected.

4.5.5 Inspection equipment. Unless otherwise specified in the contract, the contractor shall supply, maintain and calibrate inspection equipment in accordance with the provisions of MIL-I-45607 and MIL-STD-45662.

4.5.6 Packaging inspection. The sampling and inspection of the preservation - packaging, packing and container marking shall be in accordance with the provisions of packaging data sheet P11737802.

TABLE V. Performance tests.

Item	Characteristics	Requirements	Test Procedures
101	$\overline{\text{A-trigger}}$	3.3.1	4.6.2.1
102	$\overline{\text{Video}}$	3.3.2	4.6.2.2
103	Test range	3.3.3	4.6.2.3
104	$\overline{\text{Reset}}$	3.3.4	4.6.2.4
105	$\overline{\text{Malfunction 4 logic}}$	3.3.5	4.6.2.5
106	+200 volt malfunction	3.3.6	4.6.2.6
107	$\overline{\text{Malfunction 2 logic}}$	3.3.7	4.6.2.7
108	+15V interlock and range light signals	3.3.8	4.6.2.8
109	$\overline{\text{Minimum range inhibit}}$	3.3.9	4.6.2.9
110	Range signal	3.3.10	4.6.2.10
111	$\overline{\text{Alarm signal}}$	3.3.11	4.6.2.11

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:36Z
Check the source to verify that this is the current version before use.

TABLE VI. General tests.

Item	Characteristics	Requirements	Test Procedures
301	Fabrication	3.1	Applicable drawings - Visual
302	General specifications	3.1.2	MIL-F-13926 - Visual

TABLE VII. Environmental tests.

Item	Characteristics	Requirements	Test Procedures
303	High temperature	3.4.3 and 3.4.4	4.6.3.3
304	Low Temperature	3.4.3 and 3.4.4	4.6.3.4
305	Vibration	3.4.2	4.6.3.2
306	Shock	3.4.1	4.6.3.1
307	Temperature Cycling	3.4.3 and 3.4.4	4.6.3.5

4.6 Methods of inspection.

4.6.1 Test equipment. Unless the assembly is procured apart from the next higher assembly, the test equipment in table VIII shall be used where specified to perform the required tests.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:36Z
Check the source to verify that this is the current version before use.

TABLE VIII. Test equipment.

Item	Part Number	Nomenclature
1	11750202	Automatic Card and Unit, Test Set
2	11750435	Adapter, Interface
3	11821457	Fixture Shock, Vertical and Horizontal Plane
4	11821458	Shock Adapter, Plate Vib Horz-Vert Plane/ Shock-Z
5	11821520	Automatic Test Assembly Central Processor Unit
6	11821647	Vibration/Shock Test Fixture - Electronic Unit, AC, FAT

4.6.2 Performance tests.

4.6.2.1 A-trigger. Use items 1, 2 and 5 of table VIII or suitable equipment to determine compliance with 3.3.1.

4.6.2.2 Video. Use items 1, 2 and 5 of table VIII or suitable equipment to determine compliance with 3.3.2.

4.6.2.3 Test range. Use items 1, 2 and 5 of table VIII or suitable equipment to determine compliance with 3.3.3.

4.6.2.4 Reset. Use items 1, 2 and 5 of table VIII or suitable equipment to determine compliance with 3.3.4.

4.6.2.5 Malfunction 4 logic. Use items 1, 2 and 5 of table VIII or suitable equipment to determine compliance with 3.3.5.

4.6.2.6 +200 volt malfunction. Use items 1, 2 and 5 of table VIII or suitable equipment to determine compliance with 3.3.6.

4.6.2.7 Malfunction 2. Use items 1, 2 and 5 of table VIII or suitable equipment to determine compliance with 3.3.7.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:36Z
Check the source to verify that this is the current version before use.

4.6.2.8 +15V interlock and range light signal. Use items 1, 2 and 5 of table VIII or suitable equipment to determine compliance with 3.3.8.

4.6.2.9 Minimum range inhibit. Use items 1, 2 and 5 of table VIII or suitable equipment to determine compliance with 3.3.9.

4.6.2.10 Range signal. Use items 1, 2 and 5 of table VIII or suitable equipment to determine compliance with 3.3.10.

4.6.2.11 Alarm signal. Use items 1, 2 and 5 of table VIII or suitable equipment to determine compliance with 3.3.11.

4.6.3 Environmental tests.

4.6.3.1 Shock.

4.6.3.1.1 Basic design. Use items 3 and 6 of table VIII or mount the assembly in a suitable shock fixture and subject it to the shock test specified in MIL-STD-810, method 516.2, procedure I, figure 516.2-2. Apply three half sine wave shock pulses in each direction along the three axes. Peak amplitude shall be 40 +4 g with a time duration of 18 ±3 msec meausred at the 10 percent amplitude points. At the conclusion of this test, subject the assembly to the performance tests of table V.

4.6.3.1.2 High intensity. Use items 4 and 6 of table VIII or mount the assembly in a suitable shock fixture and subject it to the shock test specified in MIL-STD-810, method 516.2, procedure IV, figure 516.2-2. Apply three half sine wave shock pulses in each direction along the three axes. Peak amplitude shall be 100.0 ±10.0 g with a time duration of 1.5 +0.2 msec measured at the 10 percent amplitude points. At the conclusion of this test, subject the assembly to the performance tests of table V.

4.6.3.2 Vibration. Vibration A as specified in 4.6.3.2.1 shall be conducted only for first article inspection. Vibration B as specified in 4.6.3.2.2 shall be conducted only for quality conformance inspection.

4.6.3.2.1 Vibration A. Use items 4 and 6 of table VIII or mount the assembly in a suitable vibration fixture and subject the assembly to the vibration test specified in MIL-STD-810, method 514.2 procedure VIII, except that the test level shall be the vibration curve shown in figure 6 and duration of exposure shall be not less than 80 minutes per axis. At the conclusion of this test, subject the assembly to the performance tests of table V.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:36Z
Check the source to verify that this is the current version before use.

4.6.3.2.2 Vibration B. This test shall be conducted as in 4.6.3.2.1 except that the period of vibration shall be not less than 15 minutes in each axis.

4.6.3.3 High temperature. Subject the assembly to the high temperature test specified in MIL-STD-810, method 501.1, procedure I. The highest operating temperature shall be 140°F. The performance tests of table V shall be applied.

4.6.3.4 Low temperature. Subject the assembly to the low temperature test specified in MIL-STD-810, method 502.1, procedure I. The storage temperature shall be -65°F. The lowest operating temperature shall be -25°F. The performance tests of table V shall be applied.

4.6.3.5 Temperature cycling. With power and loads of table I applied, subject the assembly to the temperature profile specified in figure 7. At the conclusion of this test, subject the assembly to the performance tests of table V.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:36Z
Check the source to verify that this is the current version before use.




FIGURE 7. Temperature cycling.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:36Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 Packaging, packing and marking. Packaging, packing and marking shall be in accordance with packaging data sheet P11737802. The level of protection shall be as specified in the procurement document. (See 4.5.6)

6. NOTES (Common to AN/VVG-2 L.R.F.)

6.1 Intended use. The circuit card assembly is a functional module of the Laser Power Supply Control C-9135()/VVG-1, itended for use in the Fire Control Rangefinder AN/VVG-1(). The assembly functions to:

a. Buffer test range signals to the receiver-transmitter

b. Receive video signal from the receiver-transmitter and transmit it to the ranging circuit card.

c. Generate $\overline{\text{Malfunction 2}}$ and $\overline{\text{Malfunction 4}}$ signals

d. Provide +15V interlock signal to PFN charge.

6.2 Ordering data. Procurement documents should specify the following:

a. Title, number, and date of this specification

b. Applicable packaging data sheet number (see 5.1)

c. Selection of applicable levels of preservation, packaging and packing

d. Applicable stock number

e. Requirements for first article submission.

6.3 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue, due to the extensiveness of the changes.

Custodian:
Army-AR

Preparing Activity:
Army-AR
Project No. 1240-A798

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:36Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

BUSINESS REPLY CARD

FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US ARMY ARMAMENT RESEARCH & DEVELOPMENT COMMAND
ATTN: DRDAR-QAF
DOVER, NJ 07801

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:36Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.

NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE

MIL-C-50774A CIRCUIT CARD ASSEMBLY: 11737802 INTERFACE

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*	TELEPHONE NO.
	DATE

DD FORM 1426 1 OCT 76

EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:36Z
Check the source to verify that this is the current version before use.