MILITARY SPECIFICATION

HOSELINE OUTFIT: 4-INCH, FUEL HANDLING

This specification is approved for use within the USA Belvoir Research, Development, and Engineering Center, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers a fuel handling hoseline outfit for the dispensing of liquid fuels.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, and standards. The following specifications, and standards, form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DoDISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

MILITARY

MIL-C-104	- Crates, Wood; Lumber and Plywood Sheathed, Nailed and Bolted.
MIL-P-52144	- Pumping Assembly, Flammable Liquid, Bulk Transfer, Diesel Engine Driven, 350 GPM Capacity, 275 Total Head, Wheel Mounted.
MIL-H-52262	- Hose Assembly, Rubber: Light-Weight, Collapsible, 4-inch.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: USA Belvoir Research, Development, and Engineering Center, ATTN: STRBE-TSE, Fort Belvoir, VA 22060-5606 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 3835
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202640-22T21:43Z
Check the source to verify that this is the current version before use.

MIL-S-52342	- Sling Assembly: Flaking Box, Lifting.
MIL-R-52343	- Repair Kit, Hoseline.
MIL-F-52345	- Flow Control Kit, Hoseline.
MIL-G-52346	- Guard, Roadway Crossing.
MIL-S-52347	- Suspension Kit, Hoseline.
MIL-P-52348	- Packing Kit, Hoseline.
MIL-D-52349	- Displacement and Evacuation Kit, Hoseline.

STANDARDS

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	- Marking for Shipment and Storage.
MIL-STD-889	- Dissimilar Metals.
MIL-STD-1186	- Cushioning, Anchoring, Bracing, Blocking, and Waterproofing; with Appropriate Test Methods.

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

DRAWINGS

ME

TA13225E9023	- Set, Hoseline Outfit, Fuel Handling.

SUPPLY CATALOG

MILITARY

SC 3835-97-CL-E03	- Hoseline Outfit, Fuel Handling.

(Copies of specifications, standards, handbooks, drawings, publications, and other Government documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

2.2 Other publications. The following document(s) form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted shall be those listed in the issue of the DoDISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DoDISS shall be the issue of the nongovernment documents which is current on the date of the solicitation.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

D 3951 - Standard Practice for Commercial Packaging.

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:43Z
Check the source to verify that this is the currentversion before use.

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

(Nongovernment standards and other publications are normally available from the organizations which prepare or which distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, (except for associated detail specifications, specifications sheets or MS standards), the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Description. The hoseline outfit shall be as specified in SC 3835-97-CL-E03 and TA13225E9023, consisting of the major components listed in table I, and as specified herein.

TABLE I. Hoseline outfit components.

Item	NSN	Description	Specification
1	3835-00-226-0509	Displacement and evacuation kit, hoseline	MIL-D-52349
2	3835-00-686-1006	Flow control kit, hoseline	MIL-F-52345
3	3835-00-967-9029	Guard, roadway crossing	MIL-G-52346
4	4720-00-786-5201	Hose assembly and flaking box	MIL-H-52262
5	3835-00-686-1004	Packing kit, hoseline	MIL-P-52348
6	4320-01-141-5154	Pumping assembly, flammable liquid bulk transfer, 350 GPM, type I, style B	MIL-P-52144
7	3835-00-686-1007	Repair kit, hoseline	MIL-R-52343
8	3940-00-967-5976	Sling, multiple leg	MIL-S-52342
9	3835-00-686-1008	Suspension kit, hoseline	MIL-S-52347

3.2 First article. Unless otherwise specified (see 6.2), a sample shall be subjected to first article inspection (see 4.3 and 6.3). Any changes or deviations

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:43Z
Check the source to verify that this is the current version before use.

of hoseline outfits from the approved first article during production will be subject to the approval of the contracting officer. Approval of the first article will not relieve the contractor of his obligation to furnish hoseline outfits conforming to this specification.

3.3 Material. Material shall be as specified herein. Material not specified shall be selected by the contractor and be subject to all the provisions of the referenced specifications listed in table I.

3.3.1 Material deterioration prevention and control. The item(s) shall be fabricated from compatible materials, inherently corrosion resistant or treated to provide protection against the various forms of corrosion and deterioration that may be encountered in any of the applicable operation and storage environments to which the items may be exposed.

3.3.2 Dissimilar metals. Dissimilar metals shall not be used in intimate contact with each other unless protected against galvanic corrosion. Dissimilar metals and methods of protection are defined and detailed in MIL-STD-889.

3.3.3 Identification of materials and finishes. The contractor shall identify the specific material finish or treatment for use with component and subcomponent, and shall make information available upon request to the contracting officer or designated representative.

3.3.4 Recovered materials. For the purpose of this requirement, recovered materials are those materials which have been collected from solid waste and reprocessed to become a source of raw materials, as distinguished from virgin raw materials. The components, pieces and parts incorporated in the hoseline outfit may be newly fabricated from recovered materials to the maximum extent practicable, provided the hoseline outfit produced meets all other requirements of this specification. Used, rebuilt or remanufactured components, pieces and parts shall not be incorporated in the hoseline outfit.

3.4 Individual items. The quantity and size of the individual items comprising each major component shall be as specified in SC 3835-97-CL-E03.

3.5 Government-furnished property. When specified (see 6.2), the following property in the quantities indicated will be furnished by the Government (see 6.4):

Description	Identification	Quantity
Pumping assembly, flammable liquid, bulk transfer, 350 GPM, type 1 style B.	MIL-P-52144	1

3.6 Labeling. Valve controls shall be provided with double-ended arrows showing the direction of operation and labeled at each end to indicate the functional result (e.g. open, close, etc.). Labels shall be provided whenever it is necessary for personnel to identify, interpret, or follow procedures for hose deployment. Instructions shall be provided in the packing kit.

Source: https://assist.dla.mil -- Downloaded: 202640-22T21:43Z
Check the source to verify that this is the currentversion before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.2 Classification of inspection. Inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).
c. Inspection comparison (see 4.6).
d. Inspection of packaging (see 4.7).

4.3 First article inspection.

4.3.1 Examination. The first article hoseline outfit shall be examined as specified in 4.5.1. Presence of one or more defects shall be cause for rejection.

4.3.2 Tests. The first article outfit shall be tested as specified in 4.5.2.1. Failure of any test shall be cause for rejection.

4.4 Quality conformance inspection.

4.4.1 Sampling.

4.4.1.1 Sampling for examination. Sampling for examination shall be in accordance with MIL-STD-105.

4.4.1.2 Sampling for tests. Sampling for tests shall be in accordance with the applicable component specifications listed in table I.

4.4.2 Examination. Samples selected in accordance with 4.4.1.1 shall be examined as specified in 4.5.1. AQL shall be 2.5 percent defective.

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:43Z
Check the source to verify that this is the current version before use.

4.4.3 Tests. Samples selected in accordance with 4.4.1.2 shall be tested in accordance with 4.5.2.1. Cause for rejection shall be in accordance with the applicable component specifications listed in table I.

4.5 Inspection procedure.

4.5.1 Examination. The hoseline outfit shall be examined as specified herein for the following defects:

101. Material not as specified in each referenced component specification (table I).
102. Materials are not resistant to corrosion or deterioration or treated to be made resistant to corrosion or deterioration for the applicable storage and operating environment as specified.
103. Dissimilar metals as specified in MIL-STD-889 are not effectively insulated from each other as specified.
104. Contractor does not have documentation available for identification of material, material finishes, or treatments.
105. Used, rebuilt or remanufactured components, pieces, or parts incorporated in the hoseline outfit.
106. Component size and quantity not as specified in SC 3835-97-CL-E03.
107. No documented evidence of performance of examinations and tests required by component specifications (table 1).
108. Components not as specified on TA13225E9023. Each nonconforming component shall constitute one defect.
109. Labeling not as specified.

4.5.2 Tests.

4.5.2.1 Component test. Each component of the hoseline outfit(s) shall be subject to the inspection and test requirements of the applicable component specification (see table I), including first article testing, when required (see 6.2).

4.6 Inspection comparison. The Government may select hoseline outfits at any time during the contract production period and subject these hoseline outfits to the examination specified in 4.5.1 and the tests specified in 4.5.2 to determine conformance to the requirements of this specification. The inspection will be performed by the Government, at a site selected by the Government, on units selected at random from those which have been accepted by the Government and will not include the previously inspected first produced hoseline outfits. In addition to any test specified as part of the inspection comparison, the Government reserves the right to conduct any and all other tests contained in this specification as part of the inspection comparison and failure of such additional tests shall have the same effect as failure of those tests specified as inspection comparison.

4.6.1 Inspection failure. Failure of an inspection comparison hoseline outfit to meet any requirement specified herein during and as a result of the examination and tests specified in 4.6 shall be cause for rejection of the inspection

Source: https://assist.dla.mil -- Downloaded: 202640-22T21:43Z
Check the source to verify that this is the currentversion before use.

comparison hoseline outfit and shall be cause for refusal by the Government to continue acceptance of production hoseline outfits until evidence has been provided by the contractor that corrective action has been taken to eliminate the deficiencies. Correction of such deficiencies shall be accomplished by the contractor at no cost to the Government on hoseline outfits previously accepted and produced under the contract. Any deficiencies found as a result of the inspection comparison will be considered prima facie evidence that all hoseline outfits accepted prior to the completion of the inspection comparison are similarly deficient unless evidence to the contrary is furnished by the contractor and such evidence is acceptable to the contracting officer.

4.7 Inspection of packaging.

4.7.1 Quality conformance inspection of pack.

4.7.1.1 Unit of product. For the purpose of inspection, a complete pack prepared for shipment shall be considered a unit of product.

4.7.1.2 Sampling. Sampling for examination shall be in accordance with MIL-STD-105.

4.7.1.3 Examination. Samples selected in accordance with 4.7.1.2 shall be examined for the following defects. AQL shall be 2.5 percent defective.

110.	Preservation not in accordance with the applicable referenced document as specified for level A.
111.	Preservation and packing not in accordance with the referenced document as specified for commercial.
112.	Crates not as specified for level A.
113.	More than five flaking boxes packed together for level A.
114.	Blocking, bracing, and anchoring not in accordance with referenced documents as specified for level A.
115.	Pump not packed in accordance with referenced document for level A.
116.	Marking missing, illegible, incorrect, or incomplete for level A or commercial.

5. PACKAGING

5.1 Preservation. Preservation shall be level A or commercial as specified (see 6.2).

5.1.1 Level A. The hoseline outfit components shall be preserved in accordance with the level A preservation requirements of the individual component specification (see table I).

5.1.2 Commercial. The hoseline outfit components shall be preserved in accordance with the commercial preservation requirements of the individual component specification (see table I).

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:43Z
Check the source to verify that this is the current version before use.

5.2 Packing. Packing shall be level A or commercial as specified (see 6.2).

5.2.1 Level A. The hoseline outfit components, except for the pump (see 5.2.1.1), shall be packed together in five crates conforming to MIL-C-104, type 1, class 1 or 2, style A, as follows:

Crate 1 - 3 each flaking boxes with hose assemblies.
Crate 2 - 3 each flaking boxes with hose assemblies.
Crate 3 - 3 each flaking boxes with hose assemblies.
Crate 4 - 4 each flaking boxes with hose assemblies.
Crate 5 - Shall contain kits and ancillary components.

(1) Suspension kit and packing kit (1 each).
(2) Repair kit and displacement and evacuation kit (1 each).
(3) Flow control kit.
(4) Sling, multiple leg (1 each).
(5) Guard, road crossing (20 each).
(6) Regulator kit.

All components shall be blocked, braced, and anchored to the crate base in a manner to prevent movement or damage to the contents in accordance with MIL-STD-1186 and the appendix to the crate specification.

5.2.1.1 Pump. The pump shall be packed in accordance with the level A packing requirements of MIL-P-52144 and shall be shipped separate from, but at the same time as, the crates containing the other hoseline outfit components.

5.2.2 Commercial. The hoseline outfit components preserved as specified in 5.1, shall be packed in accordance with ASTM D 3951.

5.3 Marking.

5.3.1 Military. Marking for military levels of protection (level A) shall be in accordance with MIL-STD-129.

5.3.2 Commercial. Marking for commercial packaging shall be in accordance with ASTM D 3951. In addition, the weight and cube data shall also be marked on the shipping container.

6. NOTES

6.1 Intended use. The hoseline outfit is intended to provide a capability for the rapid placement of a temporary bulk transportation system for liquid fuels to give adequate POL logistical support to tactical forces.

6.2 Ordering data. Procurement documents shall specify the following:

a. Title, number, and date of this specification.
b. Time frame required for submission of the first article hoseline outfit and number of hoseline outfits required (see 3.2).

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:43Z
Check the source to verify that this is the current version before use.

c. When the Government will conduct any or all of the first produced examinations and tests. When the Government will conduct some but not all of the first produced examinations and tests, the contracting officer should specify which examinations and tests will be conducted by the Government and which examinations and tests will be conducted by the contractor (see 3.2).
d. When inspection comparison is required and the number of hoseline outfits to be furnished, when applicable (see 4.6).
e. When Government-furnished property is required (see 3.5).
f. When components shall not be tested (see 4.5.2.1).
g. Degree of preservation and degree of packing required (see 5.1 and 5.2).

6.3 First article. When a first article inspection is required, the items should be first produced hoseline outfits. The first article should consist of one or more units. The contracting officer should include specific instructions in acquisition documents regarding arrangements for examinations, tests, and approval of the first article test results and disposition of the document's first article.

6.4 Government-furnished property. The contracting officer should arrange to furnish the property specified in 3.5, when applicable (see 6.2).

Custodian:
Army - ME

Preparing activity:
Army - ME

Review activity:
DLA - CS

Project 3835-A082

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:43Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Belvoir Rsch, Development & Engrg Ctr
ATTN: STRBE-TSE
Fort Belvoir, VA 22060-5606

Source: https://assist.dla.mil -- Downloaded: 202640-22T21:43Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-H-52970C(ME)	Hoseline Outfit: 4-Inch, Fuel Handling

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR ☐ USER ☐ MANUFACTURER ☐ OTHER *(Specify)*: _____
b. ADDRESS *(Street, City, State, ZIP Code)*	

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

Source: https://assist.dla.mil -- Downloaded: 20261O-22T21:43Z
Check the source to verify that this is the current version before use.