INCH-POUND
MIL-I-82760
3 January 1989
SUPERSEDING
FA-PD-MI-2669, REV 3
7 December 1965

MILITARY SPECIFICATION

# INITIATOR, CARTRIDGE ACTUATED, DELAY, M6A1, M26, M33, REMANUFACTURED METAL PARTS ASSEMBLY

*This specification is approved for use by all Departments and Agencies of the Department of Defense.*

## 1. SCOPE

**1.1 Scope.** This specification covers the requirements for the remanufactured Cartridge Actuated Initiators M6A1, M26, M33, Metal Parts Assembly (see 6.1).

## 2. APPLICABLE DOCUMENTS

### 2.1 Government documents.

**2.1.1 Specifications, standards and handbooks.** The following specifications, standards and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DoDISS) and supplement thereto, cited in the solicitation (see 6.2).

SPECIFICATIONS

MILITARY

MIL-A-2550 Ammunition, General Specification For

STANDARDS

MILITARY

MIL-STD-105 Sampling Procedures and Tables for Inspection by Attributes

MIL-STD-109 Quality Assurance Terms and Definitions

MIL-STD-413 Visual Inspection Guide for Elastomeric O-rings

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Naval Publications and Forms Center, (Attn: NPODS), 5801 Tabor Avenue, Philadelphia, PA 19120-5099.)

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commanding Officer, Naval Ordnance Station, Standardization Branch (3730), Indian Head, MD 20640-5000, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 1377

**DISTRIBUTION STATEMENT A.** Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:24Z
Check the source to verify that this is the current version before use.

**2.1.2 Other Government documents, drawings, and publications.** The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

DRAWINGS

NAVAL ORDNANCE STATION, INDIAN HEAD, MD (CAGE Code 19200 and 19203)

| | |
|---|---|
| 8593315 | Initiator, Cartridge Actuated, Delay, Metal Parts Assembly |
| 8796826 | Box, Fiberboard (Inner) Packing, Ammunition for Initiators, Cartridge Actuated, Delay, M4A1, M6A1, M12A1, M26, M33, M44, M45A1 or M49A1 |
| 8796827 | Box, Packing, Ammunition for Initiator, Cartridge Actuated, Delay, M4A1, M6A1, M12A1, M26, M33, M44, M45A1, or M49A1 in Fiber Container, M375 |
| 9216824 | Box, Fiberboard (Outer) Alternative, Packing Ammunition, for Initiators, Cartridge Actuated, Delay, M4A1, M6A1, M33, M44, M45A1, M49A1; M12A1, or M26 |

U.S. AIR FORCE

| | |
|---|---|
| TPO 00-845-1058 | Initiator, Cartridge Actuated, M26 |

(Application for copies should be addressed to: Commanding Officer, Naval Ordnance Station, Data Control Branch (3720), Indian Head, MD 20640-5000.)

**2.2 Order of precedence.** In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

## 3. REQUIREMENTS

**3.1 Materials.** All materials used in the manufacture of the initiators shall conform strictly to the specifications referred to on the respective drawings unless specific approval in writing covering a departure therefrom has been obtained from the cognizant Navy design activity prior to manufacture. When alternate materials or methods of manufacture are specified on the drawings, the bidder's selections shall be clearly stated in the proposal. The remanufactured initiator metal parts assembly shall contain a new shear pin and O-rings.

**3.2 Protective finish.** Protective finish shall be in accordance with the applicable specifications and drawings and shall apply to all surfaces of the component, regardless of configuration. Remanufactured exterior components shall have the existing protective finish stripped and the specified protective finish reapplied (see 6.4.2).

**3.3 Hydrostatic pressure.** The initiator chamber and cap shall withstand a hydrostatic pressure of 5500 to 6500 pounds per square inch (psi) for 15 seconds, minimum, without deformation or mechanical failure (see 6.4.1).

**3.4 Shear pin strength.** The shear pin, after application of protective finish, shall shear when a load of 41 ± 5 pounds is applied at the steady rate of 0.125 inch per minute.



Source: https://assist.dla.mil -- Downloaded: 202610-23T07:24Z
Check the source to verify that this is the current version before use.

**3.5 Metal parts assembly.** Parts shall be combined to produce an assembly which conforms to the requirements of the metal parts assembly drawing. All threaded joints shall be assembled handtight.

a. When remanufacturing and loading of assembly is performed in an integrated plant, the metal parts assembly requirement may be waived and the residual magnetism requirement performed on the loaded assembly only.

**3.6 Residual magnetism.** The metal parts assembly shall not deflect the indicator of the compass more than five degrees in either direction using procedures in 4.5.4.

**3.7 Workmanship.** The requirements for workmanship are as specified on the applicable drawings, referenced specifications, and the following:

**3.7.1 Metal defects.** All components shall be free from cracks, splits, cold shuts, inclusions, porosity, or any similar defect.

**3.7.2 Burr.** No part shall have a burr which might interfere with the assembly or function of the item or which might be injurious to personnel handling the item.

**3.7.3 Foreign matter.** No part or assembly shall contain chips, dirt, grease, rust, corrosion or other foreign matter.

## 4. QUALITY ASSURANCE PROVISIONS

**4.1 Responsibility for inspection.** Unless otherwise specified in the contract or purchase order (see 6.2), the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

**4.1.1 Responsibility for compliance.** All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

**4.1.2 Quality assurance terms and definitions.** Reference shall be made to MIL-STD-109 to define the quality assurance terms used.

**4.1.3 Inspection.** Inspection shall be in accordance with MIL-A-2550.

**4.2 Inspection conditions.** Unless otherwise specified, all inspections shall be performed under the following conditions:

a. Temperature: Room ambient 68° to 77°F
b. Altitude: Sea level
c. Humidity: 50 percent relative, maximum
d. Atmospheric pressure: 14.7 psia



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:24Z
Check the source to verify that this is the current version before use.

**4.3 Quality conformance inspection.**

**4.3.1 Lot.**

**4.3.1.1 Submission of product.** Unless otherwise specified by the contracting activity, formation and identification of lots shall be in accordance with MIL-STD-105.

**4.3.1.2 Size of lot.** For the purpose of identification and shipment, the shipping lots of metal parts assemblies shall consist of 1200 assemblies, maximum, provided the homogeneity requirements of inspection lots have been retained.

**4.3.2 Examination.** Of reprocessed parts one-hundred percent examination shall be performed for all critical defects. Examination for major and minor defects shall be performed on a defect basis in accordance with the classification of defects, using the sampling plan and associated criteria specified in the contract (see 6.2 and 6.3). All nonconforming material shall be rejected. Four power (4X) magnification may be used in performing visual examination for such defects as burr and foreign matter. Inspection for rubber O-rings shall be in accordance with MIL-STD-413. When compliance with the applicable requirement is in doubt as a result of visual examination, the characteristic shall be measured or gaged to determine acceptability.

**4.3.2.1 Examination of reclaimed parts.** Examination of reuseable parts, which require no reprocessing, shall be limited to inspection of defects that require visual type inspection. One hundred percent examination shall be performed for all such defects. All nonconforming parts shall be reprocessed or rejected.

**4.3.2.2 Retainer, Cartridge, Drawing 8593313, covering a detail of Drawing 8593315.**

| Characteristic | Defect | Method of Inspection |
|---|---|---|
| Critical | | |
| 1 | Metering slots in base missing | Visual |
| Major | | |
| 101 | Pitch diameter of thread, max | Gage |
| 102 | Minor diameter of thread, max | Gage |
| 103 | Elongated slots, missing | Visual |
| 104 | Thread damaged | Visual |
| 105 | Metal defective | Visual |
| 106 | Protective finish inadequate or defective | Visual |
| 107 | Surface finish on internal radius and base, improper | Visual |
| 108 | Burr | Visual |
| 109 | Foreign matter present | Visual |
| Minor | | |
| None defined | | |

**4.3.2.3 Chamber, Initiator, Drawing 8593314 covering a detail of Drawing 8593315.**

| | | |
|---|---|---|
| Critical | | |
| None defined | | |
| Major | | |
| 101 | Pitch diameter of large thread, min. | Gage |
| 102 | Major diameter of large thread, min. | Gage |
| 103 | Pitch diameter of small thread, min. | Gage |



Source: https://assist.dla.mil -- Downloaded: 202610-23T07:24Z
Check the source to verify that this is the current version before use.

| Characteristic | Defect | Method of Inspection |
|---|---|---|
| 104 | Major diameter of small thread, min. | Gage |
| 105 | Thread damaged | Visual |
| 106 | Metal defective | Visual |
| 107 | Protective finish inadequate or defective | Visual |
| 108 | Surface finish, end of gas port, improper | Visual |
| 109 | Burr | Visual |
| 110 | Foreign matter present | Visual |
| Minor | | |
| None defined | | |

**4.3.2.4 Cap, Drawing 8595254 covering a detail of Drawing 8593315.**

| | | |
|---|---|---|
| Critical | | |
| 1 | Metal defective in mounting flange surface | Visual |
| Major | | |
| 101 | Pitch diameter of thread, max. | Gage |
| 102 | Minor diameter of thread, max. | Gage |
| 103 | Thread damaged | Visual |
| 104 | Metal defective | Visual |
| 105 | Protective finish inadequate or defective | Visual |
| 106 | Burr | Visual |
| 107 | Foreign matter present | Visual |
| Minor | | |
| None defined | | |

**4.3.2.5 Pin, Shear, Drawing 8594745, covering a detail of Drawing 8593315.**

| | | |
|---|---|---|
| Critical | | |
| None defined | | |
| Major | | |
| 101 | Diameter, max. | Gage |
| 102 | Total length, min. | Measure |
| 103 | Metal defective | Visual |
| 104 | Protective finish inadequate or defective | Visual |
| 105 | Surface finish improper | Visual |
| 106 | Burr | Visual |
| 107 | Foreign matter present | Visual |
| Minor | | |
| 201 | Total length, max. | Gage |
| 202 | Profile of end | Gage |

**4.3.2.6 Housing, Firing Pin, Drawing 8594858 covering a detail of Drawing 8593315.**

| | | |
|---|---|---|
| Critical | | |
| C1 | Surface finish of cavity | Gage |



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:24Z
Check the source to verify that this is the current version before use.

| Characteristic | Defect | Method of Inspection |
|---|---|---|
| Major | | |
| 101 | Pitch diameter of internal thread, max | Gage |
| 102 | Minor diameter of internal thread, max | Gage |
| 103 | Pitch diameter of external thread, min | Gage |
| 104 | Major diameter of external thread, min | Gage |
| 105 | Thread damaged | Visual |
| 106 | Metal defective | Visual |
| 107 | Protective finish inadequate or defective | Visual |
| 108 | Surface finish of cavity chamfer improper | Visual |
| 109 | Burr or sharp corner | Visual |
| 110 | Foreign matter present | Visual |
| Minor | | |
| None defined | | |

**4.3.2.7 Pin, firing, Drawing 8594744 covering a detail of Drawing 8593315.**

| | | |
|---|---|---|
| Critical | | |
| *None defined* | | |
| Major | | |
| 101 | Metal defective | Visual |
| 102 | Protective finish inadequate or defective | Visual |
| 103 | Surface finish of body and striker tip, improper | Visual |
| 104 | Burr | Visual |
| 105 | Foreign matter present | Visual |
| Minor | | |
| None defined | | |

**4.3.2.8 Assembly, less Shear Pin, Cap, Cartridge Retainer and Chamber, Drawing 8593315, less Drawings 8594745, 8595254, 8593313, and 8593314.**

| | | |
|---|---|---|
| Critical | | |
| 1 | Protrusion of firing pin | Gage |
| 2 | O-ring missing | Visual |
| Major | | |
| None defined | | |
| Minor | | |
| 201 | O-ring not lubricated | Visual |

**4.3.2.9 Assembly, less Cap, Chamber, Cartridge Retainer, Protective Plug and Protective Cap, Drawing 8593315 less Drawings 8595254, 8593314, 8593313, MIL-C-5501/10, and MIL-C-5501/11.**

| | | |
|---|---|---|
| Critical | | |
| 1 | Shear pin not engaged in firing pin | Visual/Manual |
| 2 | Shear pin set screw missing | Visual |



Source: https://assist.dla.mil -- Downloaded: 202610-23T07:24Z
Check the source to verify that this is the currentversion before use.

| Characteristic | Defect | Method of Inspection |
|---|---|---|
| Major | | |
| 101 | O-ring missing or not lubricated | Visual |
| 102 | Thread damaged | Visual |
| 103 | Foreign matter present | Visual |
| Minor | | |
| None defined | | |

**4.3.2.10 Assembly, Drawing 8593315.**

| | | |
|---|---|---|
| Critical | | |
| 1 | Any part missing, except as otherwise classified | Visual |
| Major | | |
| None defined | | |
| Minor | | |
| 201 | Protective cap or plug missing | Visual |
| 202 | Protective finish inadequate or defective | Visual |

**4.3.2.11 Box, Fiberboard (inner) Packing Ammunition, Drawing 8796826.**

| | | |
|---|---|---|
| Critical | | |
| None defined | | |
| Major | | |
| None defined | | |
| Minor | | |
| 201 | Contents loose | Manual |
| 202 | Box damaged | Visual |
| 203 | Marking missing, incorrect, or illegible | Visual |
| 204 | Cut, damaged or improperly sealed bag | Visual |

**4.3.2.12 Box, Packing, Ammunition, Drawing 8796827.**

| | | |
|---|---|---|
| Critical | | |
| None defined | | |
| Major | | |
| None defined | | |
| Minor | | |
| 201 | Contents loose | Visual/Manual |
| 202 | Strapping missing, loose, broken, or improperly assembled | Visual/Manual |
| 203 | Contents of box exposed | Visual |
| 204 | Box damaged | Visual |
| 205 | Marking missing, incorrect, or illegible | Visual |
| 206 | Number of units incorrect | Visual |



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:24Z
Check the source to verify that this is the current version before use.

**4.3.2.13 Box, Fiberboard (outer) Alternative, Packing Ammunition, Drawing 9216824.**

| | | |
|---|---|---|
| Critical | | |
| None defined | | |
| Major | | |
| None defined | | |
| Minor | | |
| 201 | Contents loose | Manual/Visual |
| 202 | Hardware missing, loose, broken, or improperly engaged | Visual |
| 203 | Strapping missing, loose, broken, or improperly engaged | Visual |
| 204 | Contents of box exposed | Visual |
| 205 | Box damaged | Visual |
| 206 | Marking missing, incorrect or illegible | Visual |

**4.4. Inspection testing.** The following tests shall be performed in accordance with the provisions of 4.5.

**4.4.1. Hydrostatic pressure.** Each chamber and cap shall be subjected to the hydrostatic pressure test. Failure of any cap or chamber subassembly to comply with the requirement of 3.3 shall be cause for rejection of the subassembly.

**4.4.2. Protective finish.** The number of units for protective finish tests shall be in accordance with the applicable specification. Failure of any unit in the inspection sample to comply with the requirements of the applicable specification shall be cause for rejection of the lot.

**4.4.3. Residual magnetism.** Each assembly shall be subjected to the test for excessive residual magnetism. Failure of any unit in the inspection sample to comply with the requirement of 3.6 shall be cause for rejection of the assembly as specified in 4.5.4.

**4.4.4. Shear pin strength.** Fifty pins from each lot of shear pins shall be tested for shear strength. Failure of any pin to comply with the requirement of 3.4 shall be cause for rejection of the lot.

**4.5 Test methods and procedures.**

**4.5.1 Protective finish.** Test procedures for protective finish shall be in accordance with the applicable specification referenced on the applicable drawing.

**4.5.2 Hydrostatic pressure.** Prior to the application of protective finish, the cap and chamber shall be mounted in the device, using a fixture for properly sealing all openings and subjected to the internal hydrostatic pressure to determine compliance with the requirement of 3.3.

**4.5.3 Shear pin strength.** After application of protective finish, the pin shall be subjected to the shear pin strength test to determine compliance with 3.4. The test shall be performed in a fixture in conjunction with a tensile testing machine.

**4.5.4 Residual magnetism.** The assembly shall be tested for excessive residual magnetism using an approved compass in an area free of local magnetic effects by placing the assembly 5 inches from the end and at the same height as the compass, in a north-south horizontal position (cap end at south) with the compass set in an east-west heading. The assembly shall be moved at a speed no greater than 10 feet per minute past the compass for its entire length, rotated 90 degrees in the horizontal position about its longitudinal axis and moved slowly back past the compass. This procedure shall be repeated for each 90 degree rotation of the assembly for four full passes.



Source: https://assist.dla.mil -- Downloaded: 202640-23T07:24Z
Check the source to verify that this is the currentversion before use.

**4.6 Inspection of packaging.** The sampling and inspection of the packaging, packing, and container marking shall be in accordance with the requirements of section 5.

## 5. PACKAGING

**5.1 Packing and marking.** Packing and marking shall be levels A or B as specified by the contracting activity:

Level A — In accordance with Drawings 8796826 and 8796827
Level B — In accordance with Drawings 8796826 and 9216824

**5.2 Air Force packaging.** Air Force packaging shall be in accordance with TPO 00-845-1058.

## 6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

**6.1 Intended use.** The assembly will ultimately be loaded and used in conjunction with other propellant actuated devices in aircrew emergency escape systems.

**6.2 Acquistion requirements.** Acquisition documents should specify the following:

a. Title, number, and date of this specification
b. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1)
c. The responsible inspection activity (see 4.1)
d. Inspection sampling plan and acceptance/rejection criteria (see 4.3.2 and 6.3)
e. Level of marking and packing (see 5.1).

**6.3 Inspection sampling plan and acceptance/rejection criteria.** The sampling plan and acceptance/rejection criteria of tables I and II has been used successfully in procuring, testing, and examining the remanufactured Cartridge Actuated Initiator M6A1, M26, M33 Metal Parts Assembly. For an individual defect (single characteristic), the criteria in table I has been used. For total defects within a major or minor group, the criteria in table II has been used. The contracting activity is cautioned that any deviation from the values in tables I and II should be warranted and verified statistically considering the criticality of the remanufactured metal parts assembly's function.

TABLE I. Sampling plan.

| Lot size | Sample size | Major | | Minor | |
|---|---|---|---|---|---|
| | | Accept | Reject | Accept | Reject |
| 1-300 | 100% examination | — | — | — | — |
| 301-1,300 | 110 | 1 | 2 | 2 | 3 |
| 1,301-3,200 | 150 | 2 | 3 | 3 | 4 |
| 3,201-8,000 | 225 | 3 | 4 | 4 | 5 |
| 8,001-22,000 | 300 | 4 | 5 | 5 | 6 |



Source: https://assist.dla.mil -- Downloaded: 202610-23T07:24Z
Check the source to verify that this is the current version before use.

TABLE II. Total allowable defects per sample size.

| Sample size for major defects | 110 | 150 | 225 | 300 |
|---|---|---|---|---|
| Number of defects in class | | | | |
| 2-3 | 1 | 2 | 3 | 4 |
| 4-7 | 2 | 3 | 4 | 5 |
| 8-19 | 3 | 4 | 5 | 7 |
| 20-43 | 4 | 5 | 8 | 10 |
| Over 43 | 6 | 8 | 11 | 14 |
| **Sample size for minor defects** | **110** | **150** | **225** | **300** |
| Number of defects in class | | | | |
| 2-3 | 2 | 3 | 4 | 5 |
| 4-7 | 3 | 4 | 5 | 7 |
| 8-16 | 4 | 5 | 8 | 10 |
| 17-48 | 6 | 8 | 11 | 14 |
| Over 48 | 8 | 11 | 17 | 20 |

**6.4 Definitions.**

**6.4.1 Mechanical failure.** Mechanical failure is any deformation or breakage of a part, the occurrence of which is other than a design function.

**6.4.2 Remanufactured exterior components.** Remanufactured exterior components are: Cap, Firing Pin Housing, and Chamber.

**6.5 Subject term (keyword) listing**

Ejection systems, aircrew
Emergency escape systems, aircrew
Escape systems, aircrew
Life-saving systems, aircrew

Custodian:
Navy-OS
Air Force-99

Review activity:
Air Force-70

Preparing activity:
Navy-OS

(Project 1377-0937)



Source: https://assist.dla.mil -- Downloaded: 202610-23T07:24Z
Check the source to verify that this is the currentversion before use.

# STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

*(See Instructions – Reverse Side)*

| 1. DOCUMENT NUMBER | 2. DOCUMENT TITLE |
|---|---|
| MIL-I-82760 | INITIATOR, CARTRIDGE ACTUATED, DELAY, M6A1, M26, M33 |

| 3a. NAME OF SUBMITTING ORGANIZATION | 4. TYPE OF ORGANIZATION *(Mark one)* |
|---|---|
| | ☐ VENDOR |
| b. ADDRESS *(Street, City, State, ZIP Code)* | ☐ USER |
| | ☐ MANUFACTURER |
| | ☐ OTHER *(Specify)* _____ |

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

| 7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional | b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional |
|---|---|
| c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional | 8. DATE OF SUBMISSION *(YYMMDD)* |

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

*(TO DETACH THIS FORM, CUT ALONG THIS LINE.)*

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:24Z
Check the source to verify that this is the current version before use.

**INSTRUCTIONS:** In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

*NOTE:* This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

*(Fold along this line)*

*(Fold along this line)*

DEPARTMENT OF THE NAVY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12503 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE NAVY

Commanding Officer
Naval Ordnance Station
Standardization Branch (3730)
Indian Head, MD 20640-5000

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:24Z
Check the source to verify that this is the current version before use.