MILITARY SPECIFICATION

MINE, ANTI-PERSONNEL, TRAINING: M81

This specification is approved for use by the U.S. Army Armament Research and Development Command and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the detail requirements for metal parts as well as loading, assembling and packing for a training mine used in hand emplaced mine systems.

2. APPLICABLE DOCUMENTS

SPECIFICATIONS

MILITARY

MIL-F-45060 - Fuze, Mine, Combination, M605, Parts For

MIL-M-46960 - Mine, Anti-Personnel, M16A2, Parts For

MIL-A-48078 - Ammunition, Standard Quality Assurance Provisions, General Specification For

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures And Tables For Inspection By Attributes

FSC: 1345

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Command, Attn. DRDAR-QA, Dover, New Jersey 07801 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:53Z
Check the source to verify that this is the current version before use.

DRAWINGS

US ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND PRODUCT AND PACKAGE DRAWINGS

9332440 - Mine, Anti-Personnel, Training: M81

3. REQUIREMENTS

3.1 Materials. Materials shall be in accordance with the applicable drawings and specifications.

3.2 Mine assembly. The mine assembly shall comply with all requirements specified on drawing 9332440 and with all requirements specified in applicable specifications and standards.

3.3 Workmanship. The mine shall be fabricated and finished in a thorough, workmanlike manner. It shall be free of burrs, chips, sharp edges, cracks, unblended radii, surface defects, dirt, grease, rust, corrosion products, and other foreign matter. The cleaning method used shall not be injurious to the device nor shall the parts be contaminated by the cleaning agents. All markings and stampings shall be free of harmful cleaning agents that may be injurious to the mine. All markings and stampings, shall be displayed and visibly defined. The mine shall be manufactured and/or processed in such a manner as to be uniform in quality, and free from defects that will affect life, configuration and serviceability.

3.4 First article inspection. This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract, see Table I.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection and standard quality assurance provisions. Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:53Z
Check the source to verify that this is the current version before use.

4.2 Classification of inspections. The following types of inspections shall be conducted on this item:

a. First Article Inspection
b. Quality Conformance Inspection

4.3 First article inspection

4.3.1 Submission. The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with the provisions of 4.3.2. The first article sample shall be consistant with the First Article Classification of Defects, Table I.

4.3.2 Inspections to be performed. See MIL-A-48078 and First Article Inspection Classification of Defects, Table I and drawings as applicable.

4.3.3 Rejection. See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:53Z
Check the source to verify that this is the current version before use.

TABLE I. FIRST ARTICLE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE: Mine, Anti-Personnel, Training: M81		SHEET 1 OF 1		DRAWING NUMBER / NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Mine, Anti-Personnel, M16A2, Metal Parts Arrangement (Dwg. 8885204) Examination for defects	10			4.4.2.1
	Head Assembly (Dwg. 7548285) Examination for defects	10			4.4.2.2
	Loading Assembly, Inert (Dwg. 9343008) Examination for defects	25			4.4.2.3
	Fuze, Mine, Training (Dwg. 9343007) Examination for defects	25			4.4.2.4
	Mine, Anti-Personnel, Training: M81, Loading Assembly (Dwg. 9332439) Examination for defects	25			4.4.2.5
	Mine, Anti-Personnel, Training: M81 (Dwg. 9332440) Examination for defects	25			4.4.2.6

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:53Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection

4.4.1 Inspection lot formation. Inspection lots shall comply with the lot formation provisions of MIL-A-48078.

4.4.2 Examination. See MIL-A-48078. Unless otherwise specified in the Classification of Defects and Test Tables, sampling plans for major and minor defects shall be in accordance with MIL-STD-105.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:53Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.1	Mine, Anti-Personnel, M16A2 Metal Parts Arrangement				8885204
					NEXT HIGHER ASSEMBLY 9332439
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major 101	As required by specification with the exception of part no. 8864742 requirements (a)		(a)	3.2	MIL-M-46960
Minor 201	As required by specification with the exception of part no 8864742 requirements (a)		(a)	3.2	MIL-M-46960

NOTES:

(a) First Article and lot acceptance criteria shall be as required in MIL-M-46960.

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:53Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	OF	DRAWING NUMBER
4.4.2.2	Head Assembly	1	1	7548285
				NEXT HIGHER ASSEMBLY: 9343007

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical 1	As required by specification (a)		(a)	3.2	MIL-F-45060
Major 101	As required by specification (a)		(a)	3.2	MIL-F-45060
Minor 201	As required by specification		(a)	3.2	MIL-F-45060

NOTES:
(a) First Article and lot acceptance criteria shall be as required in MIL-F-45060.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:53Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.3	Load Assembly, Inert	1 OF 1	9343008
			NEXT HIGHER ASSEMBLY: 9343007

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Overall assembly length, maximum		0.40%	3.2	Gage
102	Threads coated with sealing compound		100%	3.2	Visual
103	Breakaway torque		0.40%	3.2	Gage
Minor					
201	Evidence of poor workmanship		1.0%	3.3	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:53Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.4	Fuze, Mine, Training	1 OF 1	9343007
			NEXT HIGHER ASSEMBLY 9343007

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Markings incorrect		100%	3.2	Visual
102	Breakaway torque		0.40%	3.2	Gage
103	Threads coated with sealing compound		100%	3.2	Gage
104	Required external surfaces lacquer painted		100%	3.2	Visual
Minor					
201	Evidence of poor workmanship		1.0%	3.3	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:53Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.5	Mine, Anti-Personnel, Training: M81, Loading Loading Assembly	1 OF 1	9332439
			NEXT HIGHER ASSEMBLY 9332440

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Inert filler in place		100%	3.2	Scale/Visual
102	Filler disc adhesive in place		100%	3.2	Visual
103	Bushing adhesive in place		100%	3.2	Visual
104	Bushing assembly torque		100%	3.2	Gage
105	Plug assembly torque		100%	3.2	Gage
106	Marking		100%	3.2	Gage
Minor					
201	Exterior finish		0.65%	3.2	Visual
202	Evidence of poor workmanship		1.0%	3.3	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:53Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.6	Mine, Anti-Personnel, Training: M81	1 OF 1	9332440
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	External finish		100%	3.2	Visual
102	Fuze to body assemblies		100%	3.2	Manual
Minor					
201	Evidence of poor workmanship		1.0%	3.3	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:53Z
Check the source to verify that this is the current version before use.

4.4.3 Testing. Testing is described in the First Article and Quality Conformance Inspection tables.

4.4.4 Inspection equipment. The inspection equipment required to perform the examination and tests prescribed herein is described in the Paragraph Reference Inspection Method column in the tables of paragraphs 4.4.2.1 and 4.4.2.2. The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078 and 6.3 herein.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging. Each mine shall be preserved and packaged in accordance with 9342944.

5.2 Packing. The mine preserved and packaged shall be packed for shipment in accordance with 9342938.

5.3 Marking. Marking of the carton shall comply with 9342938.

5.4 Shipping. When mines packages of more than one lot are shipped together, each lot shall be kept separate and the division between lots clearly indicated to prevent mixing of the lots in transit.

6. NOTES

6.1 Intended use. The mine covered by this specification is intended for use as a training device.

6.2 Ordering data. See Section 6.1 and 6.2 of MIL-A-48078.

6.3 Submission of inspection equipment designs for approval. (See 6.2.3 of MIL-A-48078). Submit equipment designs as required to Commander, U.S. Army Armament Research and Development Command, ATTN: DRDAR-QAA-I, Dover, New Jersey 07801

6.4 Drawings. Drawings listed in Section 2 of this specification under the heading US Army Armament Research and Development Command (ARRADCOM) may also include drawings prepared by

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:53Z
Check the source to verify that this is the current version before use.

and identified as, Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal, or Picatinny Arsenal drawings. Technical data originally prepared by these activities is now under the cognizance of ARRADCOM.

6.5 Distribution of certificate of compliance. Distribution of the certificate of compliance for each mine lot shall be sent to: Commander, ARRADCOM, ATTN: DRDAR-QAA-M, Dover, New Jersey 07801.

Custodian:
Army-AR

Preparing Activity:
Army-AR

Project No. 1345-A-147

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:53Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.
NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE

MIL-M-63440 Mine, Anti-Personnel, Training: M81

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*	TELEPHONE NO.
	DATE

DD FORM 1426 1 OCT 76

EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:53Z
Check the source to verify that this is the current version before use.