MILITARY SPECIFICATION

TRANSPARENCY, ANIMATED; GAS SYSTEM, BROWNING AUTOMATIC RIFLE

This specification has been approved by the Naval Training Device Center, Department of the Navy

The technical requirements for procuring the animated transparency described herein shall consist of this document and the issue in effect of Specification MIL-T-82300.

1. SCOPE

1.1 This specification covers the requirements for an animated transparency of the gas system of the Browning Automatic Rifle, caliber .30 M1918A2.

1.1.1 This item has been designated by the Naval Training Device Center as Device 29HB4 for Navy procurement.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bid or request for proposal form a part of this specification to the extent specified herein:

SPECIFICATIONS

Military

MIL-T-82300	Transparencies; Animated, General Specification for

STANDARDS

Federal

FED-STD-595	Colors

DRAWINGS

Naval Training Device Center (NAVTRADEVCEN)

818600D90001	A/T, Browning Automatic Rifle Gas System

PHOTOGRAPHS

Naval Training Device Center (NAVTRADEVCEN)

NP40-2115-10-56 and NP40-2116-10-56	B.A.R. Gas System Animated Transparency, Device 29HB4

FSC 6910

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:01Z
Check the source to verify that this is the current version before use.

PUBLICATIONS

Naval Training Device Center (NAVTRADEVCEN)

NAVEXOS P-1526 Guide for the Animated Transparency, Browning Automatic Rifle Gas System

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the Contracting Officer.)

3. REQUIREMENTS

3.1 Unless otherwise specified herein, requirements shall be in accordance with MIL-T-82300.

3.1.1 Cements.- Cements used for joining plastic components shall be those cements recommended by the manufacturer of the plastic and tested by the contractor as suitable for meeting the cementing and performance requirements of this specification.

3.2 Design.- The animated transparency shall be in accordance with the design requirements of MIL-T-82300 and shall be capable of demonstrating all the utilization requirements of NAVEXOS P-1526.

3.3 Construction.- The animated transparency shall be constructed in accordance with NAVTRADEVCEN drawing 818600D90001. Construction details not specified on the drawing shall be as shown on NAVTRADEVCEN photographs NP40-2115-10-56 and NP40-2116-10-56.

3.3.1 Cementing.- Cementing shall be limited to those areas where assembly with screws is clearly impractical. Cemented joints shall be free of air bubbles and stress-crazing and shall have the transparency of the original plastic throughout the joint. The contact surface of the component to be cemented shall be thoroughly softened by means of a solvent, so that a soft layer or cushion is produced on that surface and the subsequent uniting and hardening will effect a strong homogeneous bond. Bonding by capillary attraction shall require specific written approval of the procuring activity for each specific variance. For recommendations on cementing acrylic plastics, the publications cited in the cementing requirements of MIL-T-82300 may be used.

3.3.2 Focusing mark.- The focusing mark shown on the drawing of 3.3 shall have the projected image of the cross hairs and the 1/4-inch diameter opening in the mask concentric. The cross hairs shall be placed at a level to result in optimum focus of all projected components of the device.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:01Z
Check the source to verify that this is the current version before use.

3.4 Performance.- The animated transparency, when used on the overhead projector, shall withstand the temperatures produced by a 1,000-watt projection lamp for a period of 45 minutes with the projector's heat filter removed. At the end of this period, the animated tranparency shall meet the conditions listed in the performance requirements of MIL-T-82300.

3.5 Dust seals.- The edges of the layers of the baseplate shall be sealed with white or aluminum opaque polyester tape so as to be dustproof and to mask edge lighting effects. Dust seals shall be provided wherever a laminated component or flap is used. Such seals, in projectable areas, shall be applied to the edges only.

3.6 Overall height.- The maximum thickness of the sum of those components which are projected shall not exceed 3/4-inch from the bottom of the lowest projectable component to the top plane of the highest component. The projected image shall be sharp and clear. Projectable movable components shall have a vertical separation to prevent abrasion of the moving parts.

3.7 Fasteners.- Screws shall be used for the assembly of moving parts and shall be secured to prevent loosening by rotation or movement of the parts. Threaded portions of screws shall not be used as bearing surfaces for moving parts. Rivets shall not be used without prior approval in writing from the procuring activity.

3.7.1 Selection of screws.- The minimum practical number of screws and the smallest practical head diameter of screws for fastening components shall be used within the projected image area.

3.8 Controls.- Controls for actuating the various components shall be as shown on the drawing of 3.3 to meet the utilization requirements of NAVEXOS P-1526 of 3.2. All controls shall be movable by light finger pressure.

3.9 Carrying case.- The top and bottom of the carrying case shall be 1/4-inch thick exterior grade plywood, smooth two sides, and finished with gray lacquer color number 26152 of FED -STD-595.

3.10 Color.- Colors for projectable components shall be as specified on the drawing of 3.3.

3.11 Nameplate.- A nameplate shall be affixed to each animated transparency in the location specified by the procuring activity.

4. QUALITY ASSURANCE PROVISIONS

4.1 Except as specified herein, quality assurance provisions shall be in accordance with the quality assurance provisions of MIL-T-82300.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:01Z
Check the source to verify that this is the current version before use.

4.1.1 Responsibility for inspection.- Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

5. PREPARATION FOR DELIVERY

5.1 Preparation for delivery shall be in accordance with the delivery requirements of MIL-T-82300.

6. NOTES

6.1 The notes of MIL-T-82300 shall be applicable

CUSTODIAN:
Navy-TD

PREPARING ACTIVITY:
Navy-TD
Project No. 6910-N211

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:01Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specation in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obing information on the use of this specification which will insure that suitable products can be procured with a mum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on s on reverse side, staple in corner, and send to preparing activity *(as indicated on reverse hereof)*.

IFICATION

NIZATION *(Of submitter)* | CITY AND STATE

RACT NO. | QUANTITY OF ITEMS PROCURED | DOLLAR AMOUNT $

RIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

AS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES.

COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

MITTED BY *(Printed or typed name and activity)* | DATE

FORM 1426
APR 63

REPLACES NAVSHIPS FORM 4863, WHICH IS OBSOLETE

Source: https://assist.dla.mil -- Downloaded: 20260-23T07:01Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE NAVY

POSTAGE AND FEES PA
NAVY DEPARTMENT

OFFICIAL BUSINESS

Commanding Officer
Naval Training Device Center
Specifications Control Division (3335)
Orlando, Florida 32813

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:01Z
Check the source to verify that this is the current version before use.