MILITARY SPECIFICATION

INSTRUMENT SYSTEMS, PITOT TUBE AND FLUSH STATIC PORT OPERATED, INSTALLATION OF

This amendment forms a part of Military Specification MIL-I-6115A, 29 March 1951, and has been approved by the Department of Defense and is mandatory for use by the Departments of the Army, the Navy, and the Air Force.

Page 1, preamble Delete and substitute the following: "This specification has been approved by the Department of Defense and is mandatory for use by the Departments of the Army, the Navy, and the Air Force"

Pages 1 and 2, section 2 Delete and substitute:

"2. APPLICABLE DOCUMENTS

"2.1 The following documents, of the issue in effect on date of invitation for bids, form a part of this specification to the extent specified herein:

SPECIFICATIONS

FEDERAL

WW-T-787	—Tube, Aluminum Alloy, Round, Square, Rectangular, and Other Shapes, Drawn, Seamless, 5052

MILITARY

MIL P-8585	—Primer Coating, Zinc Chromate, Low-Moisture-Sensitivity.
MIL A-8625	—Anodic Coatings, for Aluminum and Aluminum Alloys

STANDARDS

MILITARY

MS33586	—Metals, Definition of Dissimilar
MS33656	—Fitting End, Standard Dimensions for Flared Tube Connection and Gasket Seal

AIR FORCE-NAVY AERONAUTICAL

AN929	—Cap Assembly, Pressure Seal Flared Tube Fitting
AN5811	—Tube, Pitot, Electrically Heated, "L" Shaped, Inverted
AN5812	—Tube, Pitot, Electrically Heated, "L" Shaped
AN5813	—Tube, Pitot, Electrically Heated.
AN6270	—Hose Assembly—Detachable Swivel Fitting, Low Pressure
AND10375	—Colors—Fluid Line Identification
AND10410	—Pitot-Static and Pitot Tube—Wiring Diagram for.

PUBLICATIONS

NAVAL AIR MATERIAL CENTER

Report No. NAES-INSTR 16-44	—Dual Sighting Stand and Other Methods of Calibrating Altimeter and Airspeed Installation

871073-61-(X-89)

FSC 6610

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T06:36Z
Check the source to verify that this is the current version before use.

(Copies of this publication may be obtained from the Engineering Division, Documentation Branch, Bureau of Naval Weapons, Navy Department, Washington 25, D C)

(Copies of specifications, standards, drawings, and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer)

2.2 Other publications. The following document forms a part of this specification to the extent specified herein Unless otherwise indicated, the issue in effect on date of invitation for bids shall apply

NATIONAL AERONAUTICS AND SPACE ADMINISTRATION

Report 919 —Accuracy of Airspeed Measurements and Flight Calibration Procedures

(Copies of this report may be obtained from the National Aeronautics and Space Administration, 1520 H Street, N W, Washington 25, D C)"

Page 2, paragraph 3 1 1 1, lines 2 and 5: Delete "Drawing AND10398" and "MIL-P-6889" and substitute "Standard MS33586" and "MIL-P-8585", respectively

Page 2, paragraph 3 1.2, line 4 Delete "ANA Bulletin No 143" and substitute "procedures established by the procuring activity or as specified in the contract or order"

Page 3, add the following new paragraph.

"3.1.2.2 AN or MS straight threaded fittings only shall be used and shall be connected in accordance with the applicable standards listed in section 2"

Page 3, paragraph 3 2 1, line 2 Delete "Drawings" and substitute "Standards"

Page 8, paragraph 3.2 6.7.1, line 2: Delete "AN-QQ-A-696" and substitute "MIL-A-8625".

Page 8, paragraph 3 2 7.1, line 4· Delete "AN-QQ-A-696" and substitute "MIL-A-8625".

Page 9, FIGURE 4, in note above figure title: Delete "DRAWING AND10056" and substitute "STANDARD MS33656"

Page 10, paragraph 3 2 7 3, line 2· Delete "Drawing" and substitute "Standard" and add the following at the end of the paragraph: "The color coding shall specify distinctly which line is pitot pressure and which line is static pressure The marking tape shall be within 3 inches of the terminal fitting"

Page 10, paragraph 3.2 9, lines 2, 4, and 7· Delete "Drawing" and substitute "Standard".

Page 10, paragraph 3.2.11, lines 3 and 4: Delete "Drawing AND10056" and substitute "Standard MS33656".

Page 10, paragraph 3.2.15, line 2: Delete "Drawing" and substitute "Standard".

Page 11, section 4: Delete "4 SAMPLING, INSPECTION, AND TEST PROCEDURES" and substitute the following heading and new paragraph:

"4. QUALITY ASSURANCE PROVISIONS

"4.01 Inspection responsibility. The supplier is responsible for the performance of all inspection requirements as specified herein Except as otherwise specified, the supplier may utilize his own or any other inspection facilities and services acceptable to the Government Inspection records of the examination and tests shall be kept complete and available to the Government as specified in the contract or order. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements"

Page 11, paragraph 4.1: Delete the last three sentences.

Page 12, paragraph 4.2.6.1, lines 2 and 3 Delete "NACA Technical Note 1605" and substitute "National Aeronautics and Space Administration Report 919."

Page 15: Delete "Custodian: Air Force" and substitute the following: "Custodians: Army—Transportation Corps, Navy—Bureau of Naval Weapons" Delete "Other interest: Navy Bu-Aer", and add "Preparing activity: Navy—Bureau of Naval Weapons".

Custodians:
Army—Transportation Corps
Navy—Bureau of Naval Weapons

Preparing activity:
Navy—Bureau of Naval Weapons

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T06:36Z
Check the source to verify that this is the current version before use.