MILITARY SPECIFICATION SHEET

RELAYS, ELECTROMAGNETIC, TYPE I, HERMETICALLY SEALED,
100 AMPERES, SPST (N O) WITH SPDT (FORM Z) 5 AMPERES
AUXILIARY CONTACTS

This amendment forms a part of MIL-R-6106/48A, dated 28 March 1991, and is approved for use by the Department of the Air Force and is available for use by all Departments and Agencies of the Department of Defense

PAGE 1

- Figure 1, top view, .170 + .005,- .002 (4 PLACES), add "COUNTERBORE (4 PLACES) .032 DEEP, .312 DIA OTHERSIDE"

PAGE 4

- Requirements, coil data, coil resistance delete and substitute

  "Coil resistance 90 ohms minimum at +25°C for -001, 100 ohms minimum at +25°C for -002 "

- Requirements contact data operate time, delete "±25°C" and substitute "+25°C"

- Requirements, contact data, release time, delete "±25°C" and substitute "+25°C"

- Requirements, contact data, motor, delete and substitute

  "Motor 50 A for -001, 25 A for -002 "

- Requirements, contact data, overload current, delete and substitute

  "Overload current 800 A for -001 and -002 (-001 only as shown in figure 2) "

PAGE 5

Vibration random, delete and substitute

"Vibration random

M6106/48-001 2/

Frequency (Hz)	Level (g^2/Hz)
10 - 125	0 0375
125 - 250	+4 dB
250 - 1,000	0 1
1,000 - 2,000	-3 dB

M6106/48-002 2/

Frequency (Hz)	Level (g^2/Hz)
15 - 50	0 012
120 - 200	0 364
250 - 400	0 194
600 - 1,000	0 060
1,300 - 2,000	0.097

At bottom of page, add footnote 2/

"2/ Test to be performed with 5 ampere load on main contact "

PAGE 6

Electrical data dielectric withstanding voltage (sea level) delete "1800" and substitute "1500"

DISTRIBUTION STATEMENT A Approved for public release distribution is unlimited

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T06:34Z
Check the source to verify that this is the current version before use.

- Electrical data, dielectric withstanding voltage (sea level) delete "1350" and substitute "1125"

- Electrical data, dielectric withstanding voltage (altitude) delete "700" and substitute "500"

Part or Identifying Number (PIN) , delete and substitute

"Part or Identifying Numbers (PIN) M6106/48-001, M6106/48-002 "

The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications corrections, deletions) from the previous amendment were made This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notation and relationship to the last previous issue

CONCLUDING MATERIAL

Custodian
Air Force - 85

Review activities
Air Force - 99
DLA - ES

Preparing activity
Air Force - 85

Agent
DLA - ES

(Project 5945-0994)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T06:34Z
Check the source to verify that this is the current version before use.