NOTE: The document identifier and heading have been changed on this page to reflect that this is a performance specification. There are no other changes to this document. The document identifier on subsequent pages has not been changed, but will be changed the next time this document is revised.

INCH-POUND

MIL-PRF-6106/48A
AMENDMENT 3
10 July 1999
SUPERSEDING
AMENDMENT 2
23 May 1996

PERFORMANCE SPECIFICATION SHEET

RELAYS, ELECTROMAGNETIC, TYPE I, HERMETICALLY SEALED,
100 AMPERES, SPST (N.O.) WITH SPDT (FORM Z) 5 AMPERES
AUXILIARY CONTACTS

This amendment forms a part of MIL-PRF-6106/48A, dated 28 March 1991, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

* FIGURE 1, delete “Instalation” two places and substitute “Installation”

* FIGURE 1, delete “Torgue” and substitute “Torque”

PAGE 1

FIGURE 1, top view, .170 +.005,-.002 (4 PLACES), add "COUNTERBORE (4 PLACES).032 DEEP, .312 DIA OTHERSIDE"

PAGE 4

Requirements, coil data, coil resistance, delete and substitute:

"Coil resistance: 90 ohms minimum at +25°C for -001; 100 ohms minimum at +25°C for -002."

Requirements, contact data, operate time, delete "±25°C" and substitute "+25°C".

Requirements, contact data, release time, delete "±25°C" and substitute "+25°C".

Requirements, contact data, motor, delete and substitute:

"Motor: 50 A for -001; 25 A for -002."

Requirements, contact data, overload current, delete and substitute:

"Overload current: 800 A for -001 and -002 (-001 only as shown in figure 2)."

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T06:34Z
Check the source to verify that this is the current version before use.

PAGE 5

Vibration random, delete and substitute:

"Vibration random:

M6106/48-001 2/	
Frequency (Hz)	Level (g^2/Hz)
10 - 125	0.0375
125 - 250	+4 dB
250 - 1,000	0.1
1,000 - 2,000	-3 dB

M6106/48-002 2/	
Frequency (Hz)	Level (g^2/Hz)
15 - 50	0.012
120 - 200	0.364
250 - 400	0.194
600 - 1,000	0.060
1,300 - 2,000	0.097

At bottom of page, add footnote 2/:

"2/ Test to be performed with 5 ampere load on main contact."

PAGE 6

Electrical data, dielectric withstanding voltage (sea level), delete "1800" and substitute "1500".

Electrical data, dielectric withstanding voltage (sea level), delete "1350" and substitute "1125".

Electrical data, dielectric withstanding voltage (altitude), delete "700" and substitute "500".

Part or Identifying Number (PIN):, delete and substitute:

"Part or Identifying Numbers (PIN): M6106/48-001, M6106/48-002."

The margins of this amendment are marked with asterisks to indicate where changes from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodians:
Air Force - 11
DLA - CC

Preparing activity:
DLA - CC

(Project 5945-1058-14)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T06:34Z
Check the source to verify that this is the current version before use.