METRIC

A-A-59836
October 2, 2009

COMMERCIAL ITEM DESCRIPTION

CARABINER

This commercial item description is approved for use by the all Departments and Agencies of the Department of Defense or for all Federal agencies**.**

1. SCOPE.

1.1 Scope. This commercial item description covers the requirements for carabiners which are used as connectors between ropes, webbing, rock and ice protection, and anchors.

2. CLASSIFICATION. The carabiners will be furnished in the following types:

2.1 Types:

Type D - Non-locking, D-shaped
Type X - Non-locking, oval
Type H (1) - Locking, pear-shaped
Type H (2) - Auto-locking, pear-shaped

3. SALIENT CHARACTERISTICS. The carabiner design shall provide ease of use with typical combat gloves while meeting the standards in this description.

3.1 Type D. The Type D carabiner shall be "D" shaped and meet the dimension requirements in drawing 3-3-0104. The hinge pin attaching the gate to the body shall be tightly peened or pressed into the body of the carabiner. The gate shall not be of a wire gate construction. The gate shall operate easily without jamming in either direction. (See Drawing 3-3-0104).

3.1.1 Type X. The Type X carabiner shall be oval shaped and meet the dimension requirements in drawing 3-3-0105. The hinge pin attaching the gate to the body shall be tightly peened or pressed into the body of the carabiner. The gate shall not be of a wire gate construction. The gate shall operate easily without jamming in either direction. (See Drawing 3-3-0105).

Comments, suggestions, or questions on this document should be addressed to: Defense Supply Center Philadelphia, Clothing and Textiles Directorate, Attn: DSCP Standardization Team, 700 Robbins Avenue, Philadelphia, PA 19111-5096. Since contact information can change, you may want to verify the currency of this address information using Acquisition Streamlining and Standardization Information System (ASSIST) online database at http://assist.daps.dla.mil/.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:29Z
Check the source to verify that this is the current version before use.

3.1.2 Type H (1). The Type H (1) carabiner shall be pear-shaped and meet the dimension requirements in drawing 3-3-0106, also referred to as HMS, to allow for use with the Italian or Munter Hitch while belaying. The hinge pin attaching the gate to the body shall be tightly peened or pressed into the body of the carabiner. The carabiner gate shall be threaded and fitted with a knurled manual locking sleeve. The sleeve shall screw into place over the opening between the gate and carabiner body to prevent inadvertent opening of the gate during use. The gate and the locking sleeve shall operate easily without jamming in either direction. The locking sleeve shall not be capable of being screwed completely off the end of the gate. (See Drawing 3-3-0106).

3.1.3 Type H (2). The Type H (2) carabiner shall be pear-shaped, and meet the dimension requirements in drawing 3-3-0107, also referred to as HMS, to allow for use with the Italian or Munter Hitch while belaying. The hinge pin attaching the gate to the body shall be tightly peened or pressed into the body of the carabiner. The carabiner gate shall be threaded and fitted with a knurled automatic locking sleeve. The locking sleeve will automatically lock into place over the opening, over the gate and carabiner body to prevent inadvertent opening of the gate during use, when released. The automatically locking gate shall operate with a spring loaded twisting mechanism. The gate and the locking sleeve shall operate easily without jamming in either direction. The locking sleeve shall not be capable of being screwed completely off the end of the gate. (See Drawing 3-3-0107).

3.2 Physical requirements

3.2.1 Physical characteristics. The carabiners for all types shall conform to the sizes and characteristics as specified in Table I.

TABLE I. Physical characteristics

Type	Gate closed, strength kN	Gate open strength kN	Weight grams	Rope bearing Surface width Mm	Gate Opening Width Mm
D	24	8	50	8.4	15
X	23	7	45	7.8	25
H (1)	24	8	69	12.0	20
H (2)	23	N/A	105	16.0	24
Tolerance	N/A	N/A	±10%	+/-1	+/-1

3.3 Color. The carabiner shall be provided in a low reflectance, matte finish and provide low contrast with typical use terrain unless otherwise specified in the solicitation or contract order. (See 7.2)

3.4 Materials.

3.4.1 Basic material (All types). The carabiner body shall be 7075 aluminum.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:29Z
Check the source to verify that this is the current version before use.

3.5 End item testing. The carabiners shall meet the International Mountaineering and Climbing Federation Union Internationale des Associations d'Alpinisme – (UIAA) Standard 121 or EN 12275 for their respective types.

3.6 Workmanship. The finished carabiner shall conform to the quality of product established by this document. The occurrence of defects shall not exceed the contractors own quality assurance standards and the quality assurance standards defined in the technical data in the solicitation and/or contract.

3.7 Service life. The carabiner shall have no unexpected material or component failures during a continuous one-year cycle. The carabiner shall have no unexpected material or component failures during periodic use over a five year period.

3.8 Labels/barcoding/instruction slip. If applicable, all labeling, barcoding and instruction slip requirements shall be as specified in the solicitation or contract (see 7.2).

4. REGULATORY REQUIREMENTS. The offeror/contractor is encouraged to use recovered materials to the maximum extent practicable, in accordance with paragraph 23.403 of the Federal Acquisition Regulation (FAR).

4.1 Recycled, recovered, or environmentally preferable materials. Recycled, recovered, or environmentally preferable materials should be used to the maximum extent possible, provided that the material meets or exceeds the operational and maintenance requirements and promotes economically advantageous life cycle costs.

5. PRODUCT CONFORMANCE PROVISIONS.

5.1 Product conformance. The products provided shall meet the salient characteristics of this commercial item description, conform to the producer's own drawings, specifications, standards, and quality assurance practices, and be the same product offered for sale in the commercial marketplace. The Government reserves the right to require proof of such conformance.

5.2 Visual examination. The carabiner for all types shall be examined for the following defects as listed in Table II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:29Z
Check the source to verify that this is the current version before use.

TABLE II. End item examination

Examine	Defect Description
Finish	Not smooth and adherent
	Not low reflectance, matte finish
	Does not provide low contrast with typical use terrain
Construction	Not free of burrs, rough spots, slivers, flat areas or projections Any component missing or not specified type Any component fractured, slit, punctured, dented, bowed, malformed or damaged. Marking etched or indented, contains rough or sharp edges Any component loose
Gate	Gate does not fully close Gate pin not peened correctly (i.e. peening not spread evenly in the countersunk area, peened end protrudes beyond surface of gate, or metal cracks in area. Gate locking sleeve doesn't lock (Type H only)
Labels/barcoding/instruction slip. (if applicable)	Incorrect, illegible, omitted or misplaced
Marking	Omitted, missing information or illegible

5.3 Acceptance criteria. Acceptance criteria shall be as specified in the contract or purchase order (see 7.2).

6. PACKAGING.

6.1 Preservation, packing and marking. The preservation, packing and marking shall be as specified in the contract or order (see 7.2).

7. NOTES.

7.1 Sources of documents.

7.1.1 Government Documents. Copies of Government documents are available online at http://assist.daps.dla.mil/quicksearch/ or from the Standardization Documents Order Desk, Building 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.

DRAWINGS

U.S. ARMY NATICK SOLDIER CENTER

3-3-0104 Carabiner, Type D
3-3-0105 Carabiner, Type X
3-3-0106 Carabiner, Type H (1)
3-3-0107 Carabiner, H (2)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:29Z
Check the source to verify that this is the current version before use.

(Copies of drawings are available from the U.S. Army Natick Research Development and Engineering Center, Natick Soldier Center, ATTN: NSRDEC-RDNS-WPW-C, Natick, MA 01760)

7.1.2 Federal Acquisition Regulations are available online at http://acquisition.gov/far/index.html or by contacting the Superintendent of Documents at 202-512-1800.

7.1.3 Non-Government documents. Non-Government standards and other publications are normally available from the organizations that prepare or distribute the documents. These documents may be available in or through libraries or other informational services.

EUROPEAN STANDARD (EN)

EN 12275 Mountaineering Equipment – Connectors – Safety Requirements and Test Methods

(Copies are available online at www.bsi-global.com or from BSI British Standards, Customer Services 389 Chiswick High Road London W4 4AL United Kingdom)

INTERNATIONAL MOUNTAINEERING AND CLIMBING FEDERATION
UNION INTERNATIONALE DES ASSOCIATIONS D'ALPINISME (UIAA)

UIAA Safety Standard 121 Mountaineering and Climbing Equipment, Connectors

(Copies are available online at http://www.theuiaa.org or from the Union Internationale Des Associations D'Alpinisme (UIAA) Monbijoustrasse 61 Postfach CH-3000 Bern 23 Switzerland

7.2 Ordering data. The contract or order should specify the following:

a. Title, number, and date of this Commercial Item Description.
b. Type, sizes required. (See 2.1)
c. Color required. (See 3.3)
d. When required, labeling, barcoding, and instruction slip (see 3.8)
e. Acceptance criteria. (See 5.3)
f. Packaging requirements. (See 6.1)

7.3 Key words:

anchors
connectors ropes,
ice protection
rock protection
webbing

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:29Z
Check the source to verify that this is the current version before use.

MILITARY INTERESTS:

CIVIL AGENCY COORDINATION ACTIVITY
GSA – FSS

Custodian:
Army - GL
Marine Corps – MC

PREPARING ACTIVITY:
DLA-CT

Project Number: 8465-2009-001

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using ASSIST Online database at http://assist.daps.dla.mil/.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:29Z
Check the source to verify that this is the current version before use.