INCH-POUND
A-A-59866
May 12, 2010

COMMERCIAL ITEM DESCRIPTION

TEAM STOVE

The General Service Administration has authorized the use of this commercial item description for all Federal Agencies

1. SCOPE. This commercial item description (CID) covers a compact, lightweight, expeditionary style stove capable of burning logistically available military type liquid fuels.

2. CLASSIFICATION: The Team Stove shall be furnished in one type.

3. SALIENT CHARACTERISTICS: The stove shall be a single burner, open flame, with heat control varying from low to high flame. The burner shall be remotely connected by means of a flexible fuel line and a separate pump and fuel storage bottle supplied with the stove. The stove shall be collapsible for placement in a carrying container. The stove shall have minimal parts or components to facilitate easier setup and repacking, and to reduce the risk of misplacing loose parts. The Team Stove is intended to be used by personnel engaged in remote locations involving combat operations, or for use in humanitarian relief efforts.

3.1 Color. The Team Stove shall be provided in a low reflectance, matte finish and provide low contrast with typical use terrain unless otherwise specified in the solicitation or contract order. (See 7.2)

3.2 Materials. Materials used in the construction of the stove shall be heat and corrosion resistant and shall prove suitable strength to conform to the maximum weight objective (see 3.3.1), and the performance objective stated herein.

3.3 Functional Requirements

Comments, suggestions, or questions on this document should be addressed to: Defense Supply Center Philadelphia, Clothing and Textiles Directorate, Attn: DSCP Standardization Team, 700 Robbins Avenue, Philadelphia PA 19111-5096 or e-mailed to NATI-mountain@conus.army.mil. Since contact information can change, you may want to verify the currency of the address information using Acquisition Streamlining and Standardization Information System (ASSIST) online database https://assist.daps.dla.mil/online/.

AMSC N/A FSC 7310

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:29Z
Check the source to verify that this is the current version before use.

3.3.1 Weight. The weight of the Team Stove, consisting of burner/support assembly, pump, wind screen, repair parts, protective container, and instructions will not exceed 20 ounces. The weight of a separate 20 fluid ounce fuel bottle will not exceed 6.5 ounces, with cap when empty.

3.3.2 Cookware support. A stable platform having a minimum support diameter that will support a metal canteen cup, per MIL-C-43761, NSN 8465-01-118-8171, shall be provided as an integral part of the stove.

3.3.3 Stove stability. The stove shall provide stability and support when it is set up on rough or minimally uneven surfaces. Detachable or folding legs shall be provided to stabilize the stove on rough or uneven terrain.

3.3.4 Burner windshield. A means shall be provided to protect or shield the priming and burner flame from the wind such that proper pre-heat temperatures can be reached in order to ignite the fuel and maintain a uniform shape and flame color without wind distortion.

3.3.5 Fuel. The stove shall be capable of burning the following military fuels available in a battlefield environment:

-kerosene
-white gas
-JP8
-Diesel fuel

3.3.6 Burner System. The burner shall be equipped with all accessories and fuel jets required to burn the fuels specified in 3.2.5. The fuel jet shall be permanently identified to distinguish it for the particular fuel it is to burn. The burner shall be capable of operating from sea level to 16,000 feet above sea level without significantly diminished flame performance, and at temperatures ranging from -25°F to 125°F. The burner shall have a minimum heat output of 9500 BTU per hour. The stove shall safely burn the fuel without flare up or flashing of the flame. All components of the stove, including seals and O-rings, shall be capable of withstanding operational temperatures of the stove.

3.3.7 Priming. The burner shall be self-priming using fuel from within the fuel line/bottle. The fuel shall be distributed around the base of the burner to heat it up for the fuel vaporization and ignition stage. A priming wick or priming pad shall be provided to support this preheat stage. Preheat pastes shall not be necessary to prime the stove. The burner shall be readily and safely ignitable without dangerous flare up.

3.3.8 Fuel Control. The burner shall have a fuel control to adjust the flame over a heating range from low to high heat. Flame adjustment shall control the rate and volume of fuel flow into the burner such that all the fuel is vaporized without allowing the fuel to surge into the burner causing flooding or flare up.

3.3.9 Fuel bottles. The fuel bottle shall be designed to be able to be certified by Title 49, Code of Federal Regulations, Part 178 for single packaging. The cap shall have a method to allow the

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:29Z
Check the source to verify that this is the current version before use.

user to know if they have tightened it sufficiently to maintain a pressure tight, leak proof seal during transport.

3.3.10 Fuel bottle capacity. The included fuel bottle capacity must be 20±2 ounces. Larger, optional fuel bottles must meet the same requirements except for capacity.

3.3.11 Pump. A pump device for connection (screw threads) to the fuel bottle shall be provided. The pump shall create adequate pressure to pump the fuel and maintain flow to the burner unit. The fuel line connection from the pump connected at the fuel bottle shall be of a metal braided, flexible type to prevent undue stress and leaks at the fittings. All connection devices shall be designed for a leak tight fit at operational pressures.

3.3.12 Protective container. The stove shall be place in a reusable container rugged enough for use in combat environments. The container shall be large enough to hold the stove, pump, and accessories. The fuel bottle shall be carried separately.

3.3.13 Spare/Repair Parts. A spare parts kit shall be provided for the stove including all necessary standard components (such as O-rings, pump cup oil jets, etc.) and tools to service the stove in the field.

3.3.14 Operation instructions. Operating instructions shall be provided for fueling, operating and maintaining the stove. The instructions shall contain all warnings and safety recommendations.

3.3.15 Maintenance. The stove shall be maintainable and cleanable in the field. The burner shall be equipped with cleaning kit or a built-in cleaning needle for maintaining the fuel jet.

3.4. End item testing. The Team Stove with fuel bottle (minus spare/repair parts) shall be designed to be able to be certified by Title 49, Code of Federal Regulations, Part 178 for single packaging.

3.5 Workmanship. The finished Team Stove shall conform to the quality of product established by this document. The occurrence of defects shall not exceed the contractors own quality assurance standards and the quality assurance standards defined in the technical data in the solicitation and/or contract.

3.6 Service Life. Unless otherwise specified in the contract, the manufacturer's standard commercial warranty shall apply.

3.7 Labels/bar coding/instruction slip. If applicable, all labeling, bar coding and instruction slip requirements shall be as specified in the solicitation or contract (see 7.2).

4. REGULATORY REQUIREMENTS. The offeror/contractor is encouraged to use recovered materials to the maximum extent practicable, in accordance with paragraph 23.403 of the Federal Acquisition Regulation (FAR).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:29Z
Check the source to verify that this is the current version before use.

4.1 Recycled, recovered, or environmentally preferable materials. Recycled, recovered, or environmentally preferable materials should be used to the maximum extent possible, provided that the material meets or exceeds the operational and maintenance requirements and promotes economically advantageous life cycle costs.

5. PRODUCT CONFORMANCE PROVISIONS.

5.1 Product conformance. The products provided shall meet the salient characteristics of this commercial item description, conform to the producer's own drawings, specifications, standards, and quality assurance practices, and be the same product offered for sale in the commercial marketplace. The Government reserves the right to require proof of such conformance.

5.2 Visual examination. The Team Stove shall be examined for the following defects as listed in Table I.

TABLE I. End item examination

Examine	Defect Description
Finish	Not smooth and adherent Not low reflectance, matte finish Does not provide low contrast with typical use terrain
Construction	Not free of burrs, rough spots, slivers, flat areas or projections. Any component missing or not specified type Any component fractured, slit, punctured, dented, bowed, malformed, or damaged. Marking etched or indented, contains rough or sharp edges. Any component loose.
Labels/bar coding/instruction slip	Incorrect, illegible, omitted or illegible.
Marking	Omitted, missing information or illegible

5.3 Acceptance criteria. Acceptance criteria shall be as specified in the contract or purchase order (see 7.2).

6. PACKAGING

6.1 Preservation, packing and marking. The preservation, packing and marking shall be as specified in the contract or order (see 7.2).

7. NOTES:

7.1 Sources of documents.

.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:29Z
Check the source to verify that this is the current version before use.

7.1.1 Government Documents. Copies of Government documents are available online at https://assist.daps.dla.mil/online/or from the Standardization Documents Order Desk, Building 4D 700 Robbins Avenue, Philadelphia, PA 1911-5094.

Title 49, Code of Federal Regulations (CFR), Part 178, Specifications for Packaging

(Copies are available online at http://www.access.gpo.gov/cgi-bin/cfrassemble.cgi?title=200349 or from US Government Printing Office 732 North Capitol Street, NW, Washington, DC 20401-0001)

7.1.2 Federal Acquisition Regulations. Federal Acquisition Regulations are available online at http://acquisition.gov/far/index.html or by contacting the Superintendent of Documents at 202-512-1800.

7.1.3 Non-Government documents. Non-Government standards and other publications are normally available from the organizations that prepare or distribute the documents. These documents may be available through libraries or other informational services.

7.2 Ordering data. The contract or order should specify the following:

a. Title, number, and date of this Commercial Item Description
b. Type, color required (See 2 and 3.1)
c. When required, labeling, bar coding, and instruction slip (3.7)
d. Acceptance criteria. (See 5.3)
e. Packaging requirements (See 6.1)

7.3 Key words.

Heater

MILITARY INTERESTS:

Custodian:

Army - GL

CIVIL AGENCY COORDINATING ACTIVITY:
GSA-FSS

PREPARING ACTIVITY:

DLA-CT

Project: 7310-2010-006

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using ASSIST Online database at https://assist.daps.dla.mil/online/.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:29Z
Check the source to verify that this is the current version before use.