MILITARY
SPECIFICATION

MIL-A-11892(SigC)
AMENDMENT NO. 5
19 December 1961

ANTENNA GROUP OA-249( )/GRC-10
(COMPONENTS OF)

1. Paragraph 1.1 Add the following components:

Support, Antenna AB-381( )/U
Ground Plane Frequency Setting Chart

2. Section 2. APPLICABLE SPECIFICATIONS, STANDARDS, DRAWINGS, AND PUBLICATIONS Add the following:

MIL-C-5441	Chemical Films for Aluminum and Aluminum Alloys
MIL-R-16060	Rope, Manila and Substitutes.
SC-DL-84293	Guy Stake GR-111( )/G.
SC-DL-182911	Support, Antenna AB-381( )/U.

3. Section 2. APPLICABLE SPECIFICATIONS, STANDARDS, DRAWINGS AND PUBLICATIONS Delete the following:

MIL-T-16070	Treatment, Mildew Resistant for Rope (Manila).

4. Paragraph 3.3.3 Plastic materials. In third sentence, change "lined" to "linen".

5. Paragraph 3.6.3 In second line, change "makred" to "marked".

6. Paragraph 3.10.2 Antenna elements. In second line replace "Condition T" with "Condition T6".

7. Paragraph 3.10.2.2. Hardware. Replace with the following:

"3.10.2.2 Hardware.- Wing bolts and inserts shall be made of AISI "300" series stainless steel."

8. Paragraph 3.10.2.3 Color coding.-Delete "of" in second line.

9. Paragraph 3.10.2.4 Frequency setting charts.- Change title to read "Frequency setting chart for directional array."

10. Paragraph 3.10.5 Cables.- Change title to read "Cable Assembly CG-718/U".

FSC-5985

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T22:06Z
Check the source to verify that this is the current version before use.

11. Paragraph 3.10.5.1 Replace with the following:

"3.10.5.1 One cable assembly shall be provided with each Antenna AS-620( )/GRC-10 consisting of 65 feet of Radio Frequency Cable RG-8A/U in accordance with Specification JAN-C-17 with Plug Connector UG-573( )/U Industrial Products Co, Part/Dwg 1PC-8000 or equal, on each end. Cable Assembly shall be capable of withstanding a 25 pound tensile pull-out load applied for one minute with a maximum center contact displacement of .015."

12. Paragraph 3.10.5.2 In line 3 change "UG-573/U" to "UG-573( )/U". Add the following sentence:

"Cable assembly shall be capable of withstanding a 25 pound tensile pull-out load applied for one minute with a maximum center contact displacement of .015".

13. Paragraph 3.10.6 Adapter.- Change "UG-643/U" to "UG-643( )/U".

14. Add paragraph 3.10.6.1 Adapter Connector UG-567( )/U. Adapter Connector UG-567( )/U shall be Industrial Product No. IPC-83000, or equal.

15. Paragraph 3.11.1 Mast Sections. Replace "mast sections" with "Mast Section AB-300( )/U".

16. Paragraph 3.11.2 Guy Assemblies.- In second sentence, replace "300 pounds" with "600 pounds excluding adjustable guy clamp."

17. Paragraph 3.11.2.1 Nylon. Delete and replace with the following:

"3.11.2.1 Rope material.- The rope material to be used for guy assemblies shallibe 3/16 inch plus .010 inch minus .015 inch diameter, olive drab, three strand, yacht lay, pre-stretched, stabilized filament polyethelene glycol terephalate, minimum breaking strength 800 pounds; 15 percent maximum allowable elongation at 240 pounds; as made by the Columbian Rope Company, Auburn, New York or equal."

18. Paragraph 3.11.3 and paragraph 3.11.4. Delete "(Stainless steel shall be non-nickel bearing type)."

19. Paragraph 3.11.6 Rope Assembly.- Replace with the following:

"3.11.6 Rope Assembly.- The rope assembly shall be in accordance with model. Rope shall be manilla, per Federal Specification T-R-601 and shall be mildew and moisture-resistant, per Specification MIL-R-16060. Rope assembly shall be capable of a tensile load of 600 pounds without slippage of termination sleeves."

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T22:06Z
Check the source to verify that this is the current version before use.

20. Paragraph 3.11.7 Stake.- Delete and replace with the following:

"3.11.7 Guy Stake CP-111/U.- Guy Stake CP-111/U shall be constructed in accordance with Drawing SC-DL-84293."

21. Paragraph 3.11.8 Delete paragraph.

22. Add the following:

"3.14 Antenna Support AB-381( )/U. Antenna Support AB-381( )/U shall be constructed in accordance with Drawing SC-DL-182911."

23. Add the following:

"3.15 Ground plane frequency setting chart. Frequency setting charts shall be provided to indicate setting of element lengths for optimum operation at each megacycle point over the frequency range of the equipment."

24. Paragraph 4.5.2 Shock test. In first sentence delete "edge and face."

25. Section 4. SAMPLING, INSPECTION AND TEST PROCEDURE. Add the following.

"Paragraph 4.5.4. Immersion test; Antenna Support AB-381( )/U. Antenna Support AB-381( )/U shall be immersed in 6 inches of water. At 10 pound-per-square-inch pressure, there shall be no evidence of leakage."

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T22:06Z
Check the source to verify that this is the current version before use.