MIL-C-11954A
26 AUGUST 1952
SUPERSEDING
MIL-C-11954(CmlC)
21 APRIL 1952

MILITARY SPECIFICATION

CONTAINER; FOR FLOATING SMOKE POT

This specification has been approved by the Departments of the Army, the Navy, and the Air Force.

1. SCOPE

1.1 This specification covers a container for use with a floating smoke pot.

2. APPLICABLE SPECIFICATIONS, STANDARDS, DRAWINGS, AND PUBLICATIONS

2.1 The following specifications, standards, and drawings, of the issue in effect on date of invitation for bids, form a part of this specification.

SPECIFICATIONS

MILITARY

MIL-P-10577 —Packaging of Components and Subassemblies, Domestic Shipment to Assembly Plants.

U. S. ARMY

57-206-21 —Welding of Constructional Steel; Resistance, Spot.

NAVY DEPARTMENT

General Specifications for Inspection of Material.

STANDARDS

MILITARY

MIL-STD-105—Sampling Procedures and Tables for Inspection by Attributes.

MIL-STD-129—Marking of Shipments.

DRAWINGS

CHEMICAL CORPS

B36-2-103 —Container — Assembly and Bill of Material.

(Copies of specifications, standards, and drawings required by contractors in connection with specific procurement functions should be obtained from the procuring agency or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Material.—All materials and components used in the manufacture and assembly of the container shall conform to the specifications and drawings forming a part of this specification.

3.2 Manufacture and assembly.—The container shall be manufactured and assembled as specified on Drawing B36-2-103 and subsidiary drawings listed thereon.

3.3 Handle lug separation. — The handle lug, Drawing A36-2-134 which is listed on Drawing B36-2-103, shall not separate from the outer cover, Drawing B36-2-128 which is listed on Drawing B36-2-103, or from the inner cover, Drawing B36-2-108, when tested as specified in 4.4.1.

3.4 Leakage.—The container shall not leak when tested as specified in 4.4.2.

3.5 Spot resistance welding.—All spot resistance welding shall conform to Specification 57-206-21.

202387—52—(305)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T22:09Z
Check the source to verify that this is the current version before use.

3.6 Workmanship.—All work shall be done in a neat and workmanlike manner.

4. METHODS OF SAMPLING, INSPECTION, AND TESTS

4.1 Lot.—A lot shall consist of the containers produced by one manufacturer, from the same materials, and under essentially the same manufacturing conditions. The inspection lot for nondestructive inspection, within the above limitations, shall be designated by the inspector.

4.2 Sampling for nondestructive inspection.—Sampling for nondestructive inspection shall be conducted in accordance with the authorized classification of defects (4.3.4) and Standard MIL–STD–105.

4.3 Inspection.

4.3.1 *Components.*—The inspector shall ascertain that, prior to assembly, all materials, components, or subassemblies of the container procured under separate specifications or drawings have been inspected, tested, and accepted in accordance with their respective specifications or drawings.

4.3.2 *Packaging, packing, and marking.*—The inspector shall inspect the packaging, packing, and marking of the container for compliance with section 5.

4.3.3 *Procedures.*—For Navy purchases, the general inspection procedures shall be in accordance with General Specifications for Inspection of Material.

4.3.4 *Classification of defects.*—Inspection of the container shall be conducted as follows:

4.3.4.1 *Container—assembly.*—(Dwg. B36–2–103.)

Categories and defects	*Gage or other method of inspection*
Major A AQL 0.25 percent	
1a. Leakage	4.4.2
2a. Handle lug separation	4.4.1
Major AQL 1.0 percent	
*1. Component missing or incorrectly assembled	Visual
2. Clamp incorrect	Functional
3. Inside diameter incorrect	Caliper
4. Inside length incorrect	Scale
5. Inner cover section profile incorrect	Scale and visual
6. Inner cover center-hole size and location incorrect	Scale
7. Handle lugs incorrectly located	Scale
8. Damage	Visual
Minor AQL 2.5 percent	
51. Holes (29/32") size and location incorrect	Scale
52. Cover not smooth	Visual
53. Outside diameter incorrect	Caliper
54. Inner cover gasket missing, skips, excess, or inadequate	Visual
55. Beads on body	Visual
56. Coating missing, inadequate, or incorrect	Visual
57. Handle and lugs dimensions incorrect	Scale
Incidental AQL 10 percent	
101. Burrs	Visual
102. Contamination	Visual

* Retainer disc, outer cover, and clamp shall not be assembled to container.

4.3.4.2 *Disc, retainer.*—(Dwg. B36–2–124. which is listed on Dwg. B36–2–103.)

Categories and defects	*Gage or other method of inspection*
Major AQL 1.0 percent	
1. Outside diameters incorrect	Functional
Minor AQL 2.5 percent	
51. Holes, location and diameters incorrect	Scale
52. Flange length incorrect	Scale
53. Coating missing, inadequate, or incorrect	Visual
Incidental AQL 10 percent	
101. Burrs	Visual

4.3.4.3 *Handle**.—(Dwg. A36–2–133, which is listed on Dwg. B36–2–103.)

Categories and defects	*Gage or other method of inspection*
Major AQL 1.0 percent	
1. Side profile incorrect	Scale

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T22:09Z
Check the source to verify that this is the current version before use.

Categories and defects	*Gage or other method of inspection*
Minor	
None	
Incidental	
None	

* For prime Chemical Corps procurement only.

4.3.4.4 *Lug, handle**.—(Dwg. A36–2–134, which is listed on Dwg. B36–2–103.)

Categories and defects	*Gage or other method of inspection*
Major	
None	
Minor AQL 2.5 percent	
51. Length incorrect	Scale
52. Width incorrect	Scale
Incidental AQL 10 percent	
101. Corners incorrect	Visual

* For prime Chemical Corps procurement only.

4.3.4.5 *Cover, outer — assembly.* — (Dwg. B36–2–128, which is listed on Dwg. B36–2–103.)

Categories and defects	*Gage or other method of inspection*
Major A AQL 0.25 percent	
1a. Handle lug separation	4.4.1
Major AQL 1.0 percent	
1. Overall diameter incorrect	Caliper
2. Section profile of lid incorrect	Scale and visual
3. Inside diameter incorrect	Scale
4. Diameter (11.125") incorrect	Scale
5. Gasket missing, skips, excess or inadequate	Visual
Minor AQL 2.5 percent	
51. Handle dimensions and location incorrect	Scale
52. Coating missing, inadequate, or incorrect	Visual
Incidental AQL 10 percent	
101. Finish incorrect	Visual
102. Contamination	Visual

4.4 Tests.

4.4.1 *Handle lug separation.*—The handle of the outer cover and the handle of the inner cover shall each be subjected to a direct pull of 75 pounds and observed for any separation of the handle lug.

4.4.2 *Leakage.*—Three of the holes in the outer cover of the container shall be sealed and a fixture for applying a pressure attached to the fourth hole. The container shall be subjected to an internal air pressure of 3 pounds per square inch, submerged in water for a period of 2 minutes, and observed for leaks.

5. PREPARATION FOR DELIVERY

5.1 **Packaging and packing.**—The components shall be packaged and packed for shipment in accordance with Specification MIL–P–10577. Each shipping container shall contain only one type of component and no shipping container shall contain more than 500 components nor weigh more than 200 pounds.

5.2 **Marking.**—In addition to any special marking required by the contract or order, all shipping containers shall be marked in accordance with Standard MIL–STD–129.

6. NOTES

6.1 **Ordering data.** — Procurement documents should specify the following:

(a) The title, number, and date of this specification.

(b) The number of sealing machines required.

6.2 **Sealing machines.**—Machines suitable for making the pressure closure after filling should be supplied by the contractor. The number of sealing machines required to seal the containers will depend upon the quantity of containers of the particular design procured. In cases of repeat orders of duplicate design, where sealing machines may have been furnished and remain available, no additional machines are required.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T22:09Z
Check the source to verify that this is the current version before use.

Notice.—When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use or sell any patented invention that may in any way be related thereto.

Custodians:
Army—Chemical Corps
Navy—Bureau of Ordnance

Other interest:
Navy—*MC.*

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T22:09Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity *(as indicated on reverse hereof)*.

SPECIFICATION

ORGANIZATION *(Of submitter)* | CITY AND STATE

CONTRACT NO. | QUANTITY OF ITEMS PROCURED | DOLLAR AMOUNT $

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES.

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity)* | DATE

DD FORM 1 APR 63 1426 REPLACES NAVSHIPS FORM 4863, WHICH IS OBSOLETE PLATE NO. 15419

Source: https://assist.dla.mil -- Downloaded: 202610-17T22:09Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE NAVY

POSTAGE AND FEES PAID
NAVY DEPARTMENT

OFFICIAL BUSINESS

COMMANDING OFFICER
PICATINNY ARSENAL
ATTN: SMUPA-DC 7
DOVER, NEW JERSEY

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T22:09Z
Check the source to verify that this is the current version before use.