MILITARY SPECIFICATION

SCARF, BRANCH OF SERVICE, BIB TYPE

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers two types of scarf used by the Department of Defense.

1.2 Classification. Scarfs covered by this specification shall be of the following Type and Classes (see 6.2 and 6.3).

Type I - Snap Fastener
Type II - Velcro Fastener

Class 1 - Black
Class 2 - Bottle Green
Class 3 - Brick Red
Class 4 - Buff
Class 5 - Cobalt Blue
Class 6 - Crimson
Class 7 - Dark Blue
Class 8 - Green
Class 9 - Light Blue
Class 10 - Maroon
Class 11 - Old Gold
Class 12 - Orange
Class 13 - Oriental Blue
Class 14 - Purple
Class 15 - Scarlet
Class 16 - Silver Gray
Class 17 - Teal Blue
Class 18 - Ultramarine Blue
Class 19 - Yellow
Class 20 - Bleached White
Class 21 - Woodland Camouflage Pattern

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be used in improving this document should be addressed to: Director, The Institute of Heraldry, US Army, Cameron Station, Alexandria, VA 22304-5050, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 8455

AMSC N/A
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T22:07Z
Check the source to verify that this is the current version before use.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. The following specifications and standards form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

FEDERAL

V-T-285 - Thread, Polyester
DDD-L-20 - Label; for Clothing, Equipage and Tentage (General Use)
PPP-B-636 - Boxes, Shipping Fiberboard
PPP-B-676 - Boxes, Setup

MILITARY

MIL-F-10884 - Fasteners, Snap
MIL-F-21840 - Fastener Tapes, Hook and Pile, Synthetic
MIL-C-44031 - Cloth, Camouflage Pattern, Woodland, Cotton and Nylon.

STANDARDS

FEDERAL

FED-STD-191 - Textile Test Methods
FED-STD-751 - Stitch, Seam and Stitching

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129 - Marking for Shipment and Storage
MIL-STD-794 - Parts and Equipment, Procedures for Packaging of

2.1.2 Other Government documents, drawings and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein. Unless otherwise specified, the issue shall be those in effect on the date of the solicitation.

DRAWINGS

THE INSTITUTE OF HERALDRY

5-2-80 - Scarf, Branch of Service, Bib Type

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T22:07Z
Check the source to verify that this is the current version before use.

NATICK RESEARCH AND DEVELOPMENT LABORATORIES

2-1-1516 Woodland Pattern four color.

(Copies of specifications, standards and drawings required by the supplier in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

(Figure 1 is a miniature reproduction of drawing 5-2-80 and is attached for information purposes only.)

2.2 Other publications. The following document forms a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted shall be those listed in the issue of the DODISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS shall be the issue of the nongovernment documents which is current on the date of the solicitation.

THE COLOR ASSOCIATION OF THE UNITED STATES

The Standard Color Reference of America, Tenth Edition
United States Army Color Card, The Official Colors for Branches, Agencies

(Application for copies of the aforementioned documents should be addressed to The Color Association of the United States, 343 Lexington Avenue, New York, NY 10016.)

American Society for Testing Materials (ASTM)

ASTM-D-3951 - Standard Practice for Commercial Packaging

(Application for copies of ASTM publications should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, Pennsylvania 19103.)

(Nongovernment standards and other publications are normally available from the organizations which prepare or which distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, (except for associated detail specifications, specification sheets or MS standards) the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T22:07Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Standard sample. Unless otherwise specified (see 6.4), a standard sample of the applicable scarf and sewing thread shall be furnished for matching color, colorfastness and finish. Samples of the camouflage pattern may be obtained from the contracting officer upon request. Variations from this specification may appear in the standard sample; however, in such cases the specification shall govern.

3.2 First article. When otherwise specified (see 6.5), before production is commenced, a sample of the finished scarf covered by this specification shall be submitted or made available to the contracting officer or his authorized representative for inspection and tests as specified in 4.2. The approval of the first article authorizes the commencement of production, but does not relieve the contractor of responsibility for compliance with all applicable provisions of this specification. The first article shall be manufactured by the contractor in the same facilities to be used for the manufacturing of the production items.

3.3 Materials. Materials shall conform to the referenced specifications and the requirements specified herein.

3.3.1 Base cloth. The base cloth shall be a two-way texturized polyester fabric with one of the following weaves: 3 up, 2 down, twill, 2 up, 2 down, twill or plain. The polyester yarn shall be 150 denier for warp and filling before texturizing. The weight of the fabric shall be 5 (plus or minus) .4 oz per square yard. The materials for the class 21, camouflage pattern only, shall be in accordance with class 1 of MIL-C-44031.

3.3.1.1 Color. The color of the cloth for classes 1 through 20 shall conform to the list below and shall match the color of the standard sample (see 3.1), under natural (North sky) daylight having a color temperature of 7500 (plus or minus) 500 Kelvin. The color shall be a good approximation to the standard sample under incandescent lamplight at 2800 (plus or minus) 100 degrees Kelvin. The cable numbers cited are from the Standard Color Reference of America, Tenth Edition and the United States Army Color Card, The Official Colors for Branches, Agencies, (see 2.2).

Color and Cable NO.	Color and Cable NO.
Black 65018	OLD GOLD 65021
Bottle Green 80066	Orange 65004
Brick Red 65020	Oriental Blue 80176
Buff 65015	Purple 65009
Cobalt Blue 65011	Scarlet 65006
Crimson 65013	Silver Gray 65008
Dark Blue 65012	Teal Blue 80135
Green 65007	Ultramarine Blue 65010
Light Blue 65014	Yellow 65002
Maroon 65017	Bleached White 80001

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T22:07Z
Check the source to verify that this is the current version before use.

3.3.1.1.1 Colorfastness. When tested as specified in 4.5.2, the dyed cloth shall show fastness to laundering, perspiration and light equal to or better than the standard sample. If no standard sample is available, the dyed cloth shall show good fastness to laundering, perspiration and light.

3.3.1.2 Camouflage. The camouflage pattern shall be in accordance with drawing number 2-1-1516 (US Army Natick Research and Development Laboratories drawing).

3.3.1.3 Finish. The finish of the basic cloth shall match the finish of the standard sample. When no standard sample is available the finish must be approved by the contracting officer prior to production.

3.3.2 Thread. The thread for machine stitching shall be polyester thread, conforming to type I, class 3, size A of V-T-285.

3.3.2.1 Color. The color of the thread shall approximate the colors specified in 3.3.1.1, and shall match the standard sample furnished (see 3.1).

3.3.2.1.1 Colorfastness. The dyed thread shall show fastness to laundering, wet-dry cleaning, perspiration and light equal to or better than the standard sample. When no standard sample is available, the thread shall show good fastness to laundering, perspiration and light.

3.3.3 Snap fasteners. The snap fasteners shall conform to style 3 (pronged ring head type), 17 lines, finish 3 of MIL-F-10884.

3.3.4 Innerlining. The innerlining of the neck band shall be cotton buckram of light, open-weave, single ply fabric weighing 2.5 ounces (minimum) per square yard having a minimum thread count of 40 ends in the warp and 20 ends in the filling.

3.3.5 Velcro fastener. The velcro fastener shall conform to type II, class 1, MIL-F-21840 and dimensions shown on drawing 5-2-80. The fastener shall be compatible color shade to the scarf.

3.4 Construction. The scarfs shall be constructed in accordance with figure 1 and the requirements specified herein.

3.4.1 Seams and stitching. All stitching shall be in accordance with FED-STD-751, using thread specified in 3.3.2. There shall be 8 to 10 stitches to the inch. Thread breaks shall be back stitched not less than 1/2 inch. Thread tension shall be maintained so that there shall be no loose stitching and so the lock for the 301 stitching shall be embedded in the center of the materials sewn.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T22:07Z
Check the source to verify that this is the current version before use.

3.4.2 Cutting. Patterns for cutting shall be furnished by the contractor and shall provide pieces which when properly assembled will meet the dimensions specified on drawing 5-2-80. The cutting and layout of materials shall be such that the warp of the bib fabric shall be in the vertical direction and the warp of the neckband fabric shall be in the horizontal direction on the finished scarf when viewed as shown on drawing 5-2-80.

3.4.3 Manufacturing operations.

3.4.3.1 Bib. The bib shall be made of a single ply of material specified in 3.3.1. The bib shall be hemmed on both sides and one end as shown on drawing 5-2-80, using 301 stitching.

3.4.3.2 Neckband. (1): The unhemmed end of the bib shall be centered on the neckband piece and the piece folded lengthwise over the top of the bib. The neckband piece shall then be stitched along its full length 1/16 inch to 1/8 inch from the edge with a 3/8 inch turn under as shown on figure 1. The stitch type shall be 301 and the seam type shall be LSe-1. (2): The open ends of the neckband shall be adjusted to a finished length of 19 inches plus or minus 1/4 inch and closed with zig-zag stitching securely tacking the stitching ends. A 304 stitch type and a SSc-1 seam type shall be used. As an alternate the open ends of the neckband may be finished with stitch type 504 and 505, with 28 (plus or minus) 4 stitches per inch and overstitched 1/4 inch at the stitching ends or bartacked to cover the final 3 stitches. (3): Snap fasteners specified in 3.3.3 or Velcro fastener specified in 3.3.5, shall be attached in the location specified on drawing number 5-2-80. Velcro shall be attached on all sides with stitch type 301. (4): The left edge of the label shall be placed 1-1/4 inches, plus or minus 1/4 inch to the right of the vertical centerline of the neckband with the top edge of the label along the top inside edge of the neckband and stitched on all four sides with a single row of stitching using stitch type 301.

3.4.3.3 Finishing. The scarfs shall be cleaned of all spots and stains and pressed smooth. Care shall be taken to remove gloss marks and creases.

3.5 Marking. Scarf shall be marked with a label 1-1/4 inches wide by 2-1/2 inches long conforming to type VI, class 15 of DDD-L-20. Title of specification, specification number, class number and instructions to "Launder or Dry Clean" shall appear on label. Scarf manufactured for commercial sale shall be marked with the manufacturer's hallmark in lieu of the contract number and stock number."

3.6 Workmanship. Scarfs shall be clean, well made and shall meet the acceptable quality levels established by this specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T22:07Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.4)

b. Quality conformance inspection (see 4.5).

4.3 Inspection for acceptance. Inspection for acceptance shall be in accordance with the provisions of MIL-STD-105, except where otherwise indicated.

4.4 First article inspection. Inspection and testing of the first article shall be made on a completely finished scarf for all provisions of this specification applicable to the end item examination and tests.

4.5 Quality conformance inspection. Inspection shall be in accordance with the provisions set forth in MIL-STD-105, except where otherwise indicated.

4.5.1 In-process inspection. Inspection of the manufacturing process shall be made at any point to determine whether operations or assemblies are accomplished as specified on figure 1 or as specified herein. The Government reserves the right to exclude from consideration for acceptance any assembly for which in-process inspection has indicated non-conformance.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T22:07Z
Check the source to verify that this is the current version before use.

4.5.2 Inspection of components and materials. In addition to the quality assurance provisions of the referenced specifications and standards, testing shall be conducted in accordance with the test methods as specified in FED-STD-191, and shall be performed on material as listed in table II. For sample unit requirements, the inspection level shall be S-1 and the AQL shall be 6.5 defects per hundred units. The requirements shall be applicable to the sample unit. When the data in the "#determ per s/u" and the "Results reported as" columns are not specified in table II, they shall be as required by the referenced test method. The sample unit shall be one yard of fabric.

TABLE II. Testing of components.

Component and lot size expressed in terms of	Characteristic	Rqm't para	Test method	#determ per s/u	Results reported as
Basic cloth (linear yard)	Yarn (warp and filling)	3.3.1	2/		
	Weave	3.3.1	Visual	1	Pass or fail
	Weight/sq yd	3.3.1	5041		
	Texture:				
	Warp	3.3.1	5050		
	Filling	3.3.1	5050		
	Breaking Strength:				
	Warp	3.3.1	5100		
	Filling	3.3.1	5100		
	Colorfastness:				
	Wet-dry				
	Cleaning	3.3.2.1.1	5622		
	Laundering	3.3.2.1.1	5614		
	Perspiration	3.3.2.1.1	5680		
	Light 1/	3.3.2.1.1	5660		
	Finish	3.3.1.3	Visual	1	Pass or fail

1/ In the event of dispute resulting from the test with method 5660, or as a result of suspected anomalous behavior of certain dye types or formulations, the contracting officer may authorize the exposure to natural light in accordance with method 5662.

2/ A contractor's certification of compliance is acceptable for these requirements.

4.5.3 Certificate of compliance. Where certificates of compliance are submitted, the Government reserves the right to check test such items to determine the validity of the certification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T22:07Z
Check the source to verify that this is the current version before use.

4.5.4 Inspection of the end item.

4.5.4.1 Visual examination. Defects found during the examination shall be classified in accordance with 4.5.4.1.1 and 4.5.4.1.2.

4.5.4.1.1 Examination for defects in material, design, construction and workmanship.

Examine	Defect	Classification Major	Minor
Fabric	Hole, cut or tear, smash, multiple float or slub .	x	-
	Misweave	x	-
	Shade bar or streak affecting appearance	x	-
	Off shade, not within established tolerance. . . .	x	-
Construction	Pieces not cut in specified direction.	-	x
	Hem on wrong side of bib	x	-
	Not assembled as specified	-	x
	Snap fasteners defective, e.g., cannot be closed .	x	-
	Fasteners missing or misplace.	x	-
	Snap fasteners clinched too tight, i.e., cuts surrounding material.	x	-
	Noticeable puckering of neckband after all three fasteners are engaged	-	x
	Operation omitted or not as specified	x	-
	Velcro not type specified.	x	-
	Snap fasteners not type specified.	x	-
Open seams and raw edges	More than 1 inch	x	-
	One inch or less	-	x
Stitches and seams	Incorrect seam type.	x	-
	Incorrect stitch type.	x	-
	More than the maximum number of stitches per inch.	-	x
	Less than the minimum number of stitches per inch.	x	-
	Thread breaks not backstitched	-	x
	Seam crooked or irregular affecting appearance . .	-	x
	Seam more than 1/8 inch from turned under edge of neckband or pressed edge of the bib	-	x
	Needle chews or run-off seriously affecting appearance or serviceability.	x	-
	Needle chews or run-off affecting appearance or serviceability but not seriously.	-	x
	Failure to cover stitching end when applicable . .	-	x
	Loose tension resulting in loose seam.	-	x
	Tight tension i.e., fabric puckers excessively . .	-	x
Cleanness	Spot or stain affecting appearance	-	x
	Thread ends not trimmed.	-	x

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T22:07Z
Check the source to verify that this is the current version before use.

Classification Examine	Defect	Major	Minor
Pressing	Burned or scorched	x	-
	Poorly pressed i.e., has creases or shade marking.	-	x
Marking	Label missing or improperly placed, so as to be visible when worn	x	-
	Label improperly placed but not so as to be visible when worn	-	x
	Marking not as specified i.e., illegible or incorrect	-	x

4.5.4.1.2 Dimensional defects. Any dimension that is not within the specified tolerance shall be classified a defect.

4.5.4.1.3 Inspection levels and acceptable quality levels (AQL's). The inspection levels and the acceptable quality levels expressed in defects per hundred units shall be as follows:

	Inspection level	AQL Major	AQL Total
For defects applicable to 4.5.4.1.1	II	2.5	10.0
For defects applicable to 4.5.4.1.2	S-4	(one class)	2.5

4.5.5 Examination of preparation for delivery requirements. An examination shall be made to determine that packaging, packing and marking comply with the requirements of section 5 of this specification. Defects shall be scored in accordance with the list below. The sample unit shall be one shipping container fully prepared for delivery with the exception that it need not be sealed. Shipping containers fully prepared for delivery shall be examined for the defects of closure listed below. The lot size shall be the number of shipping containers in the end item inspection lot. The inspection level shall be S-2 and the acceptable quality level shall be 2.5.

Examine	Defect
Markings (exterior and interior)	Omitted, incorrect, illegible, of improper size, location sequence or method of application.
Materials	Any component missing, any component damaged, affecting serviceability.
Workmanship	Inadequate application of components such as incomplete closure of container flaps, inadequate stapling.
Contents	Number per container is more or less than required.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T22:07Z
Check the source to verify that this is the current version before use.

4.5.6 Palletization examination. An examination shall be made to determine that the palletization is in compliance with the section 5 requirements. Defects shall be scored in accordance with the list below. The sample unit shall be one palletized unit load fully packaged. The lot size shall be the number of palletized unit loads in the inspection lot. The inspection level shall be S-1 and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 6.5.

Examine	Defect
Finished dimensions	Length, width, or height exceeds specified maximum requirements.
Palletization	Pallet pattern not as specified. Interlocking of loads not as specified. Load not bonded with required straps as specified.
Weight	Exceeds maximum load limits.
Marking	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application

5. PACKAGING

5.1 Preservation. Preservation shall be levels A or C as specified (see 6.2).

5.1.1 Level A.

5.1.1.1 Unit packaging. The neckband of each scarf shall be fastened and the scarf laid out flat with the label on the outside, a sheet of tissue paper approximately 17 inches by 8 inches shall be laid over the bib portion of the scarf and the scarf folded over the tissue in thirds, beginning with the bib end. The folded scarf approximately 9 inches by 7 inches shall then be rolled with the label on the outside and placed in a snug-fitting, transparent tubular polyethylene bag. The polyethylene film shall be a minimum of .002 inch thick. All seams and closures shall be affected by heat sealing. Prior to or during the heat sealing closure operation excess air within the bag shall be expelled.

5.1.1.2 Intermediate package. Sixteen scarfs, of one type, prepared as specified in 5.1.1.1, shall be packaged in a snug-fitting, set-up paperboard box conforming to type I, variety 1, class A, style 4 of PPP-B-676. Box closure shall be in accordance with the appendix of the container specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T22:07Z
Check the source to verify that this is the current version before use.

5.1.2 Level C. Scarfs shall be packaged to afford adequate protection against deterioration and damage during shipment from the supply source to the first receiving station. The supplier may use his standard practice when it meets these requirements.

5.2 Packing. Packing shall be level A, B or C, as specified (see 6.2).

5.2.1 Level A. Scarfs preserved as specified in 5.1, shall be packed in a snug-fitting shipping container conforming to class 2, style 4 of PPP-B-621 or overseas type, style optional of PPP-B-601. Closure and reinforcement shall be in accordance with the appendix of the applicable container specification.

5.2.2 Level B. Scarfs preserved as specified in 5.1, shall be packed in a snug-fitting fiberboard box conforming to style RSC, type CF or SF, class domestic, grade 275 of PPP-B-636. Closure shall be in accordance with method II of the appendix of the container specification. The weight of the contents of each shipping container shall not exceed the size and weight limitations of the container specification.

5.2.3 Level C. Scarfs, preserved as specified in 5.1, shall be packed in a manner to insure carrier acceptance and safe delivery at destination at the lowest transportation rates for such supplies. Containers shall be in accordance with the rules and regulations of carriers applicable to the mode of transportation.

5.3 Marking. In addition to any special marking required by the contract or order, intermediate packages and shipping containers shall be marked in accordance with MIL-STD-129.

5.3.1 Marking for Cleaning. Scarf shall be marked with cleaning instructions as required by 3.5.

5.4 Palletization. Unitized loads, commensurate with the level of packing specified in the contract or order, shall be palletized in accordance with MIL-STD-147. Palletized loads shall be uniform in size and quantities to the greatest extent possible. If the container is of a size which does not conform to any of the pallet patterns specified in MIL-STD-147, the pallet pattern used shall first be approved by the contracting officer.

6. NOTES

6.1 Intended use. Scarfs covered by this specification are intended to be worn with class A uniforms to designate the wearer is assigned to a specific department or branch of service. Type I, scarfs are intended for use by the Army and type II, scarfs are intended for use by the Air Force.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T22:07Z
Check the source to verify that this is the current version before use.

6.2 Ordering data.

6.2./ Ordering data. Procurement documents should specify the following:

(a) Type and Class (see 1.2)
(b) Title, date and number of this specification.
(c) When a standard sample will not be furnished (see 3.1).
(d) When a first article is not required (see 3.2).
(e) Marking information to appear on scarf label. (see 3.5).
(f) Selection of applicable levels of packaging and packing (see 5.1 and 5.2).

6.3 The following is a list of users according to class and color 1/

Class 1	(Black)	- Chaplains Corps, US Army
Class 2	(Bottle Green)	- Special Forces and Psychological Operations Units, US Army
Class 3	(Brick Red)	- Transportation Units, US Army
Class 4	(Buff)	- Supply, Quartermaster, Supply and Services, Supply and Transportation and Support Units, US Army and Coast Guard
Class 5	(Cobalt Blue)	- Chemical Units, US Army
Class 6	(Crimson)	- Ordnance and Maintenance Units, US Army
Class 7	(Dark Blue)	- National Guard Bureau and Judge Advocate General, Adjutant General, Inspector General Units, US Army and Coast Guard
Class 8	(Green)	- Staff Specialist and Military Police Units, US Army
Class 9	(Light Blue)	- Infantry Units, US Army
Class 10	(Maroon)	- Medical Units, US Army
Class 11	(Old Gold)	- Women's Army Corps
Class 12	(Orange)	- Signal Units, US Army
Class 13	(Oriental Blue)	- Military Intelligence Units, US Army
Class 14	(Purple)	- Civil Affairs Units, US Army
Class 15	(Scarlet)	- Engineers and Artillery Units, US Army and Permanent Professors, USMA
Class 16	(Silver Gray)	- Finance Units, US Army
Class 17	(Teal Blue)	- Branch Unassigned, US Army
Class 18	(Ultramarine Blue)	- US Air Force and Aviation Units, US Army
Class 19	(Yellow)	- Armor and Cavalry, Units, US Army
Class 20	(White)	- Security Police, US Air Force and Coast Guard
Class 21	(Camouflage)	- US Army and US Air Force

1/ Warrant Officers of the US Army will wear the scarf of the branch to which assigned.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T22:07Z
Check the source to verify that this is the current version before use.

6.4 Samples. For access to samples, address the contracting activity issuing the invitation for bids.

6.5 First article. When a first article inspection is required, the item should be a first article sample, or it may be a standard production item from the contractor's current inventory as specified in 4.2. The first article should consist of completed scarf. The contracting officer should include specific instructions in acquisition documents regarding arrangements for examinations, approval of first article test results and disposition of first articles. Invitations for bids should provide that the Government reserves the right to waive the requirement for samples for first article inspection to those bidders offering a product which has been previously acquired or tested by the Government, and that bidders offering such products, who wish to rely on such production or test, must furnish evidence with the bid that prior Government approval is presently appropriate for the pending contract.

6.6 Changes from previous issue. Asterisks or vertical lines are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodians:
Army - IH
Air Force - 11
Navy - NU

Review activities:
Air Force - 82, 99
Other - CT

Preparing activity:
Army - IH

(Project No. 8455 - 0187)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T22:07Z
Check the source to verify that this is the current version before use.

STANDA IZATION DOCUMENT IMPROVEM T PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-S-11922E	Scarf, Branch of Service, Bib Type

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
	☐ USER
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T22:07Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T22:07Z
Check the source to verify that this is the current version before use.