MIL-I-11873C
19 November 1965
SUPERSEDING
MIL-I-11873B
14 December 1959

MILITARY SPECIFICATION

IMPREGNATING SET, CLOTHING, FIELD, M3

This specification is mandatory for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers one type of set for impregnating clothing in the field.

2. APPLICABLE DOCUMENTS

2.1 Government documents. The following documents of the issue in effect on the date of invitation for bids or request for proposal form a part of this specification to the extent specified herein:

SPECIFICATIONS

MILITARY

MIL-I-285	-	Impregnite, Unstabilized (CC2) and Stabilized (XXCC3).
MIL-C-429	-	Chlorinated Paraffin, Technical.
MIL-D-51207	-	Dye Mix, Olive Drab, Impregnating.

STANDARDS

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	-	Marking for Shipment and Storage.

DRAWINGS

EDGEWOOD ARSENAL

DL5-57-29	-	Impregnating Set, Clothing, Field, M3. (All drawings referenced in this specification are listed on this drawing.)

FSC 4230

Source: https://assist.dla.mil -- Downloaded: 202610-17T22:05Z
Check the source to verify that this is the current version before use.

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following document forms a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

UNIFORM CLASSIFICATION COMMITTEE

Uniform Freight Classification Ratings, Rules and Regulations.

(Application for copies of these freight classification rules should be addressed to the Uniform Classification Committee, 202 Union Station, Chicago 6, Illinois.)

3. REQUIREMENTS

3.1 Materials and components.

3.1.1 Materials. All materials cited on Drawing DL5-57-29 or on subsidiary drawings shall conform to the specifications listed thereon or the specific characteristics set forth on the drawings.

3.1.2 Components. All components of the item shall conform to the specifications and the drawings listed on Drawing DL5-57-29 and subsidiary drawings.

3.2 Manufacture and assembly. The impregnating set shall be manufactured and assembled as specified on Drawing D5-57-29.

3.3 Containers.

3.3.1 Contents. The contents of the numbered containers shall conform to table I.

Table I. Container content

Container No.	1	2	3	4
Content	Santomerse 85	Chlorinated paraffin	Impregnite XXCC3	Dye mix
Net weight (lbs)	1.65 ± 0.1	4.33 ± 0.2	16.5 ± 0.4	1.00 ± 0.05
Specification	Commercial product (see 6.4)	MIL-C-429 type I	MIL-I-285 type II	MIL-D-51207

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T22:05Z
Check the source to verify that this is the current version before use.

3.3.2 Leakage. The filled and sealed containers (except No. 3) shall show no leakage when tested as specified in 4.6.

3.4 Preproduction. When specified in the contract or order, a preproduction sample shall be produced for examination and test. The preproduction sample shall be manufactured using the same materials, methods and equipment as will be used during regular production (see 6.2).

3.5 Workmanship. The impregnating set shall be free from foreign matter, such as dirt, oily or viscous materials, and of damage, such as breaks, cracks, or separations in the box, or dents or deformations in the containers.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Special provisions.

4.2.1 Alternative inspection. The supplier may utilize any alternative inspection procedure which will provide equal or better assurance of quality by submitting a written proposal with justification and obtaining written approval from the Government prior to instituting the procedure. In case of dispute, the procedures of this specification will govern.

4.2.2 Objective evidence. The supplier shall provide objective evidence acceptable to the contracting officer that the requirements of 3.1 and section 5 for which specific inspection has not been provided in this specification have been satisfied.

4.3 Lotting. A lot shall consist of the sets produced by one manufacturer, at one plant, from the same materials, under essentially the same manufacturing conditions. However, no more than one lot of Santomerse 85, impregnite XXCC3, chlorinated paraffin or dye shall be represented in any one lot of finished sets.

4.4 Sampling for examination and nondestructive tests. Sampling shall be conducted in accordance with MIL-STD-105.

Source: https://assist.dla.mil -- Downloaded: 20261O-17T22:05Z
Check the source to verify that this is the current version before use.

4.5 Inspection provisions.

4.5.1 Examination and nondestructive tests. Sample sets shall be examined and tested in accordance with the classification of defects and MIL-STD-105.

4.5.2 Classification of defects.

4.5.2.1 Containers 1, 2, 3, and 4 (Dwgs D5-57-30, D5-57-31, and D5-57-32).

Categories	Defects	Acceptance standards
Critical:	None defined	
Major:	AQL 1.0 percent defective	
101	Weight of contents incorrect	
102	Marking incorrect	
103	Workmanship (3.5)	
Major A:	AQL 0.65 percent defective	
150	Container leakage (except No. 3)	4.6
Minor:	AQL 2.5 percent defective	
201	Marking missing	

4.5.2.2 Impregnating set, clothing, field, M3 (Dwg D5-57-29).

Categories	Defects
Critical:	None defined
Major:	AQL 1.0 percent defective
101	Component missing
102	Instruction card missing
103	Workmanship (3.5)
104	Marking incorrect
Minor:	AQL 2.5 percent defective
201	Loose pack
202	Straps loose or missing
203	Marking missing
204	Marking illegible

Source: https://assist.dla.mil -- Downloaded: 20261O-17T22:05Z
Check the source to verify that this is the current version before use.

4.6 Leakage test. The filled and sealed container shall be submerged 2 ± 1/4 inches below the surface of water maintained at 85° ± 5°C for 30 + 5 seconds and observed for bubbles.

5. PREPARATION FOR DELIVERY

5.1 Packaging and packing. The impregnating lot manufactured and assembled as specified in 3.2 requires no further packaging and packing.

5.2 Marking. In addition to any special marking required by the contract or order, unit packages and shipping containers shall be marked in accordance with MIL-STD-129. The fiber drum (container No. 3) and the nailed wood box shall be marked in 2-inch letters with the following: "DO NOT STORE OVER 120°F." On the drums, this marking shall be placed approximately 4 inches above the regular marking and also diametrically opposite on the other side of the drum. Each container shall also have the following precautionary markings: "KEEP AWAY FROM OPEN FIRES AND ALL HEATED SURFACES: AVOID INHALATION OF FUMES." Such markings shall not interfere with or obscure other markings on the containers.

6. NOTES

6.1 Intended use. This specification covers an impregnating set for emergency impregnation of protective clothing.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Whether a preproduction sample is required.
(1) Quantity required.
(2) Time allowed for supplier submission of samples for Government test and evaluation after award of contract.
(3) Name and address of test facility and shipping instructions when testing is performed by the Government.
(4) Time required for the Government to notify the supplier whether or not to proceed with production.

6.3 Precautions. Impregnite (XXCC3), which is a mixture of finely ground impregnite (CC2) and zinc oxide is flammable; therefore, necessary precautions should be taken for the protection of personnel.

Source: https://assist.dla.mil -- Downloaded: 202610-17T22:05Z
Check the source to verify that this is the current version before use.

6.4 Santomerse 85. This product may be procured from the Monsanto Chemical Company, St. Louis, Missouri.

Custodians:

Army - MU
Navy - YD
Air Force - 84

Review activities:

Navy - YD
Air Force - 84

User activities:

Army - GL
Navy - MC

Preparing activity:

Army - MU (EA)

Project No 4230-0024

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T22:05Z
Check the source to verify that this is the current version before use.