21 August 1972
SUPERSEDING
MIL-C-45404(Ord)
Change Notice 3
4 May 1964

MILITARY SPECIFICATION

CLIP, CARTRIDGE, 7.62MM, 5-ROUND

1. SCOPE

1.1 This specification covers one type of five round cartridge clip for use with the M14, 7.62MM Rifle.

2. APPLICABLE DOCUMENTS

* 2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

Military

MIL-P-116	-	Preservation, Methods of.
MIL-W-3688	-	Wax Emulsion (Rust Inhibiting).
MIL-W-13855	-	Weapons: Small Arms and Aircraft Armament Subsystem, General Specification for.
MIL-I-45607	-	Inspection Equipment, Acquisition, Maintenance and Disposition of.

STANDARDS

Military

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-109	-	Quality Assurance Terms and Definitions.
MIL-STD-171	-	Finishing of Metal and Wood Surfaces.

DRAWINGS

U.S. Army Weapons Command

B7790130	-	Clip, Cartridge, 7.62MM, 5-Round.

(Product drawings referenced in this specification form a part of B7790130.)

FSC 1305

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:54Z
Check the source to verify that this is the current version before use.

PUBLICATIONS

U.S. Army Weapons Command

P7790130 - Packaging Data Sheet for Clip, Cartridge, 7.62MM, 5-Round.

IEL7790130 - Index of Inspection Equipment List.

(Acceptance Inspection Drawings referenced in this specification form a part of IEL7790130.)

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

* 2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

American Society for Testing and Material

ASTM E18 - Test for Rockwell Hardness of Metallic Materials.

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, Pennsylvania 19103.)

3. REQUIREMENTS

* 3.1 First article. Requirements for submission of first article shall be as specified in the contract (see 6.1). Unless otherwise specified (see 6.1) the first article shall include the pilot pack (see 5.1).

* 3.2 Material, construction and design. Clips shall conform to material, construction and design requirements specified herein, on Drawing B7790130 and drawings applicable thereto, and be in accordance with the applicable material, construction and design provisions of MIL-W-13855.

* 3.2.1 Heat treatment. The spring shall be heat treated to produce a hardness within the hardness range specified on D7790131.

* 3.2.2 Assembleability. The spring shall be readily assembled to the shoe and retained in the shoe by the spring action of the tabs in the tab holes of the shoe. The spring shall not disassemble from the shoe unless the tabs on the spring are depressed.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:54Z
Check the source to verify that this is the current version before use.

* 3.2.3 Cartridge retention load. The load required to strip one end Government-standard 7.62mm cartridge from a fully loaded clip shall not be less than 1.8 pounds or greater than 4.7 pounds. Testing shall be as specified in 4.5.3.4.

* 3.3 Protective finish. The clips shall be coated with finish number 5.3.1.2 or 5.3.2.2 of MIL-STD-171 except with a supplementary wax coating in accordance with MIL-W-3688.

* 3.3.1 Supplementary wax coating. The weight of the supplementary wax coating shall be 10 milligrams (mg) ± 3 mg. Testing shall be as specified in 4.5.3.2.2.

3.4 Marking. The clips shall be clearly marked in accordance with the drawings and MIL-W-13855.

3.5 Workmanship. Workmanship shall be in accordance with the workmanship provisions of MIL-W-13855.

4. QUALITY ASSURANCE PROVISIONS

* 4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification when such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

* 4.2 Quality assurance terms and definitions. Quality assurance terms and definitions used herein are in accordance with MIL-STD-109.

* 4.3 Classification of inspection. The inspection requirements specified herein are classified as follows:

a. First article inspection 4.4.
b. Quality conformance inspection 4.5.

* 4.4 First article inspection. The first article shall be selected from the first inspection lot and submitted for inspection in accordance with the contract requirements. The first article shall be representative of the production processes to be used during quantity production. The first article shall be subjected to the quality conformance inspection specified herein and such other inspection as is necessary to determine compliance with the requirements of the contract.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:54Z
Check the source to verify that this is the current version before use.

* 4.5 Quality conformance inspection.

* 4.5.1 Inspection lot. Unless otherwise specified, the formation, size and presentation of inspection lots and applicable samples shall be in accordance with MIL-STD-105. Inspection lots shall not exceed 500,000 clips per lot. Lots shall be from the same heat of steel and within the limitations of MIL-W-13855.

* 4.5.1.1 Heat treat lot. The heat treat lot shall be limited to one heat of steel and shall consist of springs, heat treated in a batch type furnace at one charge or in a continuous type furnace during an uninterrupted period extending over not more than one eight hour shift.

4.5.2 Examination. Examination of clips and packaging shall be as specified herein and in accordance with the applicable examination provisions of MIL-W-13855.

* 4.5.2.1 Classification of defects. Classification of defects and acceptable quality levels (AQL's) for examination in accordance with MIL-STD-105 shall be as specified herein and shall include the following provisions.

a. Unless otherwise specified, AQL's apply to each listed defect.
b. Where a Government drawing is listed as the method of inspection, the contractor shall use inspection equipment fabricated in accordance with the applicable drawings. In the event the contractor desires to use alternate equipment which equals or exceeds the accuracy requirements of the specified drawing, it shall be submitted to the Government representative for approval.
c. Where "Visual" is specified as the method of inspection of protective coating, the coating must be complete, uniform in color, free from pits, corrosion, scratches and worn or bare spots.
d. Where SME (Standard Measuring Equipment) is specified as the method of inspection, the contractor may use any type of industry developed, commercially available, multi-usage equipment or special inspection equipment approved by the Government.
e. Where "Visual-Manual" is specified as the method of dimensional inspection, the characteristic should be visually inspected for completeness and manually operated functioning requirements specified on the applicable drawing.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:54Z
Check the source to verify that this is the current version before use.

* 4.5.2.1.1 Clip, Cartridge, 7.62MM, 5-Round (Drawing B7790130).

Categories	Defect	AQL	Inspection Method
Critical:	None defined.		
Major:			
101	Improper edges of cartridge guide lips.	0.65	Visual
102	Improper assembly and disassembly of parts (see 3.2.2).	0.65	Visual-Manual
103	Assembleability of cartridge clip to cartridge guide.	0.65	7271613
104	Assembleability of cartridge to cartridge clip.	0.65	7271612
105	Location of end from stop nib	1.0	7271682
Minor:			
201	Missing or defective protective coating.	2.5	Visual
202	Improper height and distance between stiffening ribs.	2.5	SME
203	Improper radius of shoe	2.5	SME
204	Missing or improper marking.	4.0	Visual
205	Workmanship	4.0	Visual

* 4.5.2.1.2 Packaging. Unless otherwise specified in each listed defect, the packaging requirements are specified on Packaging Data Sheet P7190130 (see 5.2).

Categories	Defect	AQL
Critical:	None defined.	
Major:		
101	Improper level of packaging and packing (see procurement documents).	1.0
102	Incorrect or illegible marking.	1.0
103	Missing or improper VCI liners.	1.0
104	Inadequate cleaning and drying.	1.0
105	Improper preservation application and drainage.	1.5
106	Improper containers.	1.5
107	Container interior contaminated with dirt, lint, or other foreign matter.	1.5
108	Improper closure of unit packages and shipping containers.	1.5
109	Incorrect quantity of clips per unit package	1.5
Minor:		
201	Workmanship	4.0

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:54Z
Check the source to verify that this is the current version before use.

4.5.3 Testing.

4.5.3.1 Material testing. Tests required by applicable drawings and specifications shall be performed on materials used in the manufacture of clips. The contractor shall furnish the Government representative with certified statements of findings of chemical analyses and reports of physical tests as may be required for each lot of each material used. The contractor shall also furnish the Government representative with certification that the materials used in packaging conform to the applicable specifications.

* 4.5.3.2 Protective finish testing.

4.5.3.2.1 Accelerated corrosion testing. Accelerated corrosion testing shall be in accordance with applicable drawings and specifications.

* 4.5.3.2.2 Supplementary wax coating weight. A sample of 10 clips with supplementary wax coating shall be taken from each shift's production from each production machine and tested for supplementary wax coating weight using the test method specified in 4.6.1. Failure of clips to meet the specified supplementary wax coating weight requirements shall cause rejection of the represented lot.

* 4.5.3.3 Hardness testing. Samples of springs shall be taken from each heat treat lot in accordance with MIL-STD-105, using inspection level S-4 and tested for hardness using the test method specified in 4.6.2. Acceptance shall be based on an AQL of 0.40 percent defective.

* 4.5.3.4 Cartridge retention load testing. Sample clips shall be taken from each inspection lot in accordance with MIL-STD-105, size code letter "L" regardless of the quantity in the inspection lot, and tested for cartridge retention load using the test method specified in 4.6.3. Acceptance shall be based on an AQL of 0.40 percent defective.

4.5.4 Inspection equipment.

* 4.5.4.1 Acquisition, maintenance and disposition. Unless otherwise specified, responsibility for acquisition, maintenance and disposition of acceptance inspection and test equipment prescribed on the List of Inspection Equipment IEL7190130 and for all other inspection equipment required to perform inspection prescribed by applicable specifications shall be in accordance with MIL-I-45607.

* 4.5.4.2 Accuracy of standard measuring equipment. When commercial and modified commercial inspection and test equipment is used, it must be capable of repetitive measurements to an accuracy of 10% of the total tolerance of the characteristic being inspected.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:54Z
Check the source to verify that this is the current version before use.

4.6 Test methods.

* 4.6.1 Supplementary wax coating weight test. The sample clips shall be tested by weighing the clips together to the nearest mg. The supplementary wax coating shall then be completely removed from the clips by trichoroethylene vapor degreasing, and the clips dried and re-weighed. The difference between the total weight before and after divided by the number of clips tested shall be considered as the weight of the supplementary wax coating of each clip.

* 4.6.2 Hardness test. The sample clips shall be tested using ASTM Method E18.

4.6.3 Cartridge retention load test, The sample clips shall be tested using the inspection equipment in accordance with F7271742. The clips shall be loaded with 5 Government standard 7.62mm cartridges and then inserted in the test fixture. A load shall then be gradually applied to the cartridge at one end of the clip until the cartridge at the opposite end is stripped from the clip. The maximum load required to strip the end cartridge from each clip tested shall be recorded to determine compliance with the requirements of 3.2.3. The dummy cartridges shall not be used more than 50 times. Clips subjected to this test shall be either reconditioned by replacing the spring and refinishing as necessary or scrapped.

5. PREPARATION FOR DELIVERY

* 5.1 Pilot pack. A pilot pack shall be forwarded in accordance with the contract (see 6.1). Pilot packs shall be packaged to the level of packaging specified in the contract and packed level C in accordance with the requirements of Packaging Data Sheet P7790130.

* 5.2 Preparation for delivery shall be in accordance with Packaging Data Sheet P7790130 using the levels of preservation, packaging, and packing specified in the contract (see 6.1).

6. NOTES

6.1 Ordering data. Procurement documents should specify:

* 6.1.1 Procurement requirements.

a. Title, number and date of this specification.
b. List of drawings and specifications pertinent to the clip, showing applicable revision dates.
c. Requirements for submission of first article samples by the contractor (see 3.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:54Z
Check the source to verify that this is the current version before use.

d. Index of Inspection Equipment List pertinent to the clip, showing applicable revision dates.
e. Responsibilities for acquisition, maintenance and disposition of acceptance inspection equipment if other than specified (see 4.5.4.1).
f. Responsibility for furnishing dummy cartridges.
g. Requirements for submission of pilot pack (see 3.1 and 5.1).
h. Selection of applicable levels of preservation, packaging and packing (see 5.2).
i. Disposition instruction for link test samples.

* 6.1.2 Contract data requirements. The requirements for the records of examination and all tests will be listed directly on a DD Form 1423 incorporated into the contract.

* 6.1.3 Management control systems requirement. When warranted the contract should specify the application of MIL-I-45208 on Management Control Systems Summary List, DD Form 1660.

* 6.1.4 Unless otherwise specified (see 6.1.1 e), the contract should specify the application of MIL-I-45607 and MIL-C-45662 on the Management Control Systems Summary List, DD Form 1660.

* 6.2 When action by a testing agency is required, work programming will be effected with the testing agency at the earliest practicable date.

* 6.3 The margins of this specification are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodian:
Army - WC

Preparing Activity:
Army - WC

Review Activity:
Army - MU

Project Number:
1305-A634

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:54Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?
   A. GIVE PARAGRAPH NUMBER AND WORDING.

   B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

   ☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426 REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

S/N 0102-014-1802

☆ U.S. GOVERNMENT PRINTING OFFICE: 1973—714-866/3983 2-1

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:54Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID



OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

Commander
Rock Island Arsenal
ATTN: SARRI-LE-S
Rock Island, IL 61201

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:54Z
Check the source to verify that this is the current version before use.