MIL-F-45400A(MU)
30 July 1968
SUPERSEDING
MIL-F-45400 (CmlC)
8 June 1959

MILITARY SPECIFICATION

FIN ASSEMBLY, BOMB, 4-POUND, M15

1. SCOPE

1.1 This specification covers an extensible fin for use with a 4-pound incendiary bomb.

2. APPLICABLE DOCUMENTS

2.1 Government documents. The following documents, of the issue in effect on date of invitation for bids, form a part of this specification:

SPECIFICATIONS

FEDERAL

UU-P-268	-	Paper, Kraft, Untreated, Wrapping.
MMM-A-250	-	Adhesive, Water-Resistant, For Sealing Fiberboard Boxes.
PPP-T-76	-	Tape, Pressure Sensitive Adhesive Paper, Water Resistant, For Carton Sealing.

STANDARDS

MILITARY

MIL-STD-10	-	Surface Roughness, Waviness and Lay.
MIL-STD-105	-	Sampling Procedures and Tables for Inspections by Attributes.
MIL-STD-129	-	Marking for Shipment and Storage.

DRAWINGS

US ARMY MUNITIONS COMMAND

EDGEWOOD ARSENAL

D14-5-3020 - Fin, 4-Lb. Bomb, M15, Bill of Material.

Source: https://assist.dla.mil -- Downloaded: 202610-22T02:54Z
Check the source to verify that this is the current version before use.

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following document forms a part of this specification. Unless otherwise indicated, the issue in effect on date of invitation for bids shall apply.

UNIFORM CLASSIFICATION COMMITTEE

Uniform Freight Classification

(Application for copies of these ratings, rules and regulations should be addressed to Uniform Classification Committee, 202 Union Station, 516 West Jackson Boulevard, Chicago, Illinois 60606.)

3. REQUIREMENTS

3.1 Materials and components.

3.1.1 Materials. All materials cited on Drawing D14-5-3020 or on the subsidiary drawings shall conform to the specifications listed thereon, or to the specific characteristics set forth on the drawings.

3.1.2 Components. All components of the fin shall conform to the specifications and drawings listed on Drawing D14-5-3020 and subsidiary drawings.

3.2 Assembly. The fin shall be assembled as specified on Drawing C14-5-3021.

3.3 Surface roughness. Surface roughness, specified by symbol on detail drawings, shall comply with MIL-STD-10.

3.4 Preproduction. Prior to the start of regular production, a preproduction lot of fins shall be produced in accordance with this specification for examination (see 4.3 and 6.1).

3.5 Workmanship. The fin shall be free of all foreign matter (oil, grease, etc.) and damage such as dents, cracks, and deformation which could affect its use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:54Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.

4.1.1 Supplier's responsibility. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to specified requirements.

4.1.2 Objective evidence. The supplier shall provide objective evidence acceptable to the contracting officer that the requirements of 3.1 and section 5 for which specific inspection has not been provided in this specification have been statisfied.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

(a) Preproduction inspection (see 4.3).
(b) Quality conformance inspection (see 4.4).

4.3 Preproduction inspection.

4.3.1 Sample. A preproduction sample of 500 fins shall be manufactured using the same methods, materials, equipment, and processes as will be used during regular production.

4.3.2 Inspection procedure.

4.3.2.1 For examination. Three-hundred fins shall be taken at random from the preproduction sample, and examined for conformance with the drawings and specifications thereon.

4.3.2.2 Acceptance/rejection criteria. The preproduction samples, when examined, must meet the requirements of this specification to be acceptable. The acceptance number is zero. The supplier shall obtain written approval from the contracting officer prior to proceeding with regular production.

Source: https://assist.dla.mil -- Downloaded: 20261O-22T02:54Z
Check the source to verify that this is the currentversion before use.

4.4 Quality conformance inspection.

4.4.1 Lotting. A lot shall consist of fins of one interfix number produced during one week, by one manufacturer, from the same materials, from the same drawings, under essentially the same manufacturing conditions.

4.4.2 Sampling.

4.4.2.1 For examination. Sampling shall be conducted in accordance with MIL-STD-105.

4.4.3 Inspection procedure.

4.4.3.1 For examination. Sample fins shall be examined in accordance with the classification of defects and MIL-STD-105.

4.4.3.2 Classification of defects. (See inspection data list IDL 14-5-3021 for inspection equipment required to perform the examinations specified in this section.)

(a) Fin, 4-Pound bomb, M15, assembly (Drawing C14-5-3021).

Categories		Defects
Critical:		None defined
Major:	AQL 0.25 percent defective	
**101		Inoperative
*102		Component missing, incorrect or incorrectly assembled
103		Overall length incorrect (body)
*104		Staking or welding (when applicable) incorrect
105		Safety plunger head incorrectly formed
*106		Graphite coating missing
107		Length (3.153) incorrect
108		Safety plunger hole size or location incorrect
109		Tail curl incorrect
110		Inside distance across flats incorrect
111		Workmanship (3.5)

Source: https://assist.dla.mil -- Downloaded: 202610-22T02:54Z
Check the source to verify that this is the current version before use.

4.4.3.2 Classification of defects (continued).

(a) Fin, 4-Pound bomb, M15, assembly (Drawing C14-5-3021) (continued).

Categories	Defects
Minor:	AQL 2.5 percent defective
*201	Protective finish missing

*Components which are not accessible upon final assembly shall be inspected prior to final assembly.

**The fin assembly is inoperative if the fins fail to retract when the shaft is depressed into the body or if the fins fail to spring out upon release of the shaft. Any jamming, hesitation, or irregularity of operation of the fin assembly, or hesitancy or slowness of the fins to extend upon release of the depressed shaft shall constitute an inoperative defect.

5. PREPARATION FOR DELIVERY

5.1 Packaging, level C. The fin assembly, Drawing C14-5-3021, with the fins retracted, shall have a preformed paper seamed or seamless tube placed over the fins. The tube shall be a minimum of 2-1/2-inches long and fabricated from 60-pound minimum base weight Kraft paper conforming to grade B of UU-P-268. The seamed tube shall be closed with a minimum 3/4-inch wide seam using adhesive conforming to MMM-A-250. As an alternate the fins, in retracted position, shall be wrapped with Kraft paper, same as used in tube, and secured in place with pressure-sensitive tape conforming to PPP-T-76. The minimum length of the wrap shall be 2-1/2-inches.

5.2 Packing, level C. A uniform number of fin assemblies, packaged as specified in 5.1, shall be packed to afford protection against damage during direct shipment from the supply source to the first receiving activity for immediate use. Containers used shall comply with Uniform Freight Classification Rules or other common carrier regulations applicable to the mode of transportation.

5.3 Marking. In addition to any special marking required by the contract or order, shipping containers shall be marked in accordance with MIL-STD-129.

Source: https://assist.dla.mil -- Downloaded: 202610-22T02:54Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Special marking required.
(c) Preproduction.

(1) Time allowed for supplier submission of samples for Government test and evaluation after award of contract.
(2) Name and address of test facility and shipping instructions when testing is performed by the Government.
(3) Time required for the Government to notify the supplier whether or not to proceed with production.

Custodian:

Army - MU

Preparing activity:

Army - MU(EA)

Project No. 1325-A311

Source: https://assist.dla.mil -- Downloaded: 202610-22T02:54Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?
   A. GIVE PARAGRAPH NUMBER AND WORDING.

   B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

   ☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426 REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

S/N 0102-014-1802

☆ U.S. GOVERNMENT PRINTING OFFICE: 1973—714-866/3983 2-1

Source: https://assist.dla.mil -- Downloaded: 202610-22T02:54Z
Check the source to verify that this is the currentversion before use.

FOLD

POSTAGE AND FEES PAID

U.S.MAIL

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

Commander
Frankford Arsenal
ATTN: SARFA-MDM
Philadelphia, PA. 19137

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:54Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:54Z
Check the source to verify that this is the current version before use.