MILITARY SPECIFICATION

MINE, AT, M21
LOADING, ASSEMBLING, AND PACKING

This Specification is approved for use within the U.S. Army Armament Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers quality assurance provisions and preparation for delivery for the loading and assembling of Mine, AT: M21.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. The following specifications and standards form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DoDISS) and supplement thereto, listed in the solicitation.

SPECIFICATIONS

MILITARY

MIL-P-116	Preservation, Methods of.
MIL-P-223	Powder, Black.
MIL-A-13812	Armor, Steel; Plate, Wrought, Homogeneous; For Ammunition Testing.
MIL-P-20444	Primer M42.
MIL-A-48078	Ammunition, Standard Quality Assurance Provisions, General Specification For.

Beneficial comments (recommendations additions deletions) and any pertinent data which may be of use in improving this document should be addressed to Commander, U S Army Armament Research, Development and Engineering Center Attn AMSMC-QA, Dover New Jersey 07801-5001 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter

AMSC N/A
FSC 1345
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:54Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-SRTD-105 - Sampling Procedures and Tables for Inspection by Attributes.

(Copies of specifications, standards drawings, publications and other Government documents required by the suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the Contracting Officer.)

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

DRAWINGS

US ARMY ARMAMENT RESEARCH AND DEVELOPMENT CENTER

8830860 - Box, Wire-bound, Packing, Ammunition for Mine, AT, M21 with Fuze, Mine, AT, M607.
8831342 Mine, AT, M21, Loading assembly.

PUBLICATIONS

Title 45 CFR-100-199 - Interstate Commerce Commission Rules and Regulations for the Transportation of Explosive and Other Dangerous Article.

(The Code of Federal Regulations is available from the Superintendent of Documents, US Government Printing Office, Washington, DC 20402. Orders should specify “49 CFR 100-199” (latest revision) “.)

2.2 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Material. Materials and parts shall be in accordance with applicable drawings, specifications and standards.

3.2 Loading assembly. The loading assembly shall comply with all requirements specified on Drawing (Dwg.) 8831342, all associated drawings and with all requirements specified in applicable specifications and standards.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:54Z
Check the source to verify that this is the current version before use.

3.3 Moisture content of black powder. Moisture content of black powder, at the loading station, at the time of loading the propellant cup assembly, shall be as specified in MIL-P-223 when tested as specified in 4.5.2.

3.4 Specific gravity of explosive charge. The minimum specific gravity of the bursting charge shall be 1.69 when tested as specified in 4.5.4.

3.5 Waterproofness of cup assembly. The cup assembly shall withstand a pressure of 5 pounds per square inch gauge (psig) for a period of 15 seconds minimum without evidence of leakage when tested as specified in 4.5.1.

3.6 Delay assembly functioning . The delay assembly shall function high order as evidenced by causing a perforation in a lead disc which shall be not less than 0.25 inch in diameter and have a delay time as specified on Dwg. 8831348 when tested as specified in 4.5.3.

3.7 Mine functioning. The mine shall function satisfactorily by perforating three-inch armor plate at a standoff distance of 21 inches. {see 6.4). The sum of the major and minor diameters of the penetration, as measured at the throat, and 90 degrees apart, shall be not less than 6 inches. (see 6.5). The test shall be performed as specified in 4.5.5.

3.8 First article inspection. This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

3.9 Workmanship. All parts and assemblies shall be fabricated and loaded in a thorough workmanlike manner and all manufacturing, processing, and assembly operations shall be correctly performed. They shall be clean and free of cracks, gouges, burrs, sharp edges, unblended radii, surface defects, chips, dirt, grease and oil (except where specifically required), corrosion products and other foreign matter. The cleaning method used shall not be injurious to any part or assembly, nor shall they be contaminated by the cleaning agents. Exterior surface coatings shall be continuous except for a few light scratches not exposing base material. All required markings shall be neat and sharply defined. All packing shall be dry.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection and standard quality assurance provis ions. Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:54Z
Check the source to verify that this is the current version before use.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection.

b. Quality conformance inspection.

4.3 First article inspection.

4.3.1 Submission. The contractor shall submit a first article sample as designated by the Contracting officer for evaluation in accordance with provisions of 4.3.2. The first article sample shall consist of the following items in sample quantities as indicated below and Table I.

Part Description	Drawings	Quantity
Propellant Cup Assembly	8831345	24
Relay Assembly	8831360	24
Delay Assembly	8831348	24
Loading Assembly, Prior to Assembly of Propellant Cup Assembly and Delay Assembly	8831342	24
Loading Assembly, Prior to Assembly of Shipping Plug and Closing Plug	8831342	24
Loading Assembly	8831342	24

The first article sample shall be evaluated in accordance with the provisions of 4.3.2 and 4.3.3. Unless otherwise directed by the Contracting Offlcer, loaded components shall not be submitted to a Proving Ground for any test until the above assemblies submitted in accordance with this paragraph have been accepted.

4.3.2 Inspections to be performed. See MIL–A-48078 and Table I specified herein. If any items fail to comply with any of the applicable requirements, the first article sample shall be rejected.

4.3.3 Rejection. MIL-A-48078 shall apply with the exception that the first article sample shall be rejected if two (2) or more mines fail the proving ground test. (mine functioning.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:54Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-45405C(AR)

PARAGRAPH	TITLE: Mine, AT: M21		SHEET 1 OF 1		DRAWING NUMBER: See Below
					NEXT HIGHER ASSEMBLY: --
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Propellant Cup Assembly (Dwg. 8831345)				
	Examination for Defects	24		3.2	4.4.2.1
	Waterproofness	(a)		3.5	4.5.1
	Relay Assembly (Dwg. 8831360)				
	Examination for Defects	24		3.2	4.4.2.2
	Delay Assembly (Dwg. 8831348)				
	Examination for Defects	24		3.2	4.4.2.3
	Functioning	(a)		3.6	4.5.3
	Assembly (Dwg. 8831342)				
	Examination for Defects	24		3.2	4.4.2.4 thru 4.4.2.6
	Mine functioning	(a)		3.7	4.5.5

NOTES: a. This test shall be performed on the samples subjected to the examination for defects.

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 202640-22T02:54Z
Check the source to verify that this is the current version before use.

4.4 Ouality Conformance Inspection.

4.4.1 Inspection lot formation. Inspection lots shall comply with the lot formation provisions of MIL-A-48078, In addition, each Inspection lot shall contain:

a. Metal parts assemblies of one lot interfix number from one manufacturer.

b. Boosters of one lot interfix number from one manufacturer.

c. Primers of one lot interfix number from one manufacturer. (See 4.4.5)

d. HBX-6 (H-6) of one lot interfix number from one manufacturer.

e. Black powder of one lot interfix number from one manufacturer.

f. REX of one lot interfix number from one manufacturer.

g. Lead azide of one lot interfix number from one manufacturer.

h. Delay composition of one lot interfix number from one manufacturer.

4.4.2 Examination. See MIL-A-48078.

a. Sampling plans . Unless otherwise specified in the Classification of Defects and Test Tables, sampling plans and procedures for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:54Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-45405C(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.1	Propellant Cup Assembly		8831345
			NEXT HIGHER ASSEMBLY 8831342

CATEGORY	EXAMINATION OR TEST	NO OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Cup or lid cracked or split		100%	3.2	Visual
2	Powder escaping		100%	3.2	Visual
Major					
101	Waterproofness		0.65%	3.5	4.5.1
102	Weight of charge, min.		0.40%	3.2	Balance
103	Height (less boss), max.		0.40%	3.2	Gage
104	Moisture content of black powder	(a)	-	3.3	4.5.2
Minor					
201	Poor workmanship		1.0%	3.9	Visual

NOTES: a. Not less than three (3) samples of black powder from each batch, with a maximum of 6 samples required from each lot, shall be selected for determination of moisture content. If any sample fails to comply with the specified requirement, the batch shall be rejected.

Source: https://assist.dla.mil -- Downloaded: 2026/10-22T02:54Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-45405C(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.2	Relay Assembly				8831360
					NEXT HIGHER ASSEMBLY 8831342
CATEGORY	EXAMINATION OR TEST	NO OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major					
101	Length, max.		0.40%	3.2	Gage
102	Depth to top charge, max.		0.40%	3.2	Gage
103	Cup cracked, split or punctured		0.40%	3.2	Visual
Minor					
201	Poor workmanship		1.0%	3.9	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:54Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-45405C(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.3	Delay Assembly				8831348
					NEXT HIGHER ASSEMBLY 8831342
CATEGORY	EXAMINATION OR TEST	NO OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major					
101	Functioning and burning time		0.65%	3.2/3.6	4.5.3
102	Total length, max.		0.65%	3.2	Gage
103	Primer holder assembly loose or improperly seated		0.40%	3.2	Visual/Manual
104	Relay assembly, primer, or delay composition missing		0.40%	3.2	Visual
105	Relay assembly improperly seated		0.40%	3.2	Visual
Minor					
201	Thread damaged		0.65%	3.2	Visual
202	Primer holder crimp less than 360 degrees		0.65%	3.2	Visual
203	Varnish missing from relay cup in flash hole or from primer holder or primer crimps		0.65%	3.2	Visual
204	Crimp cracked or split		0.65%	3.2	Visual
205	Poor workmanship		1.0%	3.9	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:54Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-45405C(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.4	Loading Assembly (prior to Assembly of Propellant Cup Assembly and Delay Assembly)				8831342
					NEXT HIGHER ASSEMBLY –
CATEGORY	EXAMINATION OR TEST	NO OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major					
101	Firing pin assembly damaged		0.40%	3.2	Visual
102	Foreign matter in any cavity		0.40%	3.2	Visual
Minor					
201	Poor workmanship		1.0%	3.9	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:54Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-45405C(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.5	Loading Assembly (prior to Assembly of Shipping Plug and Closing Plug)				8831342
					NEXT HIGHER ASSEMBLY --
CATEGORY	EXAMINATION OR TEST	NO OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major					
101	Delay assembly protruding into booster cavity		0.40%	3.2	Visual
102	Propellant cup assembly missing		0.40%	3.2	Visual
103	Delay assembly missing		0.40%	3.2	Visual
104	Foreign matter in booster cavity or on propellant cup assembly		0.40%	3.2	Visual
Minor					
201	Poor workmanship (excl. 104)		1.0%	3.9	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:54Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-45405C(AR)

PARAGRAPH	TITLE		SHEET 1 OF 2		DRAWING NUMBER
4.4.2.6	Loading Assembly				8831342
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Any break in the chamber for the main charge		100%	3.2	Visual
Major					
101	Shipping plug or closing plug turn when min. torque is applied in tightening direction		0.40%	3.2	Torque Test
102	Charge cap loose		0.40%	3.2	Manual
103	Component missing, including explosive		0.40%	3.2	Visual
104	Assembly damaged (dented or deformed)		0.40%	3.2	Visual
105	Specific gravity of explosive charge	(a)	-	3.4	4.5.4
106	Mine functioning	(b)	-	3.7	4.5.5
	a. Four (4) pre-weighed mines shall be loaded along with normal production during each shift of eight hours. Each of the four mines shall be identified with approximately one quarter of the shift's production and the specific gravity determined. If any test mine fails to meet the specific gravity requirement, that portion of the shift's production which is represented by the failing mine shall be rejected.				
	b. The sampling plan for this test shall use an AQL of 4.00%, Code letter G, double sampling plan. Any mine which fails to comply with the specified requirements shall be classed defective.				
NOTES:					

AMSMC Form 1570, 1 Feb 85 — Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T02:54Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-45405C(AR)

PARAGRAPH	TITLE		SHEET 2 OF 2		DRAWING NUMBER 8831342
4.4.2.6 (Cont'd)	Loading Assembly				NEXT HIGHER ASSEMBLY --
CATEGORY	EXAMINATION OR TEST	NO OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Minor					
201	Handle missing or damaged (torn, frayed or deteriorated)		0.65%	3.2	Visual
202	Protective coating damaged exposing base metal		0.65%	3.2	Visual
203	Marking misleading, unidentifiable or missing		0.65%	3.2	Visual
204	Poor workmanship		1.0%	3.9	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:54Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-45405C(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.7	Box, Packing (prior to closing)				8830860
					NEXT HIGHER ASSEMBLY
					--
CATEGORY	EXAMINATION OR TEST	NO OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major					
101	Arming wrench, mine fuze, booster, extension rod, or mine missing, improperly positioned or improperly secured		0.40%	3.2	Visual/Manual
102	Waterproofness of barrier bag destroyed by rip, tear, puncture, or separation of heat seal		0.40%	3.2	Visual
Minor					
201	Poor workmanship		1.0%	3.9	Visual

NOTES:

AMSC N/A Form 1570, 1 Feb 85 Replaces DESC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:54Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-45405C(AR)

PARAGRAPH	TITLE			SHEET 1 OF 1	DRAWING NUMBER 8830860
4.4.2.8	Box, Packing				NEXT HIGHER ASSEMBLY --
CATEGORY	EXAMINATION OR TEST	NO OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major					
101	Heat seal test	(a)	-	3.2	4.5.6
102	Contents loose when box is tilted (inadequate fillers)		0.40%	3.2	Manual
103	Wire loose or improperly stapled		0.40%	3.2	Visual/Manual
104	Rope handle inadequately secured or missing		0.40%	3.2	Visual
105	DOT marking misleading, unidentifiable or missing		0.40%	3.2	Visual
Minor					
201	Wire loop incorrectly closed		0.65%	3.2	Visual
202	Car seal missing, unsealed, or improperly positioned		0.65%	3.2	Visual
203	Marking misleading, unidentifiable, or missing		0.65%	3.2	Visual
204	Poor workmanship		1.0%	3.9	Visual

NOTES:

a. Sampling acceptance criteria shall be as specified in MIL-P-116.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:54Z
Check the source to verify that this is the current version before use.

4.4.3 Testing. Testing is described in the First Article and Quality Conformance Inspection Tables.

4.4.4 Inspection equipment. The inspection equipment required to perform the inspections and tests prescribed in this specification is identified in the "Paragraph Reference/Inspection Method" column in the tables starting with paragraph 4.4.2.1, and the test method paragraph (See 4.5). Thne contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078 and 6.2 herein.

4.4.5 Check test for deterioration of primers (see MIL-P-20444). If the total time between original acceptance of any primer lot and the assembly of that lot into the delay assembly exceeds two years, or if the primers have been subjected to adverse conditions, however brief, at any time since previous tests, the primer lot shall be subjected to and must satisfactorily pass, the ckeck test for deterioration specified in MIL-P-20444 immediately before the primer lot is assembled into the delay assembly. This test shall be performed by the contractor on primers selected by the Government Inspector at the facility assembling the primers into the delay assembly. (See 6.3)

4.4.6 Warning. This specification contains sampling procedures and tests which involve materiel potentially hazardous to personnel. It is emphasized that all applicable safety rules, procedures and regulatory requirements be strictly followed during the handling, processing and testing of these items. Hazardous component safety data sheets contained in the technical data package contain specific safety-related information.

4.5 Methods of inspection.

4.5.1 Waterproofness of cup assembly. The cup assemblies shall be placed under water in a vacuum chamber. The chamber shall be evacuated to a minimum pressure differential Of 5 p.s.i. for a period of 15 seconds, minimum. Observation shall be made for leakage as evidenced by air bubbles escaping through the water.

4.5.2 Moisture content of black powder. The contractor shall provide adequate temperature and humidity controls in explosive-loading areas so as to insure compliance with the applicable requirement. The moisture content of each lot of black powder propellant shall be determined at the loading station at the time of loading the propellant cup assemblies. This determination shall be made at least once for eight (8) hours of production. Sampling and testing of the propellant shall be in accordance with MIL-P-223. If the moisture content fails to comply with the requirement specified and loading of the cup assemblies has not begun, the propellant lot shall be rejected until corrective action has been taken as verified by repeating the moisture content determination. If loading has begun, propellant cup assemblies loaded with the non-conforming propellant shall be rejected.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:54Z
Check the source to verify that this is the current version before use.

4.5.3 Delay assembly functioning. The delay assembly shall be functioned by dropping a suitable weight from a height adequate for functioning. The delay time shall be recorded to determine compliance with the drawing. The diameter of the perforation of the lead disc shall be measured. (Note. - The minimum hole diameter is that hole which will receive a plug gage equal to the minimum size specified. A dead load of not more than five pounds should be applied to the gage in this determination to avoid false diameters resulting from burrs, raised metal, etc.)

4.5.4 Specific gravity of explosive charge. The specific gravity of the explosive' (bursting) charge shall be determined as follows:

a. Weigh mine empty (without explosive) and record.

b. Place mine in loading line at random and fill with explosive under conditions identical in all respects to these employed to fill regular mine (see 4.4.2.6).

c. Each of the marked mines filled with explosive will be allowed to cool.

d. Remove pouring funnel from mine.

e. Weigh mine and subtract empty weight from loaded weight to determine weight of explosive charge.

f. Remove explosive riser from pouring funnel.

g. Weigh explosive riser on balance and record as dry weight.

h. Weigh explosive riser completelysubmerged under water. Water temperature shall be 68 degrees Fahrenheit (F.) plus or minus 2 degrees F. Record the weight as weight under water. (When submerged the position of the explosive riser shall be such that no air is entrapped).

i. Specific gravity shall be calculated as follows:

$$\text{Specific gravity} = \frac{A}{A-B}$$

where:

A = dry weight
B = weight under water

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:54Z
Check the source to verify that this is the current version before use.

4.5.5 Mine functioning. The mines shall be functioned against three-inch, homogeneous armor plate, complying with MIL-A-13812, placed normal to the line of fire, at a 21 inch standoff. The test shall be conducted as follows: Remove the closing plug from the mine, insert an M120 Booster from an accepted lot and replace the closing plug. Remove the shipping plug from the top of the mine and from the M607 Fuze Adapter and assemble an M607 combination mine fuze from an accepted lot to the mine. Emplace the assembly in firm, level ground so that the top of the mine cover is three inches below the top of the ground. Soil shall be tapped firmly around the mine to prevent it from tilting. The plastic collar of the fuze shall be kept free from earth.

CAUTION: The fuze shall be armed by remote control with all personnel behind a suitable barricade. The fuze shall be armed by attaching a lanyard to the safety pin ring and around the safety support in such a manner that a pull on the lanyard will entirely remove the safety pin before any tension is placed on that portion of the lanyard which is connected to the safety support. Before pulling the lanyard, squeeze together the ends of the safety pin to enable the pin to slide easily out of the pin hole. Actuate the fuze by tilting the fuze extension rod. For information only, the load required to function the fuze is 5 1/4 plus or minus 1 1/2 pounds when activating the fuze by tilting the extension rod at the extreme end. Observation shall be made for Satisfactory functioning as indicated by a typical penetration as shown on figures 1 and 2.

4.5.6 Heat seal test. This test shall be performed as specified in MIL-P-116.

5. PACKAGING

5.1 Packing.

5.1.1 Level A. Packing for Mine, AT, M21, with booster assembly, M120, and fuze, mine combination, M607, shall be in accordance with Dwg. 8830860.

5.1.2 Level B. Packing shall be as specified in 5.1.1.

5.1.3 Level C. Packing shall be as specified in 5.1.1.

5.2 Marking. Marking shall be in accordance with Dwg. 8830860.

5.3 Shipping. When mines from more than one lot are shipped at one time, each lot shall be kept separate, and the division between lots clearly indicated to prevent mixing of the lots in transit.

6. NOTES

6.1 Ordering data. See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:54Z
Check the source to verify that this is the current version before use.

6.2 Submission of inspection equipment designs for approval. (See MIL-A-48078). Equipment designs shall be submitted as required to: Commander, US ARDC, ATTN: AMSMC-QAT-I (D) , Dover, New Jersey 07801-5001. Request letter of submittal should state contractor, contract number, specification number, item nomenclature, and classification of defects and tests paragraph number.

6.3 Cost of check test. The contracting officer will arrange for the contractor to be reimbursed for the expense incurred in the performance of the check test for deterioration of the primers. The tests shall be conducted at Government expense without cost to the contractor who loaded the primers, or to the contractor assembling the primers; into the delay assemblies; and shall not constitute a basis for rejection against either contractor except where deterioration boas occurred as a direct result of carelessness in handling, storage, etc., permitted while the primer lot was under the jurisdiction of either contractor.

6.4 Standoff distance. Standoff distance is defined as that vertical distance measured from the bottom surface of the armor plate to the top surface of the mine.

6.5 Throat diameter. Throat diameter is defined as the smallest diameter of the penetration and approximately half way through the plate.

6.6 Data cards. (See MIL-A-48078). Distribution of data cards shall include the following: Commander, U.S. Army Armament Research and Development Center, ATTN: AMSMC-QAT-M , Dover , New Jersey 07801-5001.

6.7 Drawings. Drawings listed in Section 2 of this specification under the heading US Army Armament Research and Development Center (ARDC) may also include drawings prepared by, and identified as, US Army Armament Research and Development Command (ARRADCOM), Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal or Picatinny Arsenal drawings. Technical data originally prepared by these activities are now under the cognizance of ARDC.

6.8 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue, due to the extensiveness of the changes.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:54Z
Check the source to verify that this is the current version before use.

6.9 Subject term (key word) listing.

Mine, AT
Loading Assembly
Delay Assembly
Waterproofness
Booster
Primer
Lead azide
Standoff distance

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1345-A265)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:54Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS. In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE. This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO 12062 WASHINGTON D C

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

COMMANDER
U S ARMY ARMAMENT RSCH DEV & ENGR CENTER
ATTN: AMSMC-QA
DOVER, NJ 07801-5001

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:54Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1 DOCUMENT NUMBER	2 DOCUMENT TITLE
MIL-M-45405C (AR)	MINE, VT, M21 LOADING, ASSEMBLING, AND PACKING

3a. NAME OF SUBMITTING ORGANIZATION	4 TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*. _____

5 PROBLEM AREAS

a. Paragraph Number and Wording

b. Recommended Wording

c. Reason/Rationale for Recommendation.

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8 DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE

(FOLD ALONG THIS LINE, CUT ALONG THIS LINE.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:54Z
Check the source to verify that this is the current version before use.