MILITARY SPECIFICATION

MINE, AT: M21, PARTS FOR

This Specification is approved for use within the U. S. Army Armament Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers quality assurance provisions and preparation for delivery for the parts for Mine, Antitank: M21.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. The following specifications and standards form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DoDISS) and supplement thereto, listed in the solicitation.

SPECIFICATIONS

FEDERAL

PPP-B-636 - Boxes, Fiber.
PPP-B-676 - Boxes, Set-up, Paperboard.
PPP-T-45 - Tape, Gummed, Paper, Reinforced and Plain, for Sealing and Securing.

MILITARY

MIL-C-2439 - Container, Ammunition, Fiber, Spirally Wound.
MIL-A-48078 - Ammunition, Standard Quality Assurance Provisions, General Specification For.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, U.S. Army Armament Research, Development and Engineering Center, Attn: AMSMC-QA, Dover, New Jersey 07801-5001 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 1345
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:55Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.

MIL-STD-129 - Marking for Shipment and Storage.

(Copies of specifications, standards, drawings, publications, and other Government documents required by the suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the Contracting Officer.)

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

DRAWINGS

US ARMY ARMAMENT RESEARCH AND DEVELOPMENT CENTER

8831343 - Mine, AT, M21, Metal Parts Assembly.

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. The issues of the documents which are indicated as DoD adopted shall be the issue listed in the current DoDISS and the supplement thereto, if applicable.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

ASTM B 117 (Part 10) - Salt Spray (Fog) Testing.

(Application for copies of ASTM publications should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, Pennsylvania 19103.)

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

Source: https://assist.dla.mil -- Downloaded: 20260-22T02:55Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Materials. Materials shall be in accordance with the applicable drawings, specifications and standards.

3.2 Parts. All parts shall comply with applicable drawings, specifications and standards.

3.3 Metal parts assembly. The metal parts assembly shall comply with all requirements specified on Drawing (Dwg.) 8831343, all associated drawings, and with all requirements specified in applicable specifications and standards.

3.4 Internal air pressure.

3.4.1 Applied through filling hole. The metal parts assembly shall show no evidence of leakage when subjected to an internal air pressure of 10 pounds per square inch gauge (psig), minimum (min.), for 10 seconds, min. when tested as specified in 4.5.2.1.

3.4.2 Applied through booster well. The metal parts assembly shall withstand an internal air pressure of 4 psig, min., for 10 seconds, min. when tested as specified in 4.5.2.2.

3.5 Link pull. The link shall show no evidence of failure or loosening when subjected to a pull of 400 pounds min., for 10 seconds, min. when tested as specified in 4.5.3.

3.6 Handle pull. The handle shall show no evidence of failure or loosening of the weld when subjected to a pull of 150 pounds, min., for 10 seconds, min. when tested as specified in 4.5.4.

3.7 Load deflection. Maximum (max.) functioning load of the firing pin assembly at or before 0.1 inch deflection of the assembly shall be not less than 85 pounds nor more than 190 pounds. ("Max functioning load" is the rupture load of the firing pin washer.) The test shall be performed as specified in 4.5.5.

3.8 Waterproofness of propellant cup. The cup shall withstand an internal air pressure of 5.0 psig, min., for 15 seconds, min., with no evidence of leakage when tested as specified in 4.5.6.

3.9 Shearing of cover. The cover shall open satisfactorily as evidenced by shearing along the cover score lines from the center outward and moving outward toward the perimeter of the mine to provide a clear path for the vertical jet that would be produced by the main charge. (See Figure 1) No part of the cover assembly, fuze, or the charge cap shall be left extending over, or shall be left lying on the mine body. Soil used to cover the mine shall be thrown away from the mine. In addition, the primer shall function satisfactorily as evidence of satisfactory functioning of the firing pin assembly. The test shall be performed as specified in 4.5.7.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:55Z
Check the source to verify that this is the current version before use.

3.10 First article inspection. This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

3.11 Workmanship.

3.11.1 Die castings. The die castings shall be of uniform quality, free of cold shuts, cracks, scale, blow holes and surface porosity and shrinkage defects. All flash must be completely removed from parting lines, internal and external profiles, cored holes and ejector pin marks. All waste material remaining from gates must be removed. The castings must be dry, clean and free from chips. All unfilled castings shall be rejected.

3.11.2 Reusable scrap. No scrap shall be used other than sprues, gates and rejected die castings of the particular material required by the item print and produced in the manufacturers plant, when the material is a zinc alloy. The material used shall be free from finishes, lubricants, cleaning agents and any other substance which may contaminate the material of the product. No aluminum scrap of any kind shall be reused.

3.11.3 Plastic parts. All plastic components shall be fabricated in a thorough, workmanlike manner and shall be free of porosity, twist, warpage, heat marks, sinks, checks, cracks, chipped edges, burrs, bubbles, blisters, scratches, excess flash, and other molding defects which would affect their serviceability.

3.11.4 Welding and brazing. All welds and brazes shall be reasonably smooth and free of craters. They shall exhibit characteristics of good fusion, penetration, and soundness of deposit representative of good welding and brazing practice. The process shall be such as to prevent warpage and distortion. There shall be no crack in or near welded or brazed areas.

3.11.5 All parts. All parts and assemblies shall be fabricated and assembled in a thorough, workmanlike manner. They shall be free of burrs, chips, weld spatter, sharp edges, chipped edges, gouges, cracks, surface defects, dirt, grease, rust, corrosion products, and other foreign matter. The cleaning method used shall not be injurious to any part nor shall the parts be contaminated by the cleaning agents. All required markings shall be neat and sharply defined. External threads shall be full, complete and undamaged for their entire length. Exterior surface coatings shall be continuous except for a few light scratches not exposing base material.

Source: https://assist.dla.mil -- Downloaded: 202610-22T02:55Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection and standard quality assurance provisions. Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection.

b. Quality conformance inspection.

4.3 First article inspection.

4.3.1 Submission. The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with provisions of 4.3.2. The first article sample shall consist of the following items in sample quantities as indicated below and Table I.

Part Description	Drawings	Quantities
Mine, AT: M21, Metal Parts Assembly	8831343	50
Shipping Plug Assembly	8831344	25
Closing Plug Assembly	8831346	25
Cap, Closing	8831347	25
Cap, Charge	8831350	25
Plug, Shipping	8831352	25
Cup	8831354	25
Lid	8831355	25
Plug, Closing	8831356	25
Holder, Primer	8831358	25
Holder, Delay	8831359	25
Cup, Relay	8831361	25
Tube, Delay	8831362	25
Link	8831363	25
Handle Assembly	8831364	25
Handle	8831365	25
Slide, Handle	8831366	25
Clip, Handle	8831367	25
Base	8831368	25
Body	8831369	25
Firing Pin Assembly	8831370	25
Washer	8831371	25
Washer, Firing Pin	8831372	25
Pin, Firing	8831373	25
Ring, Retaining	8831375	25

Source: https://assist.dla.mil -- Downloaded: 202610-22T02:55Z
Check the source to verify that this is the current version before use.

Part Description	Drawing	Quantities
Cover Assembly	8831376	25
Cover	8831377	25
Adapter, Cap	8831378	25
Sleeve	8831379	25
Wrench, Arming M26	8831380	25
Cover and Sleeve Assembly	8840500	25

NOTE: Those components produced from plastic molds or casting cavities shall have fifty (50) components from each mold or cavity submitted for this inspection.

4.3.2 Inspections to be performed. See MIL-A-48078 and Table I specified herein. If any items fail to comply with any of the applicable requirements, the first article sample shall be rejected.

4.3.3 Rejection. See MIL-A-48078. If any items fail to comply with any of the applicable requirements, the first article sample shall be rejected.

Source: https://assist.dla.mil -- Downloaded: 202610-22T02:55Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-45406C(AR)

PARAGRAPH	TITLE: Mine, AT: M21		SHEET 1 OF 8		DRAWING NUMBER: See below NEXT HIGHER ASSEMBLY: --
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Shipping Plug Assembly (Dwg. 8831344)				
	Examination for Defects	25		3.2	4.4.2.2
	Closing Plug Assembly (Dwg. 8831346)				
	Examination for Defects	25		3.2	4.4.2.4
	Cap, Closing (Dwg. 8831347)				
	Inspect for all drawing requirements	25		3.2/3.11	Gage/Visual
	Salt Spray Test	5(a)		3.2	4.5.1
	Cap, Charge (Dwg. 8831350)				
	Examination for Defects	25		3.2	4.4.2.5

NOTES: a. This test shall be performed on samples selected from among those subjected to the examination for defects. If one sample shows evidence of corrosion (red rust, salt deposits), the sample shall be rejected.

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T02:55Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection.

CLASSIFICATION OF DEFECTS & TESTS MIL-M-45406C(AR)

PARAGRAPH	TITLE		SHEET 2 OF 8		DRAWING NUMBER
	Mine, AT: M21				See Below
					NEXT HIGHER ASSEMBLY --
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Plug, Shipping (Dwg. 8831352)				
	Examination for Defects	25		3.2	4.4.2.1
	Salt Spray Test (metal plugs only)	5 (a)		3.2	4.5.1
	Cup (Dwg. 8831354)				
	Examination for Defects	25		3.2	4.4.2.6
	Waterproofness	(b)		3.8	4.5.6
	Lid (Dwg. 8831355)				
	Examination for Defects	25		3.2	4.4.2.7
	Plug, Closing (Dwg. 8831356)				
	Salt Spray Test	5(a)		3.2	4.5.1
NOTES:	(a) This test shall be performed on samples selected from among those subjected to the examination for defects. If any sample shows evidence of corrosion (red rust, salt deposits, the sample shall be rejected.				
	(b) The samples shall be subjected to this test following the examination for defects.				
NOTES:					

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:55Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 3 OF 8		DRAWING NUMBER
	Mine, AT: M21				See Below
					NEXT HIGHER ASSEMBLY
					--
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Holder, Primer (Dwg. 8831358)				
	Examination for Defects	25		3.2	4.4.2.8
	Salt Spray Test	5(a)		3.2	4.5.1
	Holder, Delay (Dwg. 8831359)				
	Examination for Defects	25		3.2	4.4.2.9
	Salt Spray Test	5(a)		3.2	4.5.1
	Cup, Relay (Dwg. 8831361)				
	Examination for Defects	25		3.2	4.4.2.10
	Tube Delay (Dwg. 8831362)				
	Examination for Defects	25		3.2	4.4.2.11
	Salt Spray Test	5(a)		3.2	4.5.1

NOTES: a. This test shall be performed on samples selected from among those subjected to the examination for defects. If any sample shows evidence of corrosion (red rust, salt deposits), the sample shall be rejected.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:55Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection.

CLASSIFICATION OF DEFECTS & TESTS MIL-M-45406C(AR)

PARAGRAPH	TITLE: Mine, AT: M21		SHEET 4 OF 8		DRAWING NUMBER: See Below NEXT HIGHER ASSEMBLY: --
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Link (Dwg. 8831363) Inspect for all drawing requirements	25		3.2 and 3.11.5	Gage/Visual
	Handle Assembly (Dwg. 8831364) Inspect for all drawing requirements	25		3.2 and 3.11.5	Gage/Visual
	Handle (Dwg. 8831365) Inspect for all drawing requirements	25		3.2 and 3.11.5	Gage/Visual
	Slide Handle (Dwg. 8831366) Inspect for all drawing requirements	25		3.2 and 3.11.5	Gage/Visual

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:55Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-45406C(AR)

PARAGRAPH	TITLE: Mine, AT: M21		SHEET 5 OF 8		DRAWING NUMBER: See Below
					NEXT HIGHER ASSEMBLY: --
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Clip, Handle (Dwg. 8831367) Inspect for all drawing requirements	25		3.2 and 3.11.5	Gage/Visual
	Base (Dwg. 8831368) Examination for Defects	25		3.2	4.4.2.12
	Body (Dwg. 8831369) Examination for Defects	25		3.2	4.4.2.13
	Firing Pin Assembly (Dwg. 8831370) Examination for Defects	25		3.2	4.4.2.15
	Washer (Dwg. 8831371) Inspect for all drawing requirements	25		3.2 and 3.11.5	Gage/Visual

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T02:55Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection.

CLASSIFICATION OF DEFECTS & TESTS MIL-M-45406C(AR)

PARAGRAPH	TITLE: Mine, AT: M21		SHEET 6 OF 8		DRAWING NUMBER: See Below
					NEXT HIGHER ASSEMBLY: --
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Washer, Firing Pin (Dwg. 8831372)				
	Inspection for all drawing requirements	25		3.2 and 3.11.5	Gage/Visual
	Pin, Firing (Dwg. 8831373)				
	Examination for Defects	25		3.2	4.4.2.14
	Ring, Retaining (Dwg. 8831375)				
	Inspection for all drawing requirements	25		3.2 and 3.11.5	Gage/Visual
	Cover assembly (Dwg. 8831376)				
	Examination for Defects	25		3.2	4.4.2.19
	Salt Spray test	5(a)		3.2	4.5.1

NOTES: a. This test shall be performed on samples selected from among those subjected to the examination for defects. If any sample shows evidence of corrosion (red rust, salt deposits), the sample shall be rejected.

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 202640-22T02:55Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-45406C(AR)

PARAGRAPH	TITLE: Mine, AT: M21		SHEET 7 OF 8		DRAWING NUMBER: See Below
					NEXT HIGHER ASSEMBLY: --
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Cover (Dwg. 8831377) Examination for Defects	25		3.2	4.4.2.16
	Adapter, Cap (Dwg. 8831378) Examination for Defects	25		3.2	4.4.2.17
	Sleeve (Dwg. 8831379) Examination for Defects	25		3.2	4.4.2.18
	Wrench, Arming (Dwg. 8831380) Examination for Defects	25		3.2	4.4.2.20
	Salt Spray Test	5 (1)		3.2	4.5.1
NOTES:	1. This test shall be performed on samples selected from among those subjected to the examination for defects. If any sample shows evidence of corrosion (red rust, salt deposits), the sample shall be rejected.				
NOTES:					

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 202640-22T02:55Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection.

CLASSIFICATION OF DEFECTS & TESTS MIL-M-45406C(AR)

PARAGRAPH	TITLE: Mine, AT: M21		SHEET 8 OF 8		DRAWING NUMBER: See Below NEXT HIGHER ASSEMBLY: --
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Cover and Sleeve Assembly (Dwg. 8840500)				
	Inspect for all drawing requirements	25		3.2, 3.11.4 & 3.11.5	Test/Visual
	Mine, AT: M21, Metal Parts Assembly (Dwg. 8831343)				
	Examination for Defects	50		3.3	4.4.2.22
	Internal Air Tests	50 (2)		3.4	4.5.2
	Link Pull Test	50 (2)		3.5	4.5.3
	Handle Pull Test	50 (2)		3.6	4.5.4
	Shearing of cover	50 (2)		3.9	4.5.7
NOTES:	2. These tests shall be conducted on the samples subjected to the examination for defects. After successful completion of the air tests, link pull and handle pull tests, the fifty (50) assemblies shall be forwarded to the designated proving ground for the shearing of the cover test.				
NOTES:					

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T02:55Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

4.4.1 Inspection lot formation. Inspection lots shall comply with the lot formation provisions of MIL-A-48078.

4.4.1.1 Cavity identification (Plastic and cast parts). The contractor shall maintain an approved cavity identification system. Components shall be grouped and identified until all inspections have been completed.

4.4.2 Examination. See MIL-A-48078.

a. Sampling plans. Unless otherwise specified in the Classification of Defects and Tests Tables, sampling plans and procedures for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:55Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-45406C(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.1	Plug, Shipping	1 OF 1	8831352
			NEXT HIGHER ASSEMBLY 8831344

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major					
101	Salt spray (metal plugs only)	(a)	-	3.2	4.5.1
102	Major diameter of thread, min.		0.40%(b)	3.2	Gage
103	Pitch diameter of thread		0.40%(b)	3.2	Gage
104	Total height		0.40%(b)	3.2	Gage
105	Poor casting or molding workmanship		0.40%(b)	3.11.1/ 3.11.4	Visual
Minor					
201	Diameter of undercut, max.		0.65%	3.2	Gage
202	Poor workmanship		1.0%	3.11.5	Visual

NOTES:

a. Five (5) plugs shall be selected from each lot for this test. Lot formation provisions shall be as specified in the applicable finish specification. If any sample shows evidence of corrosion (red rust, salt deposits) the lot shall be rejected.

b. If plug is die cast, see 4.4.3.1 or if plug is molded, see 4.4.3.2 for alternate method of sampling.

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:55Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-45406C(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.2	Shipping Plug Assembly				8831344
					NEXT HIGHER ASSEMBLY --
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major					
101	Gasket missing or peeling		0.40%	3.2	Visual
Minor					
201	Assembly damaged (nicked, chipped, cracked, or distorted)		0.65%	3.2	Visual
202	Poor workmanship		1.0%	3.11.5	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T02:55Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-45406C(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.3.3	Plug, Closing	1 OF 1	8831356
			NEXT HIGHER ASSEMBLY: 8831346

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major					
101	Salt spray	(a)	-	3.2	4.5.1
102	Thickness, max.		0.40%(b)	3.2	Gage
103	Major diameter of thread, min.		0.40%(b)	3.2	Gage
104	Pitch diameter of thread		0.40%(b)	3.2	Gage
105	Width of slot, min.		0.40%(b)	3.2	Gage
106	Thread damaged		0.40%(b)	3.2	Visual
Minor					
201	Chamfer missing		0.65%	3.2	Visual
202	Poor workmanship		1.0%	3.11.5	Visual

NOTES:

a. Five (5) closing plugs shall be selected from each lot for this test. Lot formation provisions shall be as specified in the applicable finish specification. If any sample shows evidence of corrosion (red rust, salt deposits), the lot shall be rejected.

b. See 4.4.3.4 for alternate method of sampling.

NOTES:

AMSMC Form 1570, 1 Feb 85 — Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026/10-22T02:55Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-45406C(AR)

PARAGRAPH	TITLE	SHEET	OF	DRAWING NUMBER
4.4.2.4	Closing Plug Assembly	1	1	8831346
				NEXT HIGHER ASSEMBLY --

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major					
101	Adhesion improper		0.40%	3.2	Visual/Manual
102	Slot missing		0.40%	3.2	Visual
103	Gasket missing or pealing		0.40%	3.2	Visual
104	Threads damaged		0.40%	3.2	Visual
Minor					
201	Protective finish inadequate, improper or missing		0.65%	3.2	Visual
202	Assembly damaged (nicked, chipped, split, cracked, or distorted)		0.65%	3.2	Visual
203	Poor workmanship		1.0%	3.11.5	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T02:55Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-45406C(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.5	Cap, Charge				8831350
					NEXT HIGHER ASSEMBLY --
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major					
101	Diameter of external thread relief		0.40%(a)	3.2	Gage
102	Width external thread relief		0.40%(a)	3.2	Gage
103	Minor diameter of internal thread, max.		0.40%(a)	3.2	Gage
104	Pitch diameter of internal thread		0.40%(a)	3.2	Gage
105	Major diameter of external thread		0.40%(a)	3.2	Gage
106	Pitch diameter of external thread		0.40%(a)	3.2	Gage
107	Height of hub bottom of large cavity		0.40%(a)	3.2	Gage
108	Distance between wrench holes		0.40%(a)	3.2	Gage
109	Diameter of wrench holes, min.		0.40%(a)	3.2	Gage
110	Diameter of large cavity		0.40%(a)	3.2	Gage
111	Total height		0.40%(a)	3.2	Gage
Minor					
201	Thickness of flange		0.65%(a)	3.2	Gage
202	Diameter of flange		0.65%(a)	3.2	Gage
203	Finish inadequate or improper		0.65%(a)	3.2	Visual
204	Part damaged (nicked, chipped, split, cracked, or distorted)		0.65%(a)	3.2	Visual
205	Threads damaged		0.65%(a)	3.2	Visual
206	Poor workmanship		1.0% (a)	3.11.5	Visual

NOTES: a. See 4.4.3.4 for alternate method of sampling.

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026/10-22T02:55Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.6	Cup				8831354
					NEXT HIGHER ASSEMBLY --
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major					
101	Waterproofness		0.40%	3.8	4.5.6
102	Height, less boss		0.40%(a)	3.2	Gage
103	Thickness through bottom of boss, min. (.009)		0.40%(a)	3.2	Gage
104	Outside diameter of boss		0.40%(a)	3.2	Gage
Minor					
201	Inside diameter propellant cavity		0.65%(a)	3.2	Gage
202	Poor workmanship		1.0%	3.11.5	Visual

NOTES: a. See 4.4.3.2 for alternate method of sampling.

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T02:55Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-45406C(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.7	Lid				8831355
					NEXT HIGHER ASSEMBLY --
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major					
101	Diameter of flange		0.40%(a)	3.2	Gage
102	Total height		0.40%(a)	3.2	Gage
Minor					
2301	Poor workmanship		1.0%	3.11.5	Visual

NOTES: a. See 4.4.3.2 for alternate method of sampling.

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T02:55Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-45406C(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.8	Holder, Primer				8831358
					NEXT HIGHER ASSEMBLY --
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major					
101	Outside diameter		0.40%(a)	3.2	Gage
102	Diameter of primer cavity		0.40%(a)	3.2	Gage
103	Depth of primer cavity (.115)		0.40%(a)	3.2	Gage
Minor					
201	Diameter of flash hole		0.65%(a)	3.2	Gage
202	Height of crimping lip		0.65%(a)	3.2	Gage
203	Finish improper		0.65%(a)	3.2	Visual
204	Protective finish improper, inadequate or missing		0.65%(a)	3.2	Visual
205	Poor workmanship		1.0%(a)	3.11.5	Visual

NOTES: a. See 4.4.3.1 for alternate method of sampling.

Source: https://assist.dla.mil -- Downloaded: 202640-22T02:55Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-45406C(AR)

PARAGRAPH	TITLE		SHEET 1 OF 2		DRAWING NUMBER
4.4.2.9	Holder, Delay				8831359
					NEXT HIGHER ASSEMBLY --
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major					
101	Thickness of bottom, min.		0.40%	3.2	Gage
102	Pitch diameter of threads		0.40%	3.2	Gage
103	Major diameter of threads		0.40%	3.2	Gage
104	Diameter of body		0.40%	3.2	Gage
105	Diameter of primer holder counterbore		0.40%	3.2	Gage
106	Diameter of relay cup cavity		0.40%	3.2	Gage
107	Distance between thread face and shoulder (.320)		0.40%	3.2	Gage
108	Concentricity of outside diameter with thread		0.40%	3.2	Gage
109	Thickness at crimping lip		0.40%	3.2	Gage
110	Concentricity of primer holder counterbore with threads		0.40%	3.2	Gage

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T02:55Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 2 OF 2		DRAWING NUMBER
4.4.2.9 Cont'd)	Holder, Delay				8831359
					NEXT HIGHER ASSEMBLY --
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Minor					
201	Height of crimping lip		0.65%	3.2	Gage
202	Depth from shoulder under crimping lip		0.65%	3.2	Gage
203	Distance between shoulder thread face and bottom of primer holder counterbore		0.65%	3.2	Gage
204	Diameter of flash hole, max.		0.65%	3.2	Gage
205	Diameter of wrench holes		0.65%	3.2	Gage
206	Distance between wrench holes		0.65%	3.2	Gage
207	Threads damaged		0.65%	3.2	Visual
208	Protective finish damaged, improper, inadequate or missing		0.65%	3.2	Visual
209	Poor workmanship		1.0%	3.11.5	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T02:55Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-45406C(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.10	Cup, Relay				8831361
					NEXT HIGHER ASSEMBLY --
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Crack, split or perforation		100%	3.2	Visual
Major					
101	Total height, max.		0.40% (a)	3.2	Gage
102	Thickness through bottom		0.40% (a)	3.2	Gage
103	Outside diameter, max.		0.40% (a)	3.2	Gage
Minor					
201	Inside diameter, minimum (Min.)		0.65% (a)	3.2	Gage
202	Protective finish improper, inadequate or missing		0.65%	3.2	Visual
203	Poor workmanship		1.0%	3.11.5	Visual

NOTES:
a. See 4.4.3.3 for alternate method of sampling.

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:55Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-45406C(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.11	Tube, Delay	1 OF 2	8831362
			NEXT HIGHER ASSEMBLY: 8831343

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major					
101	Salt spray	(a)	-	3.2	4.5.1
102	Total length, max.		0.40%	3.2	Gage
103	Distance between body seat shoulder and bottom		0.40%	3.2	Gage
104	Outside diameter of bottom flange, min.		0.40%	3.2	Gage
105	Distance from base to top of booster cavity		0.40%	3.2	Gage
106	Distance between firing pin assembly seat and bottom of firing pin assembly cavity (.39)		0.40%	3.2	Gage
107	Distance between booster assembly threads, max. (.570)		0.40%	3.2	Gage
108	Diameter of delay assembly cavity		0.40%	3.2	Gage
109	Diameter of firing pin cavity		0.40%	3.2	Gage
110	Diameter of booster cavity, min.		0.40%	3.2	Gage
111	Minor diameter of delay assembly thread, max.		0.40%	3.2	Gage
112	Pitch diameter of delay assembly, thread		0.40%	3.2	Gage

NOTES: a. Five (5) delay tubes shall be selected from each lot for this test. Lot formation provisions shall be as specified in the applicable finish specification. If any samples show evidence of corrosion (red rust, salt deposits), the lot shall be rejected.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:55Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-45406C(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.11 Cont'd)	Tube, Delay	2 OF 2	8831362
			NEXT HIGHER ASSEMBLY: 8831343

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Major					
113	Concentricity of firing pin cavity with thread		0.40%	3.2	Gage
114	Wall thickness of booster cavity		0.40%	3.2	Gage
Minor					
201	External braze groove missing (2)		0.65%	3.2	Visual
202	Protective coating inadequate, improper or missing		0.65%	3.2	Visual
203	Part damaged (cracked or split)		0.65%	3.2	Visual
204	Poor workmanship		1.0%	3.11.5	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85 — Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:55Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-45406C(AR)

PARAGRAPH	TITLE	SHEET	OF	DRAWING NUMBER
4.4.2.12	Base	1	1	8831368
				NEXT HIGHER ASSEMBLY 8831343

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major					
101	Height of center hole portion of base		0.40%(a)	3.2	Gage
102	Total height		0.40%(a)	3.2	Gage
Minor					
201	Part damaged (cracked, punctured or deformed)		0.65%	3.2	Visual
202	Poor workmanship		1.0%	3.11.5	Visual

NOTES:
a. See 4.4.3.3 for alternate method of sampling.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:55Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-45406C(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.13	Body				8831369
					NEXT HIGHER ASSEMBLY 8831343
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	ACL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major					
101	Spherical radius		0.40% (a)	3.2	Gage
102	Thickness of radius		0.40% (a)	3.2	Gage
103	Depth to spherical radius from bottom		0.40% (a)	3.2	Gage
104	Depth to spherical radius at center hole from top		0.40% (a)	3.2	Gage
Minor					
201	Sidewall thickness, min.		0.65% (a)	3.2	Gage
202	Part damaged (cracked or split)		0.65%	3.2	Visual
203	Poor workmanship		1.0%	3.11.5	Visual

NOTES:
a. See 4.4.3.3 for alternate method of sampling.

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:55Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-45406C(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.14	Pin, Firing		8831373
			NEXT HIGHER ASSEMBLY 8831370

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major					
101	Diameter of body		0.40%(a)	3.2	Gage
102	Concentricity of body diameter with tip		0.40%(a)	3.2	Gage
103	Diameter of tip, min.		0.40%(a)	3.2	Gage
104	Concentricity of washer boss with tip		0.40%(a)	3.2	Gage
105	Distance between tip face and body		0.40%(a)	3.2	Gage
106	Distance between tip face and top of body		0.40%(a)	3.2	Gage
Minor					
201	Finish inadequate or improper		0.65%	3.2	Visual
202	Protective finish inadequate, damage, improper or missing		0.65%	3.2	Visual
203	Poor workmanship		1.0%	3.11.5	Visual

NOTES: a. See 4.4.3.4 for alternate method of sampling.

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T02:55Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-45406C(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.15	Firing Pin Assembly				8831370
					NEXT HIGHER ASSEMBLY 8831343
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major					
101	Load Deflection	(a)		3.7	4.5.5
102	Concentricity of firing pin washer with firing pin body		0.40%	3.2	Gage
103	Washer peen incorrect		0.40%	3.2	Visual
104	Either washer missing		0.40%	3.2	Visual
105	Firing pin point damaged		0.40%	3.2	Visual
Minor					
201	Assembly damaged (chipped, nicked, scratched or distorted) (excl. 105)		0.65%	3.2	Visual
202	Poor workmanship		1.0%	3.11.5	Visual
NOTES:	(a) Beginning with the first lot produced and continuing until three consecutive lots have complied with the acceptance criteria specified, a sample of 125 assemblies shall be selected for this test. Any assembly which fails to comply with the specified requirements shall be classed defective. If three (3) or more assemblies are classed defective, the lot shall be rejected. After three consecutive lots have met the criteria specified above, a sample of 50 assemblies shall be selected for this test. If two (2) or more assemblies are classed defective, the lot shall be rejected.				

NOTES:

AMSMC Form 1570, 1 Feb 85 — Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026/10-22T02:55Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-45406C(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.16	Cover				8831377
					NEXT HIGHER ASSEMBLY 8840500
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major					
101	Diameter of hole		0.40%(a)	3.2	Gage
102	Depth of recess		0.40%(a)	3.2	Gage
103	Thickness, min.		0.40%(a)	3.2	Gage
Minor					
201	Poor workmanship		1.0%(a)	3.11.5	Visual

NOTES:

a. See 4.4.3.3 for alternate method of sampling.

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:55Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-45406C(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.17	Adapter, Cap				8831378
					NEXT HIGHER ASSEMBLY 8831376
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major					
101	Height		0.40%(a)	3.2	Gage
102	Location of groove		0.40%(a)	3.2	Gage
103	Pitch diameter of thread		0.40%(a)	3.2	Gage
104	Minor diameter of thread, max.		0.40%(a)	3.2	Gage
Minor					
201	Chamfer missing		0.65%(a)	3.2	Visual
202	Poor workmanship		1.0%(a)	3.11.5	Visual

NOTES:
a. See 4.4.3.4 for alternate method of sampling.

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:55Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-45406C(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.18	Sleeve				8831379
					NEXT HIGHER ASSEMBLY 8840500
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major					
101	Thickness of flange, min.		0.40%(a)	3.2	Gage
102	Diameter of flange, min.		0.40%(a)	3.2	Gage
103	Concentricity of center with propellant cup cavity		0.40%(a)	3.2	Gage
104	Diameter of center hole		0.40%(a)	3.2	Gage
105	Diameter of vent holes (4)		0.40%(a)	3.2	Gage
106	Hole missing		0.40%(a)	3.2	Visual
Minor					
201	Depth of propellant cup cavity, min.		0.65%(a)	3.2	Gage
202	Diameter of propellant cup cavity, min.		0.65%(a)	3.2	Gage
203	Poor workmanship		1.0%(a)	3.11.5	Visual

NOTES: a. See 4.4.3.3 for alternate method of sampling.

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T02:55Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-45406C(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.19	Cover Assembly				8831376
					NEXT HIGHER ASSEMBLY 8831343
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major					
101	Salt spray test	(a)		3.2	4.5.1
102	Thickness through bottom of score, min.		0.40%	3.2	Gage
103	Spacing of scores		0.40%	3.2	Gage
104	Radius of score arc		0.40%	3.2	Gage
105	Radius of score limits		0.40%	3.2	Gage
106	Angle between scores converging on rim		0.40%	3.2	Gage
107	Cap adapter missing or loose		0.40%	3.2	Visual/Manual
108	Extraneous matter in scores		0.40%	3.2	Visual
109	Brazing improper or unsatisfactory		0.40%	3.11.4	Visual
110	Indentation on sleeve caused by spot welding sleeve and a cover		0.40%	3.2	Visual
Minor					
201	Protective finish inadequate, improper or missing		0.65%	3.2	Visual
202	Assembly damaged (scratched, nicked, dented, chipped or distorted)		0.65%	3.2	Visual
203	Paint finish unsatisfactory or missing		0.65%	3.2	Visual
204	Poor workmanship		1.0%	3.11.5	Visual

NOTES: a. Five (5) cover assemblies shall be selected from each lot for this test. Lot formation provisions shall be as specified in the applicable finish specification. If any assembly shows evidence of corrosion (red rust, salt deposits), the lot shall be rejected.

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T02:55Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-45406C(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.20	Wrench, Arming: M26				8831380
					NEXT HIGHER ASSEMBLY –
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major					
101	Salt spray test	(a)		3.2	4.5.1
102	Distance between jaws		0.40%(b)	3.2	Gage
103	Depth to specified diameter behind to per (.85)		0.40%(b)	3.2	Gage
104	Location of radial cutouts (3)		0.40%(b)	3.2	Gage
Minor					
201	Total length		0.65%(b)	3.2	Gage
202	Thickness, min.		0.65%(b)	3.2	Gage
203	Stamping misleading, unidentifiable or missing		0.65%(b)	3.2	Visual
204	Poor workmanship		1.0%(b)	3.11.5	Visual
NOTES:	a. Ten (10) wrenches shall be selected from each lot for this test. Lot formation provisions shall be a specified in the applicable finish specification. If any wrench evidence of corrosion (red rust, salt deposits), the lot shall be rejected.				
	b. See 4.4.3.3 for alternate method of sampling.				

NOTES:

AMSMC Form 1570, 1 Feb 85 — Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:55Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-45406C(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.21	Metal parts assembly (prior to painting)				8831343
					NEXT HIGHER ASSEMBLY –
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major					
101	Height, max.		0.40%	3.3	Gage
102	Diameter of base, max.		0.40%	3.3	Gage
103	Spot weld inadequate or missing at link		0.40%	3.11.4	Visual
104	Crack or perforation through base, body, cover, sleeve, or at firing pin assembly crimp		0.40%	3.3	Visual
105	Handle chip or slide shows evidence of corrosion		0.40%	3.3	Visual
106	Brazing at required areas unsatisfactory or missing		0.40%	3.11.4	visual
107	Protective finish on any interior or exterior surface inadequate or missing		0.40%	3.3	Visual
Minor					
201	Links incorrectly located		0.65%	3.2.	Visual
202	Poor workmanship		1.0%	3.11.5	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85 — Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T02:55Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 3		DRAWING NUMBER 8831343
4.4.2.22	Metal parts assembly				NEXT HIGHER ASSEMBLY -
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major					
101	Internal air test		100%	3.4	4.5.2
102	Link pull tests	(a)		3.5	4.5.3
103	Handle pull test	(a)		3.6	4.5.4
104	shearing of cover	(b)		3.8	4.5.7
NOTES:	(a) Beginning with the first lot produced and continuing until three consecutive lots have complied with the acceptance criteria specified, a sample of 125 assemblies shall be selected for this test. Any metal parts assembly which fails to comply with the specified requirement shall be classed defective. If three (3) or more assemblies are classed defective, the lot shall be rejected. After three (3) consecutive lots have met the above criteria, a sample of 50 assemblies shall be selected for this test. If two (2) or more assemblies are classed defective, the lot shall be rejected. (b) Beginning with the first lot produced and continuing until three consecutive lots have complied with the acceptance criteria specified, a sample of 50 assemblies shall be selected. Any metal parts assembly which fails to comply with the specified requirements shall be classed defective. If two or more assemblies are classed defective the lot shall be rejected. After three (3) consecutive lots have met the criteria specified above, a sample of 35 assemblies shall be selected for this test. If two or more assemblies are classed defective, the lot shall be rejected.				
NOTES:					

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:55Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-45406C(AR)

PARAGRAPH	TITLE		SHEET 2 OF 3		DRAWING NUMBER
4.4.2.22 (Cont'd)	Metal parts assembly				8831343
					NEXT HIGHER ASSEMBLY –
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
105	Component missing		0.40%	3.3	Visual
106	Part or assembly improperly assembled		0.40%	3.3	Visual
107	Sealer inadequate or missing from retaining ring or firing pin assembly		0.40%	3.3	Visual
108	Protective coating in propellant charge cavity of sleeve inadequate, improper or missing		0.40%	3.3	Visual
109	Firing pin point damaged		0.40%	3.3	Visual
110	Part damaged (cracked, dented or deformed)		0.40%	3.11.5	Visual
Minor					
201	Handle, strap slide, or handle clip incorrectly secured		0.65%	3.3	Visual/Manual
202	Rust preventive missing from cap adapter thread or chamfer		0.65%	3.3	Visual
203	Handle damaged (torn, frayed, deteriorated)		0.65%	3.3	Visual
204	Paint on any interior or exterior surface inadequate or missing		0.65%	3.3	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T02:55Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-45406C(AR)

PARAGRAPH	TITLE		SHEET 3 OF 3		DRAWING NUMBER 8831343
4.4.2.22 (Cont'd)	Metal parts assembly				NEXT HIGHER ASSEMBLY --
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
205	Paint or coating on any thread or in delay cavity		0.65%	3.3	Visual
206	Marking misleading, unidentifiable or missing		0.65%	3.3	Visual
207	Poor workmanship (excl. 110)		1.0%	3.11.5	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T02:55Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-45406C(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.23	Box, Packing				See Section 5
					NEXT HIGHER ASSEMBLY: -
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major					
101	Box damaged so that contents are exposed or liable to become exposed		0.40%	3.2	Visual
102	Sealing strip incomplete, badly wrinkled, or not in contact with surface for at least 1/2 inch around entire circumference		0.40%	3.2	Visual
Minor					
201	Contents move when box is shaken or tilted		0.65%	3.2	Manual
202	Marking misleading, unidentifiable, or missing, including incorrect color code		0.65%	3.2	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85 — Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:55Z
Check the source to verify that this is the current version before use.

4.4.3 Testing. Testing is described in the First Article and Quality Conformance Inspection tables.

4.4.3.1 Dimensional control of cast parts. (The requirements of this paragraph apply to those dimensions which are considered "as cast", and which do not undergo subsequent operations.) In place of the normal sampling associated with the Classification of Defects, and with the approval of the Contracting Officer, a sample of at least five (5) parts (as cast) from each cavity shall be dimensionally inspected to qualify a new or reworked cavity for use in production and as a control of the cavity during production. The cast parts shall carry individual cavity identification when more than one cavity is used in production. As a control of each cavity during production, the above quantity of parts from each cavity shall be inspected for at least the defects listed in paragraph 4.4.2.1 after continuous production of each 5,000 parts or at the end of each week, whichever occurs first. Individual cavity identification must be provided. If any defective parts are found during qualification of the cavity, the cavity producing the defective part shall not be used in production. If any defective parts are found when inspection is performed for control of the cavity, the cavity producing the defective part shall be removed from production. Further, that portion of production since the last control check shall be returned to the contractor for corrective action. All cavities removed from production because of some fault, may, after reworking, be returned to production providing they pass the qualification test specified above. The contractor may request a change of inspection frequency providing he presents objective evidence to substantiate the request to the Contracting Officer.

4.4.3.2 Dimensional control of molded parts. In place of the normal sampling associated with the Classification of Defects, and with the approval of the Contracting Officer, and after a curing time for the parts has been approved (See Note), a sample of five (5) parts (as molded) from each cavity may be dimensionally inspected to qualify a new or reworked cavity for use in production or as a control of each cavity during production.

The inspection of the parts shall be performed only when the curing time for the parts has been reached. The inspection for control of each cavity during production shall be performed on the above quantities from each cavity after production of each 5000 parts or at the end of each shift, providing the number of parts produced during that shift is less than 5000 parts. Of the five (5) samples, one (1) sample shall be the last part produced. Parts that fail to comply with dimensional requirements after dimensional stability has been attained shall be classed defective.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:55Z
Check the source to verify that this is the current version before use.

If any defective parts are found during qualification of the cavity the cavity producing the defective part will not be used in production. If any defective parts are found when inspection is performed for control of the cavity, the cavity producing the defective part shall be removed from production. Further, that portion of production since the last control check shall be returned to the contractor for corrective action.

All cavities formerly removed from production because of some fault may, after reworking, be returned to production providing they pass the qualification test as above. The contractor may request a change of inspection frequency providing he presents objective evidence to substantiate the request to the Contracting Officer.

NOTE: To establish a curing time, dimensionally check ten (10) parts from each cavity at periodic intervals (e.g., every 30 min, 60 min, etc.), until dimensional stability is attained. The curing time will be from the time the part comes out of the mold until dimensional stability is attained. The inspection data used in determining the curing time shall be sent to U.S. Army Armament Research and Development Center (ARDC), Dover, NJ 07801-5001, ATTN: AMSMC-QAT-M. If there is a change in material, cycle time, or if a cavity is reworked, or a new cavity is used, a new curing time shall be established and approved.

4.4.3.3 Dimensional control of stamped parts. In place of the normal sampling associated with the Classification of Defects, and with the approval of the Contracting Officer, a sample of at least ten (10) parts may be dimensionally inspected to qualify the tool used in the stamping process for use in production. In addition, a portion of each hour's production for dimensional inspection as a control of the tool during production.

If any defective parts are found during qualification of the tool, the tool producing the defective part shall not be used in production.

If any defective parts are found when inspection is performed for control of the tool, the tool producing the defective part shall be removed from production. Further, that portion of production since the last tool control check shall be returned to the contractor for corrective action.

All tools removed from production because of some fault, may, after reworking, be returned to production providing they pass the qualification test above. The contractor may request a change of inspection frequency providing he presents objective evidence to the Contracting Officer to substantiate the request.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:55Z
Check the source to verify that this is the current version before use.

4.4.3.4 Alternate method of inspection of dimensional characteristics. In place of the normal sampling associated with the Classification of Defects, and with the approval of the Contracting Officer, a sample of at least ten (10) parts shall be dimensional inspected to qualify the machine used in the fabricating of the part for use in production. In addition, a random sample of five (5) parts shall be selected from the last portion of each hour's production for dimensional inspection as a control of the machine during production.

If any defective parts are found during qualification of the machine, the machine producing the defective shall not be used in production until adjustments or rework of the machine are made to produce acceptable parts.

If any defective parts are found when inspection is performed for control of the machine, the machine producing the defective part shall be removed from production. Further, that portion of production since the last machine control check shall be returned to the contractor for corrective action.

All machines removed from production because of some fault, may, after reworking, or readjustment, be returned to production providing they pass the qualification test above. The contractor may request a change of inspection frequency providing he presents objective evidence to the Contracting Officer to substantiate the request.

4.4.4 Inspection equipment. The inspection equipment required to perform the inspections and tests prescribed in this specification is identified in the "Paragraph Reference/Inspection Method" column in the tables starting with paragraph 4.4.2.1, and the test method paragraph (See 4.5). The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078 and 6.2 herein.

4.5 Methods of inspection.

4.5.1 Salt spray test. The salt spray test shall be performed utilizing the equipment, methods and procedures specified in ASTM B-117. Exposure time and percent sodium chloride solution shall be as specified on the applicable drawing. If not on the drawing, exposure time shall be not less than two (2) hours using an atomized sodium chloride solution of five percent (5%).

4.5.2 Internal air tests.

4.5.2.1 Applied through filling hole. The metal parts assembly shall be immersed in water and subjected to an internal air pressure of 10 psig, min., for a period of 10 seconds, min., applied through the filling hole in the body. Observation shall be made for leakage as evidenced by escaping air bubbles. Defective assemblies shall be removed from the lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:55Z
Check the source to verify that this is the current version before use.

4.5.2.2 Applied through booster well. The metal parts assembly, less firing pin assembly, shall be fitted with an approved airtight cap in place of the charge cap. The airtight cap shall not cover the brazed joint between the cap adapter and the cover, and shall not damage the cover. The cover end of the mine shall be immersed in water to a depth of approximately one inch and an internal air pressure of 4 psig, min., applied for a period of 10 seconds, min., through the booster well of the delay tube. Observation shall be made for leakage as evidenced by escaping air bubbles. Defective assemblies shall be removed from the lot.

4.5.3 Link pull. The metal parts assembly shall be affixed to the inspection equipment as referenced in 4.4.4 and a tensile pull of 400 pounds, min., applied perpendicularly to the plane of base of the link for 10 sec. min. The pull shall be evenly distributed over the link and weld.

4.5.4 Handle pull. The metal parts assembly, with handle attached, shall be affixed to the inspection equipment as referenced in 4.4.4 and a 150 pound pull applied for 10 sec. min. The force shall be applied to the center of the handle and pulled perpendicular to the surface between the handle lugs.

4.5.5 Load deflection. The firing pin assembly, with the retaining ring in the delay tube, shall be affixed to the inspection equipment referenced in 4.4.4 and push-test under a uniform load applied at a rate of one (1) inch per minute.

4.5.6 Waterproofness of cup. The open end of the cup shall be affixed to an appropriate test fixture in accordance with 4.4.4.

4.5.7 Shearing of cover. Metal parts assemblies shall be filled with dry sand (specific gravity 1.44-1.76), unless otherwise specified, so as to provide rigid support to the mine. The loaded propellant cup assembly, M607 combination mine fuze, and a primer-loaded delay assembly, shall be assembled to the metal parts assembly as indicated on the applicable drawing. The assembly shall then be emplaced in firm ground so that the top of the mine cover is three inches below the top of the ground. Soil shall be tamped firmly around the mine with the plastic collar being kept free from earth.

CAUTION: The fuze shall be armed by remote control with all personnel behind a suitable barricade. The fuze shall be armed by attaching a lanyard to the safety pin ring and around the safety support in such a manner that a pull on the lanyard will entirely remove the safety pin before any tension is placed on that portion of the lanyard which is connected to the safety support. Before pulling the lanyard, squeeze together the ends of the safety pin so that it will slide easily out of the pin hole. Actuate the fuze by tilting the fuze extension rod. For information only, the load required to function the fuze is 5 1/4 plus or minus 1 1/2 pounds when activating the fuze by tilting the extension rod at the extreme end.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:55Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 Preservation - packaging.

5.1.1 Level C. The metal parts for Mine, AT, M21, shall be packaged for shipment as follows:

5.1.1.1 Metal parts assembly (Dwg. 8831343). Five (5) metal parts assemblies shall be packed in a 175 lb. min. bursting strength, Type CF, Class Domestic, B or C flute, Style RSC fiberboard box in accordance with Spec PPP-B-636. The inside dimensions shall be: 21 15/16 by 9 7/16 by 9 3/16 inches. A 175 lb. min., "B" flute, fiberboard spacer, 12 1/4 by 9 3/8 inches shall be placed between bottom inner flaps and top inner flaps. Five assemblies shall be packed on edge with an 8 7/8 inch square, 1/8 inch thick commercial chipboard filler between each assembly. Suitable chipboard filler material shall be added as required to insure tight packing.

5.1.1.2 Closing plug assembly (Dwg. 8831346). Five (500) hundred closing plug assemblies shall be packed within a half slotted loose partition fabricated from B or C flute, 175 lb. min. bursting strength corrugated fiberboard and inserted into a Type CF, Class Domestic, B or C flute, Style RSC fiberboard box in accordance with Spec PPP-B-636. Inside dimensions of box shall be 14 7/8 by 7 7/16 by 2 11/16 inches. The partition shall be a slide fit in box in a pattern of 10 by 5, and 2 5/8 inches high. Ten assemblies shall be packed in each cell. When necessary, insert chipboard filler material as required for tight packing.

5.1.1.3 Cap, charge (Dwg. 8862478). Six hundred and twenty-five (625) charge caps shall be packed within half slotted, B or C flute, 175 lb. min. test corrugated fiberboard loose partitions within a 175 lb. min. bursting strength, Type CF, Class Domestic, B or C flute, Style RSC fiberboard box in accordance with Spec PPP-B-636. Inside dimensions of box shall be 17 7/16 by 17 7/16 by 17 1/4 inches. Each of the five partitions in a pattern of 5 by 5 shall be a slide fit in the box and 3 11/32 inches high. A 1/8 inch thick commercial chipboard pad, 17 5/16 by 17 5/16 inches shall be placed between partitions. Five assemblies shall be packed in each cell. A pad shall be inserted and the four remaining layers packed in a similar manner. Suitable filler material shall be added as required to insure tight packing.

5.1.1.4 Cap, closing (Dwg. 8831347). Twenty-five hundred (2500) closing caps shall be packed in a 175 lb. min. bursting strength, Type CF, Class Domestic, B or C flute, Style RSC fiberboard box in accordance with PPP-B-636. Inside dimensions shall be 13 by 13 by 12 1/4 inches. Suitable filler material shall be added as required to insure tight packing.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:55Z
Check the source to verify that this is the current version before use.

5.1.1.5 Holder, delay (Dwg. 8831359). One thousand, two hundred and fifty (1250) delay holders shall be packed in a Type CF, Class Domestic, B or C flute, Style RSC, 175 lb test corrugated fiberboard box in accordance with PPP-B-636. Inside dimensions shall be 14 3/4 by 14 7/16 by 10 inches. Ten holders shall be packed in a convolute or spirally wound chipboard tube fabricated in accordance with 3.3 of Spec MIL-C-2439. Inside dimensions shall be 13/16 plus or minus 1/32 inches, outside dimensions 1 1/8-1/32 by 14 5/16 inches in length. One hundred and twenty-five tubes shall be packed crosswise in box in alternate layers of 13 and 12. Suitable chipboard fillers shall be added as required for tight packing.

5.1.1.6 Cup (Dwg. 8831354). Six-hundred and twenty-five (625) cups shall be packed in a 175 lb min. bursting strength, Type CF, Class Domestic, B or C flute, Style RSC fiberboard box in accordance with PPP-B-636. Inside dimensions shall be 18 by 18 by 13 7/8 inches. Suitable filler material shall be added as required for tight packing.

5.1.1.7 Shipping plug assembly (Dwg. 8831344). One thousand two hundred and fifty (1250) plugs shall be packed in a Type CF, Class Domestic, B or C flute, Style RSC, 175 lb. test corrugated fiberboard box in accordance with PPP-B-636. Inside dimensions shall be 14 3/4 by 10 3/16 by 5 1/2 inches. Ten layers shall be packed, 125 plugs per layer, in alternate rows of 13 and 12, the hex flats all parallel, with a filler between layers. Fillers shall be chipboard, commercial, 1/8 inch thick, 14 1/2 by 10 inches. Suitable chipboard fillers shall be added as required for tight packing.

5.1.1.8 Lid (Dwg. 8831355). Twenty five hundred (2500) lids shall be packed in a 175 lb. min. bursting strength, Type CF, Class Domestic, B or C flute, Style RSC, fiberboard box in accordance with PPP-B-636. Inside dimensions shall be 16 by 16 by 15 9/16 inches. Suitable filler material shall be added as required to insure tight packing.

5.1.1.9 Wrench M26 (Dwg. 8831380). Two hundred (200) wrenches shall be packed in a 175 lb. min. bursting strength, Type CF, Class Domestic, B or C flute, Style RSC fiberboard box in accordance with PPP-B-636. Inside dimensions shall be 10 5/8 by 7 13/16 by 9 1/2 inches. Fifty wrenches shall be nested on edge, with jaws together, alternating the direction of each jaw so that the angular portion of handles form same pattern facing the same direction. A 1/8 inch thick commercial chipboard pad 10 3/8 by 6 7/16 inches shall be inserted atop wrenches. Three remaining layers shall be packed in a similar manner. Suitable dunnage shall be added in each layer and on top of contents as required for tight packing.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:55Z
Check the source to verify that this is the current version before use.

5.1.1.10 Cup, relay (Dwg. 8831361). Twenty-five hundred (2500) relay cups shall be packaged in a 125 lb. min. bursting strength, Type CF, Class Domestic, B or C flute, Style RSC fiberboard box in accordance with PPP-B-636. Inside dimensions shall be 5 by 5 by 4 1/8 inches. Suitable filler material shall be added as required for tight packing.

5.1.1.11 Holder, primer (Dwg. 8831358). Twenty-five hundred (2500) primer holders shall be packaged in a .048 inch thick, Type I or IV, Class B, Style 4 paperboard set-up box with five interior trays, Specification PPP-B-676. Trays shall be along the width of box. Five hundred holders shall be placed in each tray. Inside dimensions of box shall be 6 5/16 by 6 1/8 by 6 inches. Suitable filler material shall be added as required to insure tight packing.

5.2 Construction requirements.

5.2.1 Fiberboard box. The construction of the fiberboard boxes and the material requirements of the fiberboard boxes and partitions shall comply with PPP-B-636. When assembled, the corrugations of the boxes and partitions shall parallel the box depth. The manufacturer's joint on the box shall be secured with reinforced paper tape or metal stapled or stitched. Spacing of staples of stitches shall not average over 1 1/2 inches apart, center to center. A manufacturing tolerance of plus or minus 1/32 inch is permissible. The parts manufacturer shall be furnished preproduction samples of all packing materials so that proper fit of packing materials and metal parts can be determined. Minor modifications of packing material dimensions to provide a proper fit of all parts, as determined to be necessary by examination of sample packs, are permissible.

5.2.2 Set-up box. The construction of set-up boxes with interior trays and the material requirements shall comply with PPP-B-676.

5.3 Sealing. The set-up boxes shall be sealed in accordance with Appendix of PPP-B-676. The fiberboard box flaps shall be secured with gummed Kraft paper not less than 3 inches wide, complying with PPP-T-45, Type III, Class 2 tape. The tape shall be centered the full length of the outer flap seams, and extend over each end of the box at least 2 inches. The flap edge seams shall be similarly sealed with the tape extending at least 3 inches along the corners of the box. Tape shall be properly moistened and sufficiently compressed to insure tight adhesion to the fiberboard box.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:55Z
Check the source to verify that this is the current version before use.

5.4 Extra parts packing. When feasible for small and light-weight parts, the entire packing lot quantity, including the percentage of extra parts, shall be packed in the prime container. For medium and heavy weight parts the required quantity shall be packed in the prime container, and the extra parts provided by furnishing the proper number of prime containers.

5.5 Shipping. When component parts from more than one lot are shipped as a carload, each lot shall be kept separate and the division between lots cearly indicated to prevent mixing of lots in transit.

5.6 Marking. Marking of the boxes shall comply with Standard MIL-STD-129.

6. NOTES

6.1 Ordering data. See MIL-A-48078.

6.2 Data cards. (See MIL-A-48078). Distribution of data cards shall include the following: Commander, U S ARDC, ATTN: AMSMC-QAT-M(D), Dover, New Jersey 07801-5001.

6.3 Submission of inspection equipment designs for approval. (See MIL-A-48078). Equipment designs shall be submitted as required to: Commander, U S ARDC, ATTN: AMSMC-QAT-I(D), Dover, New Jersey 07801-5001. Request letter of submittal should state contractor, contract number, specification number, item nomenclature, and classification of defects and tests paragraph number.

6.4 Drawings. Drawings listed in section 2 of this specification under the heading US Army Armament Research and Development Center (ARDC) may also include drawings prepared by, and identified as, US Army Armament Research and Development Command (ARRADCOM), Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal or Picatinny Arsenal drawings. Technical data originally prepared by these activities are now under the cognizance of ARDC.

6.5 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue, due to the extensiveness of the changes.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:55Z
Check the source to verify that this is the current version before use.

6.6 Subject term (key word) listing.

Mine, AT
Firing Pin Assembly
Link Pull
Handle Pull
Closing Plug Assembly
Wrench, M26

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1345-A263)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:55Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

COMMANDER
US ARMY ARMAMENT RSCH DEV & ENGR CENTER
ATTN: AMSMC-QA
DOVER, NJ 07801 5001

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:55Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-M-45406C (AR)	MINE, AT: M21, PARTS FOR

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR ☐ USER ☐ MANUFACTURER ☐ OTHER *(Specify)*: _____
b. ADDRESS *(Street, City, State, ZIP Code)*	

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

Source: https://assist.dla.mil -- Downloaded: 202610-22T02:55Z
Check the source to verify that this is the current version before use.