MIL-T-45381D
19 November 1984
SUPERSEDING
MIL-T-45381C
8 January 1979

MILITARY SPECIFICATION

TRAILERS, CABLE REEL, COMMERCIAL

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers commercial, single through axle or stub axles, cable-reel trailers designed to carry one reel. Trailers procured under this specification are commercial items which shall be warranted by the manufacturer as specified in procurement documents.

1.2 Classification. Trailer shall be one of the following types, as specified (see 6.2):

Type I - Tilt loading.
Type II - Power loading.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. Unless otherwise specified (see 6.2), the following specifications, standards, and handbooks of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation, form a part of this specification to the extent specified herein.

STANDARDS

MILITARY

MIL-STD-209 - Slinging and Tiedown Provisions for Lifting and Tying Down Military Equipment.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commanding Officer (Code 156), Naval Construction Battalion Center, Port Hueneme, CA 93043, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 2330

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:51Z
Check the source to verify that this is the current version before use.

MIL-STD-281 - Automobile, Trucks, Truck-Tractors, Trailer and Trailer Dollies; Preservation and Packaging of.
MIL-STD-1223 - Non-tactical Wheeled Vehicles Treatment, Painting, Rustproofing, Undercoating, Identification Marking, and Data Plates Standards.
MS51337 - Coupler, Drawbar, Ring-Heavy Duty.
MS75021 - Connector, Receptacle, Electrical-, 12 Contact, Intervehicular, 24 Volt, Waterproof.

(Copies of specifications, standards, handbooks, drawings, and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.1.2 Other Government documents, drawings, and publications. The following other Government documents form a part of this specification to the extent specified herein.

DEPARTMENT OF TRANSPORTATION (DoT)

Federal Motor Carrier Safety Regulations.

(Application for copies should be addressed to the Superintendent of Documents, Government Printing Office, Washington, DC 20402.)

2.2 Other publications. The following document(s) form a part of this specification to the extent specified herein. The issues of the documents which are indicated as DoD adopted shall be the issue listed in the current DoDISS and the supplement thereto, if applicable.

SOCIETY OF AUTOMOTIVE ENGINEERS, INC. (SAE)

SAE Handbook.

(Application for copies should be addressed to the Society of Automotive Engineers, Inc., 400 Commonwealth Drive, Warrendale, PA 15096.)

TIRE AND RIM ASSOCIATION, INC. (TRA)

TRA Yearbook.

(Application for copies should be addressed to the Tire and Rim Association, Inc., 3200 West Market Street, Akron, OH 44313.)

(Industry association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

Source: https://assist.dla.mil -- Downloaded: 202640-22T02:51Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Description. Trailer shall be a commercial vehicle of manufacturer's latest standard single-reel design and shall include the requirements specified herein. Trailer shall have an all-steel frame with towbar, spring suspension, reel holders, landing leg, stub or full-width axle, brakes, pneumatic tires, standard lighting system, and all other parts and accessories to make a complete and serviceable unit.

3.2 First production trailer. When specified (see 6.2), the contractor shall furnish a trailer for first production trailer inspection (see 4.2.1).

3.3 Standard commercial product. The trailer shall, as a minimum, be in accordance with the requirements of this specification and shall be the manufacturer's standard commercial product. Additional or better features which are not specifically prohibited by this specification but which are a part of the manufacturer's standard commercial product, shall be included in the trailer being furnished. A standard commercial product is a product which has been sold or is being currently offered for sale on the commercial market through advertisements or manufacturer's catalogs or brochures and represents the latest production model.

3.4 Materials. Materials used shall be free from defects which would adversely affect the performance or maintainability of individual components or of the overall assembly. Materials not specified herein shall be of the same quality used for the intended purpose in commercial practice. Unless otherwise specified herein, all equipment, material, and articles incorporated in the work covered by this specification are to be new and fabricated using materials produced from recovered materials to the maximum extent possible without jeopardizing the intended use. The term "recovered materials" means materials which have been collected or recovered from solid waste and reprocessed to become a source of raw materials, as opposed to virgin raw materials. None of the above shall be interpreted to mean that the use of used or rebuilt products are allowed under this specification unless otherwise specified.

3.5 Interchangeability. All trailers of the same classification furnished with similar options under a specific contract shall be identical to the extent necessary to insure interchangeability of component parts, assemblies, accessories, and spare parts.

3.6 Design and construction. Design and construction of the trailer shall be such that no member or part shall show evidence of failure or permanent deformation under severe service conditions. Trailer shall be type I or type II as specified (see 6.2).

3.6.1 Type I. Type I trailer shall be designed for loading by tilting the trailer backwards.

3.6.2 Type II. Type II trailer shall be provided with hydraulically operated lifting mechanism to enable reels of different size to be mounted without tilting the trailer.

Source: https://assist.dla.mil -- Downloaded: 20260410-22T02:51Z
Check the source to verify that this is the current version before use.

3.7 Performance.

3.7.1 Travel speed. Trailer, fully equipped and loaded to rated payload capacity (see 3.9), shall be capable of being towed over unimproved roads and reasonably hard uneven terrain at a speed of 10 miles per hour (mph), and over improved roads at speeds as great as 50 mph (see 6.4).

3.7.2 Turning ability. When towed, the trailer shall be capable of forming a 70 degree angle with the towing vehicle without cramping or damage to trailer or towing vehicle.

3.7.3 Tracking ability. Trailer shall not exceed the allowance for tracking deviation specified in DoT Federal Motor Carrier Safety Regulations, section 393.70(a).

3.7.4 Brake performance. The brakes shall comply with the performance requirements specified in DoT Federal Motor Carrier Safety Regulations, section 393.52.

3.8 Dimensions and clearances.

3.8.1 Overall height. Overall height of the trailer (less reel) shall be the minimum practicable.

3.8.2 Width. The overall width of the trailer shall be the minimum practicable for the reel size specified (see 3.8.4), but shall not exceed 96 inches.

3.8.3 Ground clearance. Ground clearance shall be not less than 9 inches with maximum sized reel in transport position.

3.8.4 Reel width. Unless otherwise specified (see 6.2), trailer shall accommodate cable reels up to 60 inches in width.

3.8.5 Reel diameter. Trailer shall accommodate cable reels from 24 inches to 108 inches in diameter.

3.9 Rated payload capacity. Unless otherwise specified (see 6.2), the rated payload capacity shall be not less than 10,000 pounds (lb) for type I, and not less than 15,000 lb for type II.

3.10 Components.

3.10.1 Frame and towbar. Frame and towbar shall be of sturdy integrated construction, fabricated from steel tubing or structural steel sections, and braced to prevent distortion under operating conditions specified in 3.7. Length of the towbar shall be sufficient to satisfy the turning ability requirement of 3.7.2. Towbar shall conform to applicable requirements of DoT Federal Motor Carrier Safety Regulations, section 393.71(h).

3.10.2 Coupler ring. Unless otherwise specified (see 6.2), coupler ring shall be manufacturer's standard of 3 inch inside diameter. When specified

Source: https://assist.dla.mil -- Downloaded: 202610-22T02:51Z
Check the source to verify that this is the current version before use.

(see 6.2), trailer towbar shall be provided with coupler ring conforming to MS51337. Provisions shall be made to adjust the height of the coupling device with the trailer in a horizontal position on level ground. The coupler shall be adjustable from a minimum height of 18 inches to a maximum of 26 inches. The coupler shall have not less than four adjustment positions.

3.10.3 Axle and suspension. Unless otherwise specified (see 6.2), single through axle, tandem axle or stub axles shall be the manufacturer's current standard type, adequate to support the specified maximum load. Unless the loaded reel is spring suspended, the axle suspension system shall be of a springing capacity to sustain the rated payload under the performance characteristics specified herein without transmitting damaging shock to the trailer.

3.10.4 Reel spindle. Reel spindle shall be 2-1/2 inches in diameter and shall be provided with adjustable cone-shaped collars or guides for various reel widths. On type II trailer, the spindle shall be hydraulically adjustable for height from reel holders to enable leveling of the spindle when trailer is on uneven ground or embankment.

3.10.5 Reel holders. Construction of reel holders shall be such as to enable the reel to be picked up and mounted on the trailer by one man without the aid of a separate winch or crane.

3.10.6 Landing leg. The landing leg shall be adjustable for vertical rise, shall be capable of supporting the loaded trailer in a level attitude without tipping, and shall be provided with a safety lock. On type II trailer, the leg shall be hydraulically operated. Unless otherwise specified (see 6.2), four permanently installed, manually operated stabilizer jacks shall be provided on the type I trailer. Two jacks shall be located at the front and two at the rear to permit four-point stabilization of the trailer.

3.10.7 Cable payout brake. Cable payout brake shall be provided with an adjustment to control braking action.

3.10.8 Safety chain. Trailer shall be equipped with a safety chain or steel cable conforming to DoT Motor Carrier Safety Regulations, sections 393.70(d) and SAE J697.

3.10.9 Wheels and rims. Wheels shall be the manufacturer's current standard. The rim size shall be as recommended by the TRA for the size of tire furnished.

3.10.10 Tires and tubes. Tires shall be tube or tubeless type with highway tread. Tires shall be of rated capacity at least equal to the load imposed on each tire measured at the wheel at the ground, with trailer loaded as specified in 3.9. When tube-type tires are furnished, tubes shall be of heavy-duty type and of proper size for tires furnished. Tire flaps shall be provided for tube-type tires in accordance with TRA recommendations.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:51Z
Check the source to verify that this is the current version before use.

3.10.11 Fenders and splash guards. Trailer shall be equipped with fenders and splash guards. Fenders shall withstand loads of 200 pound-force per square foot without evidence of permanent deformation. Splash and stone-throw protection shall be in accordance with SAE J682.

3.10.12 Rear towbar. When specified (see 6.2), the trailer shall be equipped with a detachable rear towbar or pintle for multiple hookup.

3.10.13 Service brakes. Service brakes shall conform to DoT Federal Motor Carrier Safety Regulations, section 393.40 through 393.43 and 393.45 through 393.47.

3.10.13.1 Electric brakes. Unless otherwise specified (see 6.2), trailer shall be provided with electric-type brakes wired through the seven contact lighting socket specified in 3.10.16. An electric brake controller shall be furnished for subsequent installation in the towing vehicle. Brakes shall be operable on the 12-volt (V) system of the towing vehicle. Provisions for mounting and connecting the battery, required to operate the brakes in the event of a breakaway from the towing vehicle, shall be furnished. Battery shall not be required.

3.10.13.2 Hydraulic brakes. When specified (see 6.2), trailer shall be equipped with hydraulic vacuum brakes or air-over-hydraulic brakes of manufacturer's current standard type.

3.10.14 Parking brake. When specified (see 6.2), the trailer shall be provided with a hand-lever-operated parking brake, capable of holding the trailer, loaded with the rated payload, on a 20 percent grade on a dry hard surface, when uncoupled from the towing vehicle and headed up or down the incline. The parking brake shall conform to DoT Federal Motor Carrier Safety Regulation 393.41. The brake lever shall not require more than 30 lb of effort for application and release. When brake cables are used, they shall be of corrosion-resistant steel. Provisions shall be made for slack adjustment. Lubrication fittings shall be provided.

3.10.15 Chock blocks and cradles. When specified (see 6.2), two pairs of wood or steel chock blocks with captive chains and two cradles shall be furnished and installed on the trailer. The hook of each captive chain shall be secured to the cradle. The captive chains shall be long enough to be wrapped around the cradle to hold the chocks in place during travel, and to allow the wheels to be chocked in front and behind while parked. The chock blocks shall be of sufficient size to prevent trailer movement during reel loading operations and while parked and headed either up or down a 20 percent slope.

3.10.16 Lighting system. The lighting system shall be of 12-V potential and shall conform to DoT Federal Motor Carrier Safety Regulations, sections 393.14, 393.20, 393.22, 393.23, 393.25, through 393.29, 393.32, and 393.33 as applicable. Wiring pattern, wire color code, and coupling connector receptacle shall conform to SAE J560. The receptacle shall be located in accordance with SAE J702. Turn signal lamps shall conform to SAE J588. Taillights and turn signals shall be guarded and wiring shall be routed and anchored for protection from damage.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:51Z
Check the source to verify that this is the current version before use.

3.10.17 Receptacle system, 24-V. When specified (see 6.2), the trailer shall be equipped with one 12-contact receptacle with cover and one 7-contact receptacle with cover installed at the front of the trailer. The 12-contact receptacle shall conform to MS75021, part No. MS75021-1. The 7-contact receptacle shall conform to SAE J560 round socket for jumper cable. The 12-contact receptacle shall be provided with resistance to each circuit to reduce the voltage of a tactical Military design towing vehicle from 24 volts to 12 V. The 7-contact socket shall be wired in accordance with SAE J560 to supply 12 V directly to the trailer circuits. The 24-V, 12-contact receptacle shall be connected through the necessary resistors into the 12-V trailer circuits as follows:

A - Do not connect.
B - Connect to circuit No. 3.
C - Do not connect.
D - Connect to circuit No. 1.
E - Connect to circuits No. 2 and 6.
F - Do not connect.
H - Do not connect.
J - Connect to circuit No. 5.
K - Connect to circuit No. 7.
L - Do not connect.
M - Do not connect.
N - Do not connect.

Circuits B and J on tactical truck-tractors are combination stop and turn indicator circuits. The normal 12-V turn signal lights will function both as turn signals and stoplights and the normal 12-V stoplights will not be in operation when the trailer is connected to a towing vehicle with a 24-volt power supply. Because of this condition, the No. 4 stoplight circuit is not connected to the 24-V, 12-contact receptacle.

3.11 Lubrication. Unless otherwise specified (see 6.2), means for lubrication shall be in accordance with the manufacturer's standard practice. The lubricating points shall be easily visible and accessible. All parts requiring lubrication shall be lubricated as specified in 3.12. Hydraulic lubrication fittings shall be in accordance with SAE J534. Where high pressure lubricating equipment is used, (1,000 pound-force per square inch or higher, will damage grease seals or other parts), a suitable warning shall be affixed to the equipment in a conspicuous location.

3.12 Servicing and adjusting. Prior to acceptance of the trailer by the Government inspector, the contractor shall service and adjust the trailer for immediate operational use. The servicing and adjusting shall include at least the following: inflation of all tires, adjustment of brakes, proper functioning of all lighting, and complete lubrication with grades of lubricants recommended for ambient temperature at the delivery point. The trailer shall be conspicuously tagged to identify the lubricants and their temperature range.

3.13 Lifting and tiedown attachments. Unless otherwise specified (see 6.2), the trailer shall be equipped with lifting and tiedown

Source: https://assist.dla.mil -- Downloaded: 202640-22T02:51Z
Check the source to verify that this is the currentversion before use.

attachments. Lifting and tiedown attachments shall conform to type II or type III of MIL-STD-209. A nonferrous transportation plate shall be provided and mechanically attached to the trailer. Transportation plates shall be inscribed with a diagram showing the lifting attachments and lifting slings, the capacity of each attachment, and the required length and size of each sling cable. A silhouette of the item furnished showing the center of gravity shall be provided on the transportation plate. Tiedown attachments may be identified by stenciling or other suitable marking. Tiedown marking shall clearly indicate that the attachments are intended for the tiedown of the trailer on the carrier when shipped.

3.14 Treatment, painting, identification marking, and data plates. As specified by the procuring activity for the appropriate service (see 6.2), treatment, painting, identification marking, and data plates shall be in accordance with MIL-STD-1223.

3.14.1 Rustproofing. When specified (see 6.2), the vehicle shall be rustproofed in accordance with MIL-STD-1223.

3.14.2 Wood treatment. Wood, except apitong, shall be treated in accordance with MIL-STD-1223.

3.15 Workmanship.

3.15.1 Steel fabrication.. The steel used in fabrication shall be free from kinks, sharp bends, and other conditions which would be deleterious to the finished product. Manufacturing processes shall not reduce the strength of the steel to a value less than intended by the design. Manufacturing processes shall be done neatly and accurately. All bends shall be made by controlled means to insure uniformity of size and shape.

3.15.2 Bolted connections. Boltholes shall be accurately punched or drilled and shall have the burrs removed. Washers or lockwashers shall be provided in accordance with good commercial practice, and all bolts, nuts, and screws shall be tight.

3.15.3 Riveted connections. Rivet holes shall be accurately punched or drilled and shall have the burrs removed. Rivets shall be driven with pressure tools and shall completely fill the holes. Rivet heads, when not countersunk or flattened, shall be of approved shape and of uniform size for the same diameter of rivet. Rivet heads shall be full, neatly made, concentric with the rivet holes, and in full contact with the surface of the member.

3.15.4 Welding. Welding procedures shall be in accordance with a nationally recognized welding code. The surface of parts to be welded shall be free from rust, scale, paint, grease, or other foreign matter. Welds shall be of sufficient size and shape to develop the full strength of the parts connected by the welds. Welds shall transmit stress without permanent deformation or failure when the parts connected by the weld are subjected to proof and service loadings.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:51Z
Check the source to verify that this is the current version before use.

3.15.5 Castings. All castings shall be sound and free from patching, misplaced coring, warping, or any other defect which reduces the castings ability to perform its intended function.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Component and material inspection. Components and materials shall be inspected in accordance with all the requirements specified herein and in applicable referenced documents.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First production trailer inspection (see 4.2.1).
b. Quality conformance inspection (see 4.2.2).

4.2.1 First production trailer inspection. The first production vehicle produced under the contract shall be inspected by the contractor at his plant under the direction and in the presence of Government representatives. This inspection shall include the examination of 4.3 and the tests of 4.4. The purpose of the inspection shall be to determine trailer conformity with the requirements of the contract. Acceptance of the first production trailer shall not constitute a waiver by the Government of its right under the provisions of the contract.

4.2.2 Quality conformance inspection. The quality conformance inspection shall include the examination of 4.3, the tests of 4.6, and the packaging inspection of 4.7.

4.3 Examination. Each trailer shall be examined for compliance with the requirements specified in section 3 of this specification. Any redesign or modification of the contractor's standard product to comply with specified requirements, or any necessary redesign or modification following failure to meet specified requirements shall receive particular attention for adequacy and suitability. This element of inspection shall encompass all visual examinations and dimensional measurements. Noncompliance with any specified requirements or presence of one or more defects preventing or lessening maximum efficiency shall constitute cause for rejection.

4.4 First production trailer tests. When a first production trailer is required, the first trailer of each type shall be subjected to the tests by

Source: https://assist.dla.mil -- Downloaded: 202610-22T02:51Z
Check the source to verify that this is the currentversion before use.

the contractor as specified in 4.4.1 through 4.4.6 and when applicable, 4.4.7 through 4.4.9. Failure to pass any phase of the required tests shall be cause for the Government to refuse acceptance of all trailers until corrective action has been taken.

4.4.1 Trailer weight. The trailer shall be weighed to determine net weight and distribution of net weight on coupler ring and axle. The weight distribution shall be computed using net weight and the rated payload. Calculated imposed loads on coupler ring and axle shall be utilized to ascertain that the tires, axle, and suspension are of adequate capacity to meet the contract requirements.

4.4.2 Towing tests. The fully equipped trailer shall be towed over roads and terrain specified in 3.7.1, at a minimum distance of 50 miles, loaded with rated payload and 30 miles without load. At least 20 percent of the distance shall be over unimproved roads and reasonably hard terrain. Towing speeds shall be as specified in 3.7.1. Tracking shall be checked for conformance to 3.7.3. Trailer shall be observed during the run and examined after the test for evidence of misalignment, part failure, or other defects.

4.4.3 Turning ability test. The trailer, loaded with rated payload, shall be tested for turning ability to verify compliance with 3.7.2.

4.4.4 Service brake test. Service brakes shall be tested with rated payload on the trailer to verify compliance with the requirements of 3.7.4. Breakaway situation shall be simulated to verify braking ability upon breakaway.

4.4.5 Mounted equipment test. All mounted equipment shall be maneuvered to verify conformance to this specification. All adjustments shall be tested within their range for interference or defects.

4.4.6 Pick up and loading test. Pick up and loading of the reel shall be performed not less than five times to verify conformance to 3.10.5.

4.4.7 Parking brake test. Parking brake, when required, shall be tested to verify conformance to the requirements of 3.10.14.

4.4.8 Chock block test. When chock blocks are required, test shall be performed to verify conformance to 3.10.15.

4.4.9 Lifting and tiedown attachment tests. When required, the lifting and tiedown attachments shall be tested to conform to 3.13.

4.5 Production sample. Upon acceptance of the first production trailer it shall remain at the manufacturing facility as a production sample and shall be the last trailer shipped on the contract. The contractor shall maintain the trailer in a serviceable condition for the duration of the contract.

4.6 Production unit tests. The contractor's testing system shall, as a minimum, assure that the trailer is capable of meeting the performance

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:51Z
Check the source to verify that this is the current version before use.

requirements specified herein. The trailer shall be exercised to assure brake adjustment, light operation, landing leg operation, tracking ability, and reel pickup and loading. These operations shall be made as a final inspection check.

4.7 Packaging inspection. The trailer shall be inspected to verify conformance to the requirements of section 5.

5. PACKAGING

5.1 Trailer processing. The equipment shall be preserved and packaged in accordance with the contractor's standard practice. When specified (see 6.2), equipment shall be preserved and packaged in accordance with the mobile requirements of MIL-STD-281 with the level of preservation and packaging as specified (see 6.2).

6. NOTES

6.1 Intended use. Trailer covered by this specification is intended for use by the Government in transporting and handling of cable reels, and for use in cable-laying operations.

6.2 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number, and date of this specification.
b. Type of trailer required (see 1.2 and 3.6).
c. When specifications standards and handbooks shall be other than specified (see 2.1.1).
d. When first production vehicle is required for inspection and approval (see 3.2).
e. If cable reel width is other than specified (see 3.8.4).
f. Rated payload if other than specified (see 3.9).
g. Coupler ring if other than specified (see 3.10.2).
h. When coupler ring shall conform to MS51337 (see 3.10.2).
i. Type of axle if not as specified (see 3.10.3).
j. If stabilizer jacks for type I trailer are other than specified (see 3.10.6).
k. When a detachable rear towbar is required (see 3.10.12).
l. Electric brakes if other than specified (see 3.10.13.1).
m. When hydraulic vacuum brakes or air-over-hydraulic brakes are required (see 3.10.13.2).
n. When parking brake is required (see 3.10.14).
o. When chock blocks and cradles are required (see 3.10.15).
p. When 24-V receptacle system is required (see 3.10.17).
q. If lubrication is other than specified (see 3.11).
r. If lifting and tiedown attachments are other than specified (see 3.13).
s. When instructions for appropriate service for painting and marking are required (see 3.14).
t. When rustproofing is required (see 3.14.1).
u. When preservation and packaging in accordance with MIL-STD-281 is required, and the level of preservation and packaging required (see 5.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:51Z
Check the source to verify that this is the current version before use.

6.3 Data requirements. When this specification is used in an acquisition which incorporates a DD Form 1423, Contract Data Requirements List (CDRL) and invokes the provisions of paragraph 52.227-7031 of the Federal Acquisition Regulations (FAR), the data requirements will be developed as specified by an approved Data Item Description (DD Form 1664) and delivered in accordance with the approved CDRL (DD Form 1423) incorporated into the contract. When the provisions of FAR 52.227-7031 are not invoked, the data shall be delivered in accordance with the contract requirements.

6.4 Definitions.

6.4.1 Improved road. An improved road is a smooth, hard-surfaced road, such as a concrete or asphalt-paved highway.

6.4.2 Unimproved road. An unimproved road is an unpaved, unstabilized road with an undulating surface having occasional chuckholes and exposed rocks.

6.5 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue, due to the extensiveness of the changes.

Custodians:

Army - AT
Navy - YD
Air Force - 99

Preparing Activity:

Navy - YD

(Project 2330-0833)

Review Activity:

Air Force - 84

User Activity:

Navy - MC

Source: https://assist.dla.mil -- Downloaded: 202640-22T02:51Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE NAVY
Commander
Naval Facilities Engineering Command
200 Stovall Street
Alexandria, VA 22332

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12503 WASHINGTON D C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE NAVY

Commanding Officer (156)
Naval Construction Battalion Center
Port Hueneme, CA 93043

Source: https://assist.dla.mil -- Downloaded: 2026l0-22T02:51Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

2330-0833

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-T-45381D	TRAILERS, CABLE REEL, COMMERCIAL

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*:

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426

PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:51Z
Check the source to verify that this is the current version before use.