| INCH-POUND |

MIL-T-45381E
30 March 1991
SUPERSEDING
MIL-T-45381D
19 November 1984

MILITARY SPECIFICATION

TRAILER, CABLE REEL

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers single stub axle or tandem stub axles, cable-reel trailers designed to carry one reel. Trailers procured under this specification are modified commercial items which shall be warranted by the manufacturer as specified in procurement documents.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Standards. The following standards form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

SPECIFICATIONS
MILITARY
MIL-V-62038 - Vehicles, Wheeled, Preparation Of For Shipment Or Storage.

| Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commanding Officer (Code 156), Naval Construction Battalion Center, Port Hueneme, CA 93043-5000, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter. |

AMSC N/A FSC 2330

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:51Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-209	- Slinging and Tiedown Provisions for Lifting and Tying Down Military Equipment.
MIL-STD-1223	- Non-tactical Wheeled Vehicles Treatment, Painting, Rustproofing, Undercoating, Identification Marking,
MIL-STD-62038	- Automobile, Trucks, Truck-Tractors, Trailer and Trailer Dollies; Preservation and Packaging of and Data Plates Standards.
MS51337	- Coupler, Drawbar, Ring-Heavy Duty.
MS75021	- Connector, Receptacle, Electrical-, 12 Contact, Intervehicular, 24 Volt, Waterproof.

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from Standardization Documents Order Desk, Bldg. 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.1.2 Other Government documents, and publications. The following other Government documents, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

DEPARTMENT OF TRANSPORTATION (DoT)

Federal Motor Carrier Safety Regulations.

(Application for copies should be addressed to the Superintendent of Documents, Government Printing Office, Washington, DC 20402.)

(Copies of specifications, standards, handbooks, drawings, publications, and other Government documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

2.2 Non-Government publications. The following document(s) form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents which are current on the date of the solicitation (see 6.2).

SOCIETY OF AUTOMOTIVE ENGINEERS, INC. (SAE)

SAE Standards and Recommended Practices

SAE J534 - lubrication Fittings.
SAE J560 - Seven-Conductor Electrical Connector for Truck-Trailer Jumper Cable.
SAE J588 - Turn Signal Lamps.
SAE J682 - Rear Wheel Splash and Stone Throw Protection (DoD adopted).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:51Z
Check the source to verify that this is the current version before use.

SAE J697 - Safety Chain of Full Trailers or Converter Dollies.
SAE J702 - Brake and Electrical Connection Location.

(Application for copies should be addressed to the Society of Automotive Engineers, Inc., 400 Commonwealth Drive, Warrendale, PA 15096.)

TIRE AND RIM ASSOCIATION, INC. (TRA)

TRA Yearbook.

(Application for copies should be addressed to the Tire and Rim Association, Inc., 3200 West Market Street, Akron, OH 44313.)

(Non-Government standards and other publications are normally available from the organizations that prepare or distribute the documents. These documents also may be available in or through libraries or other informational services.)

THE EUROPEAN TYRE AND RIM TECHNICAL ORGANIZATION (ETRTO) STANDARDS MANUAL

(Application for copies of the European tyre and Rim technical organization publications should be addressed to the European tyre and technical Organization, 32, avenue Brugmann, 1060 Brussels, Belgium.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein (except for associated detail specifications, specification sheets or MS standards), the text of this specification takes precedence. Nothing in this specification, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Description. Trailer shall be hydraulically, operated self-contained commercial vehicle of the manufacturer's latest standard single-reel design and shall include the requirements specified herein. Trailer shall have an all-steel uframe with towbar, spring suspension, reel holders, landing leg, stub axles, brakes, pneumatic tires, standard lighting system, and all other parts and accessories to make a complete and serviceable unit.

3.2 First production trailer. When specified (see 6.2), the contractor shall furnish a trailer for first production trailer inspection (see 4.2.1).

3.3 Modified commercial product. The trailer shall, as a minimum, be in accordance with the requirements of this specification and shall be the manufacturer's standard commercial product, Additional or better features which are not specifically prohibited by this specification but which are a part of the manufacturer's standard commercial product, shall be included in the trailer being furnished. A standard commercial product is a product which has been sold or is being currently offered for sale on the commercial market through advertisements or manufacturer's catalogs or brochures and represents the latest production model.

3.4 Materials. Materials used shall be free from defects which would adversely affect the performance or maintainability of individual components or

Source: https://assist.dla.mil -- Downloaded: 202610-22T02:51Z
Check the source to verify that this is the current version before use.

of the overall assembly. Materials not specified herein shall be of the same quality used for the intended purpose in commercial practice. Unless otherwise specified herein, all equipment, material, and articles incorporated in the work covered by this specification are to be new and fabricated using materials produced from recovered materials to the maximum extent possible without jeopardizing the intended use. The term "recovered materials" means materials which have been collected or recovered from solid waste and reprocessed to become a source of raw materials, as opposed to virgin raw materials. None of the above shall be interpreted to mean that the use of used or rebuilt products are allowed under this specification.

3.5 Interchangeability. All trailers of the same classification furnished with similar options under a specific contract shall be identical to the extent necessary to insure interchangeability of component parts, assemblies, accessories, and spare parts.

3.6 Design and construction. Design and construction of the trailer shall be such that no member or part shall show evidence of failure or permanent deformation under severe service conditions.

3.6.1 Hydraulics. The trailer shall be provided with hydraulically operated lifting mechanism to enable reels of different size to be mounted without tilting the trailer. The hydraulic system shall be self-contained, with hand pump, or gas engine powered, pump control valves, hydraulic cylinders, hydraulic tank and all hydraulic lines. All hydraulic controls shall be mounted in one location at the front of the trailer.

3.7 Performance.

3.7.1 Travel speed. Trailer, fully equipped and loaded to rated payload capacity (see 3.9), shall be capable of being towed over unimproved roads and reasonably hard uneven terrain at a speed of 10 miles per hour (mph), and over improved roads at speeds as great as 55 mph (see 6.4).

3.7.2 Turning ability. When towed, the trailer shall be capable of forming a 70 degree angle with the towing vehicle without cramping or damage to trailer or towing vehicle.

3.7.3 Tracking ability. Trailer shall not exceed the allowance for tracking deviation specified in DoT Federal Motor Carrier Safety Regulations, section 393.70(a).

3.7.4 Brake performance. The brakes shall comply with the performance requirements specified in DoT Federal Motor Carrier Safety Regulations, section 393.52.

3.8 Dimensions and clearances.

3.8.1 Overall height. Overall height of the trailer (less reel) shall be the minimum practicable.

3.8.2 Width. The overall width of the trailer shall be the minimum practicable for the reel size specified (see 3.8.4), but shall not exceed 96 inches.

Source: https://assist.dla.mil -- Downloaded: 202610-22T02:51Z
Check the source to verify that this is the current version before use.

3.8.3 Ground clearance. Ground clearance shall be not less than 9 inches with maximum sized reel in transport position.

3.8.4 Reel width. Unless otherwise specified (see 6.2), trailer shall accommodate cable reels up to 60 inches in width.

3.8.5 Reel diameter. Trailer shall accommodate cable reels from 24 inches to 108 inches in diameter.

3.9 Rated payload capacity. Unless otherwise specified (see 6.2), the rated payload capacity shall be not less than 15,000 lb.

3.10 Components.

3.10.1 Frame and towbar. Frame and towbar shall be of sturdy integrated construction, fabricated from steel tubing or structural steel sections, and braced to prevent distortion under operating conditions specified in 3.7. Length of the towbar shall be sufficient to satisfy the turning ability requirement of 3.7.2. Towbar shall conform to applicable requirements of DoT Federal Motor Carrier Safety Regulations, section 393.71(h).

3.10.2 Coupler ring. Unless otherwise specified (see 6.2), coupler ring shall be manufacturer's standard of 3 inch inside diameter. When specified (see 6.2), trailer towbar shall be provided with coupler ring conforming to MS51337. Provisions shall be made to adjust the height of the coupling device with the trailer in a horizontal position on level ground. The coupler shall be adjustable from a minimum height of 18 inches to a maximum of 26 inches. The coupler shall have not less than four adjustment positions.

3.10.3 Axle and suspension. Unless otherwise specified (see 6.2), the trailer shall be equipped with either single stub axles or tandem stub axles standard type, adequate to support the specified maximum load. Unless the loaded reel is spring suspended, the axle suspension system shall be of a springing capacity to sustain the rated payload under the performance characteristics specified herein without transmitting damaging shock to the trailer.

3.10.4 Reel spindle. Reel spindle shall be 2-1/2 inches in diameter and shall be provided with adjustable cone-shaped collars or guides for various reel widths. Trailer, the spindle shall be hydraulically adjustable for height from reel holders to enable leveling of the spindle when trailer is on uneven ground or embankment.

3.10.5 Reel holders. Construction of reel holders shall be such as to enable the reel to be picked up hydraulically and mounted on the trailer by one man without the aid of a separate winch or crane.

3.10.6 Landing leg. The landing leg shall be hydraulically operated and adjustable for vertical rise and shall be capable of supporting the loaded trailer in a level attitude without tipping, and shall be provided with a safety lock.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:51Z
Check the source to verify that this is the current version before use.

3.10.7 Cable payout brake. Cable payout brake shall be provided with an adjustment to control braking action.

3.10.8 Safety chain. Trailer shall be equipped with a safety chain or steel cable conforming to DoT Motor Carrier Safety Regulations, sections 393.70(d) and SAE J697.

3.10.9 Wheels and rims. Wheels shall be the manufacturer's current standard. The rim size shall be as recommended by the(TRA) OR (ETRTO) for the size of tire furnished. Wheels shall be one piece, no split rims.

3.10.10 Tires and tubes. Tires shall be tubeless type with highway tread. Tires shall be of rated capacity at least equal to the load imposed on each tire measured at the wheel at the ground, with trailer loaded as specified in 3.9. Tires shall conform to (TRA) or (ETRTO).

3.10.11 Fenders and splash guards. Trailer shall be equipped with fenders and splash guards. Fenders shall withstand loads of 200 pound-force per square foot without evidence of permanent deformation. Splash and stone-throw protection shall be in accordance with SAE J682.

3.10.12 Rear towbar. When specified (see 6.2), the trailer shall be equipped with a detachable rear towbar or pintle for multiple hookup.

3.10.13 Service brakes. Service brakes shall conform to DoT Federal Motor Carrier Safety Regulations, section 393.40 through 393.43 and 393.45 through 393.47. Brake linings shall be of nonasbestos material.

3.10.13.1 Electric brakes. Unless otherwise specified (see 6.2), trailer shall be provided with electric-type brakes wired through the seven contact lighting socket specified in 3.10.16. An electric brake controller shall be furnished for subsequent installation in the towing vehicle. Brakes shall be operable on the 12-volt (V) system of the towing vehicle. Provisions for mounting and connecting the battery, required to operate the brakes in the event of a breakaway from the towing vehicle, shall be furnished.

3.10.13.2 Hydraulic brakes. When specified (see 6.2), trailer shall be equipped with hydraulic vacuum brakes or air-over-hydraulic brakes of manufacturer's current standard type.

3.10.14 Parking brake. The trailer shall be provided with a hand-lever-operated parking brake, capable of holding the trailer, loaded with the rated payload, on a 20 percent grade on a dry hard surface, when uncoupled from the towing vehicle and headed up or down the incline. The parking brake shall conform to DoT Federal Motor Carrier Safety Regulation 393.41. The brake lever shall not require more than 30 lb of effort for application and release. When brake cables are used, they shall be of corrosion-resistant steel. Provisions shall be made for slack adjustment. Lubrication fittings shall be provided.

3.10.15 Chock blocks and cradles. When specified (see 6.2), two pairs of wood or steel chock blocks with captive chains and two cradles shall be furnished and installed on the trailer. The hook of each captive chain

Source: https://assist.dla.mil -- Downloaded: 20260-22T02:51Z
Check the source to verify that this is the current version before use.

shall be secured to the cradle. The captive chains shall be long enough to be wrapped around the cradle to hold the chocks in place during travel, and to allow the wheels to be chocked in front and behind while parked. The chock blocks shall be of sufficient size to prevent trailer movement during reel loading operations and while parked and headed either up or down a 20 percent slope.

3.10.16 Lighting system. The lighting system shall be of 12-V potential and shall conform to DoT Federal Motor Carrier Safety Regulations, sections 393.14, 393.20, 393.22, 393.23, 393.25, through 393.29, 393.32, and 393.33 as applicable. Wiring pattern, wire color code, and coupling connector receptacle shall conform to SAE J560. The receptacle shall be located in accordance with SAE J702. Turn signal lamps shall conform to SAE J588. Taillights and turn signals shall be guarded and wiring shall be routed and anchored for protection from damage.

3.10.17 Receptacle system, 24-V. When specified (see 6.2), the trailer shall be equipped with one 12-contact receptacle with cover and one 7-contact receptacle with cover installed at the front of the trailer. The 12-contact receptacle shall conform to MS75021, part No. MS75021-1. The 7-contact receptacle shall conform to SAE J560 round socket for jumper cable. The 12-contact receptacle shall be provided with resistance to each circuit to reduce the voltage of a tactical Military design towing vehicle from 24 volts to 12 V. A pulse system is acceptable in lieu of a resistor box. A pulse system is acceptable in lieu of a resister box. The 7-contact socket shall be wired in accordance with SAE J560 to supply 12 V directly to the trailer circuits. The 24-V, 12-contact receptacle shall be connected through the necessary resistors into the 12-V trailer circuits as follows:

A - Do not connect.
B - Connect to circuit No. 3.
C - Do not connect.
D - Connect to circuit No. 1.
E - Connect to circuits No. 2 and 6.
F - Do not connect.
H - Do not connect.
I - Is not used.
J - Connect to circuit No. 5.
K - Connect to circuit No. 7.
L - Do not connect.
M - Do not connect.
N - Do not connect.

Circuits B and J on tactical truck-tractors are combination stop and turn indicator circuits. The normal 12-V turn signal lights will function both as turn signals and stoplights and the normal 12-V stoplights will not be in operation when the trailer is connected to a towing vehicle with a 24-volt power supply. Because of this condition, the No. 4 stoplight circuit is not connected to the 24-V, 12-contact receptacle.

3.11 Lubrication. Unless otherwise specified (see 6.2), means for lubrication shall be in accordance with the manufacturer's standard practice. The lubricating points shall be easily visible and accessible.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:51Z
Check the source to verify that this is the current version before use.

All parts requiring lubrication shall be lubricated as specified in 3.12. Hydraulic lubrication fittings shall be in accordance with SAE J534. Where high pressure lubricating equipment is used, (1,000 pound-force per square inch or higher, will damage grease seals or other parts), a suitable warning shall be affixed to the equipment in a conspicuous location.

3.12 Servicing and adjusting. Prior to acceptance of the trailer by the Government inspector, the contractor shall service and adjust the trailer for immediate operational use. The servicing and adjusting shall include at least the following: inflation of all tires, adjustment of brakes, proper functioning of all lighting, and complete lubrication with grades of lubricants recommended for ambient temperature at the delivery point. The trailer shall be conspicuously tagged to identify the lubricants and their temperature range.

3.13 Lifting and tiedown attachments. Unless otherwise specified (see 6.2), the trailer shall be equipped with lifting and tiedown attachments. Lifting and tiedown attachments shall conform to type II or type III of MIL-STD-209. A nonferrous transportation plate shall be provided and mechanically attached to the trailer. Transportation plates shall be inscribed with a diagram showing the lifting attachments and lifting slings, the capacity of each attachment, and the required length and size of each sling cable. A silhouette of the item furnished showing the center of gravity shall be provided on the transportation plate. Tiedown attachments may be identified by stenciling or other suitable marking. Tiedown marking shall clearly indicate that the attachments are intended for the tiedown of the trailer on the carrier when shipped.

3.14 Treatment, painting, identification marking, and data plates. As specified by the procuring activity for the appropriate service (see 6.2), treatment, painting, identification marking, and data plates shall be in accordance with FED-STD-297.

3.14.1 Rustproofing. When specified (see 6.2), the vehicle shall be rustproofed in accordance with FED-STD-297.

3.14.2 Wood treatment. Wood, except apitong, shall be treated in accordance with FED-STD-297.

3.15 Workmanship.

3.15.1 Steel fabrication. The steel used in fabrication shall be free from kinks, sharp bends, and other conditions which would be deleterious to the finished product. Manufacturing processes shall not reduce the strength of the steel to a value less than intended by the design. Manufacturing processes shall be done neatly and accurately. All bends shall be made by controlled means to insure uniformity of size and shape.

3.15.2 Bolted connections. Boltholes shall be accurately punched or drilled and shall have the burrs removed. Washers or lockwashers shall be provided in accordance with good commercial practice, and all bolts, nuts, and screws shall be tight.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:51Z
Check the source to verify that this is the current version before use.

3.15.3 Riveted connections. Rivet holes shall be accurately punched or drilled and shall have the burrs removed. Rivets shall be driven with pressure tools and shall completely fill the holes. Rivet heads, when not countersunk or flattened, shall be of approved shape and of uniform size for the same diameter of rivet. Rivet heads shall be full, neatly made, concentric with the rivet holes, and in full contact with the surface of the member.

3.15.4 Welding. Welding procedures shall be in accordance with a nationally recognized welding code. The surface of parts to be welded shall be free from rust, scale, paint, grease, or other foreign matter. Welds shall be of sufficient size and shape to develop the full strength of the parts connected by the welds. Welds shall transmit stress without permanent deformation or failure when the parts connected by the weld are subjected to proof and service loadings.

3.15.5 Castings. All castings shall be sound and free from patching, misplaced coring, warping, or any other defect which reduces the castings ability to perform its intended function.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

4.1.2 Component and material inspection. Components and materials shall be inspected in accordance with all the requirements specified herein and in applicable referenced documents.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First production trailer inspection (see 4.2.1).
b. Quality conformance inspection (see 4.2.2).

Source: https://assist.dla.mil -- Downloaded: 202610-22T02:51Z
Check the source to verify that this is the current version before use.

4.2.1 First production trailer inspection. The first production vehicle produced under the contract shall be inspected by the contractor at his plant under the direction and in the presence of Government representatives. This inspection shall include the examination of 4.3 and the tests of 4.4. The purpose of the inspection shall be to determine trailer conformity with the requirements of the contract. Acceptance of the first production trailer shall not constitute a waiver by the Government of its right under the provisions of the contract.

4.2.2 Quality conformance inspection. The quality conformance inspection shall include the examination of 4.3, the tests of 4.6, and the packaging inspection of 4.7.

4.3 Examination. Each trailer shall be examined for compliance with the requirements specified in section 3 of this specification. Any redesign or modification of the contractor's standard product to comply with specified requirements, or any necessary redesign or modification following failure to meet specified requirements shall receive particular attention for adequacy and suitability. This element of inspection shall encompass all visual examinations and dimensional measurements. Noncompliance with any specified requirements or presence of one or more defects preventing or lessening maximum efficiency shall constitute cause for rejection.

4.4 First production trailer tests. When a first production trailer is required, the first trailer of each type shall be subjected to the tests by the contractor as specified in 4.4.1 through 4.4.6 and when applicable, 4.4.7 through 4.4.9. Failure to pass any phase of the required tests shall be cause for the Government to refuse acceptance of all trailers until corrective action has been taken.

4.4.1 Trailer weight. The trailer shall be weighed to determine net weight and distribution of net weight on coupler ring and axle. The weight distribution shall be computed using net weight and the rated payload. Calculated imposed loads on coupler ring and axle shall be utilized to ascertain that the tires, axle, and suspension are of adequate capacity to meet the contract requirements.

4.4.2 Towing tests. The fully equipped trailer shall be towed over roads and terrain specified in 3.7.1, at a minimum distance of 50 miles, loaded with rated payload and 30 miles without load. At least 20 percent of the distance shall be over unimproved roads and reasonably hard terrain. Towing speeds shall be as specified in 3.7.1. Tracking shall be checked for conformance to 3.7.3. Trailer shall be observed during the run and examined after the test for evidence of misalignment, part failure, or other defects.

4.4.3 Turning ability test. The trailer, loaded with rated payload, shall be tested for turning ability to verify compliance with 3.7.2.

4.4.4 Service brake test. Service brakes shall be tested with rated payload on the trailer to verify compliance with the requirements of 3.7.4. Breakaway situation shall be simulated to verify braking ability upon breakaway.

Source: https://assist.dla.mil -- Downloaded: 202640-22T02:51Z
Check the source to verify that this is the current version before use.

4.4.5 Mounted equipment test. All mounted equipment shall be maneuvered to verify conformance to this specification. All adjustments shall be tested within their range for interference or defects.

4.4.6 Pick up and loading test. Pick up and loading of the reel shall be performed not less than five times to verify conformance to 3.10.5.

4.4.7 Parking brake test. Parking brake, when required, shall be tested to verify conformance to the requirements of 3.10.14.

4.4.8 Chock block test. When chock blocks are required, test shall be performed to verify conformance to 3.10.15.

4.4.9 Lifting and tiedown attachment tests. When required, the lifting and tiedown attachments shall be tested to conform to 3.13.

4.5 Production sample. Upon acceptance of the first production trailer it shall remain at the manufacturing facility as a production sample and shall be the last trailer shipped on the contract. The contractor shall maintain the trailer in a serviceable condition for the duration of the contract.

4.6 Production unit tests. The contractor's testing system shall, as a minimum, assure that the trailer is capable of meeting the performance requirements specified herein. The trailer shall be exercised to assure brake adjustment, light operation, landing leg operation, tracking ability, and reel pickup and loading. These operations shall be made as a final inspection check.

4.7 Packaging inspection. The trailer shall be inspected to verify conformance to the requirements of section 5.

5. PACKAGING

5.1 Trailer processing. The equipment shall be preserved and packed in accordance with the contractor's standard practice. When specified (see 6.2), equipment shall be preserved and packed in accordance with the mobile requirements of MIL-V-62038 with the level of preservation and packed as specified (see 6.2).

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. Trailer covered by this specification is intended for use by the Government in transporting and handling of cable reels, and for use in cable-laying operations.

6.2 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number, and date of this specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:51Z
Check the source to verify that this is the current version before use.

b. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1.1 and 2.2).
c. When first production vehicle is required for inspection and approval (see 3.2).
d. If cable reel width is other than specified (see 3.8.4).
e. Rated payload if other than specified (see 3.9).
f. Coupler ring if other than specified (see 3.10.2).
g. When coupler ring shall conform to MS51337 (see 3.10.2).
h. Type of axle if not as specified (see 3.10.3).
i. When a detachable rear towbar is required (see 3.10.12).
j. Electric brakes if other than specified (see 3.10.13.1).
k. When hydraulic vacuum brakes or air-over-hydraulic brakes are required (see 3.10.13.2).
l. When chock blocks and cradles are required (see 3.10.15).
m. When 24-V receptacle system is required (see 3.10.17).
n. If lubrication is other than specified (see 3.11).
o. If lifting and tiedown attachments are other than specified (see 3.13).
p. When instructions for appropriate service for painting and marking are required (see 3.14).
q. When rustproofing is required (see 3.14.1).
r. When packing in accordance with MIL-V-62038 is required, and the level of preservation and packing required (see 5.1).

6.3 Subject term (key word) listing.

Power loading
Self-contained
15000 lb cap
12V, 24V, lighting system

6.4 Definitions.

6.4.1 Improved road. An improved road is a smooth, hard-surfaced road, such as a concrete or asphalt-paved highway.

6.4.2 Unimproved road. An unimproved road is an unpaved, unstabilized road with an undulating surface having occasional chuckholes and exposed rocks.

Custodians:
Army - AT
Navy - YD
Air Force - 99

Preparing Activity:
Navy - YD

(Project 2330-0012)

Review Activity:
Air Force - 84

User Activity:
Navy - MC

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:51Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER	2. DOCUMENT DATE (YYMMDD)
3. DOCUMENT TITLE		

4. NATURE OF CHANGE *(Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)*

5. REASON FOR RECOMMENDATION

6. SUBMITTER			
a. NAME (Last, First, Middle Initial)		b. ORGANIZATION	
c. ADDRESS (Include Zip Code)		d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY	
a. NAME	b. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON
c. ADDRESS (Include Zip Code)	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340

DD Form 1426, OCT 89 *Previous editions are obsolete.* 198/290

Source: https://assist.dla.mil -- Downloaded: 202640-22T02:51Z
Check the source to verify that this is the current version before use.