MIL-T-45386E
20 June 1984
SUPERSEDING
MIL-T-45386D
30 April 1979

MILITARY SPECIFICATION

TRAILERS, BOLSTER, COMMERCIAL, POLE TYPE, 2 TO 20 TONS

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers single and tandem axle, commercial, pole type, bolster trailers with or without special load adapters, having minimum capacities of 2 to 20 tons.

* 1.2 Classification. Trailers shall be of the following types, classes, and styles, as specified (see 6.2):

Type I - Single axle trailer.
Type II - Tandem axle trailer.

Class A - 2-ton payload capacity (type I only).
Class B - 3-1/2 ton payload capacity (type I only).
Class C - 10-ton payload capacity.
Class E - 13-ton payload capacity (type II only).
Class F - 20-ton payload capacity (type II only).

Style 1 - Integral A-frame towbar with coupler ring.
Style 2 - Adjustable single tongue towbar with coupling ring.
Style 3 - Adjustable single tongue or telescoping towbar with fifth wheel kingpin.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

* 2.1.1 Specifications, standards, and handbooks. Unless otherwise specified (see 6.2), the following specifications, standards, and handbooks of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation, form a part of this specification to the extent specified herein.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commanding Officer (Code 156), Naval Construction Battalion Center, Port Hueneme, CA 93043, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 2330

Source: https://assist.dla.mil -- Downloaded: 202610-22T02:52Z
Check the source to verify that this is the current version before use.

SPECIFICATION

MILITARY

MIL-B-46176 - Brake Fluid, Silicone, Automotive, All Weather, Operational and Preservative.

STANDARDS

MILITARY

MIL-STD-209 - Slinging and Tiedown Provisions for Lifting and Tying Down Military Equipment.
MIL-STD-281 - Automobilies, Trucks, Truck Tractors, Trailer and Trailer Dollies; Preservation and Packing of.
MIL-STD-1223 - Nontactical Wheeled Vehicles Treatment, Painting, Rustproofing, Identification Marking and Data Plate Standards.
MS75021 - Connector, Receptable, Electrical - 12 Contact, Intervehicular, 24-Volt, Waterproof.

2.1.2 Other Government documents, drawings, and publications. The following other Government documents form a part of this specification to the extent specified herein.

DEPARTMENT OF TRANSPORTATION (DoT)

Federal Motor Vehicle Safety Standards and Regulations.
Federal Motor Carrier Safety Regulations.

(Application for copies should be addresses to the Superintendent of Documents, Government Printing Office, Washington, DC 20402.

(Copies of specifications, standards, handbooks, drawings, and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

* 2.2 Other publications. The following documents form a part of this specification to the extent specified herein. The issues of the documents which are indicated as Department of Defense adopted shall be the issue listed in the current DoDISS and the supplement thereto, if applicable.

AMERICAN WELDING SOCIETY, INC. (AWS)

AWS D1.1 Structural Welding Code.

(Applications for copies should be addressed to the American Welding Society, Inc., 2501 Northwest Seventh Street, Miami, FL 33125.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:52Z
Check the source to verify that this is the current version before use.

SOCIETY OF AUTOMOTIVE ENGINEERS, INC., (SAE)

SAE Handbook.

(Application for copies should be addressed to the Society of Automotive Engineers, Inc., 400 Commonwealth Drive, Warrendale, PA 15096.)

STATE OF CALIFORNIA

California Vehicle Code.

(Application for copies should be addressed to the Department of Motor Vehicles, 2570 24th Street, Sacramento, CA 95809.)

TIRE AND RIM ASSOCIATION, INC. (TRA)

TRA Yearbook.

(Application for copies should be addressed to the Tire and Rim Association, Inc., 3200 West Market Street, Akron, OH 44313.

(Industry association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

* 2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

3. REQUIREMENTS

* 3.1 Description. The trailers shall be the bolster, commercial, pole type, 2 to 20 tons payload capacity. Performance capabilities and components furnished shall be in accordance with the requirements as stated in section 3 of this specification.

3.1.1 Standard commercial product. The trailer shall, as a minimum, be in accordance with the requirements of this specification and shall be the manufacturer's standard commercial product. Additional or better features which are not specifically prohibited by this specification but which are a part of the manufacturer's standard commercial product, shall be included in the trailer being furnished. A standard commercial product is a product which has been sold or is being currently offered for sale on the commercial market through advertisements or manufacturer's catalogs, or brochures, and represents the latest production model.

3.2 First article. When specified (see 6.2), the contractor shall furnish a trailer for first article inspection and approval (see 4.2.1 and 6.4).

3.3 Materials. Materials used shall be free from defects which would adversely affect the performance or maintainability of individual components or of the overall assembly. Materials not specified herein shall be of the same quality used for the intended purpose in commercial practice. Unless

Source: https://assist.dla.mil -- Downloaded: 202610-22T02:52Z
Check the source to verify that this is the current version before use.

otherwise specified herein, all equipment, material, and articles incorporated in the work covered by this specification are to be new and fabricated using materials produced from recovered materials to the maximum extent possible without jeopardizing the intended use. The term "recovered materials" means materials which have been collected or recovered from solid waste and reprocessed to become a source of raw materials, as opposed to virgin raw materials. None of the above shall be interpreted to mean that the use of used or rebuilt products are allowed under this specification unless otherwise specified.

* 3.4 Interchangeability. All units of the same classification furnished with similar options under a specific contract shall be identical to the extent necessary to insure interchangeability of component parts, assemblies, accessories, and spare parts.

3.5 Trailer weights and ratings.

3.5.1 Curb weight. The curb weight of the fully equipped trailer shall include chassis, bolsters, portable towbar, and all attachments and accessories.

3.5.2 Payload. The payload capacity shall be not less than specified for the class trailer (see 1.2), with the load evenly distributed over the trailer body load area.

3.5.3 Gross weight. The gross weight shall include the curb weight of the trailer and the specified payload (see 3.5.2). The imposed loading on the axle(s), measured at the ground, shall be computed using the curb weight, and the specified payload uniformly distributed over the trailer body load area.

3.5.4 Ratings. Component and trailer ratings shall not be raised to meet the requirements of this specification.

3.6 Type. Trailer shall be of type I single axle design, or type II tandem axle design.

3.6.1 Style. Trailer shall be of the following styles:

3.6.1.1 Style 1. Style 1 trailer shall be integral A-frame towbar with coupler ring. Two stationary bolsters shall be installed on the trailer frame. When specified (see 6.2), the trailer shall be furnished with either an adjustable extension tongue with an integrated coupler ring (see 3.6.3) for the A-frame towbar, or with the portable towbar specified in 3.6.2.

3.6.1.2 Style 2. Style 2 trailer shall have an adjustable single tongue towbar with coupler ring. One swivel bolster shall be installed on trailer frame. When specified (see 6.2), another swivel bolster shall be furnished with the trailer for mounting on prime mover. When specified (see 6.2), a portable towbar conforming to 3.6.2 shall be furnished in lieu of the swivel bolters specified. When the portable towbar is furnished, one or two stationary bolsters shall be installed on the trailer frame.

3.6.1.3 Style 3. Style 3 trailer shall be provided with an adjustable single tongue or telescoping towbar, embodying a combination stationary bolster

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:52Z
Check the source to verify that this is the current version before use.

and fifth wheel kingpin hitch. Two stationary bolsters shall be positioned approximately above each axle. The adjustable tongue or towbar design shall provide for adjustments in increments of not less than 24 inches. The kingpin shall be fabricated of heat-treated alloy steel and shall conform to SAE J700.

* 3.6.2 Portable towbar. When specified (see 3.6.1.1 and 3.6.1.2), a portable towbar shall be the manufacturer's standard with coupler ring conforming to 3.6.3. The portable towbar shall be equipped with chains, screw type chain binders, and other necessary devices for securely fastening and holding the towbar to the load.

3.6.3 Coupler ring. Towbars for style 1 and 2 trailers shall be provided with manufacturer's standard coupler ring of solid steel not less than 2-5/8 inches inside diameter. The ring cross section shall not exceed 1-5/8 inch diameter.

3.7 Performance.

3.7.1 Travel speed. Trailer, fully equipped and loaded with maximum rated payload, shall be capable of being towed over unimproved roads (see 6.6), and reasonably hard, uneven terrain at a speed of 10 miles per hour (mph), and shall be capable of being towed over improved roads at speeds as great as 50 mph.

3.7.2 Turning ability. When towed, the style 1 and 2 trailers shall be capable of forming a 70 degrees (°) angle, and style 3 trailer a 90° angle with the towing vehicle, without cramping or damage to trailer or towing vehicle.

3.7.3 Trailing ability. The trailer shall not exceed the allowance for tracking deviation specified in Dot Federal Motor Carrier Safety Regulations, section 393.70(e).

3.7.4 Brake performance. The brakes shall comply with the performance requirements specified in Dot Federal Motor Carrier Safety Regulations, section 393.52. Service brakes and parking brakes shall conform to Federal Motor Vehicle Safety Standard No. 121.

3.8 Dimensions and clearances. Dimensions and clearances shall be established with the trailer uncoupled from prime mover, placed in level position on a level surface and without payload.

3.8.1 Length. Unless otherwise specified (see 6.2), the overall length of the trailer shall be the manufacturer's standard.

3.8.2 Width. Unless otherwise specified (see 6.2), the overall width shall be not more than 96 inches.

3.8.3 Ground clearance. Ground clearance shall be the maximum practicable, but not less than 9 inches with rated payload.

3.8.4 Load capacity. Trailer shall be capable of supporting and hauling the rated payloads specified in 1.2.

Source: https://assist.dla.mil -- Downloaded: 202610-22T02:52Z
Check the source to verify that this is the current version before use.

3.8.5 Height. The overall height from ground to top of bolster(s) shall be the minimum practicable. Load areas shall be approximately level when the unit is coupled to a truck tractor having a fifth wheel height of 50 inches ±1 inch.

3.9 Components.

3.9.1 Frame. Chassis frame shall be the manufacturer's current standard all-steel construction having structural capacity to withstand the flexural and torsional forces, without permanent set or part failures, under the operating conditions specified in 3.7.

3.9.2 Towbar. Towbar shall be the manufacturer's current standard all-steel construction for the class and style of trailer specified and shall provide structural strength to resist bending and twisting without permanent deformation or damage, under operating conditions specified in 3.7. Towbar shall conform to applicable requirements of DoT Federal Motor Carrier Safety Regulations, section 393.71(h).

3.9.3 Bolsters and stanchions. Bolster shall be manufacturer's current standard construction for the class and style of trailer specified and shall be mounted in accordance with standard commercial practice. Two stanchions shall be furnished with each bolster. Stanchions shall be adjustable for load width, demountable from bolster, and provided with a locking device for holding in any position.

3.9.4 Suspension. Trailer shall be equipped with manufacturer's standard suspension system with components having rated capacity at least equal to the load imposed on each member, measured at the ground, with the trailer loaded with the maximum payload specified in 1.2.

3.9.4.1 Springs. Main springs (and helper springs if required) shall be the manufacturer's current standard for the type, class, and style of trailer specified. The main springs shall be semielliptical leaf type, having capacity to support the imposed loads, without permanent set or breakage, under the service conditions specified in 3.7.

3.9.4.2 Axle(s). The axle(s) shall be the manufacturer's current standard for the type, class, and style of trailer specified. Axle rating shall be at least equal to the load imposed on each axle, measured at the ground, with the trailer loaded to gross weight.

3.9.4.2.1 Single axle. Single axle suspension system shall have leaf springs and a one-piece through shaft. The shaft shall be tubular or structural shape steel.

3.9.4.2.2 Tandem axle. Tandem axle suspension system shall have leaf springs and two one-piece through shafts, or shall employ rubber cushioned walking beams and two one-piece through shafts. The axle system shall provide sufficient articulation to maintain equal loading on each wheel.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:52Z
Check the source to verify that this is the current version before use.

3.9.5 Wheels and rims. Wheels shall be the manufacturer's current standard. Rim and tire ratings shall conform to TRA recommendations for the type and size of tires furnished. Unless otherwise specified (see 6.2), type I, class A and B trailers shall be furnished with two single wheels, and class C trailers shall be furnished with two dual wheels; type II, class C trailers shall be furnished with four single wheels, and class E and F trailers shall be furnished with four dual wheels.

3.9.6 Tires and tubes. Tires shall be tube or tubeless type with highway tread. Tires shall be rated capacity at least equal to the load imposed on each tire, measured at the wheel, at the ground, with trailer loaded with its maximum rated payload. Tires shall be of not less than 100 level quality. When tube type tires are furnished, tubes shall be of heavy-duty type, and shall be of proper size for tires furnished. Tire flaps shall be provided for tube type tires in accordance with TRA recommendations.

3.9.7 Splash guards and fenders. Trailer shall be equipped with manufacturer's standard splash guards. When specified (see 6.2), trailer shall be equipped with fenders. Splash and stone throw protection shall be in accordance with SAE J682.

3.9.8 Safety chains. Safety chains, conforming to the requirements of DoT Federal Motor Carrier Safety Regulations, section 393.70(f), 393.71(h), and SAE J697, shall be furnished.

3.9.9 Service brakes. Service brakes on all trailers shall conform to DoT Federal Motor Carrier Safety Regulations, sections 393.40, 393.42, 393.43, and 393.45 through 393.48, as applicable. Service brakes shall conform to DoT Federal Motor Vehicle Safety Standard No. 121. No part of the braking system shall extend below the bottom of the wheel rim. Unless otherwise specified (see 6.2), class A, B, and C trailers shall be equipped with the manufacturer's current standard brake system. When specified, (see 6.2), contractor shall provide certification that the brake components utilized are compatible with silicone brake fluid requirements of MIL-B-46176.

3.9.9.1 Air brakes. Unless otherwise specified (see 6.2), class E and F trailers shall be equipped with spring set, air release, internal expanding type brakes. The braking system shall include at least standard breakaway features, relay emergency valve, air reservoir, manual or automatic slack adjusters, piping, hose connections, glad hands, couplings equipped with security chains, provisions for stowing the dummy couplings, and all other components required for a complete system. Air hose coupling set shall conform to SAE J702. The air brake system shall also serve as parking brake. Air brakes shall conform to DoT Federal Motor Vehicle Safety Standard No. 121.

3.9.9.2 Emergency service brake requirements. When specified (see 6.2), the service brake system shall conform to the requirements of the California Vehicle Code, section 26508.

3.9.9.3 Electric brakes. When furnished, electric type brakes shall be wired through the seven contact lighting connector sockets specified in 3.9.14. An electrical brake controller shall be furnished for subsequent installation in the towing vehicle. Brakes shall be operable on the 12-volt system of the

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:52Z
Check the source to verify that this is the current version before use.

towing vehicle. Provisions for mounting and connecting the battery and brake operating interlock switch required to operate the brakes, in the event of a breakaway from the towing vehicle, shall be furnished. Battery shall not be furnished. When electric brakes are furnished and parking brakes are required, chock blocks (see 3.9.11), may be furnished in lieu of the parking brake.

3.9.9.4 Hydraulic brakes. When specified (see 6.2), trailer shall be equipped with hydraulic vacuum brakes or air over hydraulic brakes of manufacturer's current standard type.

* 3.9.10 Manual parking brake. When specified (see 6.2), a trailer shall be equipped with manually operated parking brakes. Brakes shall be capable of holding the trailer loaded with rated payload, on a 20 percent grade, when uncoupled from towing vehicle and headed up or down the incline.

3.9.11 Wheel chock blocks. When specified (see 6.2), a trailer shall be equipped with wheel chock blocks in lieu of the parking brake. Chock blocks shall be attached to the trailer by retaining chains.

3.9.12 Landing leg. A folding type landing leg, with pad, shall be furnished and installed.

3.9.13 Special load adapters. When specified (see 6.2), a trailer shall be equipped with two saddles and a spindle for transporting cable reels. Saddles shall be quickly demountable and interchangeable with rear bolster. Reel spindle shall be 2-1/2 inches in diameter, provided with adjustable guides for various reel sizes up to 48 inches wide and 84 inches in diameter.

3.9.14 Lighting and wiring system. Lighting and wiring system shall be manufacturer's standard of 12-volt potential negative ground and shall comply with DoT Federal Motor Carrier Safety Regulations, sections 393.16, 393.23, 393.25 through 393.29, 393.32, and 393.33, as applicable. Wiring pattern, wire color code, coupling connector socket, and installation shall conform to SAE J560. Lights and reflectors shall be recessed and guarded, and wiring shall be properly routed and anchored for protection from damage. Turn signal lamps shall comply with SAE J588, class A.

3.9.15 Receptacle system, 24-volt. When specified (see 6.2), the trailer shall be equipped with one 12-contact receptacle with cover, and one 7-contact receptable with cover installed at the front of the trailer. The 12-contact receptacle shall conform to MS75021, part no. MS75021-1. The 7-contact receptacle shall conform to SAE J560 round socket for jumper cable. The 12-contact receptacle shall be provided with resistance to each circuit to reduce the voltage of a tactical military design towing vehicle from 24 volts to 12 volts. The 7-contact socket shall be wired in accordance with SAE J560 to supply 12-volts directly to the trailer circuits. The 24-volt, 12-contact receptacle shall be connected through the necessary resistors into the 12-volt trailer circuits as follows:

A - Do not connect.
B - Connect to circuit no. 3.
C - Do not connect.
D - Connect to circuit no. 1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:52Z
Check the source to verify that this is the current version before use.

E - Connect to circuits no. 2 and 6.
F - Do not connect.
H - Do not connect.
J - Connect to circuit no. 5.
K - Connect to circuit no. 7.
L - Do not connect.
M - Do not connect.
N - Do not connect.

Circuits B and J on tactical truck tractors are combination stop and turn indicator circuits. The normal 12-volt turn signal lights will function both as turn signals and stoplights and the normal 12-volt stoplights will not be in operation when the trailer is connected to a towing vehicle with a 24-volt power supply. Because of this condition, the no. 4 on stoplight circuit is not connected to the 24-volt, 12-contact receptacle.

* 3.10 Lubrication. Unless otherwise specified (see 6.2), means for lubrication shall be in accordance with the manufacturer's standard practice. The lubricating points shall be easily visible and accessible. Hydraulic lubrication fittings shall be in accordance with SAE J534. Where use of high pressure lubricating equipment, 1,000 pound-force per square inch or higher, will damage grease seals or other parts, a suitable warning shall be affixed to the equipment in a conspicuous location.

3.11 Service and adjustment. Each trailer shall be properly serviced and adjusted for immediate operational use including at least the following: proper adjustment of electrical and brake systems, inflation of all tires, and complete lubrication.

* 3.12 Lifting and tiedown attachments. The trailer shall be equipped with lifting and tiedown attachments. Lifting and tiedown attachments shall conform to type II or type III of MIL-STD-209. A nonferrous transportation plate shall be provided and mechanically attached to the trailer. Transportation plates shall be inscribed with a diagram showing the lifting attachments and lifting slings, the capacity of each attachment, and the required length and size of each sling cable. A silhouette of the item furnished showing the center of gravity shall be provided on the transportation plate. Tiedown attachments may be identified by stenciling or other suitable marking. Tiedown marking shall clearly indicate that the attachments are intended for the tie down of the trailer on the carrier when shipped.

* 3.13 Identification plate. An identification plate will be furnished by the contracting officer for each trailer. The contractor shall stamp all necessary data in the blank spaces of the plate provided for that purpose, and securely affix a plate to each trailer in a conspicuous place with brass screws or bolts not less than 1/8 inch in diameter. The applicable nomenclature contained in the contract item description shall be placed in the top blank.

* 3.14 Instruction plates. The trailer shall be equipped with instruction plates suitably located, describing any special or important procedures to be followed in operating and servicing the equipment. Plates shall be of a material which will last and remain legible for the life of the equipment, and shall be securely affixed thereto with nonferrous screws or bolts of not less than 1/8-inch diameter.

Source: https://assist.dla.mil -- Downloaded: 202640-22T02:52Z
Check the source to verify that this is the current version before use.

* 3.15 Cleaning, treatment, and painting. Surfaces normally painted in good commercial practice shall be cleaned, treated, and painted as specified herein. The color of the finish coat shall be as specified (see 6.2). Surfaces to be painted shall be cleaned and dried to insure that they are free from contaminants such as oil, grease, welding slag and spatter, loose mill scale, water, dirt, corrosion product, or any other contaminating substances. As soon as practicable after cleaning, and before any corrosion product or other contamination can result, the surfaces shall be prepared or treated to insure the adhesion of the coating system. The painting shall consist of at least one coat of primer and one finish coat. The primer shall be applied to a clean, dry surface as soon as practicable after cleaning and treating. Painting shall be with manufacturer's current materials according to manufacturer's current processes and the total dry film thickness shall be not less than 2.5 mils over the entire surface. The paint shall be free from runs, sags, orange peel, or other defects. All machine surfaces rotating parts, lube fittings, bolted and rivited holes shall be free of paint.

3.16 Workmanship.

3.16.1 Steel fabrication. The steel used in fabrication shall be free from kinks, sharp bends, and other conditions which would be deleterious to the finished product. Manufacturing processes shall not reduce the strength of the steel to a value less than intended by the design. Manufacturing processes shall be done neatly and accurately. All bends shall be made by controlled means to insure uniformity of size and shape.

3.16.2 Bolted connections. Boltholes shall be accurately punched or drilled and shall have the burrs removed. Washers or lockwashers shall be provided in accordance with good commercial practice, and all bolts, nuts, and screws shall be tight.

3.16.3 Riveted connections. Rivet holes shall be accurately punched or drilled and shall have the burrs removed. Rivets shall be driven with pressure tools and shall completely fill the holes. Rivet heads, when not countersunk or flattened, shall be of approved shape and of uniform size for the same diameter of rivet. Rivet heads shall be full, neatly made, concentric with the rivet holes, and in full contact with the surface of the member.

3.16.4 Welding. Welding procedures shall be in accordance with a nationally recognized welding code. The surface of parts to be welded shall be free from rust, scale, paint, grease, or other foreign matter. Welds shall be of sufficient size and shape to develop the full strength of the parts connected by the welds. Welds shall transmit stress without permanent deformation or failure when the parts connected by the weld are subjected to proof and service loadings.

3.16.5 Castings. All castings shall be sound and free from patching, misplaced coring, warping, or any other defect which reduces the castings ability to perform its intended function.

3.16.6 Welders. Before assigning any welder to manual work covered by this specification, the contractor shall provide the contracting officer certification that the welder has passed qualification tests as prescribed by

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:52Z
Check the source to verify that this is the current version before use.

the following listed code for the type of welding operations to be performed and that such qualification is effective as defined by the particluar code, AWS D1.1 Structural Welding Code, Section 5, Qualification. Contractors who make only horizontal welds need not qualify welds for "all position welding." Subject to approval by the Government, contractors standard welder qualifications may be substituted in lieu of the above code. The contractor shall be responsible for determining that automatic welder equipment operators are capable of producing quality welds in accordance with AWS codes.

3.17 Rustproofing. The vehicle shall be rustproofed in accordance with MIL-STD-1223.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Component and material inspection. Components and materials shall be inspected in accordance with all the requirements specified herein and in applicable referenced documents.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.2.1).
b. Quality conformance inspection (see 4.2.2).

4.2.1 First article inspection. The first article inspection shall be performed on one complete trailer when a first article is required (see 3.2 and 6.2). This inspection shall include the examination of 4.3 and the tests of 4.4. The first article may be either a first production item or a standard production item from the supplier's current inventory provided the item meets the requirements of the specification and is representative of the design, construction, and manufacturing technique applicable to the remaining items to be furnished under the contract.

4.2.2 Quality conformance inspection. The quality conformance inspection shall include the examination of 4.3, the tests of 4.4.6, and the packaging inspection of 4.5.

4.3 Examination. Each trailer shall be examined for compliance with the requirements specified in section 3 of this specification. Any redesign or modification of the contractor's standard product to comply with specified requirements, or any necessary redesign or modification following failure to meet specified requirements shall receive particular attention for adequacy

Source: https://assist.dla.mil -- Downloaded: 202640-22T02:52Z
Check the source to verify that this is the current version before use.

and suitability. This element of inspection shall encompass all visual examinations and dimensional measurements. Noncompliance with any specified requirements or presence of one or more defects preventing or lessening maximum efficiency shall constitute cause for rejection.

4.4 Tests.

4.4.1 Towing tests. The fully equipped trailer, loaded with maximum rated payload, shall be towed a minimum of 10 miles over courses as specified in 3.6.1. At least 20 percent of the distance shall be over unimproved roads and reasonably hard terrain. Towing speeds shall be as specified in 3.7.1. Trailing ability shall be checked for conformance to the requirements of 3.7.3. Trailer shall be observed during the run and examined after the run for interference, part failure, or other defects.

4.4.2 Performance test. Trailer, with maximum rated payload, shall be towed on dry, level road free from loose material, to test conformance of service brakes to the requirements of 3.7.4. Turning ability shall be tested to verify compliance to 3.7.2. Mounted equipment shall be tested in all positions within their range.

4.4.3 Parking brake test. Parking brake shall be tested for conformance to 3.9.10.

4.4.4 Reel pickup and loading. Rear bolster shall be removed, saddles installed, and pickup and loading shall be performed at least three times to verify conformance to 3.9.13.

4.4.5 Lifting and tiedown attachment tests. When required, the lifting and tiedown attachments shall be tested to conform to 3.12.

4.4.6 Production unit tests. The contractor's testing system shall, as a minimum assure that the trailer is capable of meeting the performance requirements specified herein.

4.5 Packaging inspection. The vehicle shall be inspected to verify conformance to the requirements of section 5.

5. PACKAGING

5.1 Vehicle processing. The equipment shall be preserved and packaged in accordance with the contractor's standard practice. When specified (see 6.2), equipment shall be preserved and packaged in accordance with the mobile requirements of MIL-STD-281 with the level of preservation and packaging as specified (see 6.2).

6. NOTES

6.1 Intended use. Trailers covered by this specification are intended for use by the Government in transporting logs, poles, pipes, structural steel, piling, and other long loads.

Source: https://assist.dla.mil -- Downloaded: 202610-22T02:52Z
Check the source to verify that this is the current version before use.

6.2 Ordering data. Acquisition documents should specify the following:

a. Title, number, and date of this specification.
b. Type, class, and style of trailer required (see 1.2).
c. Specifications, standards and handbooks (see 2.1.1).
d When first article is required for inspection and approval (see 3.2, 4.2.1, and 6.4).
e. When adjustable extension tongue or portable towbar is required (see 3.6.1.1).
f. When another swivel bolster or portable towbar is required (see 3.6.1.2).
g. Overall length of trailer if not manufacturer's standard (see 3.8.1).
h. Overall width of trailer if not as specified (see 3.8.2).
i. Wheel arrangement if not as specified (see 3.9.5).
j. When fenders are required (see 3.9.7).
k. When brake system shall be compatible with brake fluid conforming to MIL-B-46176 (see 3.9.9).
l. Brake system if not as specified (see 3.9.9 or 3.9.9.1).
m. When service brake system is required to conform to California Vehicle Code (see 3.9.9.2).
n. When hydraulic brake system is required and type of brakes (see 3.9.9.4).
o. When manual parking brake is required (see 3.9.10).
p. When chock blocks are required (see 3.9.11).
q. When cable reel transporting equipment is required (see 3.9.13).
r. When 24-volt receptacle system is required (see 3.9.15).
s. When a means for lubrication other than the manufacturers standard practice is required (see 3.10).
t. Color of finish coat required (see 3.15).
u. When preservation-packaging in accordance with MIL-STD-281 is required and the level of preservation-packaging required (see 5.1).

* 6.3 Data requirements. When this specification is used in an acquisition which incorporates a DD Form 1423 Contract Data Requirements List (CDRL) and invokes the provisions of paragraph 7-104.9(n) of the Defense Acquisition Regulations (DAR), the data requirements will be developed as specified by an approved Data Item Description (DD Form 1664) and delivered in accordance with the approved CDRL (DD Form 1423) incorporated into the contract. When the provisions of DAR 7-104.9(n) are not invoked, the data shall be delivered in accordance with the contract requirements.

* 6.4 First article. When a first article inspection is required (see 3.2 and 6.2), the item will be tested and should be a first production item or it may be a standard production item from the contractor's current inventory as specified in 4.2.1. The first article should consist of one complete trailer unit. The contracting officer should include specific instructions in acquisition documents regarding arrangements for examination, test, and approval of the first article.

6.5 Changes from previous issue. The margins of this specification are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:52Z
Check the source to verify that this is the current version before use.

convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

6.6 Definitions.

6.6.1 Improved road. An improved road is a smooth, hard surfaced road, such as concrete or asphalt paved highway.

6.6.2 Unimproved road. An unimproved road is an unpaved, unstabilized road with an undulating surface having occasional chuckholes and exposed rocks.

Custodians:

Army - AT
Navy - YD
Air Force - 99

Preparing activity:

Navy - YD

(Project 2330-0832)

Review Activity:

Air Force - 84

User Activity:

Army - MI
Navy - MC

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:52Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE NAVY
Commander (04M2)
Naval Facilities Engineering Command
200 Stovall Street
Alexandria, VA 223320-2300

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12503 WASHINGTON D C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE NAVY

Commanding Officer (156)
Naval Construction BAttalion Center
Port Hueneme, CA 93043-5000

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:52Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-T-45386E	Trailers, Bolster, Commercial, Pole Type, 2 to 20 Tons

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR ☐ USER ☐ MANUFACTURER ☐ OTHER *(Specify)*:
b. ADDRESS *(Street, City, State, ZIP Code)*	

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426

PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:52Z
Check the source to verify that this is the current version before use.