MIL-T-45388C(AT)
19 May 1986
SUPERSEDING
MIL-T-45388B(AT)
9 May 1980

MILITARY SPECIFICATION

TRUCKS, VAN: FURNITURE, DIESEL AND GASOLINE ENGINE DRIVEN, 24,000 POUNDS GVW, 4x2, COMMERCIAL

This specification is approved for use by the US Army Tank-Automotive Command, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers diesel and gasoline engine driven, four-wheel, two-rear wheel drive, commercial trucks incorporating a furniture van body with a hydraulic lift gate, and having a minimum gross vehicle weight (GVW) of 24,000 pounds. Vehicles procured under this specification are commercial items which shall be warranted by the manufacturer as specified in acquisition documents.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

* 2.1.1 Specifications and standards. The following specifications and standards form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) and supplement thereto, cited in the solicitation.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: US Army Tank-Automotive Command, ATTN: AMSTA-UED, Warren, MI 48397-5000, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC-2320

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-22T02:52Z
Check the source to verify that this is the currentversion before use.

SPECIFICATONS
FEDERAL

	W-B-131	- Battery, Storage: Vehicular, Ignition, Lighting and Starting.
*	ZZ-T-381	- Tires, Pneumatic, Vehicular (Highway).

STANDARDS
FEDERAL

*	FED-STD-297	- Rustproofing of Commercial (Nontactical) Vehicles.

MILITARY

	MIL-STD-1223	- Nontactical Wheeled Vehicles Treatment, Painting, Identification Marking, and Data Plate Standards.

* 2.1.2 Other Government documents. The following other Government documents form a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

DEPARTMENT OF TRANSPORTATION (DoT)
Federal Motor Carrier Safety Regulations.
Federal Motor Vehicle Safety Standards.

(Application for copies of DoT publications should be addressed to the Department of Transportation, Federal Highway Administration, Washington, D.C. 20591.)

ENVIRONMENTAL PROTECTION AGENCY (EPA)
Control of Air Pollution from New Motor Vehicles and New Motor Vehicle Engines.
Noise Emission Standards for Transportation Equipment - Medium and Heavy Trucks.

(Application for copies of EPA publications should reference the Code of Federal Regulations, 40 CFR, and the Federal Register and should be addressed to the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C. 20402.)

* NATIONAL BUREAU OF STANDARDS (NBS)
U.S. Product Standards PS 1-83 for Construction and Industrial Plywood.

(Application for copies of NBS publications should be addressed to the National Center for Standards and Certification, Department of Commerce, Administration Building, Room A-633, Gaithersburg, Maryland 20899.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:52Z
Check the source to verify that this is the current version before use.

* (Copies of specifications, standards, and other Government documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

* 2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted shall be those listed in the issue of the DoDISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DoDISS shall be the issue of the nongovernment document which is current on the date of the solicitation.

SAE, INC.

SAE Standards and Recommended Practices

	J245	- Engine Rating Code - Spark Ignition.
	J537	- Storage Batteries (DoD adopted).
	J551	- Performance Levels and Methods of Measurement of Electromagnetic Radiation from Vehicles and Devices (20-1000 MHz).
	J588	- Turn Signal Lamps.
	J589	- Turn Signal Switch.
	J682	- Rear Wheel Splash and Stone Throw Protection (DoD adopted).
*	J683	- Tire Chain Clearance - Trucks, Buses, and Combinations of Vehicles (DoD adopted).
	J688	- Truck Ability Prediction Procedure (DoD adopted).
	J704	- Openings for Six- and Eight-Bolt Truck Transmission Mounted Power Take-Offs (DoD adopted).
	J816	- Engine Test Code - Spark Ignition and Diesel.
*	J1349	- Engine Power Test Code - Spark Ignition and Diesel.

(Application for copies of SAE publications should be addressed to SAE, Inc., 400 Commonwealth Drive, Warrendale, PA 15096.)

THE TIRE AND RIM ASSOCIATION, INC. (T&RA)

Yearbook.

(Application for copies of T&RA publications should be addressed to the Tire and Rim Association, Inc., 3200 W. Market Street, Akron, OH 44313.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:52Z
Check the source to verify that this is the current version before use.

* 2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, (except for associated detail specifications, specification sheets or MS standards) the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

* 3.1 Standard vehicle and accessories. Except as specified in 3.1.1 through 3.1.1.9, the vehicle, components, assemblies, and accessories to be delivered under the contract shall be standard or optional items which meet or exceed the requirements of this specification. All chassis items shall be as represented in the chassis manufacturer's technical data, and special bodies or mounted equipment shall be as represented in the body and equipment manufacturer's technical data. Technical data shall be limited to specifications and technical material, identical to that furnished to the authorized company representatives for selection of vehicle models and components, and shall be on file in the engineering offices of the procuring activity prior to delivery of the items. The chassis model furnished shall be not older than the chassis manufacturer's current model on the date of invitation for bids.

3.1.1 Special requirements. In addition to the standard vehicle and components specified in 3.1, the vehicle shall be furnished with special equipment as specified herein.

* 3.1.1.1 Painting and marking. Treatment, painting, marking and data plates shall be in accordance with MIL-STD-1223. The exterior color and the identification markings shall be in accordance with the requirements of MIL-STD-1223 for the military service identified by the procuring activity (see 6.2) and in accordance with 3.5.1.1 or 3.5.4.

* 3.1.1.2 Rustproofing. When specified (see 6.2), the vehicle shall be rustproofed in accordance with FED-STD-297. When specified (see 6.2), tropical rustproofing in accordance with FED-STD-297 shall be furnished.

3.1.1.3 Drain plugs. Drain plugs installed in manual transmissions and rear axles shall be of the permanent magnet type.

3.1.1.4 Heavy duty cooling system. When specified (see 6.2), a heavy duty cooling system shall be furnished that will maintain engine coolant at a temperature below the boiling point with the vehicle loaded to rated GVW and operated at an altitude of 10,000 feet above sea level or in an ambient air temperature of not less than 125 degrees Fahrenheit (°F).

Source: https://assist.dla.mil -- Downloaded: 20261O-22T02:52Z
Check the source to verify that this is the current version before use.

3.1.1.5 Coolant system and indicators. The coolant system shall include a de-aeration system, a surge tank or a coolant recovery reservoir of not less than 2-quart capacity. A high coolant temperature or low coolant level alarm buzzer and red indicator warning light shall be provided on the dash instrument panel. On tilt cab models, a radiator servicing access door shall be provided to allow verification of coolant level.

* 3.1.1.6 Wood treatment. As specified herein (see 3.5.5), wood shall be treated in accordance with MIL-STD-1223.

3.1.1.7 Towing devices. Not less than two hooks, loops, or pins for towing the vehicle shall be furnished on the front of the vehicle. The towing devices shall be installed on the chassis frame or on reinforcements attached to the chassis frame.

* 3.1.1.8 Wheel splash and stone throw protection. The vehicle shall have rigid splash shields ahead of the rear wheels and rubber mud flaps to the rear of the rear wheels. All tilt cabs shall have rubber mud flaps to the rear of the front wheels. All splash shield and mud flap installations, front and rear, shall conform to the rear splash and stone throw protection provisions of SAE J682. A metal strip not less than 1/8 inch thick and not less than one inch wide, extending the entire width of the mud flap, shall be used as a backing to preclude bolt head or bolt nut from rupturing the mud flap due to tightening operations during installation.

* 3.1.1.9 Hydraulic tailgate. The vehicle shall be equipped with a electric motor driven hydraulic tailgate having not less than 2000 pounds rated capacity. The tailgate shall fold vertically against the rear doors for travel. All operations shall be hydraulically powered or metered, providing for raising, lowering, folding and unfolding without manual assistance. All hydraulic cylinders shall be provided with flow restrictors in the down port of the cylinder to prevent the tailgate from falling rapidly in the event of a hydraulic system failure. Safety devices shall be furnished to secure the tailgate in travel position. Tailgate platform shall be of the ramp type and shall taper down to ground level, shall have a depth of not less than 36 inches including ramp and shall be of maximum length suited to width of body. Platform loading area shall be of non-skid material. The lift gate shall have toe clearance on both ends of the platform and latches to hold lift gate at loading level. Controls shall be mounted outside the body on the curbside. Rear bumper and additional rear end protection need not be furnished.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:52Z
Check the source to verify that this is the current version before use.

3.2 General design.

3.2.1 Federal Motor Vehicle Safety Standards. The vehicle and furnished accessories shall comply with all Federal Motor Vehicle Safety Standards in effect on the date of manufacture.

3.2.2 Air pollution control. The vehicle shall comply with EPA Regulations Governing Control of Air Pollution from New Motor Vehicles and New Motor Vehicle Engines in effect on the date of manufacture. In addition, vehicles destined for California shall comply with State of California regulations governing air pollution control in effect on the date of manufacture.

3.2.3 Sound level. The interior sound level shall conform to Federal Motor Carrier Safety Regulation 393.94. The vehicle exterior sound level shall conform to the EPA Noise Emission Standards for Transportation Equipment, Medium and Heavy Trucks.

3.2.4 Curb weight. Curb weight shall include weight of chassis and cab, with all attachments, accessories, and equipment; body; and full complement of fuel, lubricants, and coolant.

3.2.5 Gross vehicle weight. Gross vehicle weight (GVW) shall consist of curb weight, operator (weight computed at 175 pounds), and a payload to provide not less than the specified GVW.

3.2.6 Weight distribution. The distribution of GVW for the purpose of establishing suspension, axle and tire capacities shall be determined with the payload uniformly distributed over the load area.

3.2.7 Ratings. Vehicle ratings shall be the manufacturer's published ratings. Component and vehicular ratings shall not be raised to meet the requirements of this specification. When published ratings are not available, verification of ratings must be submitted to the engineering office of the procuring activity. Minimum GVW shall be not less than 24,000 pounds.

* 3.2.8 Overall width. The overall width of the vehicle, exclusive of mirrors, lights, reflectors and tires shall be not more than 96 inches. The width-over-tires shall be not more than 100 inches.

* 3.2.9 Accessibility. The design of the vehicle and optional equipment shall permit access for routine servicing, and shall permit access for replacement and adjustment of component parts and accessories with minimal disturbance of other components and systems.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:52Z
Check the source to verify that this is the current version before use.

3.3 Performance.

3.3.1 Speeds and gradeability. High and low speed requirements shall be met with the vehicle loaded to specified GVW.

* 3.3.1.1 High speed gradeability. The vehicle shall ascend a 1.0 percent grade at 50 miles per hour (mph). Gradeability requirements shall be met with the main transmission in direct drive, and when a two-speed axle is furnished (see 3.4.9.1), with the axle in high speed range. Gradeability shall be verified with calculations in accordance with SAE J688 (see 6.3).

3.3.1.2 Low speed. Low speed shall be calculated with engine operating at not less than 35 percent of recommended governed speed, and shall provide a vehicle speed of not more than 5 mph.

* 3.3.1.3 Maximum geared speed. Maximum geared speed at engine governed speed shall be not less than 58 mph. Conformance to geared speed specified shall be determined by calculating in accordance with the following formula:

$$\text{Maximum geared speed (mph)} = \frac{\text{Governed speed (rpm)}}{\text{Total gear reduction x tire factor}}$$

3.3.2 Service brakes. Service brakes shall control and hold the vehicle, when loaded to its specified GVW, on a 30 percent grade. The service brakes shall stop the vehicle, loaded to specified GVW, within the stopping distance requirements of Federal Motor Carrier Safety Regulation 393.52.

3.4 Chassis components.

3.4.1 Engine. The engine furnished shall be the chassis manufacturer's standard or optional engine for the commercial model truck which meets or exceeds the requirements of this specification.

* 3.4.1.1 Diesel engine. Unless otherwise specified (see 3.4.1.2), the vehicle shall be equipped with a liquid cooled, compression ignition, two-stroke or four-stroke cycle diesel engine, with not less than six cylinders. Engine net horsepower figures used in performance prediction calculations shall be determined in accordance with SAE J816 or SAE J1349. A fan clutch shall be provided. The fan clutch shall reduce the fan speed automatically when the fan is not required for engine cooling.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:52Z
Check the source to verify that this is the current version before use.

* 3.4.1.2 Gasoline engine. When specified (see 6.2), the vehicle shall be equipped with a liquid cooled, internal combustion, four-stroke cycle gasoline engine with not less than six cylinders. The engine furnished shall produce the required vehicle performance when operated on unleaded fuel with a research octane rating of 91, at engine speed not more than manufacturer's recommended operating speed. The engine shall be capable of warranted operation on unleaded fuel when used in accordance with the operator's manual. Engine net horsepower figures used in performance prediction calculations shall be determined in accordance with SAE J245 or SAE J1349. A fan clutch shall be provided. The fan clutch shall reduce the fan speed automatically when the fan is not required for engine cooling.

3.4.1.3 Oil filter. A full flow type oil filter shall be furnished.

3.4.1.4 Governor. An engine governor shall be furnished and set and sealed to limit the engine to the engine manufacturer's maximum recommended operating speed.

3.4.1.5 Coolant temperature control. Thermostatic control of engine coolant temperature shall be provided. For diesel engine driven vehicles, control shall include partial thermostatic control of coolant flow through the radiator and thermostatically controlled radiator shutters, or complete thermostatic control of all coolant flow through the radiator.

* 3.4.1.6 Power plant heaters and fuel warmer. When specified (see 6.2), a coolant heater, an engine oil heater, and a fuel warmer (diesel engine driven vehicles only) shall be provided. Unless otherwise specified (see 6.2), a battery heater shall be provided when power plant heaters are specified. Heaters shall operate on 110-volt alternating current (ac), and shall be wired through a junction block to a single three-pronged (male), weatherproof slave receptacle for receiving external power and grounding vehicle. A three-wire connecting cable, 25 feet long and of adequate line capacity to supply power for all heater units simultaneously, shall be furnished. Connecting cable shall include a matching female connector at the vehicle end and a standard three-pronged (two power plus one ground) male connector at the other end. Electrical apparatus shall conform to Federal Motor Carrier Safety Regulation 393.77(c)(7). Electrical insulation of connecting cable shall withstand normal operating stresses in low ambient air temperatures (down to minus 60°F) without cracking or loss of dielectric capacity. All heater lead wires shall be installed without interfering with vehicle component operation and without loose excess wire.

Source: https://assist.dla.mil -- Downloaded: 202640-22T02:52Z
Check the source to verify that this is the currentversion before use.

Provisions for stowage of the cable shall be provided in the vehicle cab. Heaters shall be furnished as follows:

(a) Coolant heaters, 1500-watt minimum rating, shall be installed in the engine block or in the lower coolant inlet hose. Engine thermostat with an operating range of 170°F to 195°F shall be installed.

(b) Immersion type engine oil heater, 300-watt minimum rating, with 170°F to 195°F thermostat, shall be installed in the oil pan through any convenient opening.

(c) Battery heater shall have a capacity adequate to maintain the battery electrolyte at a temperature of not less than 10°F during vehicle exposure in ambient air temperatures as low as minus 60°F, and shall embody a thermostat to limit the temperature of the electrolyte to not more than 80°F.

(d) A fuel warmer or pre-heater shall be provided on diesel engine driven vehicles to prevent clogging of fuel filters due to wax crystallization in the fuel. The fuel warmer shall use engine coolant to transfer sufficient heat to the diesel fuel to heat it from an inlet temperature of minus 40°F to an outlet temperature of plus 9°F, with a flow rate not less than the maximum fuel demand of the engine fuel system. A coolant shutoff valve shall be provided for the coolant inlet side of the fuel warmer unit.

3.4.2 Electrical systems. Electrical systems shall be in accordance with Federal Motor Carrier Safety Regulations 393.27 through 393.31 and 393.33.

* 3.4.2.1 Starting system. For diesel engine driven vehicles, a 12- or 24-volt starting system, with 12-volt direct current (dc) lighting system shall be furnished. Unless otherwise specified (see 6.2), a minimum 60-ampere alternator shall be furnished. Engine starting equipment shall include an ether starting system or glow plug. If an ether system is furnished in lieu of a glow plug, it shall be of the measured shot type. Measured shot type ether systems shall be key operated or manually operated from the driver's compartment and shall be inoperative with the engine warm. Complete provisions for a replaceable ether reservoir of not less than 12 fluid ounces shall be furnished. A reservoir need not be furnished.

* 3.4.2.2 Ignition system. For gasoline engine driven vehicles, a 12-volt dc ignition system shall be furnished. Unless otherwise specified (see 6.2), an alternator of not less than 40 amperes rated capacity, and which provides not less than 16 amperes dc output at normal engine idle speed, shall be furnished.

Source: https://assist.dla.mil -- Downloaded: 202610-22T02:52Z
Check the source to verify that this is the currentversion before use.

3.4.2.3 Lighting. All vehicle lights, reflectors, and wiring shall be as specified herein and shall conform to Federal Motor Carrier Safety Regulations 393.12, 393.13, 393.19, 393.20 and 393.22 through 393.26(d). Lights and reflectors shall not be mounted on vertical surface of rub rails (unless recessed and fully protected) or mounted on vehicle bumpers.

3.4.2.4 Turn signals. Turn signal lamps shall conform to SAE J588. Operating units shall conform to SAE J589, class A, and shall be mounted on the steering column. Vehicle shall be provided with double-faced front signal units and with single-faced rear signal units installed in accordance with SAE J588 except that turn signals shall not be mounted on engine compartment hood.

* 3.4.2.5 Batteries. Each battery shall be of 12-volt potential. The total reserve capacity rating at 80°F. and the total cold cranking ampere rating at 0°F, both measured in accordance with SAE J537, shall be not less than specified in table I. Batteries shall be of the maintenance-free type having the maintenance-free characteristics listed in W-B-131.

* TABLE I. Batteries.

Engine type	Reserve capacity (minutes)	Cold cranking (amperes)
Diesel	320	1200
Gasoline	100	450

* 3.4.2.6 Radio interference suppression. The vehicle shall be suppressed to limit electromagnetic radiation in accordance with SAE J551. Any body equipment emitting radiation shall be suppressed to the same level as the vehicle chassis.

3.4.3 Fuel system. The fuel system shall conform to Federal Motor Carrier Safety Regulations 393.65 and 393.67.

3.4.3.1 Air cleaner. An air cleaner shall be furnished. When equipped with an oil-bath type air cleaner, oil capacity shall be not less than 1 quart.

* 3.4.3.2 Fuel tank. Fuel tank(s) shall be of not less than 50 gallon total capacity (43 gallons for California). When more than one tank is provided on diesel engine driven vehicles, means shall be provided to assure an equalized fuel level in both tanks. When more than one tank is furnished on gasoline engine driven vehicles, a selector valve connecting either tank to the engine fuel intake shall be provided and means shall be provided to monitor the fuel level of either tank from a single fuel gage.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:52Z
Check the source to verify that this is the current version before use.

* 3.4.4 Exhaust system. The exhaust system shall conform to Federal Motor Carrier Safety Regulation 393.83. If vertical exhaust mufflers are being furnished, and if they are capable of being reached easily by personnel entering or leaving either side of the cab, a heat shield shall be provided. Exhaust systems, if vertical, shall be provided with a hinged rain cap.

* 3.4.5 Transmission. Unless otherwise specified (see 3.4.5.2), a manually shifted transmission shall be provided on the vehicle. Input torque capacity of transmission shall be at least equal to the maximum torque delivered by the engine. The vehicle shall be provided with not less than 5 forward speeds. Gear ratios in transmission and axles shall be matched to provide a progressive shifting pattern throughout the complete range, and shall provide required vehicle performance (see 3.3.1). The transmission shall be provided with SAE J704 power take off openings at right and left sides. The transmission shall provide for maximum ease of shifting in all speeds.

3.4.5.1 Clutch. The clutch shall be the largest capacity clutch offered for the vehicle and engine furnished, with clutch torque capacity exceeding maximum delivered engine torque.

* 3.4.5.2 Automatic or semiautomatic transmission. When specified (see 6.2), the vehicle shall be provided with an automatic or semiautomatic transmission. The transmission furnished shall provide continuous drive. The transmission shall include a hydraulic torque converter and four forward gear ratios. Normal driving range selector position shall provide not less than four gear ratios without movement of the selector. The transmission shall be provided with SAE J704 power takeoff opening(s). The input torque capacity of the transmission shall be at least equal to the maximum torque delivered by the engine.

3.4.6 Drive line components. Drive line components shall be adequate to transmit the maximum delivered torque of the engine, as developed through the maximum gear train reduction.

3.4.7 Frame. The chassis frame shall be the manufacturer's standard for the type of vehicle furnished.

3.4.8 Suspension. The vehicle shall be equipped with a suspension system, with components having a rated capacity at least equal to the load imposed on each member, measured at the ground, with vehicle loaded to specified GVW. When suspension is rated at the spring pads, unsprung weight shall be deducted. The vehicle shall be equipped with hydraulic, double-acting shock absorbers at the front wheels.

Source: https://assist.dla.mil -- Downloaded: 202610-22T02:52Z
Check the source to verify that this is the currentversion before use.

* 3.4.9 Axles. Axle ratings shall be at least equal to the load imposed on each axle, measured at the ground, with the vehicle loaded to specified GVW. Unless a two-speed axle is furnished, a single reduction rear axle shall be provided.

3.4.9.1 Two-speed axle. When specified (see 6.2), or when furnished in accordance with 3.4.5, a two-speed axle shall be furnished, equipped with electric, vacuum, or air shift and provided with ratios which will permit proper gear splitting. Gear ratio shall provide performance specified in 3.3.

* 3.4.10 Wheels, rims, tires and tubes. The vehicle shall be equipped with single front and dual rear wheels. Rims and tire ratings shall conform to Tire and Rim Association recommendations for the type and size of tires furnished. Rim and disc wheel sizes shall be the same for all wheels on each vehicle. Tire size and load range (ply rating) shall be the same for all tires on the vehicle. When specified (see 6.2), 10-stud disc type wheels shall be furnished.

* 3.4.10.1 Tires. Steel belted radial or, when specified (see 6.2), bias ply tires shall be furnished. Tires shall be tube or tubeless type with highway tread. Tires shall be of rated capacity at least equal to the load imposed on each tire, measured at each wheel at the ground, with the vehicle loaded to specified GVW. Tires shall conform to Tire and Rim Association recommendations or to ZZ-T-381 with a size designation system the same as the Tire and Rim Association.

3.4.10.2 Inner tubes. For tube type tires, inner tubes shall be of heavy duty type and shall be of proper size for tires furnished. Tire flaps shall be provided for tube type tires in accordance with Tire and Rim Association recommendations.

* 3.4.10.3 Spare wheel or rim. When specified (see 6.2), a spare wheel or rim shall be furnished. When a spare tire assembly is specified (see 3.4.10.4), a spare wheel or rim shall be furnished. The spare wheel or rim shall be the same size as those furnished on the vehicle.

* 3.4.10.4 Spare tire assembly. When specified (see 6.2), a spare tire assembly shall be furnished. The spare tire assembly shall include an inflated spare tire mounted on the spare wheel or rim. The spare tire shall be of the same size, tread design and load range (ply rating) as furnished on the vehicle.

3.4.10.5 Tire chain clearance. Tire chain clearance in accordance with SAE J683 shall be provided. Allowance for spring deflection shall be included.

Source: https://assist.dla.mil -- Downloaded: 202610-22T02:52Z
Check the source to verify that this is the current version before use.

3.4.11 Brakes. Brakes shall conform to Federal Motor Carrier Safety Regulations 393.40 through 393.43 and 393.45 through 393.52.

3.4.11.1 Service brakes. The vehicle shall be equipped with full-air brakes. The braking system, complete with all necessary components, shall include:

(a) Air compressor, unloader-head type, engine driven and engine lubricated, air or water cooled, and having a capacity of not less than 7-1/4 cubic feet per minute (cfm).
(b) Air storage reservoir(s) with not less than 2,000 cubic inches total capacity, each tank equipped with drain, and with safety and check valves between compressor and last reservoir tank.
(c) Foot control, suspended or treadle type.
(d) Air control valves.
(e) Air pressure gage, visible to the driver.
(f) Low air pressure warning, visible and audible.
(g) Service brake stop lamp switch.
(h) Alcohol aspirator with unbreakable transparent container.
(i) Automatic moisture ejector.
* (j) Automatic slack adjusters.
* (k) When specified (see 6.2), in lieu of subparagraph (h), an air dryer shall be furnished. The air dryer shall be the desiccant or after-cooled type.

3.4.11.2 Brake controls for use from a towing vehicle. When specified (see 6.2), the vehicle shall be furnished with a system for controlling the brakes from a towing vehicle (wrecker). The installation shall be complete with air brake couplers, relay emergency valve with no-bleed-back feature except when spring applied emergency brake is furnished, additional air lines and fittings. The service and emergency couplers shall be mounted on the front in a protected position providing for ready attachment of air hoses from a towing vehicle. The service and emergency couplers shall be identified and provided with dummy gladhand couplers with chains. The system shall not compromise conformance to any Federal Motor Carrier Safety Regulation referenced herein or to any Federal Motor Vehicle Safety Standard.

* 3.4.12 Cab. Unless otherwise specified, manufacturers may furnish any standard full-width model cab. When specified (see 6.2), a tilt type cab, with tilting and locking mechanism, shall be furnished. Tilt cab features shall be in accordance with the Employee Safety and Health Standards of Federal Motor Carrier Safety Regulation 399, including the first step height, which shall be not more than 24 inches. Cab doors shall be equipped with locks, operable from inside the cab through mechanical linkage, and with at least the curbside door equipped with an external, key-operated lock. Drip rails shall be installed above the cab doors. Unless otherwise specified, the cab shall have upholstered,

Source: https://assist.dla.mil -- Downloaded: 202610-22T02:52Z
Check the source to verify that this is the currentversion before use.

full-width, adjustable seat and back or individual, adjustable driver's seat and individual passenger seat. When specified (see 6.2), an individual, adjustable, driver's seat and an individual passenger seat shall be provided. The color of the upholstery and the interior finish shall be compatible with the exterior color (see 3.1.1.1). White upholstery shall not be furnished. Interior lighting shall be provided. Manufacturer's standard fastenings and two pairs of seat belts shall be installed on the vehicle. For tilt type cabs, provisions to facilitate cleaning the windshield shall be provided by means of a bumper step, or bumper step cutouts, and a grab handle located under the windshield. Safety grips shall be provided on each side of the cab to assist personnel in entering and leaving the cab.

3.4.13 Steering. Power steering shall be furnished.

3.4.14 Windshield wipers and washers. The vehicle shall be equipped with dual windshield wipers and windshield washers. Windshield wipers shall be multispeed type and operated by either air or electric motor(s).

3.4.15 Bumper. Unless the bumper is an integral part of the vehicle cab, a channel type front bumper shall be provided.

3.4.16 Tool stowage. Stowage space of sufficient size to accommodate a vehicle jack, hand tools, antiskid chains, and emergency reflective triangles shall be furnished for retaining equipment during vehicle operation. Stowage space for these tools may be furnished inside the cab. When stowage space for these tools is located outside of the cab, it shall be weatherproof and shall provide for locking with a padlock.

3.4.16.1 Tools. When specified (see 6.2), the vehicle shall be furnished with tools required for exchanging the mounted tire assembly with the spare assembly, and shall include at least a hydraulic jack, jack handle and wheelnut wrench. The jack shall be of such closed height as to permit its location under axle, or other satisfactory lift point at any wheel with the tire flat. The jack, without blocking, shall be capable of raising any wheel of the loaded vehicle to a height adequate to permit removal and replacement of the wheel and tire assembly.

3.4.17 Heater and defroster. The vehicle shall be provided with a hot water heater with fresh air intakes and discharge outlets to floor and to windshield defroster louvers. The heater shall be complete with blower and mounted controls convenient to the driver.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:52Z
Check the source to verify that this is the current version before use.

3.4.18 Controls and operating mechanisms. All controls and operating mechanisms shall be located for left hand drive. Controls shall be complete and conveniently operable by the driver. Lever controls shall be designed and located to permit easy entrance and exit of operator to and from the driver's compartment. Instruments and controls shall be identified as to their function and installed in a manner to facilitate removal and servicing. All instruments shall be visible to the driver when seated in driving position.

3.4.19 Accessories and equipment. Chassis equipment shall be complete with all accessories furnished as standard equipment by the manufacturer. The following minimum equipment shall be furnished:

(a) Key-operated ignition switch.
(b) Ammeter, charging indicator or voltmeter.
(c) Fuel gage.
(d) Oil pressure gage or indicator.
(e) Engine temperature gage or indicator.
(f) Speedometer with recording odometer.
(g) Dual sunvisors.
(h) Driver's compartment ventilator other than window.
(i) Tachometer (not required for gasoline vehicle).

3.4.20 Rearview mirrors. Outside rearview mirrors shall be mounted on each side of the cab. The mirrors shall be of the combination type having flat and convex areas enclosed in a common housing. The flat portion shall have not less than 50 square inches of reflective area. The convex portion shall have not less than 20 square inches of reflective area. The mirrors on conventional cabs shall have not less than three supporting arms. On tilt cabs, the mirrors shall have not less than two supports.

3.4.21 Horn. Manufacturer's standard electric horn shall be furnished. When specified (see 6.2), in addition, an air operated horn shall be provided.

* 3.4.22 Engine hour meter. An engine hour meter having a totalizing mechanism of not less than 9,999 hours shall be furnished for the chassis engine to register accurately the number of hours of operating time. The meter shall be of rugged construction to insure continuous trouble-free performance under severe operating conditions. The engine hour meter shall be mounted on the cab instrument panel or in the engine compartment in a readable location.

3.4.23 Back-up alarm. When specified (see 6.2), the vehicle shall be provided with an audible, pulsating, signaling device (electrical or mechanical) to caution personnel when the vehicle is in reverse gear operation.

Source: https://assist.dla.mil -- Downloaded: 202610-22T02:52Z
Check the source to verify that this is the current version before use.

* 3.4.24 Air conditioning. When specified (see 6.2), the vehicle shall be equipped with the manufacturer's standard air conditioning system. The air conditioning system shall include tinted windshield and tinted glass.

3.5 Body. The vehicle shall conform to the dimensions specified in table II. The cab to axle dimension specified in table II may be reduced not more than 2 inches when a tilt cab is furnished (see 3.4.12).

TABLE II. Dimensions.

Feature	Inches
Rear of cab to rear axle (minimum)	144
Length (inside minimum)	252
Width (inside minimum)	90
Height (inside minimum)	96
Height, ground-to-roof (maximum)	150

* 3.5.1 Body. Body subframe, rear corner posts, rear header, and rear crossmember, shall be constructed of steel. Body side posts, front posts, roof panels, rub rails or buffer sheets and, unless fiberglass reinforced plastic/plywood (FRP plywood) panels are specified, side and front wall panels shall be constructed of aluminum. Roof bows shall be aluminum or steel (see 3.5.4.). Steel used shall be of the minimum gages specified for carbon steel. High tensile steel used may be two gages lighter weight in accordance with US Standard gages. Effective means shall be taken to preclude electrolytic action between dissimilar metals.

* 3.5.1.1 FRP/plywood panels. When specified (see 6.2), FRP/plywood panels shall be furnished. FRP/plywood panels shall be fabricated of one-piece plywood core laminate with fiberglass reinforced plastic. The plywood furnished shall equal or exceed U.S. Department of Commerce Standard No. 1, C-D (plugged) with exterior glue and with all plies group 1 species or better. Core material shall be butted, scarfed or finger joined with joint gaps not greater than 1/8 inch. The fiberglass reinforced plastic (FRP) shall contain not less than 18 ounce fiberglass woven roving material. The plastic shall be fully cured under heat and pressure to insure that the resins form an integral bond to the plywood core. The exterior surfaces shall consist of a gel coat of .015 inch $\pm$ .003 inch. The gel coat shall be pigmented manufacturer's standard white. Panels shall have an overall finish panel thickness of not less than 5/8 inch. Finished panels shall exhibit a smooth vehicle exterior surface with no evidence of discontinuity.

Source: https://assist.dla.mil -- Downloaded: 202610-22T02:52Z
Check the source to verify that this is the current version before use.

* 3.5.1.2 FRP/plywood panel installation. The FRP/plywood panels shall be installed with extruded aluminum corner posts, top rails, bottom rails and side door frames. Panels shall be one piece. Vertical intermediate body posts shall not be used. Post, rails and side door frames shall have channel type receiving edges providing attachment to panels with fasteners in a double shear and shall have a grip range of not less than 2-1/2 inches. Posts, rails and door framing shall extend not more than 1/2 inch beyond the outer panel skin. Panel edges shall be sealed with waterproof mastic prior to installation. Installed panels shall be sealed with a high performance silicone caulking compound on all enclosing edges. Panels shall be secured to posts and rails using through-fasteners with a head diameter of not less than 1/2 inch. All fastener installations shall be double shear and shall be waterproof.

3.5.2 Body subframing. Body subframing shall be of welded construction, braced at all points of stress. There shall be not less than 14 full width crossmembers, including ends, of full channel or equivalent section, steel construction, attached to longitudinal sills by welds, and at front, rear, and every second intervening crossmember by gussets. When subframing is welded assembly, angle gussets, crossmembers, longitudinal sills, and welded reinforcement, when used, shall be joined by weld for not less than 50 percent of the length of the contact edge(s). Spacing of crossmembers shall be equal, ahead of, and to the rear of the wheels. Longitudinal sills shall be constructed of structural steel channel, structural I-beam, or reinforced formed channels or I-beams. Formed channel sills and I-beams shall be reinforced within the sill, at each crossmember or body mounting point with formed channel reinforcements. Crossmembers, gussets, formed longitudinal sills, and reinforcements shall be not less than 10 gage (0.1345 inch) steel. Extruded aluminum or steel side and front rails shall be furnished. Side rails shall be reinforced in the area of the double side doors and shall be furnished with rails or pockets for attaching loading ramps (see 3.5.11). When steel side and front rails (out-rails) are furnished they shall be not less than 12 gage (0.1046 inch) steel. The design of the subframe shall permit a low floor height without wheel wells, while providing tire chain clearance, and shall permit vehicle operation at speeds up to 50 mph over improved roads, when loaded with an evenly distributed payload to the rated GVW, without evidence of permanent deformation.

3.5.3 Body framing. Side and front post construction shall be extruded aluminum and shall be not less than 1.187 inches in depth and 0.330 pound per foot when side and front wall posts are spaced on 18-inch maximum centers. Side and front post construction shall be extruded aluminum and shall be not less than 1.26 inches in depth and 0.430 pound per foot, when side and front wall posts are spaced on

Source: https://assist.dla.mil -- Downloaded: 202610-22T02:52Z
Check the source to verify that this is the current version before use.

24-inch maximum centers. Front corner post construction shall be extruded aluminum and shall be not less than 1.0 inch in depth and 0.482 pound per foot. The front structure shall be capable of withstanding a horizontal static load equal to 0.4 times the payload capacity of the vehicle without permanent distortion. Rear corner posts shall be not less than 12 gage (0.1046 inch) steel.

* 3.5.4 Body exterior. Roof assembly shall be standard for the vehicle, and shall be so constructed as to insure drainage. Roof support bow construction shall be extruded aluminum or not less than 18 gage (0.0478 inch) galvanized steel, 1.38 inches in depth. When aluminum roof support bows are spaced on 24-inch maximum centers, the roof bows shall be not less than 1 inch in depth and 0.360 pound per foot and the roof panel shall be not less than 0.040 inch aluminum alloy. When aluminum roof support bows are spaced on 18-inch maximum centers, the roof bows shall be not less than 1 inch in depth and 0.380 pound per foot, and the roof panel shall be not less than 0.025 inch aluminum alloy. When steel roof support bows are used, they shall be spaced on not more than 24 inch centers and the roof panels shall be not less than 0.040 inch aluminum alloy. Body side panels shall be not less than 0.032 inch aluminum alloy and unless otherwise specified (see 6.2), shall be prepainted the manufacturers standard white. Unless FRP/plywood panels are specified (see 3.5.1.1), body side panels shall be removable to facilitate body repair. All roof and body seams and joints shall be weatherproof and all body and roof rails shall be of extruded aluminum. The front corner radius and top longitudinal edge radius shall be the largest furnished for the model offered. An aerodynamically streamlined body front shall be incorporated into the design of the body to direct airflow around the sides and over the top of the van body. The construction shall be integral with the van body front wall, sidewalls and roof, giving a curved front radius. The van body surface shall be smooth-skinned, without exposed exterior vertical posts or vertical corrugations, so as to minimize aerodynamic drag. Stretcher-leveled skins are not required. Rub rails or buffer sheets extending outward beyond the body skin shall be provided on both sides of the body. The rub rails or buffer sheets shall be permanently attached to or shall be an integral part of the exterior of the body at the floor line. Drip moldings shall be furnished along each side at the top and over the rear doors. All dissimilar metals which are used throughout the vehicle shall be insulated from one another to preclude galvanic or electrolytic action.

* 3.5.5 Body interior. When aluminum side panels are required (see 3.5.4), the interior of the body side walls, panels and the doors shall be lined with not less than 3/8-inch exterior grade plywood. The front shall be lined with not less than 1/2-inch exterior grade plywood. The

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:52Z
Check the source to verify that this is the current version before use.

ceiling shall be lined with not less than 1/4-inch exterior grade plywood installed between the roof skin and the roof bows, or below the roof bows. Interior radius corners may be lined with aluminum or 1/8-inch fiberglass material.

* 3.5.5.1 Optional equipment. When specified (see 6.2), the following optional equipment shall be furnished in the quantities and in accordance with the requirements specified by the purchaser:

(a) Furniture pads.
(b) Appliance truck.
(c) Walkboards.
(d) Piano board with straps.
(e) Floor runners, canvas.
(f) Refrigerator cover.
(g) Stove cover.
(h) Tie webbing (roll).
(i) Piano straps.

3.5.6 Flooring. The platform shall be floored longitudinally with either shiplap or tongue-and-groove joints or with laminated hardwood. Wood flooring shall be of hardwood or dense southern yellow pine not less than 1-5/16 inches thickness (finished dimensions). Wood floor parts shall be treated in accordance with 3.1.1.6. Wood floor boards shall be attached to the subframe at crossmembers with self-tapping countersunk corrosion-resistant screws. The countersunk screw holes shall be filled with wood putty and sanded smooth. The floor shall present a snag free surface. When specified (see 6.2), a protective flexible wood sealer shall be applied to the floor.

* 3.5.7 Interior rope ties. Interior rope ties, either fold down lashing rings, rope cleats, or rod type, shall be installed and secured to wall frame members. When FRP/plywood panels are specified (see 3.5.1.1), interior rope ties shall be installed using through-fasteners with a head diameter of not less than 1/2 inch. FRP/plywood fasteners installation shall be waterproofed and exposed fasteners shall be painted to match the vehicle exterior. A minimum of 36 rope ties shall be arranged in three evenly spaced tiers, four rope ties per tier on each wall; first tier located approximately 3 inches above the floor line, second tier at 1/3 of wall height, and third tier located at 2/3 of wall height. Rope ties shall not project into the cargo area beyond the wall lining.

3.5.8 Double rear doors. Double rear doors shall be provided, full width and height, with bracing to prevent sagging, and equipped with three cast steel, or equal, hinges per door. The door locking devices shall include not less than three bolts or latches, located at

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:52Z
Check the source to verify that this is the current version before use.

top, bottom and center of door. Cam type locking devices may be furnished at top and bottom of door. The center locking device shall be provided with an operating handle and shall be installed to insure positive closing under all operating conditions and with provision for the use of a padlock. Body shall be equipped at sides with catches for holding doors in fully open position. Hardware shall be manufacturer's standard.

3.5.9 Double side doors. Double side doors shall be provided ahead of the rear wheelhousing on the curbside. The opening for the side doors shall be not less than 84 inches in width and full height. The doors shall conform to 3.5.8 for bracing, hinges, bolts or latches, center locking device, operating handle, padlocking provisions, catches and hardware.

* 3.5.10 Loading ramp rails or pockets. Loading ramp rails or pockets for the ramps, specified in 3.5.11, shall be provided at the rear doors and at the side doors.

* 3.5.11 Loading ramp. A loading ramp of all metal, lightweight construction, complete with hooks and handles, shall be furnished. The upper (walking) surface of the ramp shall be of skidproof design. The ramp shall be not less than 24 inches wide and 14 feet long, and shall be capable of supporting a concentrated moving load of not less than 900 pounds in both a ramping and in a bridging position. Ramp attaching devices shall be compatible with the pockets or rails specified in 3.5.2 and 3.5.10. The ramp shall be marked as to its capacity. Markings shall be clearly visible with the ramp in any usable position.

3.5.11.1 Ramp stowage. A weatherproof and splashproof stowage compartment for the ramp shall be provided in the area under the body floor and above the chassis crossmembers. Padlocking provisions shall be furnished.

3.5.12 Interior lighting. At least two domelights shall be provided. A single light switch to control both lights shall be located at the rear right side inside the van. In addition, a light switch with a telltale light shall be installed in the cab.

3.5.13 Body mounting. Body shall be secured with U-bolts, twin studs, brackets, or J-bolts and shall include a breaker strip.

3.5.13.1 U-bolts or twin studs. When U-bolts or twin studs are used, there shall be not less than six U-bolts or twin studs per side, each having 9/16-inch minimum body diameter with 5/8-inch minimum thread diameter. Tie-plates shall be at least 1/2 inch thick. Vehicle chassis

Source: https://assist.dla.mil -- Downloaded: 202610-22T02:52Z
Check the source to verify that this is the currentversion before use.

frame shall be braced, using wood blocks at each mounting point unless mounting point is located at a full depth frame crossmember. Blocks shall incorporate a keeper strap or groove for mounting bolt, and shall be of a width and thickness to assure retention. Two tie-back straps shall be provided, one on each side of rear portion of body sub frame, to maintain body alinement on vehicle chassis. Forward body mounting bolts shall be located to the rear of the tapered portion of breaker strips (see 3.5.13.4).

3.5.13.2 Brackets. When brackets are used, they shall be bolted to the web of the chassis frame rails. The body mounting brackets shall provide means of drawing down the body on the chassis rails, and provisions shall be made to prevent lateral shifting of the breaker strips. When additional holes are required to secure mounting brackets to chassis frame rails, they shall be located within the area of the rail which is designated as being safe for drilling in accordance with the chassis manufacturer's body builder's layouts. Attachments shall not interfere with nor obstruct chassis components.

3.5.13.3 J-bolts. When J-bolts are used, there shall be not less than nine J-bolts per side, each not less than 3/8 inch in diameter. J-bolts shall encircle the lower chassis frame flange. Two tie-back straps as specified in 3.5.13.1 shall be provided. The forward J-bolts shall be located to the rear of the tapered portion of the breaker strips (see 3.5.13.4). Provisions shall be made to prevent lateral shifting of the breaker strips.

3.5.13.4 Breaker strips. A hardwood or dense southern yellow pine breaker strip, of not less than 1-1/16 inches finished thickness, shall be installed between longitudinal sills and vehicle chassis frame. Breaker strips shall have a taper of 1 inch in 18 inches at the forward end.

* 3.6 Servicing and adjusting. Prior to acceptance of the vehicle by the Government inspector, contractor shall service and adjust each vehicle for operational use including at least the following: alinement of lights; adjustment of the engine, electrical and brake systems; filling and charging of battery; alinement of front wheels; inflation of all tires; complete lubrication of chassis, engine, and running gear with grades of lubricants recommended for the ambient air temperature at the delivery point; servicing of cooling system with a solution of ethylene glycol type antifreeze and water in equal parts by volume; and filling of windshield washer reservoir with water and appropriate additives.

Source: https://assist.dla.mil -- Downloaded: 202610-22T02:52Z
Check the source to verify that this is the current version before use.

3.7 Workmanship. Defective components or parts and assemblies which have been repaired or modified to overcome deficiencies shall not be furnished. Welded, bolted, and riveted construction utilized shall be in accordance with the highest standards of the industry.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

* 4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirments of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.2 Government verification. Quality assurance operations performed by the contractor will be subject to Government verification at unscheduled intervals. Verification will consist of observation of the operations to determine that practices, methods, and procedures of the contractor's inspection are being properly applied. Failure of the contractor to promptly correct product deficiencies discovered shall be cause for suspension of acceptance until correction has been made or until conformance of product to specification criteria has been demonstrated.

4.3 First production vehicle inspection. The first production vehicle produced under the contract shall be inspected by the contractor at his plant under the direction and in the presence of Government representatives. The purpose of the inspection shall be to determine vehicle conformance with the contract. Acceptance of the first production vehicle shall not constitute a waiver by the Government of its rights under the provisions of the contract.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:52Z
Check the source to verify that this is the current version before use.

4.3.1 Vehicle weight. The first production vehicle shall be weighed to determine curb weight and distribution of curb weight on front and rear axle. The imposed loading on front and rear axles shall be computed by the contractor and verified by the Government, using the curb weight, the operator weight at 175 pounds, and the payload to provide the specified GVW. Calculated imposed loads on front and rear axles shall be compared to the rated capacities of the suspension, axles and tires furnished to insure they are of adequate capacity to meet contractual requirements.

* 4.3.2 Road test. The first production vehicle shall be examined and road tested (less payload) by the contractor in the presence of a Government representative to assure that the vehicle will operate in accordance with the contractual requirements. The road test shall be for a minimum of 30 miles at speeds up to 50 mph with at least 10 miles over improved gravel roads. One sudden stop shall be made for each 10 test miles.

* 4.3.3 Radio frequency suppression verification. The vehicle manufacturer shall indicate on the questionnaire (commercial vehicle engineering data) if the vehicle will be suppressed to limit electromagnetic radiation in accordance with SAE J551.

4.3.4 Water spray test. To determine conformance to 3.5.2 and 3.5.3, the first production vehicle shall be water spray tested to ascertain that the roof, body and doors are watertight. The water spray test shall be conducted prior to the installation of the body interior.

* 4.3.5 Hydraulic. The hydraulic tailgate shall be tested with full rated payload for a minimum of 5 complete and continuous cycles, from fully raised to fully lowered position.

4.3.6 Production sample. Upon acceptance of the first production vehicle, it shall remain at the manufacturing facility as a production sample, and be the last vehicle shipped on the contract. The contractor shall maintain the vehicle in a serviceable condition for the duration of the contract.

4.3.7 Failure. Failure of the first production vehicle to meet requirements of the contract shall be cause for the Government to refuse acceptance of all vehicles under contract until corrective action has been taken.

4.4 Inspection of production vehicles. The contractor's inspection system shall, as a minimum, assure that the vehicle conforms to the physical, workmanship and dimensional requirements and is capable of meeting performance requirements contained herein. For each vehicle under contract the contractor shall make available to the Government, at

Source: https://assist.dla.mil -- Downloaded: 20261O-22T02:52Z
Check the source to verify that this is the currentversion before use.

the point of final acceptance, records acceptable to the Government indicating that servicing and adjusting required by 3.6 have been accomplished.

4.5 Wood treatment certification. Manufacturer's records, acceptable to the Government representative, shall be furnished to verify that all wood requiring treatment in accordance with MIL-STD-1223 has been treated.

5. PACKAGING

5.1 Vehicle processing. The vehicle shall be processed for shipment, from manufacturer's plant to initial receiving activity, in accordance with the manufacturer's standard commercial practice.

6. NOTES

6.1 Intended use. The vehicle covered by this specification is intended for general nontactical use by the Government in transporting furniture and household furnishings.

* 6.2 Ordering data. Acquisition documents should specify the following:

(a) Title, number and date of this specification.
(b) Identification of appropriate service for painting and marking (see 3.1.1.1).
(c) Concealed marking, if required (see 3.1.1.1).
(d) Rustproofing, if required (see 3.1.1.2).
(e) Tropical rustproofing, if required (see 3.1.1.2).
(f) Heavy duty cooling system, if required (see 3.1.1.4).
(g) Gasoline engine, if required (see 3.4.1.2).
(h) Power plant heaters, if required (see 3.4.1.6).
(i) If a battery heater is not required (see 3.4.1.6).
(j) Alternator capacity, if other than as specified (see 3.4.2.1 and 3.4.2.2).
(k) Automatic or semiautomatic transmission, if required (see 3.4.5.2).
(l) Two-speed axle, if required (see 3.4.9.1).
(m) Disc type wheels, if required (see 3.4.10).
(n) Bias ply, or other type tires, if required (see 3.4.10.1).
(o) Spare wheel or rim, if required (see 3.4.10.3).
(p) Spare tire assembly, if required (see 3.4.10.4).
(q) Desiccant type air dryer, if required (see 3.4.11.1(k)).
(r) Brake controls for use from a towing vehicle, if required (see 3.4.11.2).
(s) Tilt type cab, if required (see 3.4.12).
(t) Individual, adjustable driver's seat and individual passenger's seat, if required (see 3.4.12).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:52Z
Check the source to verify that this is the current version before use.

(u) Tools, if required (see 3.4.16.1).
(v) Air operated horn, if required (see 3.4.21).
(w) Back-up alarm, if required (see 3.4.23).
(x) Air conditioning, if required (see 3.4.24).
(y) FRP/plywood side and end panels, if required (see 3.5.1.1).
(z) Body exterior color, if not prepainted white (see 3.5.4).
(aa) Optional equipment, including detailed requirements, if required (see 3.5.5.1).
(ab) Wood sealer on floor, if required (see 3.5.6).

* 6.3 Performance prediction. Completed copies of SAE Truck Ability Prediction Procedure form and computation for the speed requirement shall be submitted as specified in the contract. Computations shall be made under normal atmospheric pressure, in normal ambient air temperature, in still, dry, air. The factors to be used in predicting truck ability (see 3.3.1) are established as follows for the corresponding SAE Truck Ability Prediction Procedure Tables:

Table 1 - Tire Factor. This factor must relate to the size of tires furnished by the contractor in accordance with this specification.
Table 2 - Altitude Factor. 1.00.
Table 3 - Rolling Factor. 1.613.
Table 4 - Area Factor. 0.173.
Table 5 - Velocity Factor. 250.0.
Table 6 - Altitude Factor. 1.00.
Table 7 - Chassis Friction Horsepower. Use applicable power unit GVW (to nearest, higher, tabulated 1000 pounds) and the engine rpm (to nearest 100 revolutions) which is required for 50 mph geared speed. For GVW and engine speed beyond the range of this table, factors shall be extrapolated.
* Table 8 - Grade Factor. 0.75.
Table 8A - Correction Factor. Not required.
Table 9 - Road Factor. 0.0.

* 6.4 Changes from previous issue. The margins of this specification are marked with an asterisk (*) to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content regardless of the marginal notations and relationship to the last previous issue.

Custodian:
Army - AT

Preparing activity:
Army - AT
Project No. 2320-A273

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:52Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Tank-Automotive Command
ATTN: AMSTA- UED
Warren, MI 48397-5000

27

Source: https://assist.dla.mil -- Downloaded: 202640-22T02:52Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T02:52Z
Check the source to verify that this is the current version before use.