MILITARY SPECIFICATION

CHARGE, PROPELLING, M205 PARTS AND CONTAINER ASSEMBLY

This Amendment forms a part of Military Specification MIL-C-48882C (AR), dated 26 July 1982, and is approved for use by the U.S. Army Armament, Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

* 1.1, Add the following sentence:

"The M205 container assembly can be used for the propelling charge on the Cartridge, 81MM, HE M821 and M889."

PAGE 2

* 2.1.1 under Military Standards Delete:

"MIL-STD-1235 - Single and Multi-Level Continuous Sampling Procedures and Tables for Inspection by Attributes."

PAGE 3

3.4, Delete in its entirety.

3.5, Delete in its entirety.

* 3.6, Add the following sentence:

"The test shall be performed as specified in 4.5.5."

PAGE 4

* 3.10, Delete "Sequential rough handling" in both places and substitute "Transportation - vibration."

FSC 1315

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:43Z
Check the source to verify that this is the current version before use.

* 3.14.1, Delete in its entirety and substitute the following:

"3.14.1 Container parts and assemblies. The container parts and assemblies shall be free of dirt, grease, cracks, splits, cuts, tears, rips, holes, soft spots, seam separations or foreign material."

* Add new paragraph as follows:

"3.15 Fin-boom simulation test. The container assemblies shall satisfactorily pass the fin-boom simulation test specified in 4.5.10."

PAGE 5

4.3.1, under Quantity Column, Delete "110" and substitute "10".

PAGE 6

TABLE I, Delete Back Pressure test.

TABLE I, Delete Immersion test.

* TABLE I, under Container Assembly, Delete "Sequential rough handling" and substitute "Transportation-vibration".

* TABLE I- under Container Assembly, add the following:

	No. of Sample	Req. Para.	Para. Ref.
"Fin-boom simulation test	100	3.15	4.5.10"

PAGE 8

4.4.2.1.1, line 3, Delete:

"After initial qualification, the procedure shall be accomplished after any set-up change and at intervals of a least once per week per die."

4.4.2.1.2b, Delete in its entirety.

PAGE 9

4.4.2.2, Special A, Delete references to Note (a) and all "100%" under AQL column.

4.4.2.2, Notes, Delete Note (a) in its entirety.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:43Z
Check the source to verify that this is the current version before use.

PAGE 10

4.4.2.3:

Special A: Delete reference to Note (a) and add "100%" under AQL column.

Notes: Delete Note (a) in its entirety.

PAGE 12

4.4.2.5:

Delete Major 102.

Delete Major 103.

* Major 108: Delete "max."

* Add Major 113 as follows:

Major		No. Sample	Reg. Para.	Para. Ref.
"113	Fin-boom simulation test	100	3.15	4.5.10"

Notes: Delete Note (a) in its entirety.

Notes, Note (b): Delete "Part II" and substitute "Part I".

PAGE 15

* 4.4.3.1, Delete "9277371" and substitute "9381562"

PAGE 19

4.5.3, Delete in its entirety.

4.5.4, Delete in its entirety.

PAGE 22

* 4.5.7, Delete "Sequential rough handling" and substitute "Transportation-vibration test."

* Add new paragraph:

"4.5.10 "Fin-boom simulation test. The container assemblies shall be tested for flexibility needed during field use. The container assemblies shall be visually examined for any

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:43Z
Check the source to verify that this is the current version before use.

homogeneity defects prior to the test. The defect-free container assemblies shall be positioned on and removed two times from a solid bar of the maximum allowable outside diameter of the M24 fin-boom. The "snap" on and off the boom shall be performed with the container assembly oriented perpendicular to the bar. After removal the container assemblies shall be visually inspected for cracks, tears, open seams, crushed ends, and folds/creases in the container wall. The Government shall establish visual standards prior to production with the assistance of the contractor."

PAGE 23

* 6.1, Delete, "Cartridge, 81MM, HE, M374A3 and WP, M375A3." and substitute "Cartridge, 81MM, HE, M374A3, HE M821, HE M889, and WP M375A3."

6.7, Delete "QAT-A" and substitute "QAT-B".

PAGE 24

6.9, Delete "DRDRA-QAT-A" and substitute "DRDAR-QAT-B".

* 6.9, Delete references to paragraph 4.5.3.1 and 4.5.4.

NOTE: The margins of this amendment are marked with an asterisk to indicate where changes (additions, modificatons, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1315-A743)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:43Z
Check the source to verify that this is the current version before use.