MILITARY SPECIFICATION

DRAWING BOARD, ILLUMINATED, PORTABLE

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers a portable illuminated drawing board.

2. APPLICABLE DOCUMENTS

2.1 Issue of documents. The following documents of the issue in effect on date of invitation for bids or request for proposal form a part of this specification to the extent specified herein:

SPECIFICATIONS

FEDERAL

L-P-378	-Plastic Sheet and Strip (Polyolefin).
QQ-S-781	-Strapping, Steel, and Seals.
TT-E-489	-Enamel, Alkyd, Gloss (For Exterior and Interior Surfaces).
TT-V-121	-Varnish, Spar, Water Resisting.
PPP-B-601	-Boxes, Wood, Cleated-Plywood
PPP-B-621	-Boxes, Wood, Nailed and Lock-Corner.
PPP-B-636	-Boxes, Shipping, Fiberboard.
PPP-C-843	-Cushioning Material, Cellulosic.

MILITARY

MIL-P-116	-Preservation - Packaging.
MIL-T-22085	-Tape, Adhesive, Preservation and sealing.

STANDARDS

FEDERAL

FED-STD-595	-Colors.

FSC 6675

Benefical comments (recommendations, additons, deletions) any any pertinent data which may be of use in improving this document should be addressed to: US Army Mobility Equipment Research and Development Command, ATTN: DRDME-DS, Fort Belvoir, VA 22060 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:45Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-STD-105	-Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	-Marking for Shipment and Storage.
MIL-STD-130	-Identification Marking of US Military Property.
MIL-STD-1186	-Cushioning, Anchoring, Bracing, Blocking, and Waterproofing, with Appropriate Test Methods.
MIL-STD-1188	-Commercial Packaging of Supplies and Equipment.

3. REQUIREMENTS

3.1 Description. The drawing board shall be 38 inches by 31-1/4 inches by 3-3/8 inches, plus or minus 1/32 inch. The frame shall be made of clear Basswood. The ends shall be 1 inch by 3-3/8 inch, front and back shall be 5/8 inch by 3-3/8 inches. The board shall have a 22 gauge steel reflector under entire bottom shaped to distribute the light evenly under glass. The reflector shall be painted with enamel conforming to TT-E-489, class and composition optional. The top of the board shall be recessed to take a 36-3/4 by 24 inch by 7/32 inch, plus or minus 1/32 inch, plate glass. The glass shall be sandblasted or acid etched on bottom side to reduce glare and diffuse light. The glass shall be held in place with four corner clips. The front and back top rails shall be removable so that the lamps can be replaced. Adjustable hanger rods to hold the board in place when used on an inclined drawing surface shall be fastened to each end, and be moveable to 10-1/2 inches. The top of the board shall have a handle of polyvinylchoride, and shall be color No. 34079 of FED-STD-595. The handle is to be fastened to the top board with 3/16 inch by 1-1/4 inch right hand bolts with nut and lock washer. The board shall be wired for 110-125 volts alternating current with two 30 watt 36 inch fluorescent lamps 1 inch in diameter, plus or minus 1/32 inch. The control switch (off - on) shall be at the top of the board near handle. The board shall have not less than a 10 foot cord with 18 gauge wire 11/32 inch diameter, black rubber with plug, having a ground.

3.2 Material. Material shall be as specified herein. Materials not specified shall be selected by the contractor and shall be subject to all provisions of this specification (see 6.3).

3.3 Contruction. Wood boards shall be made from the same species of wood for the entire working surface of one drawing board. The working surface shall be composed of continuous wood lengths, 1-3/4 to 5 inches bonded together with waterproof resin adhesive. Bond joints, fully set, shall have a strength greater than the wood being bonded.

3.4 Finish. All fabricated wood and plastic surfaces shall be sanded smooth and shall be free of cracks, splits, and splintered edges. Surfaces shall be finished to a tolerance of plus 1/32 inch. Drawing board working surfaces shall be a true plane within 1/64 inch for 12 inches of length or

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:45Z
Check the source to verify that this is the current version before use.

width and shall not be cumulative within any 12 inch increment. Any deviation shall be evenly distributed over the entire increment. All edges shall be straight within 1/8 inch end to end.

3.4.1 Protective finishing. The drawing board, excluding glass, shall be protected with one coat of varnish conforming to TT-V-121.

3.5 Identification marking. The drawing board shall be identified in accordance with MIL-STD-130.

3.6 Workmanship. Drawings boards shall be free from defects and imperfections which might affect their serviceability.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilitites suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.2 Classification of inspection. The inspection requirements specified herein are classified as follows:

(a) Quality conformance inspection (see 4.3).
(b) Inspection of packaging (see 4.5).

4.3 Quality conformance inspection.

4.3.1 Sampling. Sampling for examination shall be in accordance with MIL-STD-105, Level 5-2.

4.3.2 Examination. Samples selected in accordance with 4.3.1 shall be examined as specified in 4.4.1. AQL shall be 2.5 percent defective.

4.4 Inspection procedure.

4.4.1 Examination. Drawings boards shall be examined for the following defects:

101. Material not as specified.
102. Finish not as specified.
103. Accuracy and tolerance dimension not as specified.
104. Contruction not as specified.
105. Workmanship not as specified.

Source: https://assist.dla.mil -- Downloaded: 20261O-22T21:45Z
Check the source to verify that this is the current version before use.

4.5 Inspection of packaging.

4.5.1 Preproduction pack inspection.

4.5.1.1 Examination. The preproduction pack shall be examined for the defects specified in 4.5.2.3. Presence of one or more defects shall be cause for rejection.

4.5.2 Quality conformance inspection of pack.

4.5.2.1 Unit of product. For the purpose of inspection, a completed pack prepared for shipment shall be considered a unit of product.

4.5.2.2 Sampling. Sampling for examination shall be in accordance with MIL-STD-105.

4.5.2.3 Examination. Samples selected in accordance with 4.5.2.2 shall be examined for the following defects. AQL shall be 2.5 percent defective.

106.	Materials, methods, and containers not as specified for level A or B.
107.	Unpainted surfaces requiring a contact preservative not coated as specified for level A.
108.	Openings into electrical components not sealed as specified for level A.
109.	Flourescent lamps not cushioned and placed in box as specified for level A.
110.	Lamp starters not preserved as specified for level A.
111.	Glass surface not cushioned as specified for level A.
112.	Drawing board not covered as specified for level A.
113.	Polyethylene not sealed as specified for level A.
114.	Drawing board not secured and protected against abrasion within the box in accordance with the referenced document for level A or B.
115.	Strapping not as specified for level A or B.
116.	Marking missing, illegible, incorrect, or incomplete.

5. PACKAGING

5.1 Preproduction pack. Unless otherwise specified (see 6.2), the contractor shall furnish a preproduction pack for examination within the time frame specified (see 6.2) to prove prior to starting production packaging that the applied preservation, packing, and marking comply with the packaging requirements of this specification. Examination shall be as specified in Section 4 and shall be subject to surveillance and approval by the Government (see 6.4). The preproduction pack may be prepared utilizing a production drawing board.

5.2 Preservation. Preservation shall be level A or Commercial, as specified (see 6.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:45Z
Check the source to verify that this is the current version before use.

5.2.1 Level A.

5.2.1.1 Unpainted metal surfaces. Unpainted exterior metal surfaces of the drawing board requiring the application of a contact preservative in accordance with MIL-P-116 shall be coated with P-1 preservative.

5.2.1.2 Electrical components. Openings in electrical components, such as starter openings, switches, receptacles, and exposed ends of wire, plugs, and other connections shall be sealed with tape conforming to MIL-T-22085, type II. The cord shall be coiled to a minumum safe diameter and the coil shall be secured to the drawing board with tape specified herein. Each fluorescent lamp shall be wrapped with cusioning material conforming to PPP-C-843, type II, class A or B, and secured with tape conforming to MIL-T-22085, type II. The lamps shall be placed together in a close-fitting box conforming to PPP-B-636, W6C. The lamp starters shall be preserved together in accordance with MIL-P-116, method IC-1 or IC-3.

5.2.1.3 Glass working surface. The mounted glass working surface shall be covered with 1-inch thick cushioning material conforming to PPP-C-843, type II, class B, secured with tape conforming to MIL-T-22085, type II.

5.2.1.4 Drawing board. The drawing board shall be completely covered with polyethylene conforming to L-P-378, thickness 4 mils or greater, with all seams and closure heat sealed.

5.2.2 Commercial. Commercial preservation shall be in accordance with MIL-STD-1188.

5.3 Packing. Packing shall be level A, B, or Commercial, as specified (see 6.2).

5.3.1 Level A. Each complete drawing board, preserved as specified in 5.2, shall be packed in a box conforming to PPP-B-621, class 2, or PPP-B-601, overseas type, grade B. Blocking, bracing, and anchoring of the contents shall be in accordance with MIL-STD-1186. Strapping shall conform to QQ-S-781, class 1, type I or IV, size as applicable. Unless otherwise specified (see 6.2), strapping shall be finish B. When specified, (see 6.2), strapping shall be finish A.

5.3.2 Level B. Each complete drawing board, preserved as specified in 5.2, shall be packed as specified in 5.3.1, except the box shall be domestic type or class as applicable.

5.3.3 Commercial. Commercial packing shall be in accordance with MIL-STD-1188.

5.4 Marking. Marking for military levels of protection shall be in accordance with MIL-STD-129. Commercial marking shall be in accordance with MIL-STD-1188.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:45Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Intended use. The drawing board is to be used for drafting, layout or military projection applications.

6.2 Ordering data. Documents should specify the following:

(a) Title, number, and date of this specification.
(b) When preproduction pack is not required (see 5.1).
(c) Time frame required for submission of preproduction pack (see 5.1).
(d) Degree of preservation and degree of packing required (see 5.2 and 5.3).
(e) When finish A strapping is required (see 5.3.1).

6.3 Recycled material. It is encouraged that recycled material be used when practicable as long as it meets the requirements of the specification (see 3.2).

6.4 Preproduction pack. Any changes or deviations of production packs from the approved preproduction pack will be subject to the approval of the contracting officer. Approval of the preproduction pack will not relieve the contractor of his obligation to preserve, pack, and mark the drawing boards in accordance with this specification.

Custodian:
Army - ME
Air Force - 99

Review activity:
DLA - GS

User activity:
Navy - YD

Preparing activity:
Army - ME

Project 6675-A230

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:45Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.
NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE

MIL-D-52975 Drawing Borad, Illuminated, Portable

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO.

DATE

DD FORM 1 OCT 76 1426 EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 20261O-22T21:45Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID

U.S. MAIL

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

Commander
USA Mobility Equipment R&D Command
ATTN: DRDME-DE/DS
Ft. Belvoir, VA 22060

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:45Z
Check the source to verify that this is the current version before use.