MILITARY SPECIFICATION

WEAPON ACCESS DELAY SYSTEMS, INTERIOR BARRIER

This specification is approved for use by the USA Belvoir Research and Development Center, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the prefabricated kit components of three types of interior barriers for weapon access delay systems.

1.2 Classification. The interior barrier of the weapon access delay system shall be the following types, as specified (see 6.2):

Type I - Weapon Access Delay System, Interior Barrier, Rectangular Structure.
Type II - Weapon Access Delay System, Interior Barrier, Full-Arched Structure.
Type III - Weapon Access Delay System, Interior Barrier, Semi-Arched Structure.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Standards. Unless otherwise specified (see 6.2), the following standards of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation, form a part of this specification to the extent specified herein.

STANDARDS

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-130	- Identification, Marking of US Military Property.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: USA Belvoir Research and Development Center, ATTN: STRBE-DS, Fort Belvoir, VA 22060-5606 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 6350

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202640-22T21:56Z
Check the source to verify that this is the current version before use.

2.1.2 Other Government drawings. The following other Government drawings form a part of this specification to the extent specified herein.

DRAWINGS

ME

TA 13226E5982	- Kit, Weapon Access Delay System, Interior Barrier, Rectangular Structure.
TA 13226E5983	- Kit, Weapon Access Delay System, Interior Barrier, Full-Arched Structure.
TA 13226E5984	- Kit, Weapon Access Delay System, Interior Barrier, Semi-Arched Structure.

(Copies of specifications, standards, and drawings required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.2 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

3. REQUIREMENTS

3.1 Description. The interior barrier components shall be in accordance with the drawing for the applicable type and as specified herein:

Type	TA
I	13226E5982
II	13226E5983
III	13226E5984

3.1.1 Drawings. The drawings forming a part of this specification are end product drawings. No deviation from the prescribed dimensions or tolerances is permissible without prior approval of the contracting officer. When tolerances could cumulatively result in incorrect fits, the contractor shall provide tolerances within those prescribed on the drawings to insure correct fit, assembly, and operation of the kit. Any data (e.g. shop drawings, layouts, flow sheets, processing procedures (etc.) prepared by the contractor or obtained from the vendor to support fabrication and manufacture of the production item shall be made available, upon request, for inspection by the contracting officer or his designated representative.

3.2 First article. When specified (see 6.2), a sample shall be subjected to first article inspection (see 4.3 and 6.3).

3.3 Materials. Materials shall be as specified herein and on the drawings. Materials not specified shall be selected by the contractor and shall be subject to all provisions of this specification.

Source: https://assist.dla.mil -- Downloaded: 202640-22T21:56Z
Check the source to verify that this is the current version before use.

3.3.1 Recovered materials. For the purpose of this requirement, recovered materials are those materials which have been collected from solid waste and reprocessed to become a source of raw materials, as distinguished from virgin raw materials. The components, pieces and parts incorporated in the weapon access delay systems may be newly fabricated from recovered materials to the maximum extent practicable, provided the weapon access delay systems produced meets all other requirements of this specification. Used, rebuilt or remanufactured components, pieces and parts shall not be incorporated in the weapon access delay systems.

3.4 Identification marking. The components shall be identified in accordance with MIL-STD-130.

3.5 Workmanship. All parts, components, and assemblies of the item shall be clean and free from any defects that will reduce the capability of the components to meet the requirements specified herein. External surfaces shall be free from burrs, slag, sharp edges, and corners.

3.5.1 Metal fabrication. Metal used in fabrication shall be free from kinks and sharp bends. The straightening of material shall be done by methods that will not cause injury to the material. Corners shall be square and true, and edges shall be rounded. Precaution shall be taken to avoid overheating. Heated steel shall be allowed to cool slowly.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requriements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items must meet all section 3 and 5 requirements. The inspections in section 4 and the minimum to be used to demonstrate compliance. Sampling in quality conformance inspection does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.2 Classification of inspection. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).

4.3 First article inspection.

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:56Z
Check the source to verify that this is the current version before use.

4.3.1 Examination. The first article(s) barrier components shall be examined as specified in 4.5.1. Presence of one or more defects shall be cause for rejection.

4.4 Quality conformance inspection.

4.4.1 Sampling. Sampling for examination shall be in accordance with MIL-STD-105.

4.4.2 Examination. Samples selected in accordance with 4.4.1 shall be examined as specified in 4.5.1. AQL shall be 4.0 percent defective.

4.5 Inspection procedure.

4.5.1 Examination. The barrier components shall be examined as specified herein for the following defects:

101. Members not within dimensions and tolerances.
102. Welding not as specified.
103. Treatment and painting not as specified.
104. Material not as specified.
105. Commercial components not as specified.
106. Components missing or not as specified.
107. Workmanship not as specified.
108. Marking missing, illegible, or incorrect.
109. Used, rebuilt, or remanufactured components, pieces or parts incorporated in the loading standards.
110. Metal fabrication not as specified.

5. PACKAGING (Not applicable, see 6.4)

6. NOTES

6.1 Intended use. The prefabricated kit components are intended to be assembled and permanently installed on the inside near the entry of weapons storage structures providing physical security and spall protection. The three types of interior barrier are intended for use on rectangular, full-arched, and semi-arched shaped structures.

6.2 Ordering data. Procurement documents should specify the following:

a. Title, number, and date of this specification.
b. Type of interior barrier required (see 1.2).
c. Date of issue of DoDISS applicable and exceptions thereto (see 2.1.1).
d. When a first article is required for inspection and approval, and number of units required (see 3.2).

6.3 First article. When a first article inspection is required, the items should be an initial production model. The first article should consist of 1 or more units. The contracting officer should include specific instructions in

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:56Z
Check the source to verify that this is the current version before use.

acquisition documents regarding arrangements for examinations and approval of the first article.

6.4 Packaging. The specification is not intended to produce a finished commodity ready for shipment but is intended to provide the required data necessary for local procurement of required material and permanent construction on site. As such, packaging requirements would not be required.

Custodian:
Army - ME

Preparing activity:
Army - ME

Project 6350-A145

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:56Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:56Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Belvoir R&D Center
ATTN: STRBE-DS
Fort Belvoir, VA 22060-5606

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:56Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-W-53056(ME)	Weapon Access Delay Systems, Interior Barrier

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: ___

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Inclu Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	d. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:56Z
Check the source to verify that this is the current version before use.