NOTE: The document identifier and heading have been changed on this page to reflect that this is a performance specification. There are no other changes to this document. The document identifier on subsequent pages has not been changed, but will be changed the next time this document is revised.

INCH-POUND

MIL-PRF-27/288A
17 May 1990
SUPERSEDING
MIL-T-27/288
8 April 1980

PERFORMANCE SPECIFICATION SHEET

TRANSFORMERS AND INDUCTORS
(AUDIO, POWER AND HIGH-POWER PULSE)
INDUCTORS, POWER, TF5S04ZZ

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-T-27.






FIGURE 1. Dimensions and configurations.

(A) denotes changes


DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T04:03Z
Check the source to verify that this is the current version before use.

| Inches | mm | Inches | mm |
|---|---|---|---|
| .005 | 0.13 | .250 | 6.35 |
| .010 | 0.25 | .281 | 7.14 |
| .015 | 0.38 | .300 | 7.62 |
| .030 | 0.76 | 400 | 10.16 |
| .063 | 1.60 | .563 | 14.30 |
| .073 | 1.85 | .600 | 15.24 |
| 082 | 2.08 | .688 | 17 48 |
| 156 | 3 96 | 1 188 | 30 18 |




WV-357V
(SEE TABLE I FOR VALUE OF "X")
CIRCUIT DIAGRAM AND MARKING

NOTES:
1. Dimensions are in inches
2. Metric equivalents are given for general information only
3. Marking shall be on the side and on top.
4. Electrical values shall be marked as specified in table I, as applicable
5. Circuit diagram BB, for series connection join terminals 2 and 3 for parallel connection join terminals 1 and 2, 3 and 4

FIGURE 1. Dimensions and configuration – Continued

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T04:03Z
Check the source to verify that this is the current version before use.

REQUIREMENTS. (When numbers in parentheses, i e , (1-2) are used, they indicate the winding and the extreme terminals of the winding.)

Electrical ratings See table I

TABLE I Electrical ratings.

| Dash number 1/ | Inductance (µh) +15 percent -5 percent 2/ 3/ | DC current (A) max 2/ 4/ | DC resistance (ohms) max 2/ | Working voltage (peak) volts 5/ | PIN arrangement (see figure 1) | Circuit diagram (see figure 1) | Voltage |
|---|---|---|---|---|---|---|---|
| 01 | 3000 | 1 2 | 1 c | 357 | A | AA | 1 volt at 10 kHz |
| 02 | 2000 | 1 5 | 8 | 357 | A | AA | 1 volt at 10 kHz |
| 03 | 1200 | 1 88 | 5 | 357 | A | AA | 1 volt at 10 kHz |
| 04 | 780 | 2 4 | 3 | 357 | A | AA | 1 volt at 10 kHz |
| 05 | 520 | 3 | 2 | 357 | A | AA | 1 volt at 10 kHz |
| 06 | 320 | 3.75 | .13 | 357 | A | AA | 1 volt at 10 kHz |
| 07 | 220 / 55 | 4.5 / 9 | 08 / .02 | 357 | B | BB | 1 volt at 10 kHz |
| 08 | 120 / 30 | 6 / 12 | .05 / .013 | 357 | B | BB | 1 volt at 10 kHz |
| 09 | 80 / 30 | 7 5 / 15 | 032 / .008 | 357 | B | BB | 1 volt at 10 kHz |

1/ Qualification test and approval to M27/288B-01, shall be sufficient to grant qualification approval to M27/288B-02 through -09

2/ Where electrical values are written one above the other they indicate the values from series or parallel connections respectively (series) / (parallel).

3/ The inductance is measured with 0 A dc applied at the specified voltage and frequency

4/ At rated dc current, inductance will exceed 80 of rated inductance

5/ Between windings, 50 volts peak.



Source: https://assist.dla.mil -- Downloaded: 2026-10-16T04:03Z
Check the source to verify that this is the current version before use.

Design and construction

Dimensions and configuration See figure 1

Duty cycle Continuous

Case: Epoxy.

Terminals Printed circuit (tinned brass)

Weight: 1.5 ounces.

Altitude 75,000 feet, maximum

Operating temperature range -55°C to +130°C

Terminal strength: MIL-STD-202, method 211, test condition A, 2 pounds.

Dielectric withstanding voltage:

At sea level 1,000 volts rms.

At reduced barometric pressure. 500 volts rms

Vibration (high frequency) MIL-STD-202, method 204

Temperature rise +45°C with 1 volt rms, 10 kHz, current as specified in table I at an ambient temperature of +85°C maximum.

Marking location. See figure 1.

Part or identifying number (PIN) M27/288- (dash number from table I).

## CONCLUDING MATERIAL

Custodians.
Army - ER
Navy - EC
Air Force - 85

Review activities
Army - MI
Navy - OS, SH
Air Force - 11, 17, 99
DLA - ES

User activities
Army - AR
Navy - AS, MC
Air Force - 19

Preparing activity
Army - ER

Agent
DLA - ES

(Project 5950-0749-02)



Source: https://assist.dla.mil -- Downloaded: 2026-10-16T04:03Z
Check the source to verify that this is the current version before use.