METRIC
DOD-STD-2139(SH)
28 December 1981

MILITARY STANDARD

SHIP INFORMATION BOOK, PREPARATION OF *(METRIC)*

NO DELIVERABLE DATA REQUIRED
BY THIS DOCUMENT

AREA TMSS

Source: https://assist.dla.mil -- Downloaded: 202640-26T07:57Z
Check the source to verify that this is the current version before use.

DEPARTMENT OF THE NAVY

NAVAL SEA SYSTEMS COMMAND

WASHINGTON, DC 20362

Ship Information Book

DOD-STD-2139(SH)

1. This Military Standard is approved for use by the Naval Sea Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

2. Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, Naval Sea Systems Command, SEA 3112, Department of the Navy, Washington, DC 20362 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:57Z
Check the source to verify that this is the current version before use.

CONTENTS

Paragraph			Page
	1.	SCOPE	1
	1.1	Scope	1
	2.	REFERENCED DOCUMENTS	1
	2.1	Issues of documents	1
	2.2	Other publications	1
	3.	DEFINITIONS (Not applicable)	2
	4.	GENERAL REQUIREMENTS	2
	4.1	General	2
	4.2	Divisions	2
	4.2.1	Surface ships	3
	4.2.2	Submarines	3
	5.	DETAILED REQUIREMENTS	3
	5.1	Style and format	3
	5.1.1	Format	4
	5.1.1.1	Numbering of pages, illustrations, and tables	4
	5.1.1.2	Illustrations	4
	5.1.1.3	Reproducible copy preparation methods and computer output typesetting	4
	5.1.1.4	Microform compatibility	4
	5.1.2	Binder, paper stock, and printing requirements	4
	5.1.3	Security classification	5
	5.1.4	Warnings and cautions	5
	5.2	Front matter, covers, and backbone	5
	5.2.1	Front matter	6
	5.2.2	Front cover	6
	5.2.3	Back cover	6
	5.2.4	Backbone	7
	5.2.5	Title page	7
	5.2.6	Foreword	7
	5.2.7	List of effective pages, change sheet, change record, table of contents, list of illustrations, list of tables and safety summary	7
	5.2.8	List of abbreviations	7
	5.2.9	Revisions	7
	5.3	Structure of SIB	7
	5.3.1	Data level descriptions	7
	5.3.2	Minimum data requirements	7
	5.3.3	Volume arrangement	8
	5.3.3.1	Surface ships	8
	5.3.3.2	Submarines	26

APPENDIX

	10.	DATA	29
	10.1	Data requirements	29

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:57Z
Check the source to verify that this is the currentversion before use.

1. SCOPE

1.1 Scope. This standard contains requirements for the preparation of Ship Information Book(s) (SIB) that is to be used as a system-level ready reference for use by operating, maintenance, and overhaul personnel, and for use in the training of such personnel in Navy schools and on board ship.

2. REFERENCED DOCUMENTS

2.1 Issues of documents. The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this standard to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-M-38784 - Manuals, Technical: General Style and Format Requirements.
MIL-P-38790 - Printing Production of Technical Manuals, General Requirements for, (Photolithographic Negatives, Reproduction Assembly Sheets, Printing).

STANDARDS

MILITARY

MIL-STD-12 - Abbreviations For Use on Drawings, Specifications, Standards and in Technical Documents.
MIL-STD-15-2 - Electrical Wiring Equipment Symbols for Ships' Plans, Part 2.

DRAWING

NAVAL SEA SYSTEMS COMMAND (NAVSEA)

803-5001049 - Piping System, Symbols and Abbreviations.

PUBLICATIONS

MILITARY

DOD 5220.22 Series - Industrial Security Manual for Safeguarding Classified Information.
NAVSEA OP 1700 - Fire Control Symbols Standard, Volume 1.

(Copies of specifications, standards, drawings, and publications required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this standard to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:57Z
Check the source to verify that this is the current version before use.

AMERICAN NATIONAL STANDARDS INSTITUTE (ANSI)
Y32.2 - Graphic Symbols for Electrical and Electronics Diagrams.
Y32.4 - Graphic Symbols for Plumbing Fixtures for Diagrams Used in Architectural and Building Construction.
Y32.10 - Fluid Power Diagrams, Graphic Symbols for.

(Application for copies should be addressed to the American National Standards Institute, Inc., 1430 Broadway, New York, NY 10018.)

(Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

3. DEFINITIONS

Not applicable.

4. GENERAL REQUIREMENTS (See appendix for data requirements)

4.1 General. The Ship Information Book (SIB) shall be prepared on an individual ship basis. It shall be complete and detailed as required so that it will serve as the primary intrasystem and intersystem technical publication covering installation and operation of ship systems and equipment. It shall provide a basic reference source, for ships' force, for planning and overhaul yards, for fleet and training commands, and for tenders and other naval activities. Coverage shall include mechanical, piping, electrical, and electronics systems and equipment on the ship. It shall provide a thorough understanding of the installations on the ship, together with intrasystem and intersystem capabilities and limitations. It shall contain or provide reference to technical information required by the crew as required for proper operation and maintenance of the systems and equipment covered. Document reference numbers shall be standard throughout all chapters of a volume, that is, reference (1) shall be a reference to the same document throughout the volume. Only very common acronyms shall be used, each of which should be spelled out when first utilized.

4.1.1 Current system diagrams may be used as the diagrammatics for each chapter. If used, the diagrams shall be revised to remove numbered references, revision symbols, notes that are not applicable, title blocks, and other information extraneous to the SIB. Connection diagrams for connecting major components in a system or plant and other illustrations required shall be prepared. Illustrations shall be neat and legible.

4.1.2 The text shall not include detailed component operating and maintenance instructions which would duplicate those in the system and component technical manuals, but shall instead refer to these technical manuals for operation and maintenance. The text shall, however, include clear instructions relating component operation to the overall system operation. Reference to the Naval Ships' Technical Manual (NSTM) shall be made where appropriate.

4.2 Divisions. The SIB shall be divided into volumes, parts, chapters, sections, and paragraphs in accordance with MIL-M-38784. Volumes of the SIB shall not exceed 40 mm (1-1/2 inches) in thickness.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:57Z
Check the source to verify that this is the current version before use.

4.2.1 Surface ships.

4.2.1.1 Over 90 meters (300 feet). The SIB shall consist of the following separately-bound volumes, or parts of volumes, as applicable, if listed separately below, with the titles as indicated:

(a) Volume 1 - Hull and hull mechanical systems.
(b) Volume 2 - Machinery plant.
    (1) Part 1 - Propulsion plant, general design and operating procedures.
    (2) Part 2 - Auxiliary machinery, piping, air conditioning, ventilation, and heating systems.
(c) Volume 3 - Power and lighting systems.
    (1) Part 1 - General description and design information of systems.
    (2) Part 2 - General description of electrically operated auxiliaries.
(d) Volume 4 - Electronic systems.
(e) Volume 5 - Interior communication systems.
    (1) Part 1 - Interior communications systems.
    (2) Part 2 - Sound-powered telephone systems, voice tubes, and message passing facilities.
(f) Volume 6 - Weapons control systems.
(g) Volume 7 - Ballasting systems, as applicable.

4.2.1.2 Under 90 meters (300 feet). The SIB may be bound in a single large volume, provided the titles indicated in 4.2.1.1 are clearly separated and indicated (for example, thumb-indexed), and width limitation is not exceeded.

4.2.2 Submarines. SIB shall consist of the following separately--bound volumes with titles as indicated:

(a) Volume 1 - General information,
(b) Volume 2 - Tactical facilities,
(c) Volume 3 - Ship control systems,
(d) Volume 4 - Steam and diesel propulsion plant systems,
(e) Volume 5 - Electrical power systems,
(f) Volume 6 - Ship service systems, and
(g) Volume 7 - Hull, mechanical, and ship emergency systems.

5. DETAILED REQUIREMENTS (See appendix for data requirements)

5.1 Style and format. Unless otherwise specified herein, the style and format requirements for preparation of the SIB and related materials shall be in accordance with MIL-M-38784. Abbreviations and symbols shall comply with MIL-STD-12, MIL-STD-15-2, NAVSEA Drawing 803-5001049, and ANSI Y32.4, as applicable.

Source: https://assist.dla.mil -- Downloaded: 202640-26T07:57Z
Check the source to verify that this is the currentversion before use.

5.1.1 Format.

5.1.1.1 Numbering of pages, illustrations, and tables. Text pages, illustrations, and tables shall be numbered consecutively in Arabic numerals within each section of a chapter. Assignments shall be a three-part number; the first two numbers separated by a hyphen and the last two numbers separated by a decimal point. The first number shall represent the chapter number, the second number shall represent the section number, and the third number shall represent the order within the section. For example: The designation 3-4.12 shall be the 12th page in the 4th section of chapter 3. For volume arrangement, see 5.3.3.

5.1.1.2 Illustrations. Illustrations shall be in accordance with 5.1, but shall be microform-compatible, as specified in 5.1.1.4. Graphic symbols for fluid power diagrams shall be in accordance with ANSI Y32.10. Information flow on pictorial, block, and signal flow diagrams shall be left to right and top to bottom. Fire control symbols shall conform to NAVSEA OP 1700.

5.1.1.3 Mechanically-reproduced copy preparation methods and computer output typesetting. Review manuscript, preliminary, and reproducible copy may be prepared by methods such as electric accounting machine, computer typesetting, punched card, magnetic tape (MTST or MTSC), paper tape, and shall conform to the requirements of 5.1, and the additional requirements of MIL-P-38790, for correction, mechanized assembly, and reproduction.

5.1.1.4 Microform compatibility. Microform compatibility of the SIB shall be as follows:

(a) Foldouts shall be prepared in the following format:
  (1) Foldout drawings shall be divided into 215 mm (8-1/2 inch) image area segments.
  (2) There shall be no drawing data, other than horizontal lines, placed closer than 3 mm (1/8 inch) from the image area limit.
  (3) Lines shall not be vertically displaced during the transition from one image area to the next.
(b) Halftone artwork shall not be used.
(c) Minimum printed size for text shall be 10 point. Nomenclature, callouts, tabular material and symbols on illustrations shall be upper case, with 8 point minimum printed size.
(d) Style and format shall be compatible for filming onto microfiche at a reduction ratio of 24:1 (98 images).

5.1.2 Binder, paper stock, and printing requirements. Cover and backbone stock, paper stock, and printing shall be in accordance with MIL-P-38790. Covers and backbones shall be printed on stock JCP RIO (891 pound type). The binder shall be constructed to permit ready insertion of revised pages.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:57Z
Check the source to verify that this is the current version before use.

5.1.3 Security classification. Classified material shall be included in the SIB only where necessary and in the following manner:

(a) Where the extent of the classified material so dictates, or if reference to separate classified drawings, addenda, or other classified publications is not practicable and this material must be included in the basic publication, the entire manual, book or volume shall be classified.
(b) Where the classified material is minimized, such classified material shall be placed in an addendum and the basic publication shall not be classified. The addendum shall be a separate additional volume and shall be classified appropriately.
(c) Classified material shall be handled and marked in accordance with DOD 5220.22 Series.
(d) Classification of one volume of a publication shall not be the cause for classifying other volumes of the same publication.

5.1.3.1 Each technical publication prepared for the Government shall incorporate on the cover and title page the following distribution control statement, unless otherwise specified: "Distribution limited to U.S. Government agencies only (Test and Evaluation) (date statement applied). Requests for this document must be referred to the Commander, Naval Sea Systems Command."

5.1.4 Warnings and cautions. Warning are used in connection with operating or maintenance procedures, practices, conditions or statements, which, if not strictly observed, could result in injury to or death of personnel. Cautions are used in connection with operating and maintenance procedures, practices, conditions, statements, which, if not strictly observed, could result in damage to, or destruction of, equipment or loss of mission effectiveness.

5.2 Front matter, covers, and backbone. Unless otherwise specified herein, requirements for front matter, covers, and backbone shall be in accordance with MIL-M-38784.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:57Z
Check the source to verify that this is the current version before use.

5.2.1 Front matter. Front matter shall consist of the following contents:

(a) The front matter for each volume, supplement, or for part 1 of multi-part volumes, shall have the following contents in the order listed:
(1) Cover (including back cover and backbone),
(2) Publication change sheet (applicable only to changes),
(3) Title page,
(4) List of effective pages,
(5) Publication change record,
(6) Foreword,
(7) Table of contents,
(8) List of illustrations,
(9) List ot tables,
(10) Safety summary, and
(11) List of abbreviations (Volume 1 only).

(b) The front matter for parts other than part 1 of multi-part volumes shall have the following contents in the order listed:
(1) Cover (including back cover and backbone).
(2) Title page.
(3) Table of contents.
(4) List of illustrations.
(5) List of tables (applicable to the part).
(6) List of abbreviations (Volume 1 only).

5.2.2 Front cover. Front cover shall contain the following:

(a) SIB identification number.
(b) Volume, part, supplement, and revision number, as applicable.
(c) The words "SHIP INFORMATION BOOK".
(d) SIB title and subtitle (volume title).
(e) NAVSEA seal.
(f) Ship name (or class) and identification number.
(g) Distribution statement.
(h) The words "PUBLISHED BY DIRECTION OF COMMANDER, NAVAL SEA SYSTEMS COMMAND".

If the SIB is classified, the front cover shall contain the security classification, espionage notice, and automatic time-phase downgrading and declassification information. When the SIB is a revision, or re-issue of an earlier publication, a supersedure notice shall be shown on the cover. If the manual is classified, the parenthetical note "(This cover is UNCLASSIFIED)" shall be placed beneath the classification marking at the bottom of the cover.

5.2.3 Back cover. The back cover, for each separately bound publication, shall contain the SIB identification number and, the applicable volume, part, supplement, and revision number. If the SIB is classified, the back cover shall also contain the security classification. When the SIB is less than 1 inch thick, the back cover shall also contain the title followed by the subtitle of the SIB.

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:57Z
Check the source to verify that this is the current version before use.

5.2.4 Backbone. Backbones shall be used for SIB that are 25 mm (1 inch) or more in thickness. The backbone shall contain the SIB identification number; the volume, part, supplement, and revision number, as applicable; the SIB title and subtitle; and the security classification, if applicable. This information shall appear vertically on the backbone of a 25- to 40-mm (1- to 1-1/2-inch) thick publication and horizontally on the backbone of a 50- to 60-mm (2- to 2-1/2-inch) thick SIB.

5.2.5 Title page. A title page shall be included in each SIB. It shall be a facsimile of the front cover, but shall also include the date of basic issue or revision. For a multipart volume, a blocked notice "SEE PART 1 OF THIS VOLUME FOR FRONT MATTER" shall be shown on the title pages of parts other than part 1. For a change, a new title page containing the change number and date of the change, shall be issued. For a change to a multipart volume, a new title page shall be issued for part 1 only. Title pages for parts other than part 1 shall not be changed.

5.2.6 Foreword. A foreword shall be included in each SIB supplement, volume, or in part 1 of a multipart volume. The foreword shall briefly describe the scope, content and structure of the entire SIB. The foreword shall include applicable classification guides for each subsystem documented. The foreword shall start as a right-hand page, immediately following the change record.

5.2.7 List of effective pages, change sheet, change record, table of contents, list of illustrations, list of tables, and safety summary. These items shall be prepared.

5.2.8 List of abbreviations. The list of abbreviations shall include abbreviations used throughout the SIB.

5.2.9 Revisions. Changes shall be in the form of replacement pages corresponding to the list of effective pages (see 5.2.7). The revision date shall be indicated on the lower right hand corner of each such revised page.

5.3 Structure of SIB. The SIB shall be arranged in chapters and sections and shall be in accordance with the data ordering document (see appendix). Volumes shall be divided into individually bound parts when required. Content of chapters and sections shall be in accordance with the volume arrangement provided in 5.3.3. Section and subsection content and location may vary within a particular chapter to accommodate necessary or unique data coverage, as specified by the contract.

5.3.1 Data level descriptions. Data presented shall be concise and to the depth necessary for supporting the objectives (see 4.1).

5.3.2 Minimum data requirements. The text, illustrations and tables prescribed in this standard reflect minimum SIB requirements. Where the system configuration provides additional capabilities, operating modes or functions, other than covered herein, such additional coverage by text, illustrations and tabulated data shall be provided. Piping system diagrams shall include identification for all valves, either by words or by symbols.

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:57Z
Check the source to verify that this is the current version before use.

5.3.3 Volume arrangement.

5.3.3.1 Surface ships. Volumes 1 through 7 shall include the following descriptions and guidance:

(a) Volume 1 of the SIB shall include a general description of the ship's design characteristics and the major shipboard arrangements and systems. Descriptive material, lists, and illustrations, as applicable, shall be under the appropriate section number and title. Sections shall be in numerical sequence. Each section of the Ship Specification including all drawings and other documents developed therefrom, shall be carefully studied for applicable subject matter for this book. In addition, subjects such as docking and towing, which may not be covered in the ship specification but for which specific information is applicable and necessary for ship operation or maintenance, shall be included in the appropriate volume.

(b) Volumes 2 through 7 of the SIB shall describe ship systems, including design functions, operations, and limitations of each system, interrelationships between systems, trouble shooting, fault isolation techniques, system check-out, and routine system maintenance. General or specific information contained in Combat Systems Technical Operations Manual (CSTOM), when prepared, the NSTM, and Equipment Technical Manuals, respectively, shall not be repeated in the SIB, except as necessary to fulfill the intent of the text. The following references, if of a permanent nature, shall be provided in the text, where applicable.
   (1) Reference to appropriate drawings.
   (2) Reference to drawing indices, books, schedules or other manuals such as damage control book, operational station book, schedule or watertight integrity tests and inspections, and equipment manuals.
   (3) Cross references between volumes of the SIB, and between sections or chapters within a volume, shall be included only where necessary for continuity, to assist in complete understanding of the text and for avoidance of repetition.

(c) Volume 2 - Machinery plant. This volume shall consist of 2 parts.
   (1) Part 1 - Propulsion plant general design and operation procedures. Part 1 shall acquaint and instruct the operators in the operation of the propulsion plant, shall describe the centralized control system, shall contain information and data in appropriate chapters and sections as outlined below, and shall conform, in general, to the sequence of the outline (as applicable to the type of propulsion plant):
      a. List of references including principal equipment manuals or other technical manuals and drawings (using NAVSEA identifications) used in part 1 preparation, table of contents, list of illustrations, and legend of symbols.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:57Z
Check the source to verify that this is the current version before use.

b. Arrangement of machinery, including brief description, arrangement drawings, list of machinery correlated with the arrangement drawings.

c. Arrangement of operating station enclosure, including associated list of equipment and arrangement drawing.

d. Machinery components including as a minimum a brief description, design ratings and characteristics including, but not restricted to, the following:

1. Main boilers:
   - Integral accessories such as burners, soot blowers, and safety valves.
   - Nonintegral auxiliaries (excluding feedwater and fuel oil) such as forced draft blowers.
   - Control systems, including composite diagram of functions such as combustion, feed water, forced draft blower, speed versus air flow, and fuel oil burner characteristic curves.

2. Main propulsion turbines:
   - Diagram of turbine steam flow and associated valve operation handwheels, and control diagram, for one propulsion set.

3. Propulsion internal combustion engines including control system.

4. Propulsion electrical system including control system.

5. Propulsion gas turbines including control system.

6. Propulsion reduction gear including as applicable:
   - Attached lubrication oil pump,
   - Shaft turning gear,
   - Revolution counter drive,
   - Internal instrumentation.

7. Propulsion shafting and propeller, including as applicable:
   - Shaft securing device,
   - Shaft brake,
   - Uncoupling shaft,
   - Thrust bearings,
   - Auxiliary thrust device,
   - Shaft bearings,
   - Fairwaters,
   - Rope guards.

8. Turbine generator (mechanical end only):
   - Diagram of turbine steam flow and associated valve operation, handwheels, and control diagram for one turbine generator set.

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:57Z
Check the source to verify that this is the current version before use.

9. Distilling plant.
10. Piping systems, including a brief description, with diagrams and lists of equipment served.
11. Collecting, holding and transfer system, including a brief description with diagrams.
12. Main steam:
    List of pressure reducing stations including rating, number, location, equipments served.
13. Auxiliary steam.
14. Feed water, including main, booster recirculation control, and differential pressure control.
15. Main condensate.
16. Auxiliary condensate.
17. Other auxiliary systems:
    Lubricating oil,
    Fuel oil service,
    Control air, and
    Machinery and piping system drainage (LP and HP).

For the above systems and components in part 1, general directions shall be included for operation, with appropriate references to diagrams or other illustrations, for normal operation, split plant operation, emergency operation, and standby operation. These procedures shall be summarized in a condensed manner, for plant-wide operations for the following conditions:

Standby
Warm-up of main propulsion plant
Underway, cruising
Underway, full power
Secure, main propulsion plant
Moored at pier, using shore electric power and steam.

(2) Part 2 - Auxiliary machinery, piping, environmental pollution control, air conditioning, ventilation and heating systems. The systems and components in part 2 shall be described in a manner to permit understanding of their intended functions, operations, and limitations. A chapter shall be devoted to each piping system, each independent auxiliary machinery plant, each air conditioning, ventilation, and heating system and an overall chapter pertaining to pumps. Wherever reference is made to a piping component, the component designation as specified in the Ships Specification shall be included. An index of all

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:57Z
Check the source to verify that this is the current version before use.

tests, inspections, cleaning requirements, adjustments and safety precautions, referred to in each chapter, shall be included at the end of each chapter, and shall refer to the section and page of the text where each is used. Tables shall be included showing the time required to flood and drain each damage control void and the time required to ballast and deballast each fuel and ballast tank or both, as applicable to expedite fueling-at-sea. The liquid loading instructions shall describe the manner in which protection against fragment damage can be maintained as ship fuel and aviation fuel are pumped down. The chapter on pumps shall be similar in format to the pump tables in section 503 of the Ship Specification and shall reference, in addition to the information contained in those tables, the applicable technical manual, compartment name and number of space containing each pump, title of system in which pump is located and the applicable SIB chapter number of the system. The chapter shall be categorized into the following subsections, as applicble: centrifugal, rotary, reciprocating, attached, hand and portable. The schedule for preparation of volume 2, part 2 shall permit issue of approved preliminary chapters at least 1 month prior to the operational check of the associated system. Part 2 shall include, but is not restricted to the following:

a. Auxiliary machinery plants:
   1. Auxiliary boilers,
   2. Refrigeration machinery,
   3. Air conditioning machinery,
   4. Steering system,
   5. Bow transfer system (where applicable) and,
   6. Fin stabilizer machinery (where applicable).

b. Air conditioning, ventilation and heating systems - Section 512
   1. Recirculating,
   2. Supply,
   3. Exhaust,
   4. Maintenance,
   5. Filter locations and,
   6. Filter and duct cleaning instructions.

c. Piping systems - One chapter for each type system as described in the noted section of the Ship Specification, as applicable.
   1. Steam - Section 253 and Section 517.
   2. Feed and condensate - Section 255 and/or Section 517.
   3. Sea water cooling - Section 256 and/or Section 524.
   4. Lubricating oil - Section 262.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:57Z
Check the source to verify that this is the current version before use.

5. Fire main and sea water sprinkling - Section 921.
6. Plumbing drainage, deck drainage, etc. - Section 528.
7. Main, secondary and special drainage - Section 529.
8. Fresh water - Section 532.
9. Machinery and piping systems drainage - Section 534.
10. Ship fuel - Section 541.
11. Aviation fuel and gasoline - Section 542.
12. Compressed air - Section 551.
13. Compressed gas - Section 552.
14. Fire extinguishing - Section 555.
15. Special - Section 558.

d. Pumps - Section 503.

e. Environmental pollution control systems - Section 593.
   1. Sewage systems,
   2. Waste water system,
   3. Solid waste system,
   4. Oil pollution control system,
   5. Air pollution control system,
   6. Chemical and industrial waste system.

Except for the chapter on pumps described above, each chapter shall be sub-divided into three sections as follows:

f. Section I - Description and principles of operation. This section shall be further subdivided into the three units described below:

   1. Unit 1 - introduction. This unit shall cover the purpose, general description and major design characteristics of the system or independent auxiliary machinery plant, and shall include a diagrammatic, schematic drawing, or both.
   2. Unit 2 - detailed description. This unit shall discuss the overall system or independent auxiliary machinery plant components, and its controls, instruments and its protective devices.
   3. Unit 3 - principles of operation. This unit shall describe system or independent auxiliary machinery plant operations, list applicable precautions and discuss applicable operating stations. This unit shall convey information in an explanatory and descriptive manner as to what operations can be performed by or with the system or independent auxiliary machinery plant. Reference shall

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:57Z
Check the source to verify that this is the current version before use.

be made to corresponding operating instructions in section II for detailed step-by-step instructions, as applicable. Operations shall be discussed under the headings of Normal, Starting, Securing, Infrequent, Abnormal and Emergency. Abnormal operation shall be defined as an operation that results when specific equipment or components of a system or independent auxiliary machinery plant is not available for service. Emergency operation shall be defined as that operation performed as a result of a malfunction or maloperation of a system or component, the consequences of which prevent or seriously restrict the operation of the system or independent auxiliary machinery plant or jeopardizes the safety of ship, personnel or both.

g. Section II - Operating instructions. This section shall be further subdivided into the four units described below:

1. Unit 1 - Introduction. This unit shall simply describe the content of the section and reference the principles of operation described in section I.
2. Unit 2 - Initial conditions and precautions. This unit shall specify those initial conditions that provide a starting point for each operating instruction and shall caution and instruct the operator so that he fully understands the extent of the operation to be performed and its effect on system/independent auxiliary machinery plant conditions, and that he shall ascertain whether or not the instruction can be accomplished without conflicting with other operations. Initial conditions shall be based on valve line-up shown on system/independent auxiliary machinery plant diagrams for normal operations.
3. Unit 3 - Procedures. This unit shall cover detailed step-by-step procedures for performing the operations of the operating instruction under normal conditions. Where necessary, steps or instructions shall be emphasized by the use of "NOTE:" "CAUTION" or "WARNING" to insure safe procedures. Each operating instruction shall be provided with a minimum valve line-up table for performing the instruction or portion thereof. Procedures shall specify which steps may be

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:57Z
Check the source to verify that this is the current version before use.

performed in any sequence or in parallel. Procedures shall also include statements which permit the crew to omit certain steps under certain conditions, while still ensuring that crucial steps are performed. In addition, procedures shall be written to permit the crew to enter a procedure at any point, provided the conditions at that point are the same as they would have been had the procedure been performed starting from the initial condition stated in the procedure. Operating procedures in each chapter shall be based on the following format:

Initial conditions,
Precautions,
Summary check list (for immediate action on casualties only),
Operations flow diagrams (for complex evolutions only), and
Detailed procedure.

Notes and references to other operating instructions within the volume shall be minimized. Wherever possible, operating procedures shall be written to cover a single evolution and shall not contain extra steps intended to make the procedure cover more than one evolution.

4. Unit 4 - Back-up operation. This unit shall be used for those systems/independent auxiliary machinery plants that have back-up methods of operation and shall be addressed as being performed only when the procedures of Unit 3 are not practicable or possible.

h. Section III - Maintenance. This section shall be further subdivided into the three units described below:

1. Unit 1 - Principles of maintenance. This unit shall cover and discuss the importance proper maintenance has in retaining system/independent auxiliary machinery plant capability; discuss items which are generally applicable to a wide range of maintenance operations, such as cleanliness, lubrication and isolation criteria; reference sources of additional maintenance information; provide general precautions for performing maintenance; and shall define and briefly discuss maintenance instructions and maintenance procedures.

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:57Z
Check the source to verify that this is the current version before use.

2. Unit 2 - Maintenance instructions. This unit shall provide specific maintenance instructions for system-independent sub-systems and independent auxiliary machinery plant. Each instruction shall have breakdowns on general information, precautions, preventive maintenance, trouble shooting and corrective maintenance. A preventative maintenance summary table shall be provided for each instruction. Preventative maintenance instructions shall be retained in this unit until formal implementation of the 3-M PMS system by NAVSEA.

3. Unit 3 - Maintenance procedures. This unit shall contain maintenance operations of a general nature, such as hydrostatic testing, component handling, routinely performed tests, and adjustment procedures for special system cleaning and preventative maintenance operations.

(d) Volume 3 - Power and lighting systems. This volume shall consist of two parts.

(1) Part 1 - General description and design information of systems. The following shall be a guide for format and applicable subject matter:

a. Generating plant - A description shall be given, including tables and illustrations included where necessary, of ship service, emergency, and special systems:

1. Type, size, and location of generators,
2. Temperature rises to be expected at various points in the generator during normal operation, and methods of measuring temperature by use of the thermocouples in the stator of the generator,
3. Use of space heaters within the generator during periods of shutdown,
4. Type of voltage regulator, method of regulation, and degree of voltage regulation.
5. Prime mover information including kind, rating, speed, reduction gear data, and manufacturer,
6. Type of governor and method of regulation, degree of frequency regulation, and generator load balancing features,
7. Overload and unbalance ratings of the generators including the short time overload ratings and special overload requirements, if any, the allowable phase unbalance for three phase generators, and allowable unbalance for three wire, d.c. generators,

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:57Z
Check the source to verify that this is the current version before use.

8. Brief power analysis to show what loads may be expected during various conditions of operation including the event of loss of part of the generating capacity, and
9. Instructions for operating the system under split plant or parallel conditions, proper bus tie connections for the various shipboard conditions, and the number of ship service generators which may be operated safely in parallel without exceeding the interrupting capacity of the circuit breakers shall be specified. A note shall be added that this will not limit the number of ship service generators which may be paralleled momentarily for transfer of load or synchronizing. It is not intended that detail instructions be included for the operation of the generator itself such as method of starting, controlling, and paralleling.

b. Distribution system. A description shall be given and illustrations included where specified, for ship's service emergency, special, power and lighting systems.

c. Type of distribution.
1. A statement of the method of distributing the electric power, covering for example, that the system is of the radial type consisting of switchboards, load centers and power panels, bus ties, feeders, mains, and submains.
2. A schematic wiring diagram as well as written descriptive material of the ship service, emergency and special electric power distribution systems, and including the following but showing nothing beyond the power panel or individual load supplies by

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:57Z
Check the source to verify that this is the current version before use.

each feeder emanating from the ship service switchboards, emergency switchboards, or load center switchboard.

Switchboard bus arrangement,
Generators (ship service, emergency, and special) and motor generator sets (including electronics, aircraft servicing, interior communication, and weapons control),
Bus ties and bus feeders,
Shore power connections,
Line voltage regulators,
Voltage and frequency monitors,
Rectifiers,
Feedback circuits,
Transformers (lighting and interior communication),
Circuit breakers, (types, frame sizes, and element ratings),
Feeder designation with name and designation of load centers, power panels, transformers, or individual loads served, and
Generator prime mover types.

3. A diagram showing the normal, alternate, and emergency feeders to the following loads:

Steering gear,
Weapons systems,
Electronic systems,
Main drainage pumps and fire pumps, and
Interior communication switchboards.

In addition, bus ties and other interconnections shall be shown. For special types of ships, other loads shall be shown that are considered of the same order of importance as those listed above. This diagram shall show the loads, switchboards, and generators in block form with no interior connections or details such as circuit breakers or bus arrangements and shall show each of these elements at their approximate frame location. No effort shall be made to differentiate between different deck levels. The cables shall be shown in their actual location only insofar as they are to port, center, or starboard. For ships with three decks or platform levels or less (excluding superstructure), a wiring deck plan of the power systems shall be included. For all other ships, an isometric diagram of the power systems shall be provided.

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:57Z
Check the source to verify that this is the current version before use.

d. Switchboard - A description shall be given and illustrations included, where specified.
   1. Number and location.
   2. Use of each unit or section, for example, whether for generator, bus tie, or distribution.
   3. Any special features applying to switchboards, such as:
      Automatic operation of the emergency generating plant,
      Feedback arrangements, and
      Current controlled contactors.
   4. Precautions to prevent paralleling of emergency generators with each other or with other generators, or the requirements for paralleling, if so specified.
   5. Requirements for paralleling with shore power.

e. Protective devices - A description shall be given and the following illustrations included:
   1. A circuit breaker coordination chart shall be prepared showing the time-current characteristics of all the circuit breakers used in series from the generator to the load on a representative feeder. The bus tie circuit breaker characteristics shall also be included on this chart. These shall be standard characteristics curves for the circuit breakers plotted on log-log paper and shall cover the complete range from the long time delay pick-up value of current of the smallest breaker to the instantaneous trip point of the breaker with the highest setting.
   2. The short circuit current characteristics of the generator shall also be shown on this chart. Following are typical examples of the types, sizes, element ratings, and settings of the breaker circuits to be covered for selective tripping:
      Generator connections to switchboard,
      Bus tie,
      Feeder,
      Main and branch,
      Uses of fuses (on both power and lighting circuits),
      Design characteristics of controllers such as:
         Manual operation,
         Magnetic operation,
         Low voltage protection (LVP), and
         Low voltage release (LVR).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:57Z
Check the source to verify that this is the current version before use.

f. Lighting system - A description shall be given and illustrations included as applicable:
   1. For ships with three decks or platform levels or less (excluding superstructure), a wiring deck plan of the lighting systems shall be included,
   2. For all other ships, an isometric diagram of the lighting distribution system shall be included,
   3. Door switches and light traps for darkened ship operation,
   4. Red illumination, description of its operation and use,
   5. Relay and portable lanterns, description of operation and use,
   6. Broad band blue illuminations, description of its operation and use.
   7. Navigation and signal light:
      Elementary wiring diagram,
      Outboard profile of the ship showing locations of the lights, and
      Operational procedures.
   8. Lights for night flight operations:
      Elementary wiring diagram,
      Equipment and light location, and
      Operational procedures.

g. Other systems and miscellaneous - A description shall be given and illustrations included:
   1. Shore power connections:
      Location,
      Reference to power system diagrams,
      Current capacity, and
      Hook-up procedures.
   2. Receptacles for portable connections for portable submersible pumps and portable welding sets:
      An illustration to show the locations and rating of outlets on the plan views of each deck on which outlets are located. In addition, an elevation view at the centerline shall be shown with all outlets as projected on the center plane. Sufficient compartmentation shall be shown to indicate accurately the location of outlets.
   3. Indication of length of cables supplied.
   4. How many cable types and in which repair station they are stowed.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:57Z
Check the source to verify that this is the current version before use.

5. Arrangements for placing in simultaneous operation in each machinery room the maximum number of submersible pumps using the specified number and lengths of portable cables supplied. This shall be shown on both plan and elevation views.
6. A drawing showing the location of main wireways on all decks.
7. Casualty power system: A description of the purpose, scope, limitations, and proper use of this system. An isometric diagram of the complete casualty power system (showing terminals) shall be included.
8. Degaussing system: A general description of the system with instructions for operation. A sketch illustrating the approximate location of the coils.
9. Isolated receptacle circuits: A general description of this system including its purpose and need for maintaining high insulation resistance to ground.
10. Electrical schematic of lighting and outlet circuits and a table showing electrical feeders and breakers by compartment.

(2) Part 2 - General description of electric equipment and electrically-operated auxiliaries.

a. This part shall be divided into four chapters as follows:
   1. Chapter 1 - Power equipment,
   2. Chapter 2 - Electric-operated auxiliaries,
   3. Chapter 3 - Lighting equipment, and
   4. Chapter 4 - Miscellaneous equipment (test panels, storage batteries, instruments, and related equipment).

b. Data, as applicable, for each item of power and lighting equipment, exclusive of power equipment tabulated in chapter 2, shall be tabulated under the following headings in chapters 1, 3, and 4:
   1. Name of equipment.
   2. Name of manufacturer.
   3. Number of units.
   4. Location (designating number in accordance with the ship specification).
   5. Electrical data (brief).
   6. Controlling equipment (type and manufacturer).
   7. Reference to applicable technical manuals.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:57Z
Check the source to verify that this is the current version before use.

8. For electric-operated auxiliaries, data shall be tabulated as follows:
   Name of auxiliary,
   Name of manufacturer of electric equipment,
   Number of units,
   Size (power of electric equipment),
   Location (designating number in accordance with the ship specification),
   Electrical data (state source of type of electric power supply),
   Controlling equipment (type and manufacturer),
   Reference to applicable technical manuals (electric and mechanical).
   Where no technical manual has been provided for an item of equipment, a brief description shall be given in addition to tabulated data relative to the function, purpose, and general features of the equipment. A wiring diagram shall also be included for such equipment.

(e) Volume 4 - Electronic systems. Many of the systems or equipment will be included in CSTOM in similar format if prepared for the ship. Information in the CSTOM shall not be repeated in the SIB, except as necessary to fulfill the intent of the text.

(1) Text - The text shall present a general overall description of the electronic systems installations so that those whose duties require a knowledge of the broad phases, purposes, and functions of the various electronic systems may quickly and easily familiarize themselves with operational capabilities and general characteristics of the installations. The text shall be divided into chapters, each covering a logical grouping of electronic equipment, units, and accessories comprising a particular system installed. Chapters shall be arranged in alphabetical order by system title. Each chapter shall begin with a general discussion of the system. The major emphasis of each chapter, however, shall be on operating capabilities and limitations. Each chapter shall include sufficient description concerning other systems that supply information to or receive information from electronic systems, to permit an understanding of the relationship between the described electronic system and other associated systems.

(2) Illustrations - Drawings required for clarification shall be included as one of the last chapters.

(3) Drawings - The following drawings shall be included:

a. Antenna arrangement (locating all installed antennas and antenna space reservations).

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:57Z
Check the source to verify that this is the current version before use.

b. Antenna system (including retractable or tilting masts, mast controls and indicators, transmission lines, connectors, and operating limitations).
c. Power supply system between distribution centers and electronic equipment and between units of electronic equipment (block diagram).
d. Radar and IFF system design drawing (block diagram).
e. Radio communication system design drawing (block diagram).
f. Sonar system drawing (block diagram).
g. ECM system design drawing (block diagram).
h. Navigation system design drawing (block diagram).
i. Radiac system design drawing (block diagram).
j. Waveguide isometric wiring diagrams (other isometric wiring diagrams are not required).

(4) Tables - Table I shall be titled "List of Electronic Equipment Installed" and shall contain data under the following heading:
a. Model or type number or both.
b. Location (compartment designation number).

(f) Volume 5 - Interior communication systems. This volume shall present a general overall description of the interior communication systems and related equipment so that those whose duties require a knowledge of the various installations may easily familiarize themselves with the principal installation and the operational features. The volume shall be divided into two separately bound parts as follows:

(1) Part 1 - Interior communication systems shall be divided into applicable chapters as follows:

Chapter 1 - IC switchboards (including IC test switchboards).
Chapter 2 - Ship control consoles and ship control indicators.
Chapter 3 - Telephone system, dial.
Chapter 4 - Amplified voice communications, recording, television, and entertainment systems.
Chapter 5 - Electrical alarm, safety, and warning systems.
Chapter 6 - Indicating, order, and metering systems.

Throughout part 1, where applicable, systems shall be arranged and listed in alphabetical order according to circuit designations. Circuit designations shall appear to the left of system titles. The description of each installation shall include the following information, as applicable:

a. Purpose - The text shall describe the basic purpose for which the subject system is installed.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:57Z
Check the source to verify that this is the current version before use.

b. System classification - Importance and readiness classification shall be designated for each system.

c. Equipment description - A listing of principal system equipments, including switching, shall be provided. The list shall denote equipment type, quantity, location, and the functional end use of each. Where equipments or components (such as loudspeakers and high temperature thermostats), are associated with a specific group or area, they shall be categorized accordingly.

d. Operation - The system operational capabilities and limitations shall be described in consonance with the applicable shipboard installation drawings. Input and output characteristics of major equipments shall be defined where they affect overall system operation. Special emphasis shall be devoted to modes of operation, transfer, and action-cutout switching to facilitate expedient operational decisions during damage emergencies, equipment failure, and changing requirements in system loads. A single line flow diagram shall be provided to supplement the written text for all systems having complex switching arrangements. Following is a list of systems having complex switching arrangements either singularly or in combination with other systems. The list is not intended to preclude diagrams for other systems, where required, to simplify the operational description:

Circuit	System title
HD-HE	Wind direction and speed system
L	Rudder order system
LB	Steering emergency signal system
LC	Gyro compass system
XLC	Auxiliary gyro compass system
LN	Ships inertial navigation system
LV	Ships aircraft inertial automatic navigator alinement system
M	Propeller order system
MB	Engine or motor order system
3MB	Engine control order system
4MB	Propulsion control order system
1MC	General announcing systems
3MC	Aviators' announcing systems
4MC	Damage control announcing system
MS	Remote switching control system
N	Rudder angle indicator system
5N-6N	Emergency rudder angle indicator systems
RC	Catapult signal system
TL	Dead reckoning system
VP	Controllable pitch propeller indicating system
Y	Underwater log system

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:57Z
Check the source to verify that this is the current version before use.

Flow diagrams shall depict transmission of signals from source or origin to destination. Typical flow diagrams, with appropriate reference to tables, may be used for systems containing duplicate sub-systems. Directional flow diagrams shall be marked to indicate the specific electrical and mechanical signal characteristics being transmitted. The text, in conjunction with supporting diagrams, shall define the interrelationships between the systems being described and associated systems.

e. System check-out - System check-out procedures shall be provided to enable periodic evaluation of the system's operational status. A systematic approach shall be included for isolating equipment failure, open circuits, shorts, and grounds in system cabling. Check-out procedures in equipment technical manuals and test memoranda shall be referenced to supplement the description as required.

f. Power supplies - Voltage, frequency, phase, source, and location of power supply (switch and fuse size not required) shall be identified. A schematic wiring diagram showing switchboard power supplies, bussing, and interties shall be included in the section covering IC switchboards.

g. Referenced material - Principal installation drawings, technical manuals, and other data pertaining to the installation shall be referenced, where applicable.

(2) Part 2 - Sound-powered telephone systems, voice tubes, and message-passing facilities shall be divided into applicable chapters as follows:

Chapter 1 - General information
Chapter 2 - Ship control circuit
Chapter 3 - Engineers' and damage control circuits
Chapter 4 - Armaments control and associated circuits
Chapter 5 - Miscellaneous circuits (not included in above categories)
Chapter 6 - Voice tubes and message-passing facilities

Chapter 1 shall include information on the telephone systems and types of circuits installed, and the function and use of associated equipment such as plotter's transfer switchboard, amplifiers, tie switches, untie switches, tie lines, and selective switches. A complete list of the telephone circuits (in alphabetical order) and a list of the selective switches shall be included. Each chapter, 2 through 5, shall describe the function of the associated circuits, and shall include a list of telephones by

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:57Z
Check the source to verify that this is the current version before use.

circuit, and a list of telephones by station. Sound-powered telephone calls provided shall be included in the list of telephones by circuit. A comprehensive description and schematic wiring diagrams shall be provided for those circuits which incorporate special transfer switching. Chapter 6 shall contain a description and list (including calls) of the voice tubes, and a description and list of the message-passing facilities.

(g) Volume 6 - Weapons. All of the systems and equipment will be in the CSTOM, if prepared for the ship. This volume shall present a general overall description of the weapons control system and special equipment, so that those whose duties require a knowledge of the various installations, may easily familiarize themselves with the principal installation and operational features. The volume shall be divided into chapters as follows:

Chapter 1 - Weapons control systems.

Chapter 2 - Weapons control switchboards.

Throughout chapters 1 and 2, where applicable, systems shall be arranged and listed in alphabetical order according to circuit designations. Circuit designations shall appear to the left of system titles. In general, the description of each installation shall include the following information, as applicable:

(1) Purpose,
(2) Type and location of major units,
(3) Principal features, method of operation (refer to applicable technical manual for detailed descriptions), and transfer and action cutout switching,
(4) Power supplies (switch and fuse sizes not required),
(5) Reference technical manuals,
(6) Reference drawings (principal installation drawings).

For a system having an extensive switching arrangement, a simplified schematic wiring diagram shall be provided to supplement the switching description. A schematic wiring diagram showing switchboard power supplies, bussing, and interties shall be included.

(h) Volume 7 - Ballasting systems. This volume shall present a comprehensive description, including basic drawings, diagrams, and tabulations, of the arrangement, functions, operational sequences, and limitations of the ballasting systems for ships having extensive ballasting systems, such as LSD and LPD. Where volume 7 is required, a sample volume will be provided by NAVSEA for guidance.

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:57Z
Check the source to verify that this is the currentversion before use.

5.3.3.2 Submarines. The SIB for submarines shall be prepared on an individual ship basis. The design yard shall prepare the books for the lead ship of the class. Copies will be made available by NAVSEA for use by the fellow yards in indicating individual ship differences. Volumes 1 through 7 shall include the following system descriptions and guidance:

(a) Volume 1 - General information. This volume shall provide direct and concise descriptions of the basic design characteristics of the class and shall summarize the purpose and limitations of the major installations, arrangements and systems. Specific operational discussions and details of systems or components shall not be included but shall be referenced to the applicable systems manuals (volumes 2 through 7). Illustrations, in general, shall not duplicate information contained in the Booklet of General Drawings, but may be developed from these drawings where necessary to present simplified arrangement and schematic drawings to supplement the text.

(b) Volumes 2 through 7 shall provide detailed system or component descriptions, including function, design characteristics, principles of operation, modes of operation, maintenance, troubleshooting guides, and system tests, checkouts, and adjustments. Reference lists, instrumentation requirements, and system diagrams shall be included, as necessary, to define or supplement the text. The volumes shall include the following systems:

(c) Volume 2 - Tactical facilities:
- (1) Torpedo weapons systems,
- (2) Periscope systems,
- (3) Radar systems,
- (4) Sonar systems,
- (5) Navigational aid systems,
- (6) Radio system,
- (7) Teletype system,
- (8) Underwater telephone system,
- (9) Signaling equipment, and
- (10) Signal ejector system.

(d) Volume 3 - Ship control system:
- (1) Ballasting including trim and drain,
- (2) Hovering and depth control system,
- (3) Steering and diving control,
- (4) Interior communication, and
- (5) Navigation.

(e) Volume 4 - Steam and diesel propulsion plant systems:
- (1) Steam plant support, and
- (2) Diesel plant support.

(f) Volume 5 - Electrical power systems:
- (1) Electric power sources,
- (2) Electric power distribution,
- (3) Electric plant control, and
- (4) Miscellaneous electrical loads.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:57Z
Check the source to verify that this is the current version before use.

(g) Volume 6 - Ship service systems:
(1) Compressed air,
(2) Compressed gas,
(3) Hydraulic,
(4) Fresh water,
(5) Air conditioning, ventilation, and atmospheric life support,
(6) Refrigeration,
(7) Snorkel,
(8) Habitability,
(9) Diesel generator support, and
(10) Fuel and compensating water.

(h) Volume 7 - Hull, mechanical, and ship emergency systems,
(1) Capstans and anchor handling,
(2) Docking, mooring, and towing,
(3) Rigging,
(4) Handling, and mine clearance,
(5) Outboard lighting,
(6) Lubrication, and
(7) Ships emergency systems.

Preparing activity:
Navy - SH
(Project TMSS-N124)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:57Z
Check the source to verify that this is the current version before use.

DATA REQUIREMENTS

10. DATA

10.1 Data requirements. When this standard is used in an acquisition which incorporates a DD Form 1423, Contract Data Requirements List (CDRL), the data requirements identified below shall be developed as specified by an approved Data Item Description (DD Form 1664) and delivered in accordance with the approved CDRL incorporated into the contract. When the provisions of DAR 7-104.9(n)(2) are invoked and the DD Form 1423 is not used, the data specified below shall be delivered by the contractor in accordance with the contract or purchase order requirements. Deliverable data required by this specification is cited in the following paragraphs.

Paragraph No.	Data requirement title	Applicable DID No.	Option
Sections 4 and 5, as applicable	Technical Manual Manuscript Copy	DI-M-2042	------
	Manual, Technical, Preliminary	DI-M-2043	------
	Manual, Technical, Standard	DI-M-2044	------
	Technical Manual, Permanent Change Pages	DI-M-2046	------

(Copies of data item descriptions required by the contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

10.1.1 The data requirements of 10.1 and any task in the standard required to be performed to meet a data requirement may be waived by the contracting/acquisition activity upon certification by the offeror that identical data were submitted by the offeror and accepted by the Government under a previous contract for identical item acquired to this standard. This does not apply to specific data which may be required for each contract, regardless of whether an identical item has been supplied previously (for example, test reports).

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:57Z
Check the source to verify that this is the currentversion before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/ vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE
DOD-STD-2139 (SH)

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A
☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?
   A. GIVE PARAGRAPH NUMBER AND WORDING.

   B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?
   ☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426 REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

S/N 0102-014-1802

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:57Z
Check the source to verify that this is the current version before use.