NOT MEASUREMENT SENSITIVE

MIL-STD-2045-14502-01
28July 1994

MILITARY STANDARD

INFORMATION TECHNOLOGY
DOD STANDARDIZED TRANSPORT PROFILE
INTERNET TRANSPORT PROFILE
FOR DOD COMMUNICATIONS

Part 1: Transport and Internet Services

AMSC N/A

AREA DCPS

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:56Z
Check the source to verify that this is the current version before use.

Foreword

This military standard is approved for use by all Departments and Agencies of the Department of Defense (DOD).

Beneficial comments (recommendations, additions, deletions) and any pertinent data that may be of use in improving this MIL-STD should be addressed to the:

Joint Interoperability and Engineering Organization (JIEO)
ATTN:TBBF
Fort Monmouth, New Jersey 07703-5613

by using the Standardization *Document Improvement Proposal (DD Form 1426) appearing at the end of this MIL-STD* or by memorandum.

This Defense Standardized Profile (DSP) is a functional DoD Data Communications Protocol Standard (DCPS) produced by the DCPS Technical Management Panel (DTMP). The MIL-STD-2045 document series was established within the DCPS Standardization Area to allow for the enhancement of commercial standards or the development of standards that are unique to DoD.

The MIL-STD-2045-10000 series, MIL-STD-2045-10000 to MIL-STD-2045-19999 inclusive, will be used to describe how DoD will implement commercial, international, national, federal, or military standards within the functional profile concept to provide required network services. The Government Open Systems Interconnection Profile (GOSIP) will serve as the base for developing the 10000 series with DoD enhancements, unique military standards, and interim standards being used only when necessary.

The MIL-STD-2045-20000 series, MIL-STD-2045-20000 to MIL-STD-2045-29999 inclusive, will be used to describe DoD enhancements and extensions to existing commercial, international, national, or federal standards.

The MIL-STD-2045-30000 series, MIL-STD-2045-30000 to MIL-STD-2045-39999 inclusive, will be used to describe protocols and services unique to DoD that will not be supported by commercial, international, national, or federal standards.

The MIL-STD-2045-40000 series, MIL-STD-2045-40000 to MIL-STD-2045-49999 inclusive, will be used to document interim standards. Interim standards document protocols and services needed by DoD until these protocols and services are described in either GOSIP or in a MIL-STD-2045-20000 or -30000 series standard.

The MIL-STD-2045-50000 series, MIL-STD-2045-50000 to MIL-STD-2045-59999 inclusive, will be used to describe how DOD will implement commercial, international, national, federal, or military standards within the functional profile concept to provide required network services. The Government Open Systems Interconnection Profiles (GOSIP) will serve as the base for developing the 50000 series with DOD enhancements, unique military standards, and interim standards being used only when necessary. The difference between MIL-STD-2045-10000 series and the MIL-STD-2045-50000 series is that the 50000 series are interim profiles

Specific details and instructions for establishing a MIL-STD-2045 document, as well as profile development guidelines, are documented in MIL-HDBK-829, Volumes. DTMP Working Groups shall be responsible for DSP development and informal service and agency coordination; the DTMP Plenary shall be responsible for final review and approval.

This document is part of a set of interim DoD data communications protocol profiles based on the Internet protocol suite, and is intended to support the interoperability of DoD communication networks, including

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:56Z
Check the source to verify that this is the current version before use.

connectivity with the Defense Data Network (DDN).

The options and parameters specified in this DSP take precedence over MIL-STD 1777, Internet Protocol and MIL-STD 1778, Transmission Control Protocol.

This part of MIL-STD 2045-14502 contains one normative annex and one informative annex:

Annex A (normative) DSPICS REQUIREMENTS LIST (DPRL).
Annex B (informative) CONCLUDING MATERIAL.

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:56Z
Check the source to verify that this is the currentversion before use.

Contents

Introduction		ix
1	Scope	1
1.1	General	1
1.2	Position within the taxonomy.	1
1.3	Scenario	1
2	References	2
2.1	Government Documents	2
2.1.1	Specifications, standards, and handbooks.	2
2.1.2	Other Government documents, drawings and publications.	2
2.2	Non-Government publications	2
2.2.1	Profiles	2
2.2.2	Base Standards	2
2.2.3	Other Non Government documents, drawings, and publications.	3
2.3	Order of precedence.	3
3	Definitions	3
4	Abbreviations and Acronyms	3
5	Requirements	4
5.1	General Requirements	4
5.2	Transport Layer Requirements	4
5.2.1	Transmission Control Protocol (TCP)	4
5.2.1.1	Major Capabilities	4
5.2.1.2	Header Format	5
5.2.1.3	Detailed Requirements	5
5.2.1.3.1	Interface Requirements	5
5.2.1.3.1.1	*ICMP messages from IP*	5
5.2.1.3.1.2	TCP/Application Layer Protocol (ALP) Interface	5
5.2.1.3.1.3	IP Options	5
5.2.1.3.1.4	Address Validation	6
5.2.1.3.2	*Connection Management and Data Transfer Requirements*	6
5.2.1.3.2.1	Push Flag	6
5.2.1.3.2.2	Window Management	6
5.2.1.3.2.3	Urgent Data	6
5.2.1.3.2.4	*TCP Options*	6
5.2.1.3.2.5	TCP Checksums	6
5.2.1.3.2.6	Initial Sequence Number (ISN) Selection	6
5.2.1.3.2.7	Opening Connections	6
5.2.1.3.2.8	*Closing Connection*	6
5.2.1.3.2.9	Retransmissions	6
5.2.1.3.2.10	Generating ACKnowledgements (ACKs)	7
5.2.1.3.2.11	Sending Data	7
5.2.1.3.2.12	*Connection Failures*	7
5.2.1.3.2.13	Send Keep-alive Packets	7
5.2.2	User Datagram Protocol (UDP)	7
5.2.2.1	Major Capabilities	7
5.2.2.2	*Detailed Requirements*	7
5.2.2.2.1	Interface Requirements	7
5.2.2.2.1.1	ICMP Messages from IP	7

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:56Z
Check the source to verify that this is the current version before use.

5.2.2.2.1.2 UDP/ALP Interface . . . 7
5.2.2.2.1.3 IP Options . . . 7
5.2.2.2.2 Data Transfer Requirements . . . 8
5.2.2.2.2.1 Checksum . . . 8
5.2.2.2.2.2 UDP Multihoming . . . 8
5.3.1 Internet Protocol . . . 8
5.3.1.1 Major Capabilities . . . 8
5.3.1.2 Datagram Format . . . 8
5.3.1.3 Detailed Requirements . . . 9
5.3.1.3.1 Interface Requirements . . . 9
5.3.1.3.1.1 Internet/Transport Layer Interface . . . 9
5.3.1.3.2 Data Transfer . . . 9
5.3.1.3.2.1 Address Handling . . . 9
5.3.1.3.2.1:1 Routing Outbound Datagrams . . . 9
5.3.1.3.2.1.2 Local Mutlihoming . . . 9
5.3.1.3.2.1.3 Source Route Forwarding . . . 9
5.3.1.3.2.1.4 Broadcasts . . . 9
5.3.1.3.2.1.5 Multicasting . . . 9
5.3.1.3.2.2 *Fragmentation and Reassembly* . . . 10
5.3.1.3.2.3 Type Of Service (TOS) . . . 10
5.3.1.3.2.4 Time-To-Live (TTL) . . . 10
5.3.1.3.3 Options . . . 10
5.3.2 Internet Control Message Protocol (ICMP) . . . 10
5.3.2.1 Major Capabilities . . . 10
5.3.2.2 ICMP Message Format . . . 10
5.3.2.2.1 ICMP Messages . . . 11
5.3.2.3 Detailed Requirements . . . 11
5.3.2.3.1 Error Reporting . . . 11
5.3.2.3.1.1 ICMP Error Messages Not Sent . . . 11
5.3.2.3.2 Query Messaging . . . 11

Annexes

A DSPICS REQUIREMENTS LIST (DPRL) . . . A-1
A.1 Introduction . . . A-1
A.1.1 Notation . . . A-1
A.1.2 Footnotes . . . A-2
A.1.3 Instructions for Completing the DPRL . . . A-2
A.2 Standards Referenced . . . A-3
A.3 DSPICS Requirements List . . . A-3
A.3.1 General Information . . . A-3

B CONCLUDING MATERIAL . . . B-1
B.1 Deviations from the Base Standards/Referenced Profiles . . . B-1
B.2 Subject Term (Keyword) Listing . . . B-1
B.3 Preparing Activity: . . . B-1
B.4 Reviewing Activity: . . . B-1
B.5 Custodians: . . . B-2

Figures

1 Transport Profile Scenario . . . 1

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:56Z
Check the source to verify that this is the current version before use.

Tables

A.3.1.1	Identification of PICS	A-3
A.3.1.2	Identification of IUT	A-3
A.3.1.3	Global Statement of Conformance	A-4
A.4	Basic Requirements	A-4
A.4.1	PICS Proforma for Transmission Control Protocol (TCP)	A-5
A.4.1.1	Identification	A-5
A.4.1.2	Protocol Summary	A-5
A.4.1.3	General/Major Capabilities	A-5
A.4.1.4	Interfaces	A-6
A.4.1.5	Frame Structure	A-6
A.4.1.6	TCP Procedure	A-7
A.4.2	PICS Proforma for User Datagram Protocol (UDP)	A-10
A.4.2.1	Identification	A-10
A.4.2.2	Protocol Summary	A-10
A.4.2.3	General/Major Capabilities	A-11
A.4.2.4	Interfaces	A-11
A.4.2.5	Frame Structure	A-11
A.4.2.6	UDP Procedure	A-12
A.4.3	PICS Proforma for Internet Protocol (IP)	A-13
A.4.3.1	Identification	A-13
A.4.3.2	Protocol Summary	A-13
A.4.3.3	General/Major Capabilities	A-13
A.4.3.4	Interfaces	A-16
A.4.3.5	Frame Structure	A-16
A.4.3.6	Procedure	A-26
A.4.4	PICS Proforma for Internet Control Message Protocol (ICMP)	A-33
A.4.4.1	Identification	A-33
A.4.4.2	Protocol Summary	A-33
A.4.4.3	Interfaces	A-33
A.4.4.4	Frame Structure	A-33
A.4.4.5	ICMP Message Formats	A-34
A.4.4.6	ICMP Procedure	A-39

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:56Z
Check the source to verify that this is the current version before use.

Introduction

This DOD Standardized Profile (DSP) is defined within the context of functional standardization, in accordance with the principles specified by MIL-HDBK-829. The context of functional standardization is one part of the overall field of Information Technology (IT) standardization activities - covering base standards, profiles, and registration mechanisms. A profile defines a combination of base standards that collectively perform a specific well-defined IT function. Profiles standardize the selection of options and other variations in the base standards to promote system interoperability and to provide a basis for the development of uniform, internationally recognized system tests.

One of the most important roles for a DSP is to serve as the basis for the development of recognized tests. DSPs also guide implementors in developing systems that fit the needs of the US Department Of Defense (DAD). DSPs are produced not simply to 'legitimize' a particular choice of base standards and options, but to promote real system interoperability. The development and widespread acceptance of tests based on this and other DSPs is crucial to the successful realization of this goal.

This MIL-STD is part of a set of interim Command and Control (C^2) common data communication profiles. It will cease to exist upon the transition of the various military service and agency (S/A) networks to GOSIP. The purpose is to record what presently exists in, and what is needed, to achieve the interoperability of the various S/A data communication networks deployed to support a Joint Task Force (JTF).

This profile is part one of a six part transport profile. This part specifies the corresponding transport and network layers for the Transmission Control Protocol/Internet Protocol (TCP/IP) protocol suite. The transport layer consists of TCP and UDP, and the network layer consists of IP and ICMP.

The base standards specified in this DSP include Request For Comments (RFCs) designated as Official Internet Architecture Board (IAB) standards, other RFCs, and Open Systems Interconnection (OSI) Layer Standards from the Open Systems Interconnection (OSI) Reference Model.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:56Z
Check the source to verify that this is the current version before use.

Information Technology - Defense Standardized Profile (DSP) - Internet Transport Profiles - Part 1: Transport Services

1 Scope

1.1 General

This standardized profile applies to end systems concerned with implementing the TCP/IP protocol suite. It specifies a combination of protocols that provide a connectionless or a connection-oriented transport service over a connectionless network service. The subnetwork technology requirements are contained in parts 4 and 5 of this profile.

1.2 Position within the taxonomy.

This profile contains requirements for both a connection-oriented and a connectionless transport service. It also contains requirements for a connectionless network service.

1.3 Scenario

This profile specifies the provision for connectionless or connection-oriented transport service between an end system connected to a subnetwork and another compatible end system through the IP connectionless network service. The compatible end system may use mutually agreed upon access methods contained within this DSP, or may conform to a mutually agreed upon alternative access methods. An end system is compatible only if the suboptions (e.g., TCP) are compatible. This profile contains the subnetwork independent requirements. A complete transport profile requires knowledge of the subnetwork type, access method, circuit type, and service type.

The layer standards that make up this profile are shown in Figure 1.

<table>
<tr><td>Transport Layer</td><td>IAB STD 7 (TCP)
IAB STD 6 (UDP)</td><td rowspan="2">TCP/IP Group Profile
MIL-STD 2045-14502
Part 1</td></tr>
<tr><td rowspan="2">Network Layer</td><td>IAB STD 5 (IP & ICMP)</td></tr>
<tr><td colspan="2">SUBNETWORK INDEPENDENT PART-4</td></tr>
<tr><td>Data Link Layer</td><td colspan="2" rowspan="2">SUBNETWORK DEPENDENT PART-5</td></tr>
<tr><td>Physical Layer</td></tr>
</table>

Figure 1. Transport Profile Scenario

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:56Z
Check the source to verify that this is the current version before use.

2 References

2.1 Government Documents

2.1.1 Specifications, standards, and handbooks.

The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

MIL-HDBK 829:	July 1994	*Guidelines for DOD Standardized Profiles.*
MIL-STD-2045-14502-2,	July 1994	*Point-to-Point Links*
MIL-STD-2045-14502-3,	July 1994	*Wide Area Network Access*
MIL-STD-2045-14502-4,	July 1994	*Local Area Network (LAN) Media Independent Requirements*
MIL-STD-2045 14502-5	July 1994	Carrier-Sense Multiple Access With Collision Detection (CSMA/CD) *Local Area Network (LAN) Media Dependent Requirements*
MIL-STD-2045-14502-6,	July 1994	*Combat Net Radio (CNR*

DOD activities may obtain copies of DOD directives through their own publication channels or from the DOD Single Stock Point, Standardization Document Order Desk, 700 Robbins Avenue, Building 4D, Philadelphia, PA 19111-5094. Other federal agencies and the public may purchase copies from the U.S. Department of Commerce, National Technical Information Service, 5285 Port Royal Road, Springfield, VA 22161.

Copies of Federal Information Processing Standards (FIPS) are available to Department of Defense activities from the Commanding Officer, Naval Publications and Forms Center, 5801 Tabor Avenue, Philadelphia, PA 19120-5099. Others must request copies of FIPS from the National Technical Information Services, 5285 Port Royal, Springfield, VA 22161-2171.

2.1.2 Other Government documents, drawings and publications.

NONE

2.2 Non-Government publications

The following documents form a part of this document to the extent specified herein. Unless otherwise specified the issues of the documents which are DOD adopted are those listed in the issue of the DODISS cited in the solicitation

2.2.1 Profiles

NONE

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:56Z
Check the source to verify that this is the current version before use.

2.2.2 Base Standards

IAB STD 3 *(RFC 1122: 1989, Requirements For Internet Hosts - Communication Layers, RFC 1123: 1989, Requirements For Internet Hosts - Application and Support)*

IAB STD 5 *(RFC 791: 1981, Internet Protocol, RFC 950: 1985, Internet standard subnetting procedure, RFC 919: 1984, Broadcasting Internet datagrams, RFC 922: 1984, Broadcasting Internet datagrams in the presence of subnets, RFC 792: 1981, Internet Control Message Protocol, RFC 1112: 1989, Host extensions for IP multicasting)*

IAB STD 6 *(RFC 768: 1980, User Datagram Protocol)*

IAB STD 7 *(RFC 793: 1981, Transmission Control Protocol)*

2.2.3 Other Non Government documents, drawings, and publications.

The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted are those listed in the issue of the DODISS cited in the solicitation

"Round Trip Time Estimation," P. Karn & C. Partridge, ACM SIGCOMM-87, August 1987.

"*Congestion Avoidance and Control*," V. Jacobson, ACM SIGCOMM-88, August 1988.

"Congestion Control in IP/TCP," J. Nagle, RFC-896, January 1984.

2.3 Order of precedence.

In the event of a conflict between the test of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3 Definitions

Internet Architecture Board (IAB) Standards (STD): The IAB has established this as an official standard protocol for the Internet. These protocols are assigned STD numbers and are based on one or more RFCs.

Request For Comments (RFC): RFCs are the working notes of the "Network Working Group," which is the Internet research and development community.

Note: All standards are published RFCs, but not all RFCs specify standards.

4 Abbreviations and Acronyms

ACK ACKnowledgement
ALP Application Layer Protocol
DOD Department Of Defense
DSP Defense Standardized Profile

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:56Z
Check the source to verify that this is the current version before use.

GOSIP	Government Open Systems Interconnection Profile
IAB	Internet Architecture Board
ICMP	Internet Control Message Protocol
IP	Internet Protocol
IHL	Internet Header Length
ISN	Initial Sequence Number
MSS	Maximum Segment Size
RFC	Request For Comments
STD	Standard
SYN	Synchronization
TCP	Transmission Control Protocol
TOS	Type Of Service
TTL	Time To Live
UDP	User Datagram Protocol

5 Requirements

A conforming implementation of this profile shall be unconditionally compliant (as defined in RFC 1122, paragraph 1.3.2), and therefore, shall satisfy all the MUST and all the SHOULD requirements of the reference base standards.

A conforming implementation of this profile shall not implement any capability that has been identified by the base standard as "SHOULD NOT" be implemented.

5.1 General Requirements

A conforming implementation of this profile shall be unconditionally compliant and therefore, shall satisfy all the **"MUST"** and all the **"SHOULD"** requirements of the reference base standards and shall not implement any capability that has been identified by the base standards as **"SHOULD NOT"**.

Implementations claiming conformance to this DSP shall support the following elements as stated.

(a) All requirements in the remainder of section 5.
(b) All mandatory requirements of the standards referenced by this profile.
(c) All of the constraints specified in Annex A (normative).

5.2 Transport Layer Requirements

A conforming implementation of this profile shall use TCP (IAB STD 7, RFC 793) and/or UDP (IAB STD 6, RFC 768), and shall conform to Requirements for Internet Hosts - Communication Layers (IAB STD 3, RFC 1122).

5.2.1 Transmission Control Protocol (TCP)

5.2.1.1 Major Capabilities

A conforming implementation of TCP shall support the following capabilities in accordance to the indicated base standards:

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:56Z
Check the source to verify that this is the current version before use.

(a) data transfer as specified in RFC 793, sections 1.5, 2.8, and 3.7.
(b) addressing as specified in RFC 793, section 2.7 and RFC 1122, section 4.2.2.1.
(c) fragmentation and reassembly as specified in RFC 793, sections 1.5, 2.7, and 3.3 and RFC 1122, section 4.2.2.6.
(d) piggyback acknowledgement as specified in RFC 793, sections 1.5, 2.6, and 3.7 and RFC 1122, section 4.2.3.2.
(e) flow control as specified in RFC 793, section 1.5, 2.6, and 3.7 and RFC 1122, section 4.2.3.3.
(f) checksum computation as specified in RFC 793, sections 1.5 and 3.1 and RFC 1122, section 4.2.2.7.
(g) error recovery as specified in RFC 793, sections 1.5 and 3.7, and RFC 1122, sections 4.2.3.1 and 4.2.2.15.
(h) precedence and security as specified in RFC 793, sections 1.5 and 2.9.
(i) multiplexing as specified in RFC 793, sections 1.5, 2.7, and 3.8 and RFC 1122, section 4.2.2.1 and 4.2.2.18.

5.2.1.2 Header Format

A conforming implementation shall support the following fields as described in RFC 793, section 3.1:

(a) source port
(b) destination port
(c) sequence number
(d) acknowledgement number
(e) data offset
(f) reserved field
(g) control bits
(h) window field
(i) checksum
(j) urgent pointer
(k) options
(l) padding
(m) data

5.2.1.3 Detailed Requirements

This paragraph identifies additional requirements, or clarifications of requirements to support military use of internet standards referenced by this DSP.

5.2.1.3.1 Interface Requirements

5.2.1.3.1.1 ICMP messages from IP

A conforming implementation shall act upon ICMP messages as stated in RFC 1122, section 4.2.3.9.

5.2.1.3.1.2 TCP/Application Layer Protocol (ALP) Interface

A conforming implementation shall include the features described in RFC 1122, section 4.2.4.

5.2.1.3.1.3 IP Options

A conforming implementation shall support the IP options delineated in RFC 1122, section 4.2.3.8.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:56Z
Check the source to verify that this is the current version before use.

5.2.1.3.1.4 Address Validation

A conforming implementation shall perform the functions described in RFC 1122, section 4.2.3.10.

5.2.1.3.2 Connection Management and Data Transfer Requirements

5.2.1.3.2.1 Push Flag

The push flag shall be implemented as described in RFC 1122, section 4.2.2.2 and RFC 793, section 2.8.

5.2.1.3.2.2 Window Management

Window management shall be implemented as described in RFC 1122, sections 4.2.2.3, 4.2.2.16, and 4.2.2.17 and RFC 793, section 3.1.

5.2.1.3.2.3 Urgent Data

Urgent Data shall be labeled as described in RFC 1122, section 4.2.2.4 and RFC 793, section 3.1.

5.2.1.3.2.4 TCP Options

TCP Options shall be implemented as described in RFC 1122, sections 4.2.2.5 , 4.2.2.6 and RFC 793, section 3.1.

5.2.1.3.2.5 TCP Checksums

A conforming implementation shall compute and check checksums as stated in RFC 1122, section 4.2.2.7 and RFC 793, section 3.1.

5.2.1.3.2.6 Initial Sequence Number (ISN) Selection

ISN selection shall be performed as described in RFC 1122, section 4.2.2.9 and RFC 793, section 3.3.

5.2.1.3.2.7 Opening Connections

The following features shall be implemented as described in RFC 793, section 3.4 and RFC 1122, sections 4.2.2.10, 4.2.2.11, 4.2.2.18, 4.2.3.7, and 4.2.3.10.

5.2.1.3.2.8 Closing Connection

Closing a connection shall be implemented as described in RFC 793, section 3.5 and RFC 1122, sections 4.2.2.12 and 4.2.2.13.

5.2.1.3.2.9 Retransmissions

Retransmission shall be implemented as described in RFC 1122, sections 4.2.2.15 and 4.2.3.1:

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:56Z
Check the source to verify that this is the current version before use.

5.2.1.3.2.10 Generating ACKnowledgements (ACKs)

A conforming implementation shall generate ACKs as described in RFC 1122, sections 4.2.2.20, 4.2.2.21, 4.2.3.2, and 4.2.3.3.

5.2.1.3.2.11 Sending Data

A conforming implementation shall perform the functions described in RFC 1122, sections 4.2.2.19, and 4.2.3.4.

5.2.1.3.2.12 Connection Failures

A conforming implementation shall act upon a connection failure as described in RFC 1122, section 4.2.3.5.

5.2.1.3.2.13 Send Keep-alive Packets

There are no additional requirements to those described in RFC 1122, section 4.2.3.6.

5.2.2 User Datagram Protocol (UDP)

5.2.2.1 Major Capabilities

A conforming implementation of UDP shall support the following:

a) data transfer as specified in RFC 768, page 2 and RFC 1122, section 4.1.1.
b) port addressing as specified in RFC 768, pages 1 and 2 and RFC 1122, sections 4.1.1, 4.1.3.1, and 4.1.3.5, and 4.1.3.6.
c) checksum as specified in RFC 768, page 2 and RFC 1122, sections 4.1.1 and 4.1.3.4.

5.2.2.2 Detailed Requirements

5.2.2.2.1 Interface Requirements

5.2.2.2.1.1 ICMP Messages from IP

A conforming implementation shall act upon all ICMP messages as stated in RFC 1122, section 4.1.3.3.

5.2.2.2.1.2 UDP/ALP Interface

A conforming implementation shall provide UDP Application Services as described in RFC 1122, section 4.1.4.

5.2.2.2.1.3 IP Options

A conforming implementation shall pass IP options as described in RFC 1122, section 4.1.3.2.

Source: https://assist.dla.mil -- Downloaded: 2026l0-26T07:56Z
Check the source to verify that this is the currentversion before use.

5.2.2.2.2 Data Transfer Requirements

5.2.2.2.2.1 Checksum

A conforming implementation shall allow for a checksum as described in RFC 1122, section 4.1.3.4.

5.2.2.2.2.2 UDP Multihoming

A conforming implementation shall provide for UDP Multihoming as described in RFC 1122, section 4.1.3.5.

5.3 Network Layer Requirements

A conforming implementation of this profile shall use IAB STD 5, specifically the Internet Protocol (IP) and the Internet Control Message Protocol (ICMP). A conforming implementation of the IP protocol shall conform to IAB STD 3, RFC 1122 (Requirements For Internet Hosts - Communication Layers).

The DoD Internet Protocol, IP, forms the network layer of this profile. IP is specified in RFC 791, as amended by *RFC 950 (IP Subnet Extensions)*, RFC 919 (IP Broadcast Datagrams), and RFC 922 (IP Broadcast Datagrams with subnets). It also includes ICMP, the Internet Control Message Protocol, specified by RFC 792, which provides a mechanism for communicating control and error information between hosts or between hosts and gateways. Although ICMP is an integral part of IP, it uses the support of IP as if it (ICMP) were a higher layer protocol.

5.3.1 Internet Protocol

5.3.1.1 Major Capabilities

A conforming implementation shall support the following capabilities:

(a) data transfer as specified in RFC 791, sections 1.1 and 2.3.
(b) addressing as specified in RFC 791, sections 2.3, 3.1, and 3.2 and RFC 1122, section 3.2.1.3.
(c) *fragmentation/reassembly as specified in* RFC 791, section 2.3 and 3.2 and RFC 1122, section 3.2.1.4.
(d) checksum as specified in RFC 791, section 1.4 and 3.2 (page 14) and RFC 1122, section 3.2.1.2.
(e) Type of Service (TOS) field as specified in RFC 791, section 1.4 and RFC 1122, section 3.2.1.6.

5.3.1.2 Datagram Format

A conforming implementation *shall support the following fields as described in* RFC 791, *section* 3.1:

(a) version number, also as specified in RFC 1122, section 3.2.1.1
(b) Internet Header Length (IHL)
(c) type of service (TOS), also as specified in RFC 1122, section 3.2.1.6
(d) total length of datagram
(e) segment identification, also as specified in RFC 1122, section 3.2.1.5
(f) control flags
(g) fragment offset, also as specified in RFC 791, section 3.2 and RFC 1122, sections 3.2.1.4 and 3.2.1.5
(h) time-to-live (TTL), also as specified in RFC 1122, section 3.2.1.7

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:56Z
Check the source to verify that this is the current version before use.

(i) protocol
(j) header checksum, also as specified in RFC 1122, section 3.2.1.2
(k) source address, also as specified in RFC 1122, section 3.2.1.3
(l) destination address, also as specified in RFC 1122, section 3.2.1.3
(m) IP options, also as specified in RFC 1122, section 3.2.1.8
(n) padding
(o) data

5.3.1.3 Detailed Requirements

5.3.1.3.1 Interface Requirements

5.3.1.3.1.1 Internet/Transport Layer Interface

The procedure calls described in RFC 791, section 3.3 and RFC 1122, section 3.4 shall constitute the Internet/Transport Interface.

5.3.1.3.2 Data Transfer

5.3.1.3.2.1 Address Handling

5.3.1.3.2.1.1 Routing Outbound Datagrams

A conforming implementation providing gateway functionality shall support the functions described in RFC 1122, section 3.3.1.

5.3.1.3.2.1.2 Local Mutlihoming

A conforming implementation shall provide for the requirements as described in RFC 1122, section 3.3.4.

5.3.1.3.2.1.3 Source Route Forwarding

A conforming implementation shall provide for the requirements as described in RFC 1122, section 3.3.5.

5.3.1.3.2.1.4 Broadcasts

A conforming implementation shall provide for the requirements as described in RFC 1122, section 3.3.6.

5.3.1.3.2.1.5 Multicasting

A conforming implementation shall provide for the requirements as described in RFC 1122, sections 3.2.3 and 3.3.7.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:56Z
Check the source to verify that this is the current version before use.

5.3.1.3.2.2 Fragmentation and Reassembly

A conforming implementation shall provide for the requirements as described in RFC 793, section 3.1 and RFC 1122, sections 3.2.1.4, 3.2.1.5, 3.3.2 and 3.3.3.

5.3.1.3.2.3 Type Of Service (TOS)

A conforming implementation shall provide the Type of Service (TOS) field as specified in RFC 791, section 1.4 and RFC 1122, section 3.2.1.6.

5.3.1.3.2.4 Time-To-Live (TTL)

A conforming implementation shall provide the TTL field as specified in RFC 791, section 3.1 and RFC 1122, section 3.2.1.6.

5.3.1.3.3 Options

All the options specified in RFC 791, section 3.1 and RFC 1122, section 3.2.1.8 shall be mandatory to implement but optional to use.

5.3.2 Internet Control Message Protocol (ICMP)

5.3.2.1 Major Capabilities

A conforming implementation shall support the following capabilities as described in RFC 792, page 1.

(a) error reporting
(b) control messages

5.3.2.2 ICMP Message Format

ICMP messages are sent using the basic IP header. The first octet of the data portion of the datagram is an ICMP type field; the value of this field determines the format of the remaining data. Any field labeled "unused" is reserved for later extensions and shall be zero when sent, but receivers shall not use these fields (except to include them in the checksum). Each ICMP message also contains a code field. ICMP uses the following IP header fields, as described in RFC 791, pages 2-3:

(a) version
(b) IHL
(c) type of service (TOS)
(d) total length
(e) identification
(f) flags
(g) fragment offset
(h) time To Live (TTL)
(i) protocol identification
(j) checksum
(k) source address
(l) destination address

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:56Z
Check the source to verify that this is the current version before use.

5.3.2.2.1 ICMP Messages

The following messages shall be implemented but are optional to use:

(a) destination unreachable
(b) time exceeding
(c) parameter problem
(d) source quench
(e) redirect
(f) echo
(g) echo reply
(h) timestamp
(i) timestamp Reply
(j) address mask request
(k) address mask reply

5.3.2.3 Detailed Requirements

5.3.2.3.1 Error Reporting

A conforming implementation shall use the error messages described in RFC 792 and RFC 1122, section 3.2.2.1 through 3.2.2.5.

5.3.2.3.1.1 ICMP Error Messages Not Sent

A conforming host shall not be capable of sending ICMP error messages as a result of receiving the messages described in RFC 1122, section 3.2.2.

5.3.2.3.2 Query Messaging

Query messages shall be used in accordance with RFC 792 and RFC 1122, section 3.2.2.6 through 3.2.2.9.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:56Z
Check the source to verify that this is the current version before use.

ANNEX A (normative)

DSPICS REQUIREMENTS LIST (DPRL)

A.1 Introduction

This document provides the DoD Standardized Profile Implementation Conformance Statements (DSPICS) Requirements List (DPRL) for implementations of the DoD Standardized Profile (DSP) 2045-14502. The DSPICS for an implementation is generated by completing the DPRL in accordance with the following instructions.

An implementation shall satisfy the mandatory conformance requirements of the base standards referenced in this profile.

An implementation's completed DPRL is called the DSPICS. The DSPICS states which capabilities and options of the protocol have been implemented. The following can use the DSPICS:

(a) The protocol implementor, as a checklist to reduce the risk of failure to conform to the standard through oversight.

(b) The supplier and acquirer or potential acquirer of the implementation, as a detailed indication of the capabilities of the implementation, stated relative to the common basis for understanding provided by the standard DSPICS proforma.

(c) The user or potential user of the implementation, as a basis for initially checking the possibility of inter-working with another implementation (note that, while inter-working can never be guaranteed, failure to internetwork can often be predicted from incompatible DSPICSs).

(d) A protocol tester, as the basis for selecting appropriate tests against which to assess the claim for conformance of the implementation.

A.1.1 Notation

The following notations and symbols from MIL-HDBK 829, which references ISO/IEC TR 10000-1 and -2, are used in the DPRL to indicate the status of features:

Status Symbols

m	- mandatory.
m.<n>	- support of every item of the group labeled by the same numeral <n> required, but only one is active at a time.
o	- optional.
o.<n>	- optional, but support of at least one of the group of options labeled by the same numeral <n> is required.
c	- conditional.
-	- non-applicable (i.e. logically impossible in the scope of the profile).
x	- excluded or prohibited.
i	- out of scope of profile (left as an implementation choice).

In addition, the symbol "•" is used to indicate an option whose status is not constrained by the profile (status in the base standard). The o.<n> notation is used to show a set of selectable options (i.e., one or more of the set must be

Source: https://assist.dla.mil -- Downloaded: 2026l0-26T07:56Z
Check the source to verify that this is the currentversion before use.

implemented) with the same identifier <n>.

Two character combinations may be used for dynamic conformance requirements. In this case, the first character refers to the static (implementation) status, and the second refers to the dynamic (use); thus "mo" means "*mandatory to be implemented, optional to be used.*"

Notations for Conditional Status

The following predicate notations are used:

<predicate>:: This notation introduces a group of items, all of which are conditional on <predicate>.

<predicate>: This notation introduces a single item which is conditional on <predicate>.

In each case, the predicate may identify a profile feature, or a boolean combination of predicates. ("^" is the symbol for logical negation.)

<index>: This predicate symbol means that the status following it applies only when the DPICS states that the features identified by the index are supported. In the simplest case, <index> is the identifying tag of a single DPICS items. The symbol <index> also may be a Boolean expression composed of several indices.

<index>:: When this group predicate is true, the associated clause should be completed.

Notations used in the Protocol Feature Column

<r> Symbol used to denote the receiving system.
<t> Symbol used to denote the transmitting system.

Support Column Symbols

The support of every item as claimed by the implementor is stated by circling the appropriate answer (Yes, No, or N/A) in the support column:

Yes Supported by the implementation.
No Not supported by the implementation.
N/A Not applicable.

Base standard requirements are shown using the equivalent notations in upper case (e.g., M, O, X).

A.1.2 Footnotes

Footnotes to the proforma are indicated by superscript numerals. The footnote appears on the page of the first occurrence of the numeral. Subsequent occurrences of a numeral refer to the footnote of the first occurrence.

A.1.3 Instructions for Completing the DPRL

A DSP implementor shows the extent of compliance to a DSP by completing the DPRL; that is, compliance to all mandatory requirements and the options that are not supported are shown. The resulting completed DPRL is called a DSPICS. Where this profile refines the features of the base standards, the requirements expressed in this DPRL shall be applied (as indicated in DPRL items with no "Profile Support" column) to constrain the allowable responses in the base standard DPICS proforma. When this profile makes additional requirements, the "Profile

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:56Z
Check the source to verify that this is the current version before use.

Support" column for such DPRLs shall be completed. In this column, each response shall be selected either from the indicated set of responses, or it shall comprise one or more parameter values as requested. If a conditional requirement is inapplicable, use the Not Applicable (NA) choice. If a mandatory requirement is not satisfied, exception information must be supplied by entering a reference Xi, where i is a unique identifier, to an accompanying rationale for the noncompliance. When the profile requirement is expressed as a two-character combination (as defined in A.1.1 above), the response shall address each element of the requirement; e.g., for the requirement "mo," the possible compliant responses are "yy" or "yn."

A.2 Standards Referenced

This profile specifies the provision of TCP service in an End System from which a standardized IP network service operating over point-to-point circuits is available (or can be made available). It uses the following standards:

IAB STD 3 *(RFC 1122: 1989, Requirements For Internet Hosts - Communication Layers, RFC 1123: 1989, Requirements For Internet Hosts - Application and Support)*

IAB STD 5 *(RFC 791: 1981, Internet Protocol, RFC 950: 1985, Internet standard subnetting procedure, RFC 919: 1984, Broadcasting Internet datagrams, RFC 922: 1984, Broadcasting Internet datagrams in the presence of subnets, RFC 792: 1981, Internet Control Message Protocol, RFC 1112: 1989, Host extensions for IP multicasting)*

IAB STD 6 *(RFC 768: 1980, User Datagram Protocol)*

IAB STD 7 *(RFC 793: 1981, Transmission Control Protocol)*

A.3 DSPICS Requirements List

A.3.1 General Information

A.3.1.1 Identification of PICS

Ref	Question	Response
1	Date of Statement (DD/MM/YY)	
2	PICS serial number	
3	System Conformance statement cross-reference	

A.3.1.2 Identification of IUT

Ref	Question	Response
1	Implementation name	
2	Implementation version	
3	Machine name	

Source: https://assist.dla.mil -- Downloaded: 2026l0-26T07:56Z
Check the source to verify that this is the current version before use.

Ref	Question	Response
4	Machine version	
5	Operating System name	
6	Operating System version	
7	Special Configuration	
8	Other Information	

A.3.1.3 Global Statement of Conformance

Ref	Question	Response
1	Are all mandatory IAB STD requirements met for:	
2	IAB STD 3, RFC 1122?	
3	IAB STD 6 (UDP)	
4	IAB STD 7 (TCP)	
5	IAB STD 5 (IP,ICMP)	

A.4 Basic Requirements

The following table lists the detailed requirements for an TCP/IP implementation.

Index	Protocol	Clause of Profile	Profile Status	Support
tcp	IAB STD 7 and IAB STD 3, RFC 1122, section 4.2, TCP, implemented?	5.2	o.1	Yes No
udp	IAB STD 6 and IAB STD 3, RFC1122, section 4.1, UDP, implemented?	5.2	o.1	Yes No
ip	IAB STD 5 and IAB STD 3, RFC 1122, section 3, IP, implemented?	5.3	m	Yes
icmp	IAB STD 5 and IAB STD 3, RFC 1122, section 3, ICMP, implemented?	5.3	m	Yes
inhost	IAB STD 3, Internet Hosts, implemented	5.2	m	Yes

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:56Z
Check the source to verify that this is the current version before use.

A.4.1 PICS Proforma for Transmission Control Protocol (TCP)

A.4.1.1 Identification

Supplier	
Contact Point for Queries	
Implementation name(s) and Versions	
Other Information Necessary for full identification - eg, name(s) and version(s) for machines and/or operating systems; System Name(s)	

A.4.1.2 Protocol Summary

Protocol Version	
Addenda Implemented	
Amendments Implemented	
Date of Statement	

A.4.1.3 General/Major Capabilities

Item	Protocol Feature	Base Standard		Profile		Support
		Reference	Status	Clause	Status	
dt	Data Transfer	RFC 793:1.5, 2.8,3.7	M	5.2.1.1	m	Yes
pa	Port Addressing	RFC 793: 2.7 RFC 1122: 4.2.2.1	M		m	Yes
frg	Fragmentation	RFC 793: 1.5,2.7,3.3 RFC 1122: 4.2.2.6	M		m	Yes
ras	Reassembly		M		m	Yes
pa	Piggyback Acknowledgement	RFC 793: 1.5,2.8,3.7 RFC 1122: 4.2.3.2	M		m	Yes
flc	Flow Control	RFC 793: 1.5,2.8,3.7 RFC 1122: 4.2.3.3	M		m	Yes
chks	Checksum	RFC 793: 1.5,3.1 RFC 1122: 4.2.2.7	M	5.2.1.1	m	Yes

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:56Z
Check the source to verify that this is the current version before use.

A.4.1.4 Interfaces

Item	Protocol Feature	Base Standard		Profile		Support
		Reference	Status	Clause	Status	
ICMP	Internet Control Message Protocol	RFC 1122, 4.2.3.9.	M	5.2.1.3.1	m	Yes
ALP	TCP/Application Layer Protocol	RFC 1122, 4.2.4.	M		m	Yes
IP	Internet Protocol Options	RFC 1122, 4.2.3.10, 4.2.3.8.	M		m	Yes
AV	Address Validation		M		m	Yes

A.4.1.5 Frame Structure

Item	*Protocol Feature*	Base Standard		Profile		*Support*
		Reference	Status	Clause	Status	
hdr	*Header Format*	RFC 793: 3.1	M		m	Yes
sp	Source Port	RFC 793: 3.1	M		m	Yes
dp	Destination Port	RFC 793: 3.1	M		m	Yes
sn	*Sequence Number*	RFC 793: 3.1	M		m	Yes
an	Acknowledgment Number	RFC 793: 3.1	ack:M		ack:m	Yes N/A
dof	Data Offset	RFC 793: 3.1	M		m	Yes
res	Reserved (must be zero)	RFC 793: 3.1	M		m	Yes
Control Field						
urg	Urgent Pointer field significant	RFC 793: 3.1	M		m	Yes
ack	Acknowledgment field significant	RFC 793: 3.1	M		m	Yes
psh	Push function	RFC 793: 3.1	M		m	Yes
rst	Reset the connection	RFC 793: 3.1	M		m	Yes
syn	Synchronize sequence numbers	RFC 793: 3.1	M		m	Yes
fin	No more data from sender	RFC 793: 3.1	M		m	Yes
win	Window	RFC 793: 3.1	M		m	Yes
cks	Checksum	RFC 793: 3.1	M		m	Yes
up	Urgent Pointer	RFC 793: 3.1	M		m	Yes
opt	Options	RFC 793: 3.1	M		m	Yes
eol	End of Option List	RFC 793: 3.1	M		mo	Yes N/A

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:56Z
Check the source to verify that this is the current version before use.

Item	Protocol Feature	Base Standard		Profile		Support
		Reference	Status	Clause	Status	
nop	No-Operation	RFC 793: 3.1	M		mo	Yes N/A
mss	Maximum Segment size	RFC 793: 3.1	M		mo	Yes N/A
pad	Padding	RFC 793. 3.1	M		mo	Yes N/A

A.4.1.6 TCP Procedure

Item	Protocol Feature	Base Standard		Profile		Support
		Reference	Status	Clause	Status	
rtc	Retranmission Timeout Calculation	RFC 793, 1.5,d 3.7, RFC 1122, 4.2.3.1 , 4.2.2.15	M			
mux	Multiplexing	RFC 793, 1.5, 2.7, 3.8 RFC 1122, 4.2.2.1, 4.2.2.18	M			
isnsel	/Use clock-driven ISN selection	RFC 793: 3.3 RFC 1122: 4.2.2.9	M		m	Yes
op1	Support simultaneous open attempts	RFC 793: 3.4 RFC 1122: 4.2.2.10	M		m	Yes
op2	SYN-RCVD remembers last state	RFC 793: 3.4 RFC 1122: 4.2.2.11	M		m	Yes
op3	Passive open call interfere with others	RFC 793: 3.8 RFC 1122: 2.2.2.18	x		x	No
op4	Function: simultaneous LISTENs for same port	RFC 1122: 4.2.2.18	M		m	Yes
op5	Ask IP for source address for SYN if necc.	RFC 1122: 4.2.2.7	M		m	Yes
op5a	Otherwise, use local address of connection	RFC 1122: 4.2.2.7	M		m	Yes
op6	OPEN to broadcast/multicast IP Address	RFC 1122: 4.2.3.10	X		x	No
op7	Silently discard segment to broadcast/multicast address	RFC 1122: 4.2.3.10	M		m	Yes
	Closing Connections:					
cl1	RST can contain data	RFC 1122: 4.2.2.12	O	5.2.1.3.2.7	m	Yes

Source: https://assist.dla.mil -- Downloaded: 2026l0-26T07:56Z
Check the source to verify that this is the currentversion before use.

Item	Protocol Feature	Base Standard		Profile		Support
		Reference	Status	Clause	Status	
cl2	Inform application of aborted connection	RFC 1122: 4.2.2.13	M		m	Yes
cl3	Half-duplex close connections	RFC 1122: 4.2.2.13	O		o	Yes No
cl31	Send RST to indicate data lost	RFC 1122: 4.2.2.13	O		m	Yes
cl4	In TIME-WAIT state for 2xMSL seconds	RFC 1122: 4.2.2.13	M		m	Yes
cl41	Accept SYN from TIME-WAIT state	RFC 1122: 4.2.2.13	O		o	Yes No
	Retransmissions:					
rt1	Jacobsen slow start algorithm	RFC 1122: 4.2.2.15	M	5.2.1.3.2.8	m	Yes
rt2	Jacobson congestion avoidence algorithm	RFC 1122: 4.2.2.15	M	5.2.1.3.2.8	m	Yes
rt3	Retransmit with same IP ident	RFC 1122: 4.2.2.15	O		o	Yes No
rt4	Karn's algorithm	RFC 1122: 4.2.3.1	M		m	Yes
rt5	Jacobson's RTO estimation algorithm	RFC 1122: 4.2.3.1	M		m	Yes
rt6	*Exponential Backoff*	RFC 1122: 4.2.3.1	M		m	Yes
rt7	SYN RTO calculation same as data	RFC 1122: 4.2.3.1	O		m	Yes
rt8	Recommended initial values and bounds	RFC 1122: 4.2.3.1	O		m	Yes
	Generating ACK's:					
ga1	Queue out of order segment	RFC 1122: 4.2.2.20	O	5.2.1.3.2.9	m	Yes
ga2	Process all queued before send ACK	RFC 1122: 4.2.2.20	M		m	Yes
ga3	Send ACK for out of order segment	RFC 1122: 4.2.2.21	O		o	Yes No
ga4	Delayed ACK's	RFC 1122: 4.2.3.2	O		m	Yes
ga41	Delay < 0.5 seconds	RFC 1122: 4.2.3.2	ga4:M		m	Yes
ga42	Every 2nd full sized segment ACK'd	RFC 1122: 4.2.3.2	ga4:M		m	Yes
ga5	Receiver SWS-Avoidance Algorithm	RFC 1122: 4.2.3.3	M		m	Yes
	Sending Data:					

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:56Z
Check the source to verify that this is the current version before use.

Item	Protocol Feature	Base Standard		Profile		Support
		Reference	Status	Clause	Status	
sd1	Configurable TTL	RFC 1122: 4.2.2.19	M	5.2.1.3.2.10	m	Yes
sd2	Sender SWS-avoidance algorithm	RFC 1122: 4.2.3.4	M		m	Yes
sd3	Nagle algorithm	RFC 1122: 4.2.3.4	O		m	Yes
sd31	Application can disable Nagle algorithm	RFC 1122: 4.2.3.4	sd3:M	5.2.1.3.2.10	m	Yes
	Connection Failures:					
cf1	Negative to IP on R1 retransmissions	RFC 1122: 4.2.3.5	M	5.2.1.3.2.11	m	Yes
cf2	Close connection on R2 retransmissions	RFC 1122: 4.2.3.5	M		m	Yes
cf3	ALP can set R2	RFC 1122: 4.2.3.5	M		m	Yes
cf4	Inform ALP of R1<=retransmissions<R2	RFC 1122: 4.2.3.5	O		m	Yes
cf5	Recommend values for R1, R2	RFC 1122: 4.2.3.5	O		m	Yes
cf6	Same mechanism for SYNs	RFC 1122: 4.2.3.5	M		m	Yes
cf6a	R2 at least 3 minute for SYN	RFC 1122: 4.2.3.5	M		m	Yes
	Send Keep alive packets:		O		o	Yes No
ka1	Application can request	RFC 1122: 4.2.3.6	M	5.2.1.3.2.12	m	Yes
ka2	Default is "off"	RFC 1122: 4.2.3.6	M		m	Yes
ka3	Only send if idle for interval	RFC 1122: 4.2.3.6	M		m	Yes
ka4	Interval configurable	RFC 1122: 4.2.3.6	M		m	Yes
ka5	Default at least 2 Hrs	RFC 1122: 4.2.3.6	M		m	Yes
ka6	Tolerant of lost ACK's	RFC 1122: 4.2.3.6	M		m	Yes

Source: https://assist.dla.mil -- Downloaded: 2026l0-26T07:56Z
Check the source to verify that this is the currentversion before use.

A.4.2 PICS Proforma for User Datagram Protocol (UDP)

A.4.2.1 Identification

Supplier	
Contact Point for Queries	
Implementation name(s) and Versions	
Other Information Necessary for full identification - eg, name(s) and version(s) for machines and/or operating systems; System Name(s)	

A.4.2.2 Protocol Summary

Protocol Version	
Addenda Implemented	
Amendments Implemented	
Date of Statement	

A.4.2.3 General/Major Capabilities

Item	Protocol Feature	Base Standard		Profile		Support
		Reference	Status	Clause	Status	
dt	Data Transfer	RFC 768, RFC 1122: 4.1.1	M	5.2.2.1	m	Yes
pa	Port Addressing	RFC 768, RFC 1122: 4.1.1, 4.1.3.1, 4.1.3.5, 4.1.3.6	M		m	Yes
uchks	Checksum	RFC 768 RFC 1122: 4.1.1, 4.1.3.4	M		m	Yes

A.4.2.4 Interfaces

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:56Z
Check the source to verify that this is the current version before use.

Item	Protocol Feature	Base Standard		Profile		Support
		Reference	Status	Clause	Status	
uuc	User/UDP Interface	RFC 768	M		m	Yes
urp	Creation of new receive ports	RFC 768	M		m	Yes
usend	Send	RFC 768	M		m	Yes
urecc	Receive	RFC 768	M		m	Yes
ulli	UDP/Lower Level Interface	RFC 768	M		m	Yes
ulli1	IP used for Lower Level	RFC 768	M		m	Yes
ulli2	Source Internet Address	RFC 768	M		m	Yes
ulli3	Destination Internet Address	RFC 768	M		m	Yes

A.4.2.5 Frame Structure

Item	Protocol Feature	Base Standard		Profile		Support
		Reference	Status	Clause	Status	
uhf	Header Format	RFC 768	M		m	Yes
usp	Source Port	RFC 768	M		m	Yes
udp	Destination Port	RFC 768	M		m	Yes
ucb	Length	RFC 768	M		m	Yes
ucks	Checksum	RFC 768	M		m	Yes

A.4.2.6 UDP Procedure

Item	Protocol Feature	Base Standard		Profile		Support
		Reference	Status	Clause	Status	
us	UDP Send port unreachable	RFC 1122: 4.1.3.1	O	5.2.2.1	m	Yes
IP options in UDP:						
iu1	Pass received IP options to applic layer	RFC 1122: 4.1.3.2	M	5.2.2.2.1.3	m	Yes
iu2	Applic layer can specify IP options to Send	RFC 1122: 4.1.3.2	M	5.2.2.2.1.3	m	Yes
iu3	UDP passes IP options down to IP layer	RFC 1122: 4.1.3.2	M		m	Yes

Source: https://assist.dla.mil -- Downloaded: 2026l0-26T07:56Z
Check the source to verify that this is the current version before use.

Item	Protocol Feature	Base Standard		Profile		Support
		Reference	Status	Clause	Status	
icm	Pass ICMP msgs up to applic layer	RFC 1122: 4.1.3.3	M		m	Yes
UDP checksums:						
uc1	Able to generate/check checksum	RFC 1122: 4.1.3.4	M	5.2.2.2.2.1	m	Yes
uc2	Silently discard bad checksum	RFC 1122: 4.1.3.4	M		m	Yes
uc3	Sender Option to not generate checksum	RFC 1122: 4.1.3.4	O		o	Yes No
uc31	Default is to checksum	RFC 1122: 4.1.3.4	M		m	Yes
uc4	Receiver Option to require checksum	RFC 1122: 4.1.3.4	O		o	Yes No
UDP Multihoming:						
um1	Pass specific-dest address to application	RFC 1122: 4.1.3.5	M	5.2.2.2.2.2	m	Yes
um2	Applic Layer can specify local IP addr	RFC 1122: 4.1.3.5	M		m	Yes
um3	Applic layer specify wild local IP addr	RFC 1122: 4.1.3.5	M		m	Yes
um4	Applic layer notified of local IP address used	RFC 1122: 4.1.3.5	O		m	Yes
bip	Bad IP source address silently discarded by UDP/IP	RFC 1122: 4.1.3.6	M		m	Yes
vip	Only send valid IP source address	RFC 1122: 4.1.3.6	M		m	Yes
UDP Application Interface Services:						
ua1	Full IP interface of 3.4 for application	RFC 1122: 4.1.4	M	5.2.2.2.1.2	m	Yes
ua11	Able to specify TTL, TOS, IP options when sending	RFC 1122: 4.1.4	M		m	Yes
ua12	Pass received TOS up to applic layer	RFC 1122: 4.1.4	O		o	Yes No

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:56Z
Check the source to verify that this is the current version before use.

A.4.3 PICS Proforma for Internet Protocol (IP)

A.4.3.1 Identification

Supplier	
Contact Point for Queries	
Implementation name(s) and Versions	
Other Information Necessary for full identification - eg, name(s) and version(s) for machines and/or operating systems; System Name(s)	

A.4.3.2 Protocol Summary

Protocol Version	
Addenda Implemented	
Amendments Implemented	
Date of Statement	

A.4.3.3 General/Major Capabilities

Item	*Protocol Feature*	Base Standard		Profile		Support
		Reference	Status	Clause	Status	
dt	Data Transfer	RFC 791: 1.1, 2.3	M	5.3.1.1	m	Yes
add	Addressing	RFC 791: 3.1, RFC 1122: 3.2.1.3	M		m	Yes
ada	Class A addresses supported	RFC 791: 3.2 RFC 1122: 3.2.1.3	M	5.3.1.1	m	Yes
adb	Class B addresses supported	RFC 791: 3.2 RFC 1122: 3.2.1.3	M	5.3.1.1	m	Yes
adc	Class C addresses supported	RFC 791: 3.2 RFC 1122: 3.2.1.3	M		m	Yes

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:56Z
Check the source to verify that this is the current version before use.

Item	Protocol Feature	Base Standard		Profile		Support
		Reference	Status	Clause	Status	
frg	Fragmentation	RFC 791: 3.2, RFC 1122: 3.2.1.4	M		m	Yes
frg1	Forward datagrams of 68 octets without fragmentation	RFC 791: 3.2 RFC 1122: 3.2.1.4	M	5.3.1.1	m	Yes
frg2	Receive datagrams of 576 octets either in one piece or in fragments	RFC 791: 3.2 RFC 1122: 3.2.1.4	M		m	Yes
frg3	Don't Fragment Supported	RFC 791: 3.2 RFC 1122: 3.2.1.4	M		m	Yes
tos	Type Of Service	RFC 791: 3.2 RFC 1122: 3.2.1.6	M	5.3.1.1	m	Yes
tpre	Precedence	RFC 791: 3.2 RFC 1122: 3.2.1.6	M		m	Yes
tdel	Delay	RFC 791: 3.2 RFC 1122: 3.2.1.6	M		m	Yes
tthr	Throughput	RFC 791: 3.2 RFC 1122: 3.2.1.6	M		m	Yes
trel	Reliability	RFC 791: 3.2 RFC 1122: 3.2.1.6	M		m	Yes
ttl	Time To Live	RFC 791: 3.2	M		m	Yes
opt	Options	RFC 791: 3.2	M	5.3.1.1	m	Yes
chk	Checksum	RFC 791: 3.2 RFC 1122: 3.2.1.2	M		m	Yes

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:56Z
Check the source to verify that this is the current version before use.

A.4.3.4 Interfaces

Item	Protocol Feature	Base Standard		Profile		Support
		Reference	Status	Clause	Status	
lni	Local Network Interface	RFC 791: 3.3, RFC 1122: 3.4	M	5.3.1.3.1.1	m	Yes
uli	Upper Level Interface	RFC 791: 3.3, RFC 1122: 3.4	M		m	Yes

A.4.3.5 Frame Structure

Item	Protocol Feature	Base Standard		Profile		Support
		Reference	Status	Clause	Status	
hdr	Header Format	RFC 791: 3.1	M	5.3.1.2	m	Yes
vs	version	RFC 791: 3.1 RFC 1122: 3.2.1.1	M		m	Yes
ihl	IHL	RFC 791: 3.1	M		m	Yes
htos	Type of Service (TOS)	RFC 791: 3.1 RFC 1122: 3.2.1.6	M		m	Yes
prec	Precedence	RFC 791: 3.1 RFC 1122: 3.2.1.6	M		m	Yes
idel	Low Delay (bit 3)	RFC 791: 3.1 RFC 1122: 3.2.1.6	M		m	Yes
hthr	High Throughput (bit 4)	RFC 791: 3.1 RFC 1122: 3.2.1.6	M		m	Yes
hrel	High Reliability (bit 5)	RFC 791: 3.1 RFC 1122: 3.2.1.6	M		m	Yes
hx1	TOS bit 6	RFC 791: 3.1 RFC 1122: 3.2.1.6	M		m	Yes
hx2	TOS bit 7	RFC 791: 3.1 RFC 1122: 3.2.1.6	M		m	Yes
totl	Total Length	RFC 791: 3.1	M		m	Yes

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:56Z
Check the source to verify that this is the current version before use.

Item	Protocol Feature	Base Standard		Profile		Support
		Reference	Status	Clause	Status	
totl2	host prepares to accept up to 576 octets	RFC 791: 3.1	O	5.3.1.2	o	Yes No
totl3	hosts send datagrams larger then 576 octets	RFC 791: 3.1	O		o	Yes No
id	Identification	RFC 791: 3.1 RFC 1122: 3.2.1.5	M		m	Yes
flg	Flags	RFC 791: 3.1	M		m	Yes
flg2	Don't Fragment (bit 1)	RFC 791: 3.1	M		m	Yes
flg3	More Fragments (bit 2)	RFC 791: 3.1	M		m	Yes
frgo	Fragmentation Offset	RFC 791: 3.1, 3.2 RFC 1122: 3.2.1.4, 3.2.1.5	M		m	Yes
frgo2	Measured in 8 octets	RFC 791: 3.1, 3.2 RFC 1122: 3.2.1.4, 3.2.1.5	M		m	Yes
frgo3	First Fragment offset zero	RFC 791: 3.1, 3.2 RFC 1122: 3.2.1.4, 3.2.1.5	M		m	Yes
httl	Time to Live	RFC 791: 3.1 RFC 1122: 3.2.1.7	M		m	Yes
httl2	Measured in units of seconds	RFC 791: 3.1 RFC 1122: 3.2.1.7	M		m	Yes
prot	Protocol	RFC 791: 3.1	M		m	Yes
hchk	Header Checksum	RFC 791: 3.1 RFC 1122: 3.2.1.2	M		m	Yes
hchk2	On Header only	RFC 791: 3.1 RFC 1122: 3.2.1.2	M		m	Yes
hchk3	Checksum is 16 bit ones complement of the one's complement sum of all 16 bit words in the header	RFC 791: 3.1 RFC 1122: 3.2.1.2	M		m	Yes
sadd	Source Address	RFC 791: 3.1 RFC 1122: 3.2.1.3	M	5.3.1.2	m	Yes
dadd	Destination Address	RFC 791: 3.1 RFC 1122: 3.2.1.3	M		m	Yes

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:56Z
Check the source to verify that this is the current version before use.

Item	Protocol Feature	Base Standard		Profile		Support
		Reference	*Status*	*Clause*	*Status*	
hopt	Options	RFC 791: 3.1 RFC 1122: 3.2.1.8	MO		mo	Yes
hopt1	variable bit length	RFC 791: 3.1 RFC 1122: 3.2.1.8	MO		mo	Yes
opttr	Options Transmitted in datagrams	RFC 791: 3.1 RFC 1122: 3.2.1.8	MO		mo	Yes
sop	Single option supported	RFC 791: 3.1 RFC 1122: 3.2.1.8	M		mo	Yes
mulop	Multiple option octet supported	RFC 791: 3.1 RFC 1122: 3.2.1.8	M		mo	Yes
otyp	Option-type supported	RFC 791: 3.1 RFC 1122: 3.2.1.8	M		mulop:m	Yes
otyp1	1 bit copied flag	RFC 791: 3.1 RFC 1122: 3.2.1.8	M		otyp:m	Yes
otyp2	2 bits option class	RFC 791: 3.1 RFC 1122: 3.2.1.8	M		otyp:m	Yes
otyp3	5 bits option number	RFC 791: 3.1 RFC 1122: 3.2.1.8	M		otyp:m	Yes
eoo	End of Options List	RFC 791: 3.1 RFC 1122: 3.2.1.8	M		mo	Yes
eoo1	Used at end of option list	RFC 791: 3.1 RFC 1122: 3.2.1.8	M		eoo:m	Yes N/A
noop	No operation	RFC 791: 3.1 RFC 1122: 3.2.1.8	M		mo	Yes
noop1	Used to align options on 32 bit boundary	RFC 791: 3.1 RFC 1122: 3.2.1.8	M		noop:m	Yes N/A
sec	Security	RFC 1122: 3.2.1.8 RFC 1108	O	5.3.1.2	mo	Yes
sec2	Must be copied upon fragmentation	RFC 1122: 3.2.1.8	M		sec:m	Yes
sec3	Compartments	RFC 1122: 3.2.1.8	M		sec:m	Yes

Source: https://assist.dla.mil -- Downloaded: 2026l0-26T07:56Z
Check the source to verify that this is the currentversion before use.

Item	Protocol Feature	Base Standard		Profile		Support
		Reference	Status	Clause	Status	
sec5	Handling Restrictions	RFC 1122: 3.2.1.8	M		sec:m	Yes
sec7	Transmission Control Code	RFC 1122: 3.2.1.8	M		sec:m	Yes
lsrr	Loose Source and Record Route	RFC 791: 3.1 RFC 1122: 3.2.1.8	M		mo	Yes
lsrr1	Copied upon fragmentation	RFC 791: 3.1 RFC 1122: 3.2.1.8	M		lsrr:m	Yes
lsrr2	Appears at most once in datagram	RFC 791: 3.1 RFC 1122: 3.2.1.8	M		lsrr:m	Yes
lsrrol	Option Length	RFC 791: 3.1 RFC 1122: 3.2.1.8	M		lsrr:m	Yes
lsrrptr1	Pointer	RFC 791: 3.1 RFC 1122: 3.2.1.8	M		lsrr:m	Yes
lsrrptr2	Smallest value is 4	RFC 791: 3.1 RFC 1122: 3.2.1.8	M		lsrr:m	Yes
ssrr	Strict Source and Record Route	RFC 791: 3.1 RFC 1122: 3.2.1.8	M		mo	Yes
ssrr1	Copied upon fragmentation	RFC 791: 3.1 RFC 1122: 3.2.1.8	M		ssrr:m	Yes
ssrr2	Appears at most once in datagram	RFC 791: 3.1 RFC 1122: 3.2.1.8	M		ssrr:m	Yes
ssrrol	Option length	RFC 791: 3.1 RFC 1122: 3.2.1.8	M		ssrr:m	Yes
ssrrptr1	Pointer	RFC 791: 3.1 RFC 1122: 3.2.1.8	M		ssrr:m	Yes
ssrrptr2	Smallest value is 4	RFC 791: 3.1 RFC 1122: 3.2.1.8	M	5.3.1.2	ssrr:m	Yes
rr	Record Route	RFC 791: 3.1 RFC 1122: 3.2.1.8	O		mo	Yes
rr1	Datagram forwarded when route data area is full	RFC 791: 3.1 RFC 1122: 3.2.1.8	M		rr:m	Yes
rr2	Not copied upon fragmentation	RFC 791: 3.1 RFC 1122: 3.2.1.8	M		rr:m	Yes N/A

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:56Z
Check the source to verify that this is the current version before use.

Item	Protocol Feature	Base Standard		Profile		Support
		Reference	Status	Clause	Status	
rr3	Placed in first fragment only	RFC 791: 3.1 RFC 1122: 3.2.1.8	M		rr:m	Yes
rr4	Appears at most once in a datagram	RFC 791: 3.1 RFC 1122: 3.2.1.8	M		rr:m	Yes
rrol	Option Length	RFC 791: 3.1 RFC 1122: 3.2.1.8	M		rr:m	Yes
rrptr	Pointer	RFC 791: 3.1 RFC 1122: 3.2.1.8	M		rr:m	Yes
rrptr1	Smallest Value is 4	RFC 791: 3.1 RFC 1122: 3.2.1.8	M		rr:m	Yes
si	Stream Identifier	RFC 791: 3.1 RFC 1122: 3.2.1.8	X		x	No
sirx	Ignore stream ID when received	RFC 791: 3.1 RFC 1122: 3.2.1.8	M		m	Yes
itme	Internet Timestamp	RFC 791: 3.1 RFC 1122: 3.2.1.8	O		mo	Yes N/A
itol	Option Length	RFC 791: 3.1 RFC 1122: 3.2.1.8	M		itme:m	Yes N/A
itol1	Max length 40 bits	RFC 791: 3.1 RFC 1122: 3.2.1.8	M		itme:m	Yes N/A
itol2	Measured in number of octets	RFC 791: 3.1 RFC 1122: 3.2.1.8	M	5.3.1.2	itme:m	Yes N/A
itptr	Pointer	RFC 791: 3.1 RFC 1122: 3.2.1.8	M		itme:m	Yes N/A
itptr1	Smallest value is 5	RFC 791: 3.1 RFC 1122: 3.2.1.8	M		itme:m	Yes N/A
itptr2	Measured in number of octets from the beginning of this option	RFC 791: 3.1 RFC 1122: 3.2.1.8	M		itme:m	Yes N/A
itovr	Overflow	RFC 791: 3.1 RFC 1122: 3.2.1.8	M		itme:m	Yes N/A
itflg	Flag	RFC 791: 3.1 RFC 1122: 3.2.1.8	M		itme:m	Yes N/A

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:56Z
Check the source to verify that this is the current version before use.

Item	Protocol Feature	Base Standard		Profile		Support
		Reference	Status	Clause	Status	
itts	Timestamp	RFC 791: 3.1 RFC 1122: 3.2.1.8	M		itme:m	Yes N/A
itts1	Right justified	RFC 791: 3.1 RFC 1122: 3.2.1.8	M		itme:m	Yes N/A
itrj3	Measured in milliseconds past midnight UT	RFC 791: 3.1 RFC 1122: 3.2.1.8	M		itme: o.3	Yes No N/A
itrj4	Other value used to measure time with first bit set to 1	RFC 791: 3.1 RFC 1122: 3.2.1.8	M		itme: o.3	Yes No N/A
itrj5	Datagram forwarded without timestamp if timestamp area is full	RFC 791: 3.1 RFC 1122: 3.2.1.8	M		itme:m	Yes N/A
padd	Padding	RFC 791: 3.1	M		m	Yes
padd1	Pad with zero to end on 32 bit boundary	RFC 791: 3.1	M	5.3.1.2	m	Yes

A.4.3.6 *Procedure*

Item	Protocol Feature	Base Standard		Profile		Support
		Reference	Status	Clause	Status	
iil	Implement IP and ICMP	RFC 1122: 3.1	M	5.3.1.3.1.1	m	Yes
rm	Handle remote multihoming in application layer	RFC 1122: 3.1	M		m	Yes
lm	Support local multihoming	RFC 1122: 3.1	O		o	Yes No
gs	Meet gateway specs if forward datagrams	RFC 1122: 3.1	M		m	Yes
cs	Configuration switch for embedded gateway	RFC 1122: 3.1	M		m	Yes
cs1	Config. switch default to non-gateway	RFC 1122: 3.1	M		m	Yes
cs2	Auto-config based on number of interfaces	RFC 1122: 3.1	O		x	No
ldd	Able to log discarded datagrams	RFC 1122: 3.1	O		m	Yes
ldd1	Record in counter	RFC 1122: 3.1	O		m	Yes
sdv	Silently discard version not equal to 4	RFC 1122: 3.2.1.1	M		m	Yes

Source: https://assist.dla.mil -- Downloaded: 2026l0-26T07:56Z
Check the source to verify that this is the current version before use.

Item	Protocol Feature	Base Standard		Profile		Support
		Reference	Status	Clause	Status	
vchk	Verify IP checksum, silently discard bad datagram	RFC 1122: 3.2.1.2	M		m	Yes
Addressing:						
add1	Subnet addressing (RFC 950)	RFC 1122: 3.2.1.3	M	5.3.1.2	m	Yes
add2	Source address must be host's own IP address	RFC 1122: 3.2.1.3	M		m	Yes
add3	Silently discard datagram with bad destination address	RFC 1122: 3.2.1.3	M		m	Yes
add4	Silently discard datagram with bad source address	RFC 1122: 3.2.1.3	M	5.3.1.2	m	Yes
rea	Support reassembly	RFC 1122: 3.2.1.4	M	5.3.1.3.2	m	Yes
idf	Retain same ID field in identical datagram	RFC 1122: 3.2.1.5	O		o	Yes No
TOS:						
tos1	Allow transport layer to set TOS	RFC 1122: 3.2.1.6	M	5.3.1.3.2.3	m	Yes
tos2	Pass received TOS up to transport layer	RFC 1122: 3.2.1.6	O		m	Yes
tos3	Use RFC 975 link layer mappings for TOS	RFC 1122: 3.2.1.6	O		x	No
TTL:						
ttl1	Send packet with TTL of 0	RFC 1122: 3.2.1.7	X	5.3.1.3.2.4	x	No
ttl2	Discard received packets with TTL < 2	RFC 1122: 3.2.1.7	X		x	No
ttl3	Allow transport layer to set TTL	RFC 1122: 3.2.1.7	M		m	Yes
ttl4	Fixed TTL is configurable	RFC 1122: 3.2.1.7	M		m	Yes
IP Options:						
op1	Allow transport layer to send IP options	RFC 1122: 3.2.1.8	M	5.3.1.3.3	m	Yes
op2	Pass all IP options received to higher layer	RFC 1122: 3.2.1.8	M		m	Yes
op3	IP layer silently ignore unknown options	RFC 1122: 3.2.1.8	M		m	Yes
op4	Security option	RFC 1122: 3.2.1.8a	O		o	Yes No

Source: https://assist.dla.mil -- Downloaded: 202640-26T07:56Z
Check the source to verify that this is the currentversion before use.

Item	Protocol Feature	Base Standard		Profile		Support
		Reference	Status	Clause	Status	
op5	Send Stream Identifier option	RFC 1122: 3.2.1.8b	O		x	No
op6	Silently ignore Stream Identifier option	RFC 1122: 3.2.1.8b	M		m	Yes
op7	Record Route option	RFC 1122: 3.2.1.8d	O		o	Yes No
op8	Timestamp option	RFC 1122: 3.2.1.8e	O	5.3.1.3.3	o	Yes No
Source Route Option:						
sr1	Originate and terminate Source Route Options	RFC 1122: 3.2.1.8c	M	5.3.1.3.3	m	Yes
sr2	Datagram with completed SR passed up to transport layer	RFC 1122: 3.2.1.8c	M		m	Yes
sr3	Build correct (non-redundant) return route	RFC 1122: 3.2.1.8c	M		m	Yes
sr4	Send multiple SR options in one header	RFC 1122: 3.2.1.8c	X		x	No
Routing Outbound Datagrams:						
ro1	Use address mask in local/remote decision	RFC 1122: 3.3.1.1	M	5.3.1.3.2.1.1	m	Yes
ro2	Operate with no gateways on connection network	RFC 1122: 3.3.1.1	M		m	Yes
ro3	Maintain "route cache" of next-hop gateways	RFC 1122: 3.3.1.2	M		m	Yes
ro4	Treat Host and Net Redirect the same	RFC 1122: 3.3.1.2	O		m	Yes
ro5	If no cache entry, use default gateway	RFC 1122: 3.3.1.2	M		m	Yes
ro51	Support multiple default gateways	RFC 1122: 3.3.1.2	M		m	Yes
ro6	Provide table of static routes	RFC 1122: 3.3.1.2	O		o	Yes No
ro61	Flag: route overridable by Redirects	RFC 1122: 3.3.1.2	O		o	Yes No
ro7	Key route cache on host, not net address	RFC 1122: 3.3.1.3	O		o	Yes No
ro8	Include TOS in route cache	RFC 1122: 3.3.1.3	O		m	Yes
ro9	Able to detect failure in next-hop gateway	RFC 1122: 3.3.1.4	M		m	Yes

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:56Z
Check the source to verify that this is the current version before use.

Item	Protocol Feature	Base Standard		Profile		Support
		Reference	Status	Clause	Status	
ro10	Assume route is good forever	RFC 1122: 3.3.1.4	O		x	No
ro11	Ping gateways continuously	RFC 1122: 3.3.1.4	X		x	No
ro12	Ping only when traffic is being sent	RFC 1122: 3.3.1.4	M	5.3.1.3.2.1.1	m	Yes
ro13	Ping only when no positive indication	RFC 1122: 3.3.1.4	M		m	Yes
ro14	Higher and lower layers give advice	RFC 1122: 3.3.1.4	O	5.3.1.3.2.1.1	m	Yes
ro15	Switch from failed default gateway to another	RFC 1122: 3.3.1.5	M		m	Yes
ro16	Manual method of entering config info	RFC 1122: 3.3.1.6	M		m	Yes
Reassembly and fragmentation:						
rf1	Able to reassemble incoming datagrams	RFC 1122: 3.3.2	M	5.3.1.3.2.2	m	Yes
rf11	At least 576 byte datagrams	RFC 1122: 3.3.2	M		m	Yes
rf12	EMTU_R configurable or indefinite	RFC 1122: 3.3.2	O		m	Yes
rf2	Transport layer able to learn MMS_R	RFC 1122: 3.3.2	M		m	Yes
rf3	Send ICMP Time Exceeded Message on reassembly timeout	RFC 1122: 3.3.2	M		m	Yes
rf31	Fixed reassembly timeout value	RFC 1122: 3.3.2	O		m	Yes
rf4	Pass MMS_S to higher layers	RFC 1122: 3.3.3	M		m	Yes
rf5	Local fragmentation of outgoing packets	RFC 1122: 3.3.3	O		o	Yes No
rf51	Else do not send bigger then MMS_S	RFC 1122: 3.3.3	M		m	Yes
rf6	Send max 576 to off-net destination	RFC 1122: 3.3.3	O		m	Yes
rf7	All-Subnets-MTU configuration flag	RFC 1122: 3.3.3	O		o	Yes No
Multihoming:						
mh1	Reply with same address as specific destination address	RFC 1122: 3.3.4.2	O	5.3.1.3.2.1.2	m	Yes
mh2	Allow application to choose local IP address	RFC 1122: 3.3.4.2	M		m	Yes

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:56Z
Check the source to verify that this is the current version before use.

Item	Protocol Feature	Base Standard		Profile		Support
		Reference	Status	Clause	Status	
mh3	Silently discard datagram in "wrong" interface	RFC 1122: 3.3.4.2	O	5.3.1.3.2.1.2	o	Yes No
mh4	Only send datagram through "right" interface	RFC 1122: 3.3.4.2	O		o[1]	Yes No
Source Route Forwarding:						
sf1	Forward datagram with Source Route option	RFC 1122: 3.3.5	O	5.3.1.3.2.1.3	o	Yes No
sf11	Obey corresponding gateway rules	RFC 1122: 3.3.5	sf1:M		sf1:m	Yes N/A
sf111	Update TTL by gateway rules	RFC 1122: 3.3.5	sf1:M		sf1:m	Yes N/A
sf112	Able to generate ICMP error code 4,5	RFC 1122: 3.3.5	sf1:M		sf1:m	Yes N/A
sf113	IP source address not local host	RFC 1122: 3.3.5	sf1:O		sf1:o	Yes No
sf114	Update Timestamp, Record Route options	RFC 1122: 3.3.5	sf1:M		sf1:m	Yes N/A
sf12	Configurable for non-local SRing	RFC 1122: 3.3.5	sf1:M		sf1:m	Yes N/A
sf121	Defaults to OFF	RFC 1122: 3.3.5	sf1:M		sf1:m	Yes N/A
sf13	Satisfy gateway access rules for non-local SRing	RFC 1122: 3.3.5	sf1:M		sf1:m	Yes N/A
sf14	If not forward, send Destination Unreachable (cd 5)	RFC 1122: 3.3.5	sf1:O		sf1:m[2]	Yes N/A
Broadcast:						
br1	Broadcast address as IP source address	RFC 1122: 3.2.1.3	X	5.3.1.3.2.1.4	x	No
br2	Receive 0 or -1 broadcast formats OK	RFC 1122: 3.3.6	O		m	Yes
br3	Configurable option to send 0 or -1 broadcast	RFC 1122: 3.3.6	O		o	Yes No
br31	Default to -1 broadcast	RFC 1122: 3.3.6	br3:O	5.3.1.3.2.1.4	br3:m	Yes N/A

Note 1 Unless has embedded gateway functionality or is source routed

Note 2 This requirement is overruled if datagram is an ICMP error message

Source: https://assist.dla.mil -- Downloaded: 202640-26T07:56Z
Check the source to verify that this is the current version before use.

Item	Protocol Feature	Base Standard		Profile		Support
		Reference	Status	Clause	Status	
br4	Recognize all broadcast address formats	RFC 1122: 3.3.6	M		m	Yes
br5	Use IP broadcast/multicast address in link layer broadcast	RFC 1122: 3.3.6	M		m	Yes
br6	*Silently discard link layer only broadcast* datagrams	RFC 1122: 3.3.6	O		m	Yes
br7	Use limited broadcast address for connected network	RFC 1122: 3.3.6	O		m	Yes
Multicast:						
mc1	*Support local IP multicasting* (RFC 1112)	RFC 1122: 3.3.7	O	5.3.1.3.2.1.5	m	Yes
mc2	Support IGMP (RFC 1112)	RFC 1122: 3.3.7	O		o	Yes No
mc3	Join all hosts group at startup	RFC 1122: 3.3.7	O		m	Yes
mc4	*Higher layers learn interface multicast capability*	RFC 1122: 3.3.7	O		m	Yes
Interface:						
in1	Allow transport layer to use all IP mechanisms	RFC 1122: 3.4	M	5.3.1.3.1.1	m	Yes
in2	Pass interface ident up to transport layer	RFC 1122: 3.4	O		m	Yes
in3	Pass all IP options up to transport layer	RFC 1122: 3.4	M		m	Yes
in4	Transport layer can send certain ICMP messages	RFC 1122: 3.4	M		m	Yes
in5	Pass specified ICMP messages up to transport *layer*	RFC 1122: 3.4	M		m	Yes
in51	Include IP header + 8 octets or more from originator	RFC 1122: 3.4	M		m	Yes

Source: https://assist.dla.mil -- Downloaded: 202640-26T07:56Z
Check the source to verify that this is the currentversion before use.

A.4.4 PICS Proforma for Internet Control Message Protocol (ICMP)

A.4.4.1 Identification

Supplier	
Contact Point for Queries	
Implementation name(s) and Versions	
Other Information Necessary for full identification - eg, name(s) and version(s) for machines and/or operating systems; System Name(s)	

A.4.4.2 Protocol Summary

Protocol Version	
Addenda Implemented	
Amendments Implemented	
Date of Statement	

A.4.4.3 Interfaces

Item	Protocol Feature	Base Standard		Profile		Support
		Reference	Status	Clause	Status	
iui	ICMP Uses IP	RFC 792	M	5.3.2.2	m	Yes

A.4.4.4 Frame Structure

Item	Protocol Feature	Base Standard		Profile		Support
		Reference	Status	Clause	Status	
mf	Message Format	RFC 792	M	5.3.2.2	m	Yes
vs	version 4	RFC 792	M		m	Yes
ihl	IHL	RFC 792	M		m	Yes
htos	Type of Service 0	RFC 792	M		m	Yes

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:56Z
Check the source to verify that this is the current version before use.

Item	Protocol Feature	Base Standard		Profile		Support
		Reference	Status	Clause	Status	
totl	Total Length in octets	RFC 792	M		m	Yes
id	Identification	RFC 792	M		m	Yes
flg	Flags	RFC 792	M		m	Yes
frgo	Fragmentation Offset	RFC 792	M		m	Yes
httl	Time to Live	RFC 792	M		m	Yes
prot	Protocol - ICMP = 1	RFC 792	M		m	Yes
hchk	Header Checksum	RFC 792	M		m	Yes
sadd	Source Address	RFC 792	M		m	Yes
dadd	Destination Address	RFC 792	M		m	Yes

A.4.4.5 ICMP Message Formats

Item	Protocol Feature	Base Standard		Profile		Support
		Reference	Status	Clause	Status	
DU	Destination Unreachable	RFC 792 RFC 1122: 3.2.2.1	M	5.3.2.3.1	m	Yes
	Destination Address	RFC 792 RFC 1122: 3.2.2.1	M		m	Yes
	Type = 3	RFC 792 RFC 1122: 3.2.2.1	M		m	Yes
	Code	RFC 792 RFC 1122: 3.2.2.1	M		m	Yes
	Checksum	RFC 792 RFC 1122: 3.2.2.1	M	5.3.2.3.1	m	Yes
	Internet Header	RFC 792 RFC 1122: 3.2.2.1	M		m	Yes
	64 bits of data datagram	RFC 792 RFC 1122: 3.2.2.1	M		m	Yes
TEM	Time Exceeded Message	RFC 792 RFC 1122: 3.2.2.4	M		m	Yes
	Destination address	RFC 792 RFC 1122: 3.2.2.4	M		m	Yes

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:56Z
Check the source to verify that this is the current version before use.

Item	Protocol Feature	Base Standard		Profile		Support
		Reference	Status	Clause	Status	
	Type = 11	RFC 792 RFC 1122: 3.2.2.4	M		m	Yes
	Code	RFC 792 RFC 1122: 3.2.2.4	M		m	Yes
	Checksum	RFC 792 RFC 1122: 3.2.2.4	M		m	Yes
	Internet Header	RFC 792 RFC 1122: 3.2.2.4	M		m	Yes
	64 bits of data datagram	RFC 792 RFC 1122: 3.2.2.4	M		m	Yes
PPM	Parameter Problem Message	RFC 792 RFC 1122: 3.2.2.5	M		m	Yes
	Destination address	RFC 792 RFC 1122: 3.2.2.5	M		m	Yes
	Type = 12	RFC 792 RFC 1122: 3.2.2.5	M		m	Yes
	Code = 0	RFC 792 RFC 1122: 3.2.2.5	M		m	Yes
	Checksum	RFC 792 RFC 1122: 3.2.2.5	M		m	Yes
	Pointer	RFC 792 RFC 1122: 3.2.2.5	M	5.3.2.3.1	m	Yes
	Internet Header	RFC 792 RFC 1122: 3.2.2.5	M		m	Yes
	64 bits of data datagram	RFC 792 RFC 1122: 3.2.2.5	M		m	Yes
SQM	Source Quench Message	RFC 792 RFC 1122: 3.2.2.3	M		m	Yes
	Destination address	RFC 792 RFC 1122: 3.2.2.3	M		m	Yes
	Type = 4	RFC 792 RFC 1122: 3.2.2.3	M		m	Yes

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:56Z
Check the source to verify that this is the current version before use.

Item	Protocol Feature	Base Standard		Profile		Support
		Reference	Status	Clause	Status	
	Code = 0	RFC 792 RFC 1122: 3.2.2.3	M		m	Yes
	Checksum	RFC 792 RFC 1122: 3.2.2.3	M		m	Yes
	Internet Header	RFC 792 RFC 1122: 3.2.2.3	M		m	Yes
	64 bits of data datagram	RFC 792 RFC 1122: 3.2.2.3	M		m	Yes
RM	Redirect Message	RFC 792 RFC 1122: 3.2.2.2	M		m	Yes
	Type = 5	RFC 792 RFC 1122: 3.2.2.2	M		m	Yes
	Code	RFC 792 RFC 1122: 3.2.2.2	M		m	Yes
	Checksum	RFC 792 RFC 1122: 3.2.2.2	M		m	Yes
	Gateway Internet Address	RFC 792 RFC 1122: 3.2.2.2	M		m	Yes
	Internet Header	RFC 792 RFC 1122: 3.2.2.2	M	5.3.2.3.1	m	Yes
	64 bits of data datagram	RFC 792 RFC 1122: 3.2.2.2	M		m	Yes
EM	Echo Message	RFC 792 RFC 1122: 3.2.2.6	M	5.3.2.3.2	m	Yes
	Destination address	RFC 792 RFC 1122: 3.2.2.6	M		m	Yes
	Type = 8	RFC 792 RFC 1122: 3.2.2.6	M		m	Yes
	Code = 0	RFC 792 RFC 1122: 3.2.2.6	M		m	Yes
	Checksum	RFC 792 RFC 1122: 3.2.2.6	M		m	Yes

Source: https://assist.dla.mil -- Downloaded: 20261O-26T07:56Z
Check the source to verify that this is the current version before use.

Item	Protocol Feature	Base Standard		Profile		Support
		Reference	Status	Clause	Status	
	Identifier	RFC 792 RFC 1122: 3.2.2.6	M		m	Yes
	Sequence number	RFC 792 RFC 1122: 3.2.2.6	M		m	Yes
ERM	Echo Reply Message	RFC 792 RFC 1122: 3.2.2.6	M		m	Yes
	Source Address	RFC 792 RFC 1122: 3.2.2.6	M		m	Yes
	Type = 0	RFC 792 RFC 1122: 3.2.2.6	M		m	Yes
	Code = 0	RFC 792 RFC 1122: 3.2.2.6	M		m	Yes
	Checksum	RFC 792 RFC 1122: 3.2.2.6	M		m	Yes
	Identifier	RFC 792 RFC 1122: 3.2.2.6	M		m	Yes
	Sequence number	RFC 792 RFC 1122: 3.2.2.6	M	5.3.2.3.2	m	Yes
TM	Timestamp Message	RFC 792 RFC 1122: 3.2.2.8	M		m	Yes
	Destination address	RFC 792 RFC 1122: 3.2.2.8	M		m	Yes
	Type = 13	RFC 792 RFC 1122: 3.2.2.8	M		m	Yes
	Code = 0	RFC 792 RFC 1122: 3.2.2.8	M		m	Yes
	Checksum	RFC 792 RFC 1122: 3.2.2.8	M		m	Yes
	Identifier	RFC 792 RFC 1122: 3.2.2.8	M		m	Yes
	Sequence number	RFC 792 RFC 1122: 3.2.2.8	M		m	Yes

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:56Z
Check the source to verify that this is the current version before use.

Item	Protocol Feature	Base Standard		Profile		Support
		Reference	Status	Clause	Status	
TRM	Timestamp Reply Message	RFC 792 RFC 1122: 3.2.2.8	M		m	Yes
	Source Address	RFC 792 RFC 1122: 3.2.2.8	M		m	Yes
	Type = 14	RFC 792 RFC 1122: 3.2.2.8	M		m	Yes
	Code = 0	RFC 792 RFC 1122: 3.2.2.8	M		m	Yes
	Checksum	RFC 792 RFC 1122: 3.2.2.8	M		m	Yes
	Identifier	RFC 792 RFC 1122: 3.2.2.8	M		m	Yes
	Sequence number	RFC 792 RFC 1122: 3.2.2.8	M		m	Yes
IRM	Information Request Message	RFC 792 RFC 1122: 3.2.2.7	X	5.3.2.3.2	x	No
IRRM	Information Reply Message	RFC 792 RFC 1122: 3.2.2.7	X	5.3.2.3.2	x	No
	No ICMP messages sent out for ICMP message	RFC 792 RFC 1122: 3.2.2	M	5.3.2.3.1.1	m	Yes
	ICMP messages are only sent out about errors in handling fragment zero of fragmented datagrams	RFC 792 RFC 1122: 3.2.2	M		m	Yes

Source: https://assist.dla.mil -- Downloaded: 202640-26T07:56Z
Check the source to verify that this is the currentversion before use.

A.4.4.6 ICMP Procedure

Item	Protocol Feature	Base Standard		Profile		Support
		Reference	Status	Clause	Status	
sd	Silently discard ICMP msg with unknown type	RFC 1122: 3.2.2	M	5.3.2.3	m	Yes
oc	Include more than 8 octets of orig datagram	RFC 1122: 3.2.2	O		o	Yes No
oc1	Included octets same as received	RFC 1122: 3.2.2	M		m	Yes
dm	Demux ICMP error to transport protocol	RFC 1122: 3.2.2	M		m	Yes
stos	Send ICMP error message with TOS=0	RFC 1122: 3.2.2	O		m	Yes
si	Send ICMP error message for:					
si1	ICMP error message	RFC 1122: 3.2.2	X	5.3.2.3.1.1	x	No
si2	IP broadcast or IP multicast	RFC 1122: 3.2.2	X		x	No
si3	Link layer broadcast	RFC 1122: 3.2.2	X		x	No
si4	Non-initial fragment	RFC 1122: 3.2.2	X		x	No
si5	Datagram with non-unique source address	RFC 1122: 3.2.2	X		x	No
ricm	Return ICMP error messages	RFC 1122: 3.3.8	M	5.3.2.3.1.1	m	Yes
Dest. Unreachable:						
du1	Generate Dest. Unreachable (code 2/3)	RFC 1122: 3.2.2.1	O	5.3.2.3.1	m	Yes
du2	Pass ICMP Dest. Unreachable to higher layer	RFC 1122: 3.2.2.1	M		m	Yes
du3	Higher layer act on Dest. Unreachable	RFC 1122: 3.2.2.1	O		m	Yes
du31	Interpret Destination Unreachable as only hint	RFC 1122: 3.2.2.1	M		m	Yes
Redirect:						
rd1	Host send redirect	RFC 1122: 3.2.2.2	O	5.3.2.3.1	x	No
rd2	Update route cache when receive Redirect	RFC 1122: 3.2.2.2	M		m	Yes

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:56Z
Check the source to verify that this is the current version before use.

Item	Protocol Feature	Base Standard		Profile		Support
		Reference	Status	Clause	Status	
rd3	Handle both host and Net redirect	RFC 1122: 3.2.2.2	M		m	Yes
rd4	Discard illegal redirect	RFC 1122: 3.2.2.2	O		m	Yes
Source Quench:						
sq1	Send Source Quench if buffering exceeded	RFC 1122: 3.2.2.3	O	5.3.2.3.1	o	Yes No
sq2	Pass Source Quench to higher layer	RFC 1122: 3.2.2.3	M		m	Yes
sq3	Higher layer act on Source Quench	RFC 1122: 3.2.2.3	O		m	Yes
sq4	Time Exceeded: pass to higher layer	RFC 1122: 3.2.2.4	M		m	Yes
Parameter Problem:						
pp1	Send parameter problem messages	RFC 1122: 3.2.2.5	O	5.3.2.3.1	m	Yes
pp2	*Pass Parameter Problem to higher layer*	RFC 1122: 3.2.2.5	M		m	Yes
pp3	Report parameter problem to user	RFC 1122: 3.2.2.5	O		o	Yes No
ICMP Echo request or Reply:						
ec1	Echo server and echo client	RFC 1122: 3.2.2.6	M	5.3.2.3.2	m	Yes
ec2	Echo client	RFC 1122: 3.2.2.6	O		m	Yes
ec3	Discard Echo Request to broadcast address	RFC 1122: 3.2.2.6	O		o	Yes No
ec4	Discard Echo Request to multicast address	RFC 1122: 3.2.2.6	O		o	Yes No
ec5	Use specific-dest address as Echo-Reply source	RFC 1122: 3.2.2.6	M		m	Yes
ec6	Send same data in Echo Reply	RFC 1122: 3.2.2.6	M		m	Yes
ec7	Pass Echo Reply to higher layer	RFC 1122: 3.2.2.6	M	5.3.2.3.2	m	Yes
ec8	*Reflect Record Route, Time Stamp options*	RFC 1122: 3.2.2.6	O		m	Yes
ec9	Reverse and reflect Source Route option	RFC 1122: 3.2.2.6	M		m	Yes
irr	ICMP Information Request or Reply:	RFC 1122: 3.2.2.7	O		x	No

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:56Z
Check the source to verify that this is the current version before use.

Item	Protocol Feature	Base Standard		Profile		Support
		Reference	Status	Clause	Status	
itr	ICMP Timestamp and Timestamp Reply:	RFC 1122: 3.2.2.8	O		o	Yes No
itr1	Minimize delay variability	RFC 1122: 3.2.2.8	itr:O		itr:m	Yes
itr2	Silently discard broadcast Timestamp	RFC 1122: 3.2.2.8	itr:O		itr:o	Yes No
itr3	Silently discard multicast Timestamp	RFC 1122: 3.2.2.8	itr:O		itr:o	Yes No
itr4	Use specific-dest address as TS reply source	RFC 1122: 3.2.2.8	itr:M		m	Yes
itr5	Reflect Record Route, Time Stamp Options	RFC 1122: 3.2.2.6	itr:O		itr:m	Yes
itr6	Reverse and reflect source route option	RFC 1122: 3.2.2.8	itr:M		itr:m	Yes
itr7	Pass timestamp reply to higher layer	RFC 1122: 3.2.2.8	itr:M		itr:m	Yes
itr8	Obey rules for "standard value"	RFC 1122: 3.2.2.8	itr:M		itr:m	Yes
ICMP Address Mask Request and Reply:						
iar1	Address Mask Source Configurable	RFC 1122: 3.2.2.9	M	5.3.2.3.2	m	Yes
iar2	Support static configuration of address mask	RFC 1122: 3.2.2.9	M		m	Yes
iar3	Get address mask dynamically during booting	RFC 1122: 3.2.2.9	O		o	Yes No
iar4	Get address via ICMP Address Mask Request/Reply	RFC 1122: 3.2.2.9	O		o	Yes No
iar41	Retransmit Address Mask Req. if no reply	RFC 1122: 3.2.2.9	M		m	Yes
iar42	Assume default mask if no reply	RFC 1122: 3.2.2.9	O	5.3.2.3.2	m	Yes
iar43	Update address mask from first reply only	RFC 1122: 3.2.2.9	M		m	Yes
iar5	Reasonableness check on Address Mask	RFC 1122: 3.2.2.9	O		m	Yes
iar6	Send unauthorized Address Mask Reply Message	RFC 1122: 3.2.2.9	X		x	No
iar61	Explicitly configured to be agent	RFC 1122: 3.2.2.9	M		m	Yes
iar7	Static Configuration ==> Addr-Mask-Authoritative flag	RFC 1122: 3.2.2.9	O		m	Yes

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:56Z
Check the source to verify that this is the current version before use.

Item	Protocol Feature	Base Standard		Profile		Support
		Reference	Status	Clause	Status	
iar71	Broadcast Address Mask Reply when initiated	RFC 1122: 3.2.2.9	M		m	Yes

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:56Z
Check the source to verify that this is the currentversion before use.

ANNEX B (informative)

CONCLUDING MATERIAL

B.1 Deviations from the Base Standards/Referenced Profiles

This MIL-STD documents the data contained in the IAB standards 3, 5, 6, and 7 in the ISO/IEC TR 10000, "Framework and Taxonomy of International Standardized Profiles" and MIL-HDBK-829 format. This DSP does not deviate from the protocol as written in the RFC base standards.

The classification of the requirements in RFCs have been changed in the DSPICS to the following:

RFC	MIL-STD
MUST	Mandatory
SHOULD	Mandatory
MAY	Optional
SHOULD NOT	Prohibited
MUST NOT	Prohibited

B.2 Subject Term (Keyword) Listing

User Datagram Protocol
Internet Activities Board
Transmission Control protocol
Internet Protocol
IAB 3
IAB 5
IAB 6
IAB 7
Internet Message Control Protocol
ICMP
TCP
Network
RFC
UDP

B.3 Preparing Activity:

Defense Information Systems Agency (DISA) - DC
Project: DCPS-0013

B.4 Reviewing Activity:

Army	SC, PT
Air Force	13, 17, 29, 33, 90
DLA	DH
DMA	MP
DIA	DI
DOT	OST
NSA	NS
OASD	IQ, DO, MA, IR
ODISC4	AC
NAVY	EC, CH, ND, TD, OM
USMC	MC, CG

Source: https://assist.dla.mil - Downloaded: 2026-10-26T07:56Z
Check the source to verify that this is the current version before use.

B.5 Custodians:

DISA:	DC
Army:	SC
Air Force:	90
Navy:	OM
DIA:	DI
NSA:	NS
USMC:	MC
DLA:	DH
Other:	Joint Staff/Architecture & Integration USSPACECOM

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:56Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1,2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER MIL-STD 2045-14502-1	2. DOCUMENT DATE (YYMMDD) 940728

3. DOCUMENT TITLE Information Technology - Defense Standardized Profiles - Internet Transport Profile for DOD Communications - Part 1: Transport Services

4. NATURE OF CHANGE *(Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)*

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME *(Last, First, Middle Initial)*	b. ORGANIZATION	
c. ADDRESS *(Include Zip Code)*	d. TELEPHONE *(Include Area Code)* (1) Commercial (2) DSN *(If applicable)*	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY **DEFENSE INFORMATION SYSTEMS AGENCY (DISA)**

a. NAME Rose D. Satz	b. TELEPHONE *(Include Area Code)* (1) Commercial (2) DSN
c. ADDRESS *(Include Zip Code)* Director JIEO Attn: TBBF Ft. Monmouth, NJ 07703-5613	**IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT:** Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 DSN 289-2340

DD Form 1426, OCT 89 *Previous editions are obsolete.* 198290

Source: https://assist.dla.mil -- Downloaded: 202640-26T07:56Z
Check the source to verify that this is the current version before use.