NOT MEASUREMENT SENSITIVE

MIL-STD-2045-14502-05
28July 1994

MILITARY STANDARD

INFORMATION TECHNOLOGY
DOD STANDARDIZED TRANSPORT PROFILE
INTERNET TRANSPORT PROFILE
FOR DOD COMMUNICATIONS

Part 5: Local Area Network (LAN)
Media Dependent Requirements

AMSC N/A

AREA DCPS

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:56Z
Check the source to verify that this is the current version before use.

Foreword

This military standard is approved for use by all Departments and Agencies of the Department of Defense (DOD).

Beneficial comments (recommendations, additions, deletions) and any pertinent data that may be of use in improving this MIL-STD should be addressed to the:

Joint Interoperability and Engineering Organization (JIEO)
ATTN: TBBF
Fort Monmouth, New Jersey 07703-5613

by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this MIL-STD or by memorandum.

This Defense Standardized Profile (DSP) is a functional DOD Data Communications Protocol Standard (DCPS) produced by the DCPS Technical Management Panel (DTMP). The MIL-STD-2045 document series was established within the DCPS Standardization Area to allow for the enhancement of commercial standards or the development of standards that are unique to DOD.

The MIL-STD-2045-10000 series, MIL-STD-2045-10000 to MIL-STD-2045-19999 inclusive, will be used to describe how DOD will implement commercial, international, national, federal, or military standards within the functional profile concept to provide required network services. The Government Open Systems Interconnection Profile (GOSIP) will serve as the base for developing the 10000 series with DOD enhancements, unique military standards, and interim standards being used only when necessary.

The MIL-STD-2045-20000 series, MIL-STD-2045-20000 to MIL-STD-2045-29999 inclusive, will be used to describe DOD enhancements and extensions to existing commercial, international, national, or federal standards.

The MIL-STD-2045-30000 series, MIL-STD-2045-30000 to MIL-STD-2045-39999 inclusive, will be used to describe protocols and services unique to DOD that will not be supported by commercial, international, national, or federal standards.

The MIL-STD-2045-40000 series, MIL-STD-2045-40000 to MIL-STD-2045-49999 inclusive, will be used to document interim standards. Interim standards document protocols and services needed by DOD until these protocols and services are described in either GOSIP or in a MIL-STD-2045-20000 or -30000 series standard.

The MIL-STD-2045-50000 series, MIL-STD-2045-50000 to MIL-STD-2045-59999 inclusive, will be used to describe how DOD will implement commercial, international, national, federal, or military standards within the functional profile concept to provide required network services. The Government Open Systems Interconnection Profiles (GOSIP) will serve as the base for developing the 50000 series with DOD enhancements, unique military standards, and interim standards being used only when necessary. The difference between MIL-STD-2045-10000 series and the MIL-STD-2045-50000 series is that the 50000 series are interim profiles

Specific details and instructions for establishing a MIL-STD-2045 document, as well as profile development guidelines, are documented in MIL-HDBK-829, Volumes 1 and 2. DTMP Working Groups shall be responsible for DSP development and informal Service or Agency coordination; the DTMP Plenary shall be responsible for final review and approval.

This document is part of a set of interim DOD data communications protocol profiles based on the Internet protocol suite and is intended to support the interoperability of DOD communication networks, including connectivity with the Defense Data Network (DDN).

The options and parameters specified in this DSP take precedence over MIL-STD 1777, Internet Protocol and MIL-STD 1778, Transmission Control Protocol.

This part of MIL-STD 2045-14502 contains one normative annex and one informative annex:

Annex A (normative) DSPICS REQUIREMENTS LIST (DPRL)
Annex B (informative) CONCLUDING MATERIAL

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:56Z
Check the source to verify that this is the current version before use.

Contents

Introduction		v
1	Scope	1
1.1	General	1
1.2	Position Within the Taxonomy	1
1.3	Scenario	1
2	References	2
2.1	Government Documents	2
2.1.1	Specifications, standards, and handbooks.	2
2.1.2	Other Government documents, drawings and publications.	2
2.2	Non-Government publications.	2
2.2.1	Profiles	2
2.2.2	Base Standards	2
2.2.3	Other Non Government documents, drawings, and publications	2
2.3	Order of precedence	3
3	Definitions	3
4	Symbols and Abbreviations	3
5	Requirements	3
5.1	General Requirements	3
5.2	Data Link Layer Requirements	4
5.2.1	Static Conformance Requirements	4
5.2.2	Dynamic Conformance Requirements	4
5.3	Physical Layer Requirements	4
5.3.1	Static Conformance Requirements	4
5.3.2	Dynamic Conformance Requirements	4

Annexes

A	DSPICS REQUIREMENTS LIST (DPRL)	A-1
A.1	Introduction	A-1
A.1.1	Notation	A-1
A.1.2	Footnotes	A-2
A.1.3	Instructions for Completing the DPRL	A-2
A.2	Standards Referenced	A-3
A.3	DSPICS Requirements List	A-3
A.3.1	General Information	A-3
A.3.2	Data Link Layer DPRL (MAC Sublayer)	A-4
A.3.3	Physical Layer	A-4
B	CONCLUDING MATERIAL	B-1
B.1	Deviations from the Base Standards	B-1
B.2	Subject Term (Keyword) Listing	B-1
B.3	Preparing Activity:	B-1
B.4	Reviewing Activity:	B-1
B.5	Custodians:	B-1

Figures

Figure 1.	Transport Profile Scenario	1

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:56Z
Check the source to verify that this is the current version before use.

Tables

A.3.1.1	Implementation Identification	A-3
A.3.1.2	Protocols	A-3
A.3.1.3	Environments	A-3
A.3.2.1	MAC Frame Structure	A-4
A.3.3.1	MAU/Medium Interface (B5::)	A-4
A.3.3.2	MAU/Medium Interface (B2::)	A-4
A.3.3.3	MAU/Medium Interface (BT::)	A-5

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:56Z
Check the source to verify that this is the current version before use.

Introduction

This MIL-STD is part of a set of interim Command and Control (C^2) common data communication profiles. It will cease to exist upon the transition of the various military service and agency (S/A) networks to GOSIP. The purpose is to record what presently exists in, and what is needed to achieve the interoperability of the various S/A data communication networks deployed to support a Joint Task Force (JTF).

This DSP is defined within the context of functional standardization, in accordance with the principles specified by MIL-HDBK-829, volume 2, "Guidelines For Data Communications Protocol Standards (DCPS) DOD Standardized Profiles (DSPs)." The context of functional standardization is one part of the overall field of Information Technology (IT) standardization activities covering base standards, profiles and registration mechanisms. A profile defines a combination of base standards that collectively perform a specific well-defined Information Technology function. Profiles standardize the selection of options and other variations in the base standards to promote system interoperability.

The base standards of this DSP include: Request For Comments (RFCs) designated as Official Internet Architecture Board (IAB) standards, other RFCs, and Open Systems Interconnection (OSI) Layer Standards from the Open Systems Interconnection (OSI) Reference Model.

This document is intended to be part of a complete TCP/IP based transport profile, which specifies an internet connection-mode transport service over an internet connectionless mode network service operating over several types of subnetworks. This transport profile is a multipart profile, of which this is Part 5. Part 5 specifies media-dependent requirements for Carrier-Sense Multiple Access with Collision Detection (CSMA/CD) LANs.

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:56Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:56Z
Check the source to verify that this is the current version before use.

Information Technology - Defense Standardized Profile (DSP) - Internet Transport Profile for DOD Communications - Part 5: Media-Dependent Requirements for CSMA/CD LANs

1 Scope

1.1 General

This Defense Standardized Profile (DSP) MIL-STD 2045-14502 applies to end systems operating in the Defense Data Network (DDN). It specifies a combination of layer protocols that collectively provide the Transmission Control Protocol (TCP) over the Internet Protocol (IP) operating over DDN subnetworks. This part of the DSP addresses Layer 1 and 2 requirements for a CSMA/CD Local Area Network (LAN).

1.2 Position Within the Taxonomy

This profile contains requirements for both connection-oriented and a connectionless transport service. It also contains requirements for a connectionless network service.

1.3 Scenario

This profile specifies the provision for connectionless or connection-oriented transport service between an end system connected to a subnetwork and another compatible end system through the IP connectionless network service. The compatible end system may use mutually agreed upon access methods contained within this DSP, or may conform to a mutually agreed upon alternative access methods. An end system is compatible only if the suboptions (e.g., TCP) are compatible. This profile provides the subnetwork dependent requirements and the subnetwork access requirements for group XA transport profiles.

The layer standards that make up this profile are shown in Figure 1.

<table>
<tr><td>TRANSPORT LAYER</td><td>IAB STD 7 (TCP)
IAB STD 6 (UDP)</td><td rowspan="2">TCP/IP Group Profile
MIL-STD
2045-14502,
Part 1</td></tr>
<tr><td rowspan="2">NETWORK LAYER</td><td>IAB STD 5 (IP)</td></tr>
<tr><td>RFC 826 (ARP)
RFC 1042 (IP over IEEE 802.2)</td><td rowspan="2">LAN Media-
Independent
Requirements
MIL-STD
2045-14502,
Part 4</td></tr>
<tr><td rowspan="2">DATA LINK LAYER</td><td>LLC (ISO 8802-2)</td></tr>
<tr><td>MAC (ISO 8802-3)</td><td rowspan="2">Media-Dependent
Requirements
for CSMA/CD
LANs
MIL-STD
2045-14502,
Part 5</td></tr>
<tr><td>PHYSICAL LAYER</td><td>PLS, AUI, MAU (ISO 8802-3)</td></tr>
</table>

Figure 1. Transport Profile Scenario

The requirements placed on an end system in the DSP are only those necessary to operate the specified set of protocols. The DSP does not specify the required functions for relays. Such functions are out of scope of this document.

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:56Z
Check the source to verify that this is the current version before use.

2 References

2.1 Government Documents

2.1.1 Specifications, standards, and handbooks.

The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

MIL-HDBK 829:	July 1994	*Guidelines for DOD Standardized Profiles.*
MIL-STD-2045-14502-1,	July 1994	*Transport and Internet Services*
MIL-STD-2045-14502-2,	July 1994	*Point-to-Point Links*
MIL-STD-2045-14502-3,	July 1994	*Wide Area Network Access*
MIL-STD-2045 14502-4	July 1994	*Local Area Network (LAN) Media Independent Requirements*
MIL-STD-2045-14502-6,	July 1994	*Combat Net Radio (CNR*

DOD activities may obtain copies of DOD directives through their own publication channels or from the DOD Single Stock Point, Standardization Document Order Desk, 700 Robbins Avenue, Building 4D, Philadelphia, PA 19111-5094. Other federal agencies and the public may purchase copies from the U.S. Department of Commerce, National Technical Information Service, 5285 Port Royal Road, Springfield, VA 22161.

Copies of Federal Information Processing Standards (FIPS) are available to Department of Defense activities from the Commanding Officer, Naval Publications and Forms Center, 5801 Tabor Avenue, Philadelphia, PA 19120-5099. Others must request copies of FIPS from the National Technical Information Services, 5285 Port Royal, Springfield, VA 22161-2171.

2.1.2 Other Government documents, drawings and publications.

NONE

2.2 Non-Government publications.

2.2.1 Profiles

(a) ISO/IEC ISP 10608-2: 1992 *Information Processing Systems - International Standardized Profile TAnnnn- Connection-mode Transport Service over Connectionless-mode Network Service, Part 2: TA51 profile including subnetwork-dependent requirements for CSMA/CD Local Area Networks (LANs).*

2.2.2 Base Standards

(a) ISO 8802-3:1992-03 *Information processing systems - Local and metropolitan area Networks - Part 3: Carrier sense multiple access with collision detection (CSMA/CD) access method and physical layer specifications.*

(b) ISO 8802-2:1990/ PDAM9:1990-12, *System considerations for multi-segment 10 Mb/s baseband networks (Section 13), twisted-pair medium attachment unit (MAU) and baseband medium, Type 10 BASE-T (Section 14).*

2.2.3 Other Non Government documents, drawings, and publications

None

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:56Z
Check the source to verify that this is the current version before use.

2.3 Order of precedence

In the event of a conflict between the test of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3 Definitions

For the purposes of this DSP, the following terms have the meanings stated in DOD Standardized Profile Guidelines (ref. 2.4 (a)):

(a) Base Standard.
(b) DOD Protocol Implementation Conformance Statement (DPICS).
(c) DOD Standardized Profile (DSP).
(d) DOD Standardized Profile Implementation Conformance Statement (DSPICS).
(e) DSPICS Requirements List (DPRL).

The following terms are additionally defined for the purposes of this DSP:

Internet Architecture Board (IAB) Standard (STD): The IAB has established this as an official standard protocol for the Internet. These protocols are assigned STD numbers.

Request For Comments (RFCs): RFCs are the working notes of the "Network Working Group," that is the Internet research and development community.

Note: All Internet standards are published as RFCs, but not all RFCs specify standards.

4 Symbols and Abbreviations

The symbols and abbreviations used in this DSP are defined in MIL-HDBK 829, in the referenced base standards, or in the standards referenced by the base standards. The following is a partial list:

IAB	Internet Architecture Board
RFC	Request For Comments
STD	Standard
TCP	Transmission Control Protocol
UDP	User Datagram Protocol
MAC	Media Access Control

5 Requirements

5.1 General Requirements

This profile is based on ISO/IEC ISP 10608-2: 1992 (ref. 2.3(a)). The additions to the ISP provided by the DSP are detailed in this clause.

A conforming implementation of MIL-STD 2045-14502 shall satisfy:
A conforming implementation of MIL-STD 2045-14502 shall be unconditionally compliant and therefore shall satisfy all the "must" and all the "should" requirements of the reference base standards and shall not implement any capability that has been identified by the base standards as "should not". The following requirements shall be implemented.

(a) All requirements in the remainder of this clause 5.
(b) All mandatory requirements of the base standards referenced by this DSP.
(c) All the constraints specified in Annex A (normative), DPRL.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:56Z
Check the source to verify that this is the current version before use.

5.2 Data Link Layer Requirements

Conforming implementations shall meet the requirements of Annex A of this DSP.

5.2.1 Static Conformance Requirements

There are no additional static conformance requirements.

5.2.2 Dynamic Conformance Requirements

There are no additional dynamic conformance requirements.

5.3 Physical Layer Requirements

Conforming implementations shall meet the requirements for ISO 8802-3 CSMA/CD LANs and Annex A of this DSP.

5.3.1 Static Conformance Requirements

Coaxial cable requirements for 10 BASE 5 and 10 BASE 2 CSMA/CD LANs are specified in ISO 8802-3, clauses 8.4 and 10.5, respectively. The specified cable is suitable for office type environments. Since this profile applies to LANs operating in a tactical military environment, an option for better-than-specified performance is required. Shielding effectiveness, ruggedness and resistance to water penetration are examples of areas where better performance is required. Flexible solid shielded coaxial cable with moisture penetration resistant outer insulation and dielectric materials will satisfy the requirements. The requirements of the relevant ISO 8802-3 clauses must still be met. Andrew Corporation types FSJ4-50B cable (NATO Stock No. 6145-00-427-7170) for 10 BASE 5 and FSJ1-50 (NATO Stock No. 6145-00-290-3453) for 10 BASE 2 are examples of cables that will meet the requirements for the tactical military environment. Respective male cable connectors would be Andrew Corporation types 44ASW(N) (NATO Stock No. 5935-01-193-5551) and 40622(BNC) (NATO Stock No. 5935-00-264-7847).

ISO 8802-3, clause 8.5.3, provides for severed or piercing tap, MAU to cable connections for 10 BASE 5. Piercing tap connectors are not sufficiently rugged or moisture penetration resistant to satisfy tactical military requirements. They have also been reported to cause problems (e.g., intermittent connections to the shield and center conductor of the coaxial cable) when used in office environments. Therefore, connections will be of the severed cable type with type N connectors on the cable and connections to the cable made with "T" connectors when the MAU is incorporated in the DTE and with an appropriately designed MAU when an AUI cable is used. The other requirements of clause 8.5.3 still apply.

The 10 BASE T twisted-pair cable connector specified by ISO 8802-3/PDAM9 is suitable for office type environments. However, it is not rugged enough to be suitable for the tactical military environment. An optional ruggedized quick disconnect connector is required for LAN use in this environment. A suitable substitute is TBD.

5.3.2 Dynamic Conformance Requirements

There are no additional dynamic conformance requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:56Z
Check the source to verify that this is the current version before use.

ANNEX A (normative)

DSPICS REQUIREMENTS LIST (DPRL)

A.1 Introduction

This document provides the DSPICS Requirements List (DPRL) for implementations of the Defense Standardized Profile (DSP) 2045-14502. The DSPICS for an implementation is generated by completing the DPRL in accordance with the instructions given below.

An implementation shall satisfy the mandatory conformance requirements of the base standards referenced in this profile.

A completed DPRL is called the DSPICS for the implementation in question. The DSPICS is a statement of which capabilities and options of the protocol have been implemented. The following can use the DSPICS:

(a) the protocol implementor, as a check-list to reduce the risk of failure to conform to the standard through oversight.

(b) the supplier and acquirer - or potential acquirer - of the implementation, as a detailed indication of the capabilities of the implementation, stated relative to the common basis for understanding provided by the standard DSPICS proforma.

(c) the user - or potential user - of the implementation, as a basis for initially checking the possibility of interworking with another implementation (note that, while interworking can never be guaranteed, failure to internetwork can often be predicted from incompatible DSPICSs).

(d) a protocol tester, as the basis for selecting appropriate tests against which to assess the claim for conformance of the implementation.

A.1.1 Notation

The following notations and symbols from MIL-HDBK 829, which references ISO/IEC TR 10000-1 and -2, are used in the DPRL to indicate the status of features:

Status Symbols

m	- mandatory.
m.<n>	- support of every item of the group labeled by the same numeral <n> required, but only one is active at a time.
o	- optional.
o.<n>	- optional, but support of at least one of the group of options labeled by the same numeral <n> is required.
c	- conditional.
-	- non-applicable (i.e. logically impossible in the scope of the profile).
x	- excluded or prohibited.
i	- out of scope of profile (left as an implementation choice)

In addition, the symbol "•" is used to indicate an option whose status is not constrained by the profile (status in the base standard). The o.<n> notation is used to show a set of selectable options (i.e., one or more of the set must be implemented) with the same identifier <n>.

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:56Z
Check the source to verify that this is the currentversion before use.

Two character combinations may be used for dynamic conformance requirements. In this case, the first character refers to the static (implementation) status, and the second refers to the dynamic (use); thus `mo' means "mandatory to be implemented, optional to be used."

Notations for Conditional Status

The following predicate notation is used:

<predicate>:: This notation introduces a group of items, all of which are conditional on <predicate>.

<predicate>: This notation introduces a single item which is conditional on <predicate>.

In each case, the predicate may identify a profile feature, or a boolean combination of predicates. ("^" is the symbol for logical negation).

<index>: This predicate symbol means that the status following it applies only when the DPICS states that the features identified by the index is supported. In the simplest case, <index> is the identifying tag of a single DPICS items. <index> also may be a Boolean expression composed of several indices.

<index>:: When this group predicate is true, the associated clause should be completed.

Notations used in the Protocol Feature Column

<r>	Symbol used to denote the receiving system.
<t>	Symbol used to denote the transmitting system.

Support Column Symbols

The support of every item as claimed by the implementor is stated by circling the appropriate answer (either Yes, No or N/A) in the support column:

Yes	Supported by the implementation.
No	Not supported by the implementation.
N/A	Not applicable.

Base standard requirements are shown using the equivalent notations in upper case (e.g., M, O, X).

A.1.2 Footnotes

Footnotes to the proforma are indicated by superscript numerals. The footnote appears on the page of the first occurrence of the numeral. Subsequent occurrences of a numeral refer to the footnote of the first occurrence.

A.1.3 Instructions for Completing the DPRL

A DSP implementor shows the extent of compliance to a DSP by completing the DPRL; that is, compliance to all mandatory requirements and the options that are not supported are shown. The resulting completed DPRL is called a DSPICS. Where this profile refines the features of the base standards, the requirements expressed in this DPRL shall be applied (as indicated in DPRL items with no "Profile Support" column) to constrain the allowable responses in the base standard DPICS proforma. When this profile makes additional requirements, the "Profile Support" column for such DPRLs shall be completed. In this column, each response either shall be selected from the indicated set of responses, or comprise one or more parameter values as requested. For an inapplicable conditional requirement, a Not Applicable (NA) check-box is provided. If a mandatory requirement is not satisfied, exception information must be supplied by entering a reference Xi, where i is a unique identifier, to an accompanying rationale for the noncompliance. When the profile requirement is expressed as a two-character combination (as defined in A.1.1 above), then the response shall address each element of the requirement; e.g., for the requirement "mo," the possible compliant responses are "yy" or "yn."

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:56Z
Check the source to verify that this is the current version before use.

A.2 Standards Referenced

This XA profile specifies the provision of TCP service in an end system from which a standardized IP network service operating over CSMA/CD LANs is available (or can be made available). It uses the following standards:

ISO 8802-3	Data Link Layer Protocol (MAC)
ISO 8802-3	Physical Layer Specification

A.3 DSPICS Requirements List

A.3.1 General Information

The following tables give the DPRL for ISO 8802-3 CSMA/CD LAN requirements for the MAC sub-layer of the data link layer and the physical layer for 10 BASE 5, 10 BASE 2, and 10 BASE T cable mediums.

A.3.1.1 Implementation Identification

Supplier	
Contact point for queries about the profile	
Implementation Name(s) and Version(s)	
Date of statement	
Other Information: Machine Name, Operating Systems, System Name	

A.3.1.2 Protocols

Item	Protocol Feature	Base Standard		Profile		Supported
		Reference	Status	Clause	Status	
MAC	Media Access Control	ISO 8802-3			m	Yes
PLS	Physical Layer Signalling	ISO 8802-3			m	Yes
MAU	Medium Attachment Unit	ISO 8802-3			m	Yes

A.3.1.3 Environments

Item	Protocol Feature	Base Standard		Profile		Supported
		Reference	Status	Clause	Status	
MOE	Military Office Type Environment	N/A			o.1	Yes No
MTE	Military Tactical (Interference) Environment	N/A			o.1	Yes No

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:56Z
Check the source to verify that this is the current version before use.

A.3.2 Data Link Layer DPRL[1] (MAC Sublayer)

A.3.2.1 MAC Frame Structure

Item	Protocol Feature	Base Standard		Profile		Supported
		Reference	Status	Clause	Status	
MAS	Address Size 16 bits 48 bits	IS:3.2.3	O.1 O.1		oo mm	Yes No Yes
	Destination Address type	IS:3.2.3.1				
DA/1	Individual		O.2		mo.2	Yes No
DA/2	Group-Multicast		O.2		mo.2	Yes No
DA/3	Broadcast		O.2		mo.2	Yes No

A.3.3 Physical Layer[1]

A.3.3.1 MAU/Medium Interface (B5::)

Item	Protocol Feature	Base Standard		Profile		Supported
		Reference	Status	Clause	Status	
B5I/2a	Coaxial Cable (Office Environment)	IS:8.4	O.2	5.3.1	MOE:m	Yes N/A
B5I/2b	Coaxial Cable (Tactical Environment)	N/A	O.2	5.3.1	MTE:m	Yes N/A
	Coaxial Connectors					
B5I/5a B5I/5b	- MAU to Cable - Severed Cable - Piercing Tap	IS:8.5.3 IS:8.5.3	O.3 O.3	5.3.1	m x	Yes No

A.3.3.2 MAU/Medium Interface (B2::)

Item	Protocol Feature	Base Standard		Profile		Supported
		Reference	Status	Clause	Status	
B2I/2a	Coaxial Cable (Office Environment)	IS:10.5	O.4	5.3.1	MOE:m	Yes N/A
B2I/2b	Coaxial Cable (Tactical Environment)	N/A	O.4	5.3.1	MTE:m	Yes N/A

[1]References to IS in this section (A.3.2) are to clauses of ISO 8802-3 with all clause 14 references to ISO 8802-3/PDAM9.

[1]References to IS in this section (A.3.3) are to clauses of ISO 8802-3 with all clause 14 references to ISO 8802-3/PDAM9.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:56Z
Check the source to verify that this is the current version before use.

A.3.3.3 MAU/Medium Interface (BT::)

Item	Protocol Feature	Base Standard		Profile		Supported
		Reference	Status	Clause	Status	
BTI/3a	Connector (Office Environment)	IS:14.5	O.5	5.3.1	MOE:m	Yes N/A
BTI/3b	Connector (Ruggedized)	N/A	O.5	5.3.1	MTE:m	Yes N/A

Source: https://assist.dla.mil -- Downloaded: 2026t0-26T07:56Z
Check the source to verify that this is the currentversion before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:56Z
Check the source to verify that this is the current version before use.

ANNEX B (informative)

CONCLUDING MATERIAL

B.1 Deviations from the Base Standards

This MIL-STD documents the base standard protocols in the ISO/IEC TR 10000, Framework and Taxonomy of International Standardized Profiles and MIL-HDBK-829 format. This DSP does not deviate from the protocol as written in the base standards.

B.2 Subject Term (Keyword) Listing

CSMA/CD
ISO 8802-2
LAN
MAC
Media-Dependent
RFC
TCP
UDP

B.3 Preparing Activity:

Defense Information Systems Agency (DISA) - DC
Project: DCPS-0013

B.4 Reviewing Activity:

Army	SC, PT
Air Force	13, 17, 29, 33, 90
DLA	DH
DMA	MP
DIA	DI
DOT	OST
NSA	NS
OASD	2IQ, DO, IR
ODISC4	AC
NAVY	CH, ND, TD, OM
USMC	MC, CG

B.5 Custodians:

DISA:	DC
Army:	SC
Air Force:	90
Navy:	OM
DIA:	DI
NSA:	NS
USMC:	MC
DLA:	DH
Other:	Joint Staff/Architecture & Integration USSPACECOM

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:56Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:56Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1,2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER MIL-STD 2045-14502-5	2. DOCUMENT DATE *(YYMMDD)* 940728

3. DOCUMENT TITLE Defense Standardized Profiles - Internet Transport Profiles for DOD Communications - Part 5: Media Dependent Requirements for CSMA/CD LANs

4. NATURE OF CHANGE *(Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)*

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME *(Last, First, Middle Initial)*	b. ORGANIZATION	
c. ADDRESS *(Include Zip Code)*	d. TELEPHONE *(Include Area Code)* (1) Commercial (2) DSN *(If applicable)*	7. DATE SUBMITTED *(YYMMDD)*

8. PREPARING ACTIVITY **DEFENSE INFORMATION SYSTEMS AGENCY (DISA)**

a. NAME Rose D. Satz	b. TELEPHONE *(Include Area Code)* (1) Commercial (2) DSN
c. ADDRESS *(Include Zip Code)* Director JIEO Attn: TBBF Ft. Monmouth, NJ 07703-5613	**IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT:** Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 DSN 289-2340

DD Form 1426, OCT 89 *Previous editions are obsolete.* 198290

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:56Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:56Z
Check the source to verify that this is the current version before use.