MILITARY SPECIFICATION

AMPLIFIER, DISTRIBUTION AM-2123( )(V)/U

This amendment forms a part of Military Specification MIL-A-22305C(SHIPS), dated 16 October 1963.

PAGE 1

* TITLE: Delete "AM-2123(V)/U" and substitute "AM-2123( )(V)/U".

2.1, SPECIFICATIONS, MILITARY: Add "MIL-C-5015 - Connectors, Electric, AN Type".

2.1, STANDARDS, MILITARY: Add "MS 3102 - Connectors, Receptacle, Electric, Box Mounting" and "MS 3106 - Connectors, Plug, Electric, Straight".

PAGE 2

* 3.1: Delete and substitute:

"3.1 First article. When specified (see 6.1), the contractor shall furnish sample unit(s) for first article inspection and approval (see 4.2 and 6.2)."

3.3.1, third sentence: Delete.

Table I: Delete.

PAGE 3

3.3.6 and Table II: Delete and substitute:

"3.3.6 Size. Limiting dimensions for rack mounting shall be as specified in MIL-STD-189. The overall dimensions of the equipment with outer enclosure shall be as shown in Table II.

Table II. Overall dimensions.

Width	21	inches (max.)
Height	5-1/4	inches
Depth	13	inches (max.)

"

3.4.2, second and third sentences: Delete and substitute "A detachable line cord and plug conforming to type II of J-C-175 shall be supplied for connection to the 115-volt source attached to the rear of the equipment through chassis receptacle type MS3102(E or R)-14S-7P and mating cable connector type MS-3106(E or R)-14S-7S in accordance with MS3102, MS3106 and MIL-C-5015. Chassis connector type MS3102(E or R)-12S-3P shall be located on the rear panel for connection to the d.c. source. A mating cable connector type MS-3106(E or R)-12S-3S shall be supplied. Protective caps are not required for these connectors."

PAGE 4

3.4.6, second sentence: Delete and substitute "The panel meter selector switch shall be continually required; the input level controls, if used, shall be infrequently required (may be operable by screwdriver through holes in the front panel), and have suitable locking devices."

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T11:51Z
Check the source to verify that this is the current version before use.

* 4.1.1: Delete and substitute:

"4.1.1 Classification of tests. The first article inspection specified herein, and quality conformance inspection as specified in MIL-E-16400 shall be performed on the equipment."

* 4.2: Delete and substitute:

"4.2 First article inspection. Unless otherwise specified (see 6.1), two equipments shall be required for first article inspection. First article inspection shall consist of all examination and testing necessary to determine compliance with the requirements of this specification. First article inspection shall include the tests specified in Table III. Any failure whatsoever during the course of testing shall be cause for rejection."

PAGE 5

* Table III: Delete and substitute:

" Table III. First article inspection.

Inspection	Reference
Surface examination	MIL-E-16400
Operating test	MIL-E-16400
Weights and dimensions	3.3.6 and 3.3.7
Heat	MIL-E-16400
Enclosure	MIL-STD-108 and 3.3.5
Power line voltage and frequency	MIL-E-16400 and 3.4.2
Radio interference	MIL-E-16400
Signal level	4.4.1
Bandwidth	4.4.2
Impedance	4.4.3
Isolation	4.4.4
Distortion	4.4.5
Temperature	MIL-E-16400
Humidity	MIL-E-16400
Shock and vibration	MIL-E-16400
Inclination	MIL-E-16400
Salt spray test	MIL-E-16400
Accelerated life	MIL-E-16400
Reliability	4.1.3

PAGE 6

* 4.3.2.1, last line: Delete "those in Group II" and substitute "the signal level, bandwidth, impedance, isolation, and distortion tests".

4.4.1: Delete and substitute:

"4.4.1 Signal level. This test shall be run four times with input voltages (three input lines energized simultaneously) and output terminations (all outputs) as specified in table VI. The run sequence shall be A, C, B, D. All output levels shall be measured for each run. Requirements of 3.4.3.2 and 3.4.4.1 apply. If one or more manual level adjustments are provided, they shall be set (if necessary) twice only (once at the beginning of a run A, and again at the beginning of run B) to adjust all output levels simultaneously between 4.0 and 5.0 volts."

PAGE 7

4.4.4: Delete and substitute:

"4.4.4 Isolation. All inputs shall be energized simultaneously with 3.0-volt signals. Output voltage shall be measured at three output connectors, open circuits, one at each frequency. Measurements shall be made first with all remaining outputs open, then with all remaining outputs shorted. Change in measured amplitudes shall not exceed 1 percent."

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T11:51Z
Check the source to verify that this is the current version before use.

* 6.1: Add "(d) Number of first article samples to be submitted if other than specified in 4.2."

* 6.2: Delete and substitute:

"6.2 First article. When a first article is required, it shall be tested and approved under the appropriate provisions of 7-104.55 of the Defense Acquisition Regulation (DAR). The first article should be a first production item. The first article should consist of the number of units specified in the contract. The contracting officer should include specific instructions in all procurement instruments regarding arrangements for examinations, test, and approval of the first article."

* 6.2.1: Delete.

The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Preparing activity:
NAVY - EC
(Project 5820-N732)

U.S. GOVERNMENT PRINTING OFFICE 1979 — 603-121/136

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T11:51Z
Check the source to verify that this is the current version before use.