MIL-G-63386(AR)
AMENDMENT 2
31 August 1982
SUPERSEDING
AMENDMENT 1
23 July 1981

MILITARY SPECIFICATION

GAS GENERATOR ASSEMBLY

This Amendment forms a part of Military Specification MIL-G-63386(AR), dated 28 October 1980, and is approved for use by the U.S. Army Armament Research and Development Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 4

* 4.3.1: Under drawings, delete "9298522" and substitute "9298532".
Under Part Description, delete "Charge Assembly" and substitute "Charge Holder".

PAGE 5

* TABLE 1: Under Header, Bridged Assembly. Delete "dwg. 9298522" and substitute "dwg. 9298532".

PAGE 6

* TABLE 1: Under Gas Generator Assembly. Delete "All fire voltage function, 125, 3.2, 4.5.7".

PAGE 10

* 4.4.2.3: Major 103, Delete in its entirety.

PAGE 14

* 4.4.2.7: Major 107, delete "125"
Major 108, delete defect in its entirety

PAGE 18

* 4.5.4: First line, delete the words "of gas generator assembly". Fifth line, add "(9298532)" after "...applicable drawing".

* 4.5.6: Environmental conditioning and functioning. Delete paragraph in its entirety and substitute:

FSC 1345

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:46Z
Check the source to verify that this is the current version before use.

"4.5.6: Environmental conditioning and functioning. The Gas Generator Assemblies shall be tested as follows, in sequence specified, using approved equipment:

a. Measure resistance of the bridgewire in accordance with 4.5.4.

b. Measure insulation resistance in accordance with 4.5.5.

c. Condition for two (2) hours minimum at -65 ± 5°F.

d. Remove from cold chamber and within 20 sec. transfer to a hot chamber at 165 ± 5°F.

e. Condition for two (2) hours minimum at 165 ± 5°F and 20% maximum relative humidity.

f. Remove from hot chamber.

g. Vibrate for 15 minutes, minimum in a sweep covering a frequency range of 25-500-25 cycles per second, parallel to the transverse orthogonal axis, with base charge down and a 2 ± 0.2 G's peak.

h. Measure resistance of bridgewire in accordance with 4.5.4.

i. Measure insulation resistance in accordance with 4.5.5.

j. The Gas Generator assemblies shall be functioned as specified in 4.5.8."

PAGE 19

* 4.5.7: Delete the paragraph in its entirety.

* 4.5.8: Delete first paragraph in its entirety and substitute the following:

"4.5.8: Gas generator output functioning. "This test shall be performed for each gas generator assembly lot. The assemblies shall be assembled in a fixture in accordance with Dwg. 9298530 which is instrumented to provide a record of pressure versus time. The assemblies and fixture shall be conditioned at the required test temperature for two (2) hours minimum prior to test. The Gas Generator Assembly shall be initiated with the all fire voltage specified on the applicable drawing and the pressure/time results evaluated against the applicable requirements. If any Gas Generator Assembly fails to function or more than one (1) pressure/time failure accurs, that lot shall be rejected.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:46Z
Check the source to verify that this is the current version before use.

5.3.1, Change "ELECTRIC BLASTING CAPS--HANDLE CAREFULLY" to "DETONATING FUZE, CLASS C EXPLOSIVE".

* Change note at end of paragraph from "Insert number of blasting caps...." to "Insert number of gas generator...."

The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
ARMY-AR

Preparing activity:
Army-AR

(Project 1345-A206)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:46Z
Check the source to verify that this is the current version before use.