MIL-P-63293B (AR)
AMENDMENT 1
29 February 1984

MILITARY SPECIFICATION

PROJECTILE, 105MM, HEAT-T-MP, M456A2
METAL PARTS

This amendment forms a part of Military Specification MIL-P-63293B (AR), dated 18 October 1983, and is approved by the US Army Armament Munitions and Chemical Command and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 8

4.3.4.4: Add new paragraph "4.3.4.4 Deletion of the file test. The contractor, at his option, may select the wheel abrasive test (instead of the file test) to be used during regular production. In this case paragraphs 4.3.4.2 and 4.3.4.3 do not apply".

PAGE 12

4.4.2.1: Major Defect 124, in the Number of Samples Units column, delete "4.4.3.3.1" and substitute "4.4.3.3".

PAGE 15

4.4.2.2: Major Defect 119, in the Number of Samples Units column, delete "4.4.3.3.1" and substitute "4.4.3.3".

PAGE 20

4.4.2.6: Major Defect 111, in the Number of Samples Units column, delete "4.4.3.3.1" and substitute "4.4.3.3".

FSC: 1315

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:34Z
Check the source to verify that this is the current version before use.

PAGE 35

4.4.3.3 and 4.4.3.3.1: Delete these paragraphs in their entirety and substitute:

"4.4.3.3 Abrasion resistance test

4.4.3.3.1 Fin and boom assembly - file abrasive test. One fin and boom assembly (or set of components thereof) from each eight hours production or fraction thereof from the protective coating process shall be subjected to this test to determine compliance with paragraph 9.4.4 of MIL-C-60536, except that the information obtained during the file test in 4.3.4.2 shall be utilized as indicated in 4.3.4.3. Failure of the assembly or components to comply with the applicable requirements shall be cause for rejection of the product processed since the last acceptable test was performed.

4.4.3.3.2 Test panels - wheel abrasive test. If the contractor decides to use the wheel abrasive test during regular production (see 4.3.4.4), two test panels as specified in paragraph 9.4.3 of MIL-C-60536 shall be processed along with the product from each eight hours production. These test panels shall be subjected to a test in accordance with paragraph 9.4.3 of MIL-C-60536. Failure of any test to comply with the applicable requirement shall be cause for rejection of the product processed since the last accepptable test was performed."

PAGE 40

4.5.4.2: Delete this paragraph in its entirety and substitute:

"4.5.4.2 Abrasion resistance. The sample provided by 4.4.3.3.1 shall be tested using a filing machine of a type and model that was used in establishing correlation as indicated in 4.3.4.2. The samples shall be tested using the same type (roughness) file, the same length of stroke, the same number of strokes and the same file pressure as was used on the first article sample. If the contractor decides to do the wheel abrasive test (4.4.3.3.2), the test must be performed in accordance with paragraph 9.4.3 of MIL-C-60536."

4.5.5: Delete last sentence and substitute: "When ballistically testing the projectile metal parts, reference/calibration components shall be used as a minimum in the target-impact-dispersion phase."

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:34Z
Check the source to verify that this is the current version before use.

PAGE 45

5.1.1.2: Delete last sentence and substitute: "Pack sixteen (16) fin and boom assemblies arranged in a 4 x 4 pattern, using interlocking separators."

Custodian:
Army-AR

Preparing Activity:
Army-AR

(Project 1315-A608)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:34Z
Check the source to verify that this is the current version before use.