MILITARY SPECIFICATION

READ SWITCH: 10526456

This amendment forms a part of Military Specification MIL-R-60198(MU), dated 24 February 1965.

Paragraph 3.4.3: Change values "0.3 volts" and "1.5 volts" to "0.4 volts" and "0.44 volts" respectively.

Paragraph 4.2.4: Under Characteristic 106, change Test Procedure "4.5.2.1.6" to "4.5.2.1.6.1".

Paragraph 4.5.1.1, last sentence: Delete "as specified in 4.5.1.2 prior to determining" and substitute "to determine".

Paragraph 4.5.1.2, last sentence: Delete "as specified in 4.5.1.3 prior to determining" and substitute "to determine".

Paragraph 4.5.1.3.1, last sentence: Delete "thoroughly dried and then".

Paragraph 4.5.1.3.2: Delete in its entirety and substitute:

"4.5.1.3.2 Operating.- This test shall be conducted in accordance with the humidity test defined in Procedure III of MIL-F-13926, except that the humidity shall be maintained at 92 to 97 percent for the 24-hour period, and the test shall cease at the end of that period (Method 106 of MIL-STD-202 shall be excluded). Throughout the test period, the board shall be capable of performing the tests of 4.5.2.1.6.2. In order to demonstrate this capability, the tests of 4.5.2.1.6.2 shall be performed a minimum of once each 6 hours of the 24-hour period. The final test shall be conducted during the final portion of the 24-hour period. Between tests, the board shall be electrically energized as described in 4.5.2.1.6.2".

Paragraph 4.5.1.4: Delete in its entirety and substitute:

"4.5.1.4 Salt spray.- This test shall be conducted in accordance with the salt spray test defined in Method 101, Condition B of MIL-STD-202 using a 5 percent salt solution. At the end of the exposure period, salt deposits shall be removed from the board by a gentle wash, not exceeding 30 minutes, in running water not warmer than 100°F, using a soft-hair brush or plastic-bristle brush. The board shall then be air dried in a controlled environment at 72°F ± 5°F and a relative humidity of 30 to 50 percent for a period of 24 hours. The board shall be inspected visually for any physical damage, then tested in accordance with 4.5.2.1.6.1 and

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:17Z
Check the source to verify that this is the current version before use.

4.5.2.4. The board shall subsequently be inspected as specified in 4.5.1.5 prior to determining compliance with 3.4 as required by 3.3.6.

Paragraph 4.5.1.5: Delete "to 4.5.5" and substitute "4.5.2.5".

Paragraph 4.5.1.6: Delete last sentence and substitute: "After approval future performance of fungus testing may be omitted based on homogenious processes of coating".

Paragraph 4.5.2.1.4.2, second sentence: Delete "coltage" and substitute "voltage".

Paragraph 4.5.2.1.5.1: Change "14/watt" to 1/4 watt".

Paragraph 4.5.2.1.6: Change "3.4.1.3" to "3.4.1.6".

Paragraph 4.5.2.1.6.1: 1st sentence: Change "putput" to "output".

Paragraph 4.5.2.1.6.2.1: Change "Pin 49A" to "Pin 39A".

Table XI, Column B, Line 8: Delete "-11.0 ± 2.0 volts" and substitute "-13.4 ± 2.0 volts".

Table XIII, Column C, Line 4: Delete "0.53 ± 0.2 VDC" and substitute "+0.24 ± 0.2 VDC".

Table XIV, Column C, Line 4: Delete "+0.53 ± 0.2 VDC" and substitute "+0.24 ± 0.2 VDC".

Paragraph 4.5.2.4: Change "strove" to"strobe".

Custodian:

Army - MU

Preparing activity:

Army - MU

Project No. 1220-A049

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:17Z
Check the source to verify that this is the current version before use.