
21 February 1986

FEDERAL SPECIFICATION SHEET

RUBBER, SILICONE; RUBBER STRIP

This specification is approved by the Assistant Administrator, Office of Federal Supply and Services, General Services Administration, for the use of all Federal agencies.

The complete requirements for procuring the strip described herein shall consist of this document and the latest issue of ZZ-R-765/GEN.



PART NO. ZZR765/16-001F5

NOTES:
1. Dimensions are in inches.
2. Strengthening Feature: Backing.
3. External Strengthening Feature Location: One Side.
4. Strengthening Feature Material: Polytetrafluoroethylene.
5. Nonmetallic Hardness Rating: 45.0 min. to 55.0 max. Shore Durometer A.
6. Minimum Tensile Strength: 1200 psi.
7. Temperature Rating: -70°C to 204°C (-94.0° to 400.0°F).
8. Fabrication Method: Solid.
9. Surface Condition: Smooth.
10. Color: Natural.
11. When metric units are required, units for inch and psi may be converted to the metric equivalent as follows:

English	Multiply by	Equals	Metric unit
inch	2.54	=	centimeter (cm)
psi	6.894×10^{-3}	=	mega pascal (MPa)


AMSC: N/A

/FSC 9320/

DISTRIBUTION STATEMENT A Approved for public release; distribution unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:27Z
Check the source to verify that this is the current version before use.

PART NUMBERING SYSTEM FOR FEDERAL SPECIFICATION ZZ-R-765/GEN



MILITARY INTERESTS:

Custodians

Army -- MR
Navy -- AS
Air Force -- 20

Review activity

DLA -- GS

CIVIL AGENCY COORDINATING ACTIVITY:

GSA -- FSS

PREPARING ACTIVITY:

Army -- MR

Project No. 9320-0384

(WP# ID-7059A/DISK-0353A. FOR AMMRC USE ONLY).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:27Z
Check the source to verify that this is the current version before use.