
FEDERAL SPECIFICATION SHEET

RUBBER, SILICONE; NONMETALLIC SPECIAL SHAPED SECTION

This specification is approved by the Assistant Administrator, Office of Federal Supply and Services, General Services Administration, for the use of all Federal agencies.

The complete requirements for procuring the sections described herein shall consist of this document and the latest issue of ZZ-R-765/GEN.

RIBS OPTIONAL



HALF ROUND, HOLLOW CORE

PART NO.
ZZR765/34-001F6

NOTES:
1. Dimensions are in inches.
2. Length: 120 inches nominal.
3. Nonmetallic Hardness Rating: 55.0 minimum to 65.0 maximum Shore Durometer A.
4. Minimum Tensile Strength: 1200 psi.
5. Color: Black.
6. Temperature Rating: -70° to 204° (-94°F to 400°F).
7. When metric units are required, units for inch and psi may be converted to the metric equivalent as follows:

English	Multiply by	Equals	Metric unit
inch	2.54	=	centimeter (cm)
psi	6.894×10^{-3}	=	mega pascal (MPa)

AMSC: N/A


FSC 9320

DISTRIBUTION STATEMENT A Approved for public release; distribution unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:27Z
Check the source to verify that this is the current version before use.

ZZ-R-765/34

PART NUMBERING SYSTEM FOR FEDERAL SPECIFICATION ZZ-R-765/GEN



MILITARY INTERESTS:

Custodians

Army -- MR
Navy -- AS
Air Force -- 20

Review activity

DLA -- GS

CIVIL AGENCY COORDINATING ACTIVITY:

GSA -- FSS

PREPARING ACTIVITY:

Army -- MR

Project No. 9320-0386

(KBWP# ID-7078A/DISK-0535A. FOR AMMRC USE ONLY).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:27Z
Check the source to verify that this is the current version before use.